

Runwise Deployment Guide

Runwise deploys to [Vercel](https://vercel.com/) automatically on every merge to main.

Architecture

```
GitHub (main branch)
  %
  %¼
  Vercel CI/CD
    %
    % % % Build: npm run build (SvelteKit + Vite)
    % % % Deploy: @sveltejs/adapter-vercel
```

Vercel Configuration

The project uses @sveltejs/adapter-vercel. A vercel.json is committed to the repository with the following configuration:

- `www !` apex redirect — all requests to `www.runwise.app/*` are permanently redirected (HTTP 301) to `https://runwise.app/*` to consolidate SEO link equity on the canonical apex domain.
- Security headers — applied to all responses:
 - X-Content-Type-Options: nosniff
 - X-Frame-Options: DENY
 - Referrer-Policy: strict-origin-when-cross-origin
 - Permissions-Policy: camera=(), microphone=(), geolocation=()
- OG image caching — `/og/*` (social preview images) gets `Cache-Control: public, max-age=86400, stale-while-revalidate=604800` (1-day cache, up to 1-week stale-while-revalidating). Deliberately moderate rather than `immutable/long-lived`: these filenames aren't content-hashed and get overwritten in place on a redesign, so a long-immutable cache would hide a future redesign from cached copies for up to a year.

Note: Content-Security-Policy is intentionally omitted — it would block Google Fonts (loaded in `+layout.svelte`) and future ad scripts. Strict-Transport-Security is omitted because the `.app` TLD enforces HTTPS at the browser level (HSTS preloaded).

`/_app/immutable/*` (hashed JS/CSS build output) is cached separately and automatically by @sveltejs/adapter-vercel itself (Cache-Control: public, immutable, max-age=31536000) — this is not configured in vercel.json and doesn't need to be; it's safe to cache aggressively because these filenames carry content hashes.

Environment

Environment Variables

Set optional variables in the Vercel dashboard under Environment Variables (left sidebar). See `.env.example` for the full list with descriptions. No environment variables are required for a first-time deploy — the site builds and serves every tool page without them. The contact form on `/about` is the one feature that needs configuration beyond a first-time deploy; see below.

Contact Form Email (Resend)

The `/about` page's contact form sends via [Resend](https://resend.com), installed as a Vercel Marketplace integration rather than a hand-wired SMTP/SDK setup:

```
vercel link # if not already linked
vercel integration add resend -m domain=<your-domain> -m region=us-east-1 --plan free
vercel env add CONTACT_EMAIL production # the inbox that should receive submissions
```

```
vercel env pull --yes          # sync RESEND_API_KEY/RESEND_EMAIL_DOMAIN/  
CONTACT_EMAIL locally
```

DNS verification is automatic if Vercel manages your domain's nameservers (as it does for runwise.app, registered through Vercel) — the integration provisions the SPF/DKIM records for you, with no mailbox required at the sending address (contact@<domain>; nobody ever reads mail sent **from** it, only mail sent **to** CONTACT_EMAIL). If your domain's DNS is hosted elsewhere, Resend's dashboard will show the SPF/DKIM records to add manually instead — check vercel integration list / the Resend dashboard for verification status before relying on real delivery.

First-Time Setup

Import the GitHub repository into Vercel
Vercel detects SvelteKit automatically — no manual configuration needed
Every push to `main` triggers a production deployment
Every PR gets a preview deployment URL

Deployments

Local Production Preview

```
npm run build  
npm run preview
```

Opens a local server serving the production build at http://localhost:4173.

Monitoring

View deployment status, build logs, and runtime errors in the [Vercel dashboard](https://vercel.com/dashboard).