

Runwise Deployment Guide

Runwise deploys to [Vercel](https://vercel.com/) automatically on every merge to main.

Architecture

```
GitHub (main branch)
  %
  %¼
  Vercel CI/CD
    %
    % % % Build: npm run build (SvelteKit + Vite)
    % % % Deploy: @sveltejs/adapter-vercel
```

Vercel Configuration

The project uses @sveltejs/adapter-vercel. A vercel.json is committed to the repository with the following configuration:

- www !' apex redirect — all requests to `www.runwise.app/\*` are permanently redirected (HTTP 301) to `https://runwise.app/\*` to consolidate SEO link equity on the canonical apex domain.
- Security headers — applied to all responses:
 - X-Content-Type-Options: nosniff
 - X-Frame-Options: DENY
 - Referrer-Policy: strict-origin-when-cross-origin
 - Permissions-Policy: camera=(), microphone=(), geolocation=()

Note: Content-Security-Policy is intentionally omitted — it would block Google Fonts (loaded in +layout.svelte) and future ad scripts. Strict-Transport-Security is omitted because the .app TLD enforces HTTPS at the browser level (HSTS preloaded).

Environment

Environment Variables

Set optional variables in the Vercel dashboard under Environment Variables (left sidebar). See .env.example for the full list with descriptions. No environment variables are required for a first-time deploy.

First-Time Setup

Import the GitHub repository into Vercel
Vercel detects SvelteKit automatically — no manual configuration needed
Every push to `main` triggers a production deployment
Every PR gets a preview deployment URL

Deployments

Local Production Preview

```
npm run build  
npm run preview
```

Opens a local server serving the production build at <http://localhost:4173>.

Monitoring

View deployment status, build logs, and runtime errors in the [Vercel dashboard](<https://vercel.com/dashboard>).