

Runwise Developer Guide

Stack

Prerequisites

- Node.js 22 or later
 - npm
-

Setup

```
git clone https://github.com/alanwaddington/runwise.git
cd runwise
npm install
npm run dev
```

Open http://localhost:5173.

Cleaning up extraneous WASM fallback packages (optional)

npm install/npm ci always installs 5 extra packages — @emnapi/core, @emnapi/runtime, @emnapi/wasi-threads, @napi-rs/wasm-runtime, @tybys/wasm-util — even though npm ls reports them as extraneous and neither npm ci nor npm prune remove them. This is a known upstream npm limitation: they're the WASM32-WASI fallback runtime bundled with @tailwindcss/oxide and @rollup/plugin-binding (Vite's bundler), and npm doesn't correctly skip them via its cpu platform gating when they're nested this way. They're devDependencies-only, unreferenced anywhere in source, and have zero footprint in the deployed Vercel build — safe to ignore.

If you'd like to reclaim the ~9.5MB anyway:

```
npm run clean:wasm
```

This is optional, local-only, and does not change package.json or the lockfile — you'll need to re-run it after every fresh npm install/npm ci if you want to keep node_modules lean.

Project Structure

```
src/
% % % app.css          # Global styles + Tailwind theme tokens
% % % app.html         # SvelteKit HTML shell
% % % lib/
% % % % affiliates.ts  # Affiliate product definitions per route (Amazon Associates,
Garmin, and direct/non-affiliate links)
% % % % seo.ts        # SEO metadata map (PAGES), sitemap config, OG images –
includes /about, /guides, and each guide's route (generated from lib/content/guide-
index.ts, NOT the full guides/ content – see below)
% % % % components/   # Shared UI components
% % % % % AdUnit.svelte      # Consent-gated Google AdSense ad unit
% % % % % AdUnit.test.ts    #
% % % % % AffiliateLinks.svelte  # Per-route affiliate product cards (Amazon,
Garmin, or direct links)
% % % % % AffiliateLinks.test.ts
% % % % % CollapsibleField.svelte  # Generic animated show/hide wrapper (max-height/
opacity, aria-hidden, inert)
% % % % % CollapsibleField.test.ts
% % % % % ContactForm.svelte    # /about's contact form – client validation, hidden
honeypot field, loading/success/error states, posts to /api/contact
```

```

% % % % ContactForm.test.ts
% % % % CookieBanner.svelte # GDPR cookie consent banner (fixed bottom)
% % % % CookieBanner.test.ts
% % % % EducationalSection.svelte # Homepage "training fundamentals" / "common
mistakes" / "how Runwise helps" sections
% % % % GuideArticle.svelte # Shared long-form article layout for /guides/*
pages – title, intro, "Sourced from" credibility callout, sections
% % % % GuideArticle.test.ts
% % % % HeroSection.svelte
% % % % HeroSection.test.ts
% % % % IconWarning.svelte # Shared inline warning-triangle SVG icon
% % % % IconWarning.test.ts
% % % % InputField.svelte
% % % % InputField.test.ts
% % % % MedicalDisclaimer.svelte # "Not medical advice" notice – rendered at the top
of HR Zones, VO2 Max, and Workouts only (the YMYL-adjacent tools), links to /about for
sourcing
% % % % MedicalDisclaimer.test.ts
% % % % PageExplainer.svelte # Per-route "About this tool" footer content,
driven by lib/content/explainers.ts; sections may include outbound reference links
% % % % PageExplainer.test.ts
% % % % PatternBadge.svelte # Consolidated workout-pattern badge (Race-Prep,
mixed-zone pair key, etc.) – one component, own row under the card title, replaces two
earlier inconsistent badge styles
% % % % ResultDisplay.svelte
% % % % ResultDisplay.test.ts
% % % % SeoHead.svelte # Per-page meta tags, OG, JSON-LD, AdSense account
verification
% % % % SeoHead.test.ts
% % % % SiteFooter.svelte # Footer with About, Guides, and Privacy Policy
links, plus the Manage Cookies button
% % % % SiteFooter.test.ts
% % % % SiteNav.svelte
% % % % SiteNav.test.ts
% % % % Toast.svelte # App-wide success/failure notification, driven by
stores/toast.ts (bottom-of-viewport, auto-dismissing)
% % % % Toast.test.ts
% % % % ToolCard.svelte
% % % % ToolCard.test.ts
% % % % ToolIcon.svelte
% % % % ToolLayout.svelte
% % % % ToolLayout.test.ts
% % % % WorkoutProfileChart.svelte # Segment-by-segment bar chart (warm-up/work/
recovery/cool-down) for a single workout
% % % % WorkoutProfileChart.test.ts
% % % % WorkoutRail.svelte # Horizontal scroll-snap card rail with uniform
card height/width and keyboard (Arrow Left/Right) scroll support (WAI-ARIA APG
scrollable-region pattern)
% % % % WorkoutRail.test.ts
% % % % config/
% % % % toolValidation.ts # Per-field validation rule config shared across tool
pages
% % % % content/
% % % % explainers.ts # Per-route PageExplainer content (heading/intro/
sections, optional outbound links)
% % % % guide-index.ts # Lightweight per-guide metadata (slug/route/title/
excerpt) ONLY – this is what seo.ts imports (rendered on every page via SeoHead), so
guide article bodies never ship outside their own route's chunk
% % % % guide-index.test.ts # Asserts GUIDE_INDEX stays in sync with the full GUIDES
content (same slugs/order, matching route/title/excerpt) – guards against the two going
out of sync
% % % % guides.test.ts # Enforces exactly 10 guides, unique slugs, a 900-word
minimum, and that EVERY guide names its source methodology in body prose
% % % % guides/ # One file per guide (title/excerpt/sourcesCredited/intro/
sections, same content shape as explainers.ts), re-exported as GUIDES from guides/
index.ts; each /guides/<slug>/+page.svelte imports its own file directly rather than
the aggregated array, so a route's own chunk carries only its own article
% % % % server/ # Server-only logic backing src/routes/api/contact
% % % % contactValidation.ts # Pure validation of a contact submission –
required fields, email format, message length, honeypot detection
% % % % contactValidation.test.ts
% % % % mailer.ts # Wraps the Resend SDK to send the contact-form
notification email to CONTACT_EMAIL
% % % % mailer.test.ts
% % % % rateLimiter.ts # Per-key sliding-window rate limiter (in-memory;
per-instance, not global – see the Contact Form section below)

```

```

% % % % rateLimiter.test.ts
% % % % stores/ # Svelte stores for cross-component state
% % % % consent.ts # GDPR consent read/write (localStorage)
% % % % consent.test.ts
% % % % consentBannerVisible.ts # Writable store: true = show banner
% % % % toast.ts # Writable store + showToast()/dismissToast() driving
Toast.svelte
% % % % validation/ # Shared client+server validation primitives (kept separate
from lib/utils since they're used by both a Svelte component and a server route)
% % % % email.ts # isValidEmail() – single source of truth for the
contact form's email regex, used by ContactForm.svelte and contactValidation.ts
% % % % email.test.ts
% % % % messageLength.ts # MAX_MESSAGE_LENGTH (5000) – shared between the
textarea's maxlength and the server's validation cap
% % % % (no test file – a single exported constant)
% % % % utils/ # Pure utility modules (no Svelte dependency)
% % % % pace.ts # Pace/speed conversion functions
% % % % pace.test.ts
% % % % race-predictor.ts # Riegel formula, time parsing/formatting, prediction
table
% % % % race-predictor.test.ts
% % % % race-result-params.ts # Serializes/parses a race result to/from URL query
params, shared between /training-paces and /workouts
% % % % race-result-params.test.ts
% % % % training-paces.ts # VDOT calculation (Daniels' formula), training zone
pace derivation
% % % % training-paces.test.ts
% % % % hr-zones.ts # Max HR zones, Friel LTHR zones, LTHR sub-zones,
Tanaka age estimate, calculateDanielsLthrZones + calculateDanielsMaxHrZones (E/M/T/I/R
HR zones from either method, HrConfidence: high/medium/low/none – R is always 'none',
no HR target)
% % % % hr-zones.test.ts
% % % % vo2max.ts # ACSM normative data, getFitnessCategory,
getAcsmTable, CATEGORY_COLOURS
% % % % vo2max.test.ts
% % % % parkrun.ts # Reference distance list, Riegel prediction, split
generation, PB comparison, WMA age grading
% % % % parkrun.test.ts
% % % % validation.ts # Shared input validation helpers (validatePositive,
validateRange)
% % % % power-zones.ts # Per-device (Stryd/Garmin/COROS/Polar) running-power
zone tables and calculatePowerZones()
% % % % power-zones.test.ts
% % % % workouts.ts # Pace-mode workout generation (Daniels weekly-
mileage scaling), buildWorkoutsResult, roundWorkoutSegments, sumSegmentMinutes, the
Workout.pattern field
% % % % workouts.test.ts
% % % % power-workouts.ts # Power-mode equivalent of workouts.ts (device power !=
estimated pace != same session shapes)
% % % % power-workouts.test.ts
% % % % hr-workouts.ts # HR-mode equivalent of workouts.ts – duration-based
(no distance), buildHrWorkoutsResult(hrInput, ...) dispatches on HrInput's { method:
'lthr' | 'maxhr' } discriminant, falls back to a default pace when no race result is
available
% % % % hr-workouts.test.ts
% % % % workout-patterns.ts # Pattern-tagged workout variants shared across
zones: race-pace tempo/reps (race-prep); buildFartlekWorkout (M/T/I);
buildProgressionWorkout (T/I); buildDecayWorkout (I/R); buildRepExpansionWorkouts (I/R,
distance + time-based). All wired into buildZoneWorkouts (workouts.ts), Pace mode only.
% % % % workout-patterns.test.ts
% % % % recovery-workouts.ts # buildRecoveryWorkouts(): Easy float, Recovery
striders, Shakeout run – fixed flexible durations, not derived from weekly mileage/pace
like everything else; wired into R zone's buildZoneWorkouts output but gated in
separately, not through the (zone, pace, volumeKm) pattern-builder signature above.
buildShakeoutWorkout() is separately exported so race-prep.ts can pull in just that one
variant.
% % % % recovery-workouts.test.ts
% % % % mixed-zone-workouts.ts # Two-zone-blend workouts (E+M/M+T/T+I),
buildMixedZoneWorkouts
% % % % mixed-zone-workouts.test.ts
% % % % race-prep.ts # 4-8 week race-prep plan (scales with
weeksUntilRace) – curates/relabels buildZoneWorkouts output rather than a separate
workout library; buildRacePrepResult, isRacePrepEligible; supports Pace, Power, and HR
modality via a "Train by" sub-selector independent of the page's top-level mode. Taper
week's final workout is always a Shakeout run (buildShakeoutWorkout, recovery-
workouts.ts), tagged zone: 'E' in every modality so it resolves to the Easy pace/power/

```

```

HR band rather than a harder zone's.
% % % % race-prep.test.ts
% % % % segment-targets.ts # Per-segment pace/power/bpm target-range math,
shared by the /workouts UI and fit-export.ts; getOpenEndedBpmBound() handles Daniels'
open-ended E/R HR zones ("<N bpm"/">N bpm"), which have no second bound to narrow toward
% % % % segment-targets.test.ts
% % % % fit-export.ts # Encodes a generated workout as a downloadable FIT
file (via @garmin/fitsdk), for watch upload – falls back to a one-sided target for open-
ended HR zones rather than throwing
% % % % fit-export.test.ts
% % % % vite-plugins/
% % % % git-dates.ts # Vite plugin exposing virtual:git-dates – a per-route
lastmod date map derived from git history
% % % % git-dates.test.ts
% % % routes/
% % % +layout.svelte # Root layout – CookieBanner + header + main + SiteFooter
% % % +page.svelte # Home page – HeroSection + ToolCard grid + a closing link to /
about
% % % +error.svelte # Error page
% % % pace/
% % % race-predictor/
% % % training-paces/
% % % hr-zones/
% % % vo2max/
% % % parkrun/
% % % power-zones/ # Power Zones Calculator (Stryd/Garmin/COROS*/Polar) – *COROS
currently hidden pending further research
% % % workouts/ # Workout Suggestions (Pace/Power/HR/Race-Prep modes, plus
Mixed-Zone Sessions) – includes the workout detail modal and "Download as .FIT" export
% % % privacy/ # Privacy Policy page
% % % about/ # Project identity, sourced-methodology summary, and the
embedded ContactForm
% % % guides/
% % % +page.svelte # Guides index, listing every entry in lib/
content/guide-index.ts (NOT the full guides/ content)
% % % % understanding-vdot/
% % % % hr-zones-vs-power-zones/
% % % % how-race-predictions-work/
% % % % reading-your-vo2max/
% % % % understanding-running-pace/
% % % % parkrun-age-grading-explained/
% % % % running-power-zones-explained/
% % % % interval-training-explained/
% % % % how-runwise-builds-workouts/
% % % % choosing-your-training-metric/ # Each a thin wrapper importing its own
guide directly from lib/content/guides/<slug>.ts and rendering GuideArticle with it
% % % % api/
% % % % contact/
% % % % +server.ts # POST /api/contact – validate !' honeypot check !' rate limit !'
send via lib/server/mailer.ts. The project's first mutating server route.

```

Design System

Tokens (`src/app.css`)

Dark mode is applied automatically via prefers-color-scheme, with an explicit `html.light/html.dark` class override (set pre-paint by `app.html`) taking priority once JS has run. Always use design tokens (`text-ink`, `text-muted`, `bg-bg`, `border-ink/10`) rather than hardcoded Tailwind colours where tokens exist.

Namespace note: color tokens must live under the `--color-*` prefix, not `--text-*` — Tailwind v4 reserves `--text-*` for font-size scale tokens (`--text-sm`, `--text-lg`, etc.), and a `--text-muted-style` color token silently compiles to an invalid font-size declaration instead of color, with no build error. (This was a real, previously-shipped bug — see PR #71.)

Text Contrast (WCAG AA)

Secondary text (help hints, labels, table headers, footer) uses `.text-muted (!' --color-muted)`, which achieves ~4.63:1 contrast in light mode and ~6.92:1 in dark mode against the page background — both pass WCAG 2.1 AA (4.5:1 minimum). The dark-mode value is set once, at the token level, in `src/app.css` (`html.dark` and the no-JS prefers-color-scheme fallback) — never override it per-component.

An ESLint rule (runwise/no-low-contrast-text, in eslint-plugin-runwise/rules/no-low-contrast-text.js) errors on text-gray-400/text-gray-500 in Svelte files, including dark:/hover:-prefixed variants — there is no exemption for dark:text-gray-400 (it predates --color-muted's dark-mode fix and is no longer needed anywhere in the codebase).

Focus Rings (WCAG AA — SC 2.4.7)

All interactive elements (<button> and <a>) must have visible focus indicators for keyboard and assistive-technology users (WCAG 2.1 SC 2.4.7 Focus Visible).

Standard pattern:

```
<!-- Buttons -->
<button class="... focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-
accent focus-visible:ring-offset-2">

<!-- Inline links (inside text) – add rounded-sm for clean ring shape -->
<a href="..." class="rounded-sm ... focus-visible:outline-none focus-visible:ring-2
focus-visible:ring-accent focus-visible:ring-offset-2">
```

Ring offset note: Most elements use ring-offset-2. Tab buttons inside tight tablist containers use ring-offset-1 — choose whichever fits the layout.

Enforcement: The custom ESLint plugin eslint-plugin-runwise (in eslint-plugin-runwise/) provides two rules for Svelte files, both at 'error' severity in eslint.config.js:

```
eslint-plugin-runwise/
% % % index.js                # Plugin entry point
% % % rules/
% % %   require-focus-visible.js # Checks <button>/<a> for the full focus-visible
pattern
% % %   no-low-contrast-text.js  # Bans text-gray-400/text-gray-500 (any variant) in
class attributes
```

Both rules operate on the Svelte template AST directly (SvelteElement, SvelteAttribute, SvelteLiteral) rather than plain ESTree nodes — Svelte class attributes are not standard Literal nodes, and the element name lives on SvelteElement.name.name with its attributes on SvelteElement.startTag.attributes, not on SvelteStartTag directly. Getting this AST path wrong makes a rule fail completely silently (it simply never matches, with zero lint errors either way) rather than throwing — if you write or modify a rule targeting Svelte templates, verify it actually fires against a deliberately-broken scratch .svelte file before trusting a clean npm run lint run.

Collapsible Content

Any field or block that toggles visibility based on user input (e.g. a "Custom" option revealing an extra input) should use the shared CollapsibleField component rather than a bespoke inline pattern:

```
<CollapsibleField expanded={isCustom}>
  "Ä-ç Wdf-VÆB ååå öå
</CollapsibleField>
```

Why not {#if} or the native hidden attribute:

- {#if} unmounts/remounts the content, so there's nothing to animate — the field would snap in/out instantly.
- The native `hidden` attribute also snaps instantly and sets no `aria-hidden`, so assistive technology gets no signal that the field is (or isn't) currently relevant.

What CollapsibleField does instead: the content stays mounted at all times (so its state — e.g. a partially-typed value — survives being hidden and re-shown) and visibility is purely a CSS transition (max-h-0 opacity-0 !" max-h-24 opacity-100 mb-4, overflow-hidden transition-all duration-200), paired with two accessibility attributes toggled together:

aria-hidden alone is not enough: it only affects the accessibility tree — it does not remove a nested focusable element from the tab order. Without inert, a sighted keyboard user can Tab into an invisible field (confirmed as a real, fixed bug — see PR #72 review, finding "aria-hidden properly set"). Always pair aria-hidden with inert (or tabindex="-1" on every focusable descendant, which doesn't scale) whenever hiding content that contains interactive elements.

inert's focus-blocking enforcement is real-browser behaviour that jsdom does not implement (it only reflects the IDL property, not the enforcement) — CollapsibleField.test.ts asserts the property, but the actual behavioural guarantee is covered by e2e/collapsible-field-focus.test.ts (Playwright/Chromium).

Hover Feedback (touch and mouse)

hover: classes must use the `--color-hover` token (`.hover\:text-hover`) rather than reusing `.text-ink` directly — this keeps the hover-state color relationship an explicit, named design decision instead of an incidental side effect of `--color-ink` flipping per theme.

Tailwind v4 wraps hover: utilities in `@media (hover: hover)` by default, to prevent "sticky hover" on touch devices (where a tap has no true hover-then-release gesture). This project overrides that default via a custom variant in `src/app.css`:

```
@custom-variant hover (&:hover);
```

This makes every hover: utility sitewide apply on tap as well as mouse hover — chosen deliberately so that touch users get the same hover feedback as mouse users. The accepted trade-off: tapping an element leaves it visually "stuck" in its hover-colored state until another hoverable element is tapped. If you ever need the touch-safe default back for a specific element, use an explicit `@media (hover: hover)` wrapper on that element's own styles rather than reverting the global variant.

Components

Contact Form

`/about` embeds `ContactForm.svelte`, which posts JSON to `POST /api/contact` (`src/routes/api/contact/+server.ts`) — the first mutating server route in the project (every other `+server.ts`, `robots.txt` and `sitemap.xml`, is GET-only static text).

```
ContactForm.svelte
% fetch POST { name, email, message, honeypot }
%
src/routes/api/contact/+server.ts
% 1. parse JSON (400 on failure)
% 2. validateContactSubmission() — lib/server/contactValidation.ts
%    !' honeypot filled? return 200 {ok:true} without sending (bot gets no signal)
%    !' invalid? return 400 {error}
% 3. rateLimiter.isAllowed(clientAddress) — lib/server/rateLimiter.ts
%    !' over limit? return 429 {error}
% 4. sendContactEmail() — lib/server/mailer.ts
%
Resend API !' CONTACT_EMAIL inbox (replyTo: the submitter's own address)
```

Email delivery is provisioned via the Resend integration on the Vercel Marketplace (vercel integration add resend), which auto-populates `RESEND_API_KEY` and `RESEND_EMAIL_DOMAIN` as project env vars. `CONTACT_EMAIL` — the real inbox that receives submissions — is a separate, manually-configured secret (see the Deployment Guide's Environment Variables section for all three).

Spam mitigation is hand-rolled, not a marketplace product (none exists for this): a honeypot field plus a per-IP sliding-window rate limiter (`rateLimiter.ts`, 5 requests / 10 minutes). The rate limiter's state is a plain in-memory Map, scoped to a single Vercel Fluid Compute instance — it reduces obvious scripted abuse but is not a global guarantee across concurrent instances. If abuse becomes a real problem, Vercel BotID (a first-party Vercel product) is the natural next step.

Shared client/server validation: the email-format check (`lib/validation/email.ts`) and the message length cap (`lib/validation/messageLength.ts`) are each defined once and imported by both `ContactForm.svelte` and `contactValidation.ts`, so the client-side `maxlength`/format check can never silently drift from what the server actually enforces.

Adding a New Tool

```
Create `src/routes/<tool-name>/+page.svelte`
Import `ToolLayout` and pass `title`, `description`, and `route` props
Add the tool to the `tools` array in `src/routes/+page.svelte`
Add the tool link to `SiteNav.svelte`
Register the route in `src/lib/seo.ts` (`PAGES` map) with a title, description, OG image path, and sitemap
priority — this drives the page's meta tags, `sitemap.xml` entry, `robots.txt` allow rules, and JSON-LD
structured data
```

Add tests alongside the page

Testing

Unit and component tests (Vitest)

```
npm run test          # Run all tests once
npm run test -- --watch # Watch mode
```

Tests live alongside their source files (*.test.ts). Follow the existing pattern:

```
import { describe, it, expect, afterEach } from 'vitest';
import { render, cleanup, screen } from '@testing-library/svelte';
import MyComponent from './MyComponent.svelte';

afterEach(() => { cleanup(); });

describe('MyComponent', () => {
  it('renders correctly', () => {
    render(MyComponent, { props: { ... } });
    expect(screen.getByRole('...')).toBeInTheDocument();
  });
});
```

E2E tests (Playwright)

```
npx playwright install chromium # First time only
npm run test:e2e                # Run E2E tests against the production build
```

E2E tests live in the e2e/ directory. They run against the production preview server (npm run build && npm run preview on port 4173). Configuration is in playwright.config.ts.

e2e/helpers.ts holds shared setup functions (cookie-consent seeding, race-result form filling, mode switching) for multi-file feature areas — introduced for /workouts' Phase 3 E2E suite (e2e/workouts-*.test.ts: race-prep flow, HR mode + pattern badges, FIT download × 3 modalities + mobile viewport, modal keyboard behavior) since four new spec files needed near-identical setup; most existing single-file E2E specs still duplicate their own setup inline, which is fine at that scale.

Accessibility scanning (e2e/workouts-accessibility.test.ts) uses @axe-core/playwright's AxeBuilder to scan for WCAG AA violations, kept in its own file separate from flow-behavior tests so an accessibility regression and a functional regression don't obscure each other. Only asserts on results.violations (definite failures) — axe-core also returns results.incomplete (elements it can't reach a confident verdict on, e.g. small rounded-background badges) which isn't a hard pass/fail signal; those need the manual audit process below instead.

Manual accessibility audits (keyboard-only navigation, screen-reader spot-checks) are documented as dated findings docs under docs/accessibility/, mirroring the docs/pr-reviews/ precedent — see docs/accessibility/workouts-manual-audit.md for the format. Run these for any page with non-trivial interactive state (modals, multi-step flows) that axe-core's static-scan approach can't verify — focus management in particular (does focus actually move into a modal on open? does Tab stay trapped inside it?) is invisible to both jsdom component tests and automated contrast/ARIA scanners alike; only driving the real page with a keyboard catches it.

Code Quality

```
npm run check          # TypeScript / svelte-check
npm run lint           # ESLint
npm run format         # Prettier (auto-fix)
npm run test:e2e       # Playwright E2E tests (requires built app)
npm run check:bundle-size # /workouts client bundle gzip budget (builds if needed)
```

check:bundle-size (scripts/check-workouts-bundle-size.js) walks Vite's own client build manifest from the /workouts route entry through its transitive static imports, gzips the result, and fails if it exceeds a 100 KB budget — a regression guard added so a future accidentally-static heavy dependency import (e.g. @garmin/fitsdk, normally dynamically imported only on FIT download) doesn't silently balloon the route's initial page weight unnoticed.

Workflow

This project follows an issue-driven workflow:

```
/analyse <issue>    !' requirements + acceptance criteria
/design <issue>      !' architecture + work breakdown
/develop <issue>     !' TDD implementation
/verify <PR>         !' runtime verification
/pr-reviewer <PR>    !' acceptance criteria audit
/merge <PR>          !' merge + close issues
```