

Martin B-57 Canberra

- B-57B (Early)
- B-57B
- B-57B (PAF)
- B-57G

Radar: APW-11 ECCM: 0 Arcs: 180+ Search: Gr. Nav. (90) Track: Gr. Attack (30) Lock-On: 7	ECM: IFF RWR: — DDS: — DJM: — AJM: — BJM: —	Weapon Stations Diagram:															
Guns: Eight .50 cal M3 To Hit: 4/2/1 Ammunition: 7.0 Gunsight: TT+1/HT+2/BT+3 Ranging: — AtA/AtG: 5/7*	Technology: None	Load Point Limits: CL : 0–8 1/2: 9–15 Weight Limit: 12,000 DT : 16+															
Bomb System: Manual		<table border="1"> <thead> <tr> <th>Station</th> <th>Limit</th> <th>Allowed Loads</th> </tr> </thead> <tbody> <tr> <td>1 and 11</td> <td>2,200</td> <td>FT</td> </tr> <tr> <td>2–3 and 9–10</td> <td>250</td> <td>BB RP RK</td> </tr> <tr> <td>4–5 and 7–8</td> <td>750</td> <td>BB RP RK</td> </tr> <tr> <td>6</td> <td>6,000</td> <td>BB</td> </tr> </tbody> </table>	Station	Limit	Allowed Loads	1 and 11	2,200	FT	2–3 and 9–10	250	BB RP RK	4–5 and 7–8	750	BB RP RK	6	6,000	BB
Station	Limit	Allowed Loads															
1 and 11	2,200	FT															
2–3 and 9–10	250	BB RP RK															
4–5 and 7–8	750	BB RP RK															
6	6,000	BB															
Notes: 1. 2. High transonic drag (HTD). Low roll rate (LRR). 3. Tail Warning Radar. APS-54 with ECCM of 0, arc of 30—, and search capability of 30–10. The radar has no tracking capability.		Load Notes: 1. Station 6 is the internal bomb bay. It can carry six illumination flares and either (a) six 1,000 lb BB, (b) eight 750 lb BB, (c) nine 500 lb BB, or (d) twelve 250 lb BB. All BB must be HE type. 2. Stations 2 to 5 and 7 to 10 can each carry two RKs.															
		VPs: 16/11/5/3															
		v2 0000000 0000-00-00T00:00:00															

B-57B Canberra										Crew: Pilot and Weapons Officer				
										Maneuver HFPs/DPs: LR/DR 1.0 2.0 VR 1.0				
Power APs/DPs: ○○										Turn DPs:				
CL	1/2	DT	Fuel							CL	1/2	DT		
AB	—	—	—	—		TT	0.0	0.0	0.0					
M	1.0	1.0	0.5	3.0		HT	1.0	1.0	1.0					
N	0.0	0.0	0.0	1.0		BT	1.0	1.0	—					
I	1.0	1.0	2.0	0.0		ET	—	—	—					
SPBR	1.0	1.0	2.0	—		Only one vertical roll allowed per game turn.								
					Cruise Spd. CL: 4.5 Restr. Arcs: 60—									
					Climb Spd.: 3.5 Blind Arcs: 30—									
					Visibility: 8 Internal Fuel: 875									
					Size: −1 AtA Refuel: No									
					Vulnerability: +0 Ejection Seat: Std									
Speeds and Ceilings							Climb Capabilities							
Alt. Band	Conf. Ceil.	CL 48	1/2 42	DT 35	Dive Speed	CL AB	Oth	1/2 AB	Oth	DT AB	Oth			
EH+	46+	3.0 – 5.0	—	—	6.0	—	0.5	—	—	—	—	EH+		
VH	36–45	2.5 – 5.5	3.0 – 5.0	—	6.0	—	0.5	—	0.5	—	—	VH		
HI	26–35	2.5 – 5.5	2.5 – 5.5	3.0 – 5.0	6.5	—	0.5	—	0.5	—	0.5	HI		
MH	17–25	2.0 – 5.0	2.5 – 5.0	2.5 – 5.0	6.5	—	1.0	—	0.5	—	0.5	MH		
ML	8–16	2.0 – 5.0	2.0 – 5.0	2.5 – 4.5	6.5	—	1.0	—	1.0	—	0.5	ML		
LO	0–7	1.5 – 5.0	2.0 – 5.0	2.0 – 4.5	6.5	—	1.0	—	1.0	—	1.0	LO		

Radar: APW-11 ECCM: 0 Arcs: 180+ Search: Gr. Nav. (90) Track: Gr. Attack (30) Lock-On: 7	ECM: IFF RWR: — DDS: — DJM: — AJM: — BJM: —	Weapon Stations Diagram:															
Guns: Four 20 mm M39 To Hit: 4/2/1 Ammunition: 8.0 Gunsight: TT+1/HT+2/BT+3 Ranging: — AtA/AtG: 5/7*	Technology: None	Load Point Limits: CL : 0–8 1/2: 9–15 Weight Limit: 12,000 DT : 16+															
Bomb System: Manual		<table border="1"> <thead> <tr> <th>Station</th> <th>Limit</th> <th>Allowed Loads</th> </tr> </thead> <tbody> <tr> <td>1 and 11</td> <td>2,200</td> <td>FT</td> </tr> <tr> <td>2–3 and 9–10</td> <td>250</td> <td>BB RP RK</td> </tr> <tr> <td>4–5 and 7–8</td> <td>750</td> <td>BB RP RK</td> </tr> <tr> <td>6</td> <td>6,000</td> <td>BB</td> </tr> </tbody> </table>	Station	Limit	Allowed Loads	1 and 11	2,200	FT	2–3 and 9–10	250	BB RP RK	4–5 and 7–8	750	BB RP RK	6	6,000	BB
Station	Limit	Allowed Loads															
1 and 11	2,200	FT															
2–3 and 9–10	250	BB RP RK															
4–5 and 7–8	750	BB RP RK															
6	6,000	BB															
Notes: 1. 2. High transonic drag (HTD). Low roll rate (LRR). 3. Tail Warning Radar. APS-54 with ECCM of 0, arc of 30—, and search capability of 30–10. The radar has no tracking capability.		Load Notes: 1. Station 6 is the internal bomb bay. It can carry six illumination flares and either (a) six 1,000 lb BB, (b) eight 750 lb BB, (c) nine 500 lb BB, or (d) twelve 250 lb BB. All BB must be HE type. 2. Stations 2 to 5 and 7 to 10 can each carry two RKs.															
		VPs: 16/11/5/3															

Radar: RB-1A ECCM: 0 Arcs: 180+ Search: Gr. Nav. (180) Track: Gr. Attack (60) Lock-On: 7	ECM: IFF RWR: — DDS: — DJM: — AJM: — BJM: —	Weapon Stations Diagram:															
Guns: Four 20 mm M39 To Hit: 4/2/1 Ammunition: 8.0 Gunsight: TT+1/HT+2/BT+3 Ranging: — AtA/AtG: 5/7*	Technology: None	Load Point Limits: CL : 0–8 1/2: 9–15 Weight Limit: 12,000 DT : 16+															
Bomb System: Manual		<table border="1"> <thead> <tr> <th>Station</th> <th>Limit</th> <th>Allowed Loads</th> </tr> </thead> <tbody> <tr> <td>1 and 11</td> <td>2,200</td> <td>FT</td> </tr> <tr> <td>2–3 and 9–10</td> <td>250</td> <td>BB RP RK</td> </tr> <tr> <td>4–5 and 7–8</td> <td>750</td> <td>BB RP RK FT</td> </tr> <tr> <td>6</td> <td>6,000</td> <td>BB</td> </tr> </tbody> </table>	Station	Limit	Allowed Loads	1 and 11	2,200	FT	2–3 and 9–10	250	BB RP RK	4–5 and 7–8	750	BB RP RK FT	6	6,000	BB
Station	Limit	Allowed Loads															
1 and 11	2,200	FT															
2–3 and 9–10	250	BB RP RK															
4–5 and 7–8	750	BB RP RK FT															
6	6,000	BB															
Notes: 1. 2. High transonic drag (HTD). Low roll rate (LRR). 3. Tail Warning Radar. APS-54 with ECCM of 0, arc of 30—, and search capability of 30–10. The radar has no tracking capability.		Load Notes: 1. Station 6 is the internal bomb bay. It can carry six illumination flares and either (a) six 1,000 lb BB, (b) eight 750 lb BB, (c) nine 500 lb BB, or (d) twelve 250 lb BB. All BB must be HE type. 2. Stations 2 to 5 and 7 to 10 can each carry two RKs.															
		VPs: 16/11/5/3															
		v2 0000000 0000-00-00T00:00:00															

Radar: APW-11 ECCM: 0 Arcs: 180+ Search: Gr. Nav. (90) Track: Gr. Attack (30) Lock-On: 7	ECM: IFF RWR: A DDS: A DJM: — AJM: — BJM: —	Weapon Stations Diagram:															
Guns: — To Hit: — Ammunition: — Gunsight: TT+1/HT+2/BT+3 Ranging: — AtA/AtG: —	Technology: TV/IR Optics and Laser Designator – A																
Bomb System: Computed	Load Point Limits: CL : 0–8 1/2: 9–15 Weight Limit: 12,000 DT : 16+	<table border="1"> <thead> <tr> <th>Station</th> <th>Limit</th> <th>Allowed Loads</th> </tr> </thead> <tbody> <tr> <td>1 and 11</td> <td>2,200</td> <td>FT</td> </tr> <tr> <td>2–3 and 9–10</td> <td>250</td> <td>BB RP RK</td> </tr> <tr> <td>4–5 and 7–8</td> <td>750</td> <td>BB RP RK BG</td> </tr> <tr> <td>6</td> <td>6,000</td> <td>BB</td> </tr> </tbody> </table>	Station	Limit	Allowed Loads	1 and 11	2,200	FT	2–3 and 9–10	250	BB RP RK	4–5 and 7–8	750	BB RP RK BG	6	6,000	BB
Station	Limit	Allowed Loads															
1 and 11	2,200	FT															
2–3 and 9–10	250	BB RP RK															
4–5 and 7–8	750	BB RP RK BG															
6	6,000	BB															
Notes: 1. 2. High transonic drag (HTD). Low roll rate (LRR). 3. Tail Warning Radar. APS-54 with ECCM of 0, arc of 30—, and search capability of 30–10. The radar has no tracking capability.		Load Notes: 1. Station 6 is the internal bomb bay. It can carry six illumination flares and either (a) six 1,000 lb BB, (b) eight 750 lb BB, (c) nine 500 lb BB, or (d) twelve 250 lb BB. All BB must be HE type. 2. Stations 2 to 5 and 7 to 10 can each carry two RKs.															
VPs: 20/13/7/3		v2 0000000 0000-00-00T00:00:00															