

Mikoyan-Gurevich MiG-21

- MiG-21F
- MiG-21F-13
- MiG-21PF
- MiG-21PFM
- MiG-21FL
- MiG-21S
- MiG-21M
- MiG-21SM
- MiG-21MF
- MiG-21bis

MiG-21F										Crew: Pilot			
										Maneuver HFPs/DPs:			
Power APs/DPs/FPs: ○										LR/DR	1.0	1.0	
AB 3.0 3.0 2.5 5.0										VR	0.0		
M 2.0 2.0 1.5 2.0										Turn DPs:			
N 0.0 0.0 0.0 1.0										CL	1/2	DT	
I 0.5 0.5 0.5 0.0										TT	1.0	1.0	1.0
SPBR 0.5 0.5 1.0 —										HT	2.0	2.0	2.0
										BT	3.0	4.0	4.0
										ET	4.0	—	—

MiG-21F-13								Crew: Pilot			
Power APs/DPs/FPs: ○								Maneuver HFPs/DPs:			
AB 3.0 3.0 2.5 5.0 M 2.0 2.0 1.5 2.0 N 0.0 0.0 0.0 1.0 I 0.5 0.5 0.5 0.0 SPBR 0.5 0.5 1.0 —								LR/DR	1.0	1.0	
								VR	0.0		
				Turn DPs:							
				CL 1/2 DT				CL	1/2	DT	
				TT 1.0 1.0 1.0				TT	1.0	1.0	
				HT 2.0 2.0 2.0				HT	2.0	2.0	
				BT 3.0 4.0 4.0				BT	3.0	4.0	
				ET 4.0 — —				ET	4.0	—	
				Cruise Speed: 6.0 Restr. Arcs: 180L Climb Speed: 4.5 Blind Arcs: 30– Visibility: 5 Internal Fuel: 200 Size: +0 AtA Refuel: No Vulnerability: -2 Ejection Seat: Std							
Speeds and Ceilings											
Alt. Band	Conf. Ceil.	CL	1/2	DT	Dive Speed	CL AB Oth	1/2 AB Oth	DT AB Oth	Alt. Band		
EH+	46+	3.5 – 11.0	3.5 – 10.0	4.0 – 9.0	12.0	1.0 0.5	1.0 0.5	1.0 0.5	EH+		
VH	36–45	3.0 – 12.0	3.0 – 11.0	3.5 – 10.0	12.0	1.0 0.5	1.0 0.5	1.0 0.5	VH		
HI	26–35	2.5 – 10.0	3.0 – 9.0	3.0 – 8.0	11.0	2.0 1.0	2.0 0.5	1.5 0.5	HI		
MH	17–25	2.0 – 9.0	2.5 – 8.0	2.5 – 7.5	10.0	2.0 1.0	2.0 1.0	1.5 0.5	MH		
ML	8–16	2.0 – 7.5	2.0 – 7.5	2.5 – 7.0	8.0	3.0 1.5	3.0 1.0	2.0 1.0	ML		
LO	0–7	1.5 – 6.5	2.0 – 6.5	2.0 – 6.5	7.0	4.0 2.0	3.0 1.0	2.0 1.0	LO		
Radar: SRD-5ND Kvant ECCM: 0 Arcs: Limited Search: — Track: 10–6 Lock-On: 5				ECM: IFF RWR: — DDS: — DJM: — AJM: — BJM: —				Weapon Stations Diagram:			
Guns: One 30 mm NR-30 To Hit: 4/2/1 Ammunition: 2.0 Gunsight: TT+0/HT+2/BT+3 Ranging: RE AtA/AtG: 4/3				Technology: None				Load Point Limits: CL : 0–2 1/2: 3–4			
								Weight Limit: 2,200 DT : 5+			
				Station Limit Allowed Loads 1 and 3 550 BB RP RK DR IRM 2 1,100 FT							
				Load Notes: 1. From 1961, may use AA-2 IRMs.							
Bomb System: Manual											
Notes:											
1. The Mikoyan-Gurevich MiG-21F-13 is a day fighter. This is an improved version of the MiG-21F, with provision for AA-2 IRMs, but with only one NR-30 gun and still without a search radar. The NATO reporting name for the aircraft is Fishbed-C and for the radar is High Fix. 2. The thick front canopy gives a +1 modifier to sighting rolls for targets in the 180+ arc.											
VPs: 16/11/5/3								v1.0000000 0000-00-00T00:00:00			

MiG-21PF					Crew: Pilot				
					Maneuver HFPs/DPs:				
Power APs/DPs/FPs: ○					LR/DR	1.0	1.0		
					VR	0.0			
					Turn DPs:				
					CL	1/2	DT		
					TT	1.0	1.0	1.0	
					HT	2.0	2.0	2.0	
					BT	3.0	4.0	4.0	
					ET	4.0	—	—	

MiG-21PFM										Crew: Pilot								
										Maneuver HFPs/DPs:								
Power APs/DPs/FPs: ○										LR/DR	1.0	1.0						
AB 3.0 3.0 2.5 5.0										VR	0.0							
M 2.0 2.0 1.5 2.0										Turn DPs:								
N 0.0 0.0 0.0 1.0										CL	1/2	DT						
I 0.5 0.5 0.5 0.0										TT	1.0/2.0	1.0/2.0	1.0/2.0					
SPBR 0.5 0.5 1.0 —										HT	2.0/3.0	2.0/3.0	3.0/4.0					
										BT	3.0/4.0	4.0/5.0	4.0/5.0					
										ET	4.0/5.0	—	—					
										Selectable combat flaps. If selected and speed ≤ 4.5, use higher drag and reduce minimum speeds by 0.5.								
Speeds and Ceilings												Climb Capabilities						
Alt. Band	Conf. Ceil.	CL 58	1/2 56	DT 54	Dive Speed	CL AB Oth	1/2 AB Oth	DT AB Oth	Alt. Band									
EH+	46+	3.5 – 11.0	3.5 – 10.0	4.0 – 9.0	12.0	1.0 0.5	1.0 0.5	1.0 0.5	EH+									
VH	36–45	3.0 – 12.0	3.0 – 11.0	3.5 – 10.0	12.0	1.0 0.5	1.0 0.5	1.0 0.5	VH									
HI	26–35	2.5 – 10.0	3.0 – 9.0	3.0 – 8.0	11.0	2.0 1.0	2.0 0.5	1.5 0.5	HI									
MH	17–25	2.0 – 9.0	2.5 – 8.0	2.5 – 7.5	10.0	2.0 1.0	2.0 1.0	1.5 0.5	MH									
ML	8–16	2.0 – 7.5	2.0 – 7.5	2.5 – 7.0	8.0	3.0 1.5	3.0 1.0	2.0 1.0	ML									
LO	0–7	1.5 – 6.5	2.0 – 6.5	2.0 – 6.5	7.0	4.0 2.0	3.0 1.0	2.0 1.0	LO									
Radar: RP-21M Sapfir				ECM:	IFF	Weapon Stations Diagram:												
ECCM:	0			RWR:	A													
Arcts:	180+			DDS:	—													
Search:	30–6			DJM:	—													
Track:	18–6			AJM:	—													
Lock-On:	7			BJM:	—													
Guns: —				Technology: None		Load Point Limits: CL : 0–2 1/2: 3–4												
To Hit:	—																	
Ammunition:	—					Weight Limit: 2,200 DT : 5+												
Gunsight:	TT+0/HT+2/BT+3																	
Ranging:	RE			Station Limit Allowed Loads														
AtA/AtG:	—									1 and 3	550 BB RP RK DR BRM IRM							
Bomb System: Manual										2	1,100 FT GP							
Notes:																		
1. The Mikoyan-Gurevich MiG-21PFM is an all-weather interceptor. It is a development of the MiG-21PF with blown flaps, improved RP-21M radar, the capability to carry the GP-9 gun pod, and from 1966 the capability to carry the Kh-66 ASM. The NATO reporting name for the aircraft is Fishbed-F and for the radar is Spin Scan-A.																		
2. The thick front canopy gives a +1 modifier to sighting rolls for targets in the 180+ arc.																		
VPs: 18/12/6/3										v1.0000000 0000-00-00T00:00:00								

MiG-21FL					Crew: Pilot				
					Maneuver HFPs/DPs:				
Power APs/DPs/FPs: ○					LR/DR	1.0	1.0		
					VR	0.0			
					Turn DPs:				
					CL	1/2	DT		
					TT	1.0	1.0	1.0	
					HT	2.0	2.0	2.0	
					BT	3.0	4.0	4.0	
					ET	4.0	—	—	

MiG-21S										Crew: Pilot		
					Maneuver HFPs/DPs:					LR/DR 1.0 1.0 VR 0.0		
Power APs/DPs/FPs: ○					Turn DPs:					CL 1/2 DT TT 1.0/2.0 1.0/2.0 1.0/2.0 HT 2.0/3.0 2.0/3.0 3.0/4.0 BT 4.0/5.0 4.0/5.0 4.0/5.0 ET 4.0/5.0 5.0/6.0 —		
CL 1/2 DT Fuel					Cruise Speed: 6.0 Restr. Arcs: 180L Climb Speed: 4.5 Blind Arcs: 30– Visibility: 5 Internal Fuel: 220 Size: +0 AtA Refuel: No Vulnerability: -2 Ejection Seat: Std					Selectable combat flaps. If selected and speed ≤ 4.5, use higher drag and reduce minimum speeds by 0.5.		
Speeds and Ceilings					Climb Capabilities							
Alt. Band	Conf. Ceil.	CL 56	1/2 50	DT 44	Dive Speed	CL AB Oth	1/2 AB Oth	DT AB Oth	Alt. Band			
EH+	46+	4.0 – 11.0	4.5 – 10.0	—	12.0	1.0 0.5	1.0 0.5	— —	EH+			
VH	36–45	3.5 – 12.0	4.0 – 11.0	5.0 – 9.0	12.0	1.0 0.5	1.0 0.5	1.0 0.5	VH			
HI	26–35	3.0 – 10.5	3.5 – 9.0	4.0 – 8.0	12.0	2.0 0.5	1.0 0.5	1.0 0.5	HI			
MH	17–25	2.5 – 9.0	3.0 – 8.0	3.0 – 7.0	10.0	3.0 1.0	2.0 1.0	1.5 0.5	MH			
ML	8–16	2.0 – 8.5	2.5 – 7.5	2.5 – 6.5	9.0	4.0 1.0	3.0 1.0	1.5 0.5	ML			
LO	0–7	2.0 – 8.0	2.0 – 7.0	2.5 – 6.0	8.5	4.0 2.0	3.0 1.0	2.0 1.0	LO			
Radar: RP-22 Saphir		ECM: IFF		Weapon Stations Diagram:								
ECCM:	0	RWR:	A									
Arcts:	180+	DDS:	—									
Search:	48–12	DJM:	—									
Track:	30–8	AJM:	—									
Lock-On:	7	BJM:	—									
Guns: —		Technology:		Load Point Limits:						CL : 0–4 1/2: 5–6		
To Hit:	—	None		Weight Limit: 4,400						DT : 7+		
Ammunition:	—			Station 1 and 5 Limit 550 BB RP RK EP FT BRM IRM RHM								
Gunsight:	TT+0/HT+2/BT+3			2 and 4 1,100 BB RP RK FT DR IRM								
Ranging:	RE			3 1,100 EP PP FT GP								
AtA/AtG:	—			Load Notes:								
Bomb System: Manual				1. May use AA-1 BRMs, AA-2 IRMs, and AA-2C RHMs. 2. Station 3 may carry a GP-9 gun pod.								
Notes:												
1. The Mikoyan-Gurevich MiG-21S is an all-weather interceptor. It is equipped with the RP-22 radar and is able to use the AA-2 IRMs and RHMs and AA-1 BRMs. It has internal guns, but is able to mount a GP-9 gun pod. The NATO reporting name for the aircraft is Fishbed-J and for the radar is Jay Bird. 2. The thick front canopy gives a +1 modifier to sighting rolls for targets in the 180+ arc.												
					VPs: 22/15/7/4					v1.000000 0000-00-00T00:00:00		

MiG-21M										Crew: Pilot																																																																																
					Maneuver HFPs/DPs:					LR/DR 1.0 1.0																																																																																
Power APs/DPs/FPs: ○					VR 0.0																																																																																					
<table border="1"> <thead> <tr> <th></th><th>CL</th><th>1/2</th><th>DT</th><th>Fuel</th></tr> </thead> <tbody> <tr> <td>AB</td><td>3.0</td><td>2.5</td><td>2.0</td><td>5.0</td></tr> <tr> <td>M</td><td>1.5</td><td>1.0</td><td>1.0</td><td>2.0</td></tr> <tr> <td>N</td><td>0.0</td><td>0.0</td><td>0.0</td><td>1.0</td></tr> <tr> <td>I</td><td>0.5</td><td>0.5</td><td>1.0</td><td>0.0</td></tr> <tr> <td>SPBR</td><td>0.5</td><td>1.0</td><td>1.0</td><td>—</td></tr> </tbody> </table>						CL	1/2	DT	Fuel	AB	3.0	2.5	2.0	5.0	M	1.5	1.0	1.0	2.0	N	0.0	0.0	0.0	1.0	I	0.5	0.5	1.0	0.0	SPBR	0.5	1.0	1.0	—	<table border="1"> <thead> <tr> <th></th><th>Cruise Speed:</th><th>6.0</th><th>Restr. Arcs:</th><th>180L 60-</th></tr> </thead> <tbody> <tr> <td></td><td>Climb Speed:</td><td>4.5</td><td>Blind Arcs:</td><td>30-</td></tr> <tr> <td></td><td>Visibility:</td><td>5</td><td>Internal Fuel:</td><td>220</td></tr> <tr> <td></td><td>Size:</td><td>+0</td><td>AtA Refuel:</td><td>No</td></tr> <tr> <td></td><td>Vulnerability:</td><td>-2</td><td>Ejection Seat:</td><td>Std</td></tr> </tbody> </table>						Cruise Speed:	6.0	Restr. Arcs:	180L 60-		Climb Speed:	4.5	Blind Arcs:	30-		Visibility:	5	Internal Fuel:	220		Size:	+0	AtA Refuel:	No		Vulnerability:	-2	Ejection Seat:	Std	Turn DPs:																									
	CL	1/2	DT	Fuel																																																																																						
AB	3.0	2.5	2.0	5.0																																																																																						
M	1.5	1.0	1.0	2.0																																																																																						
N	0.0	0.0	0.0	1.0																																																																																						
I	0.5	0.5	1.0	0.0																																																																																						
SPBR	0.5	1.0	1.0	—																																																																																						
	Cruise Speed:	6.0	Restr. Arcs:	180L 60-																																																																																						
	Climb Speed:	4.5	Blind Arcs:	30-																																																																																						
	Visibility:	5	Internal Fuel:	220																																																																																						
	Size:	+0	AtA Refuel:	No																																																																																						
	Vulnerability:	-2	Ejection Seat:	Std																																																																																						
					<table border="1"> <thead> <tr> <th></th><th>CL</th><th>1/2</th><th>DT</th><th></th></tr> </thead> <tbody> <tr> <td>TT</td><td>1.0/2.0</td><td>1.0/2.0</td><td>1.0/2.0</td><td></td></tr> <tr> <td>HT</td><td>2.0/3.0</td><td>2.0/3.0</td><td>3.0/4.0</td><td></td></tr> <tr> <td>BT</td><td>4.0/5.0</td><td>4.0/5.0</td><td>4.0/5.0</td><td></td></tr> <tr> <td>ET</td><td>4.0/5.0</td><td>5.0/6.0</td><td>—</td><td></td></tr> </tbody> </table>						CL	1/2	DT		TT	1.0/2.0	1.0/2.0	1.0/2.0		HT	2.0/3.0	2.0/3.0	3.0/4.0		BT	4.0/5.0	4.0/5.0	4.0/5.0		ET	4.0/5.0	5.0/6.0	—																																																									
	CL	1/2	DT																																																																																							
TT	1.0/2.0	1.0/2.0	1.0/2.0																																																																																							
HT	2.0/3.0	2.0/3.0	3.0/4.0																																																																																							
BT	4.0/5.0	4.0/5.0	4.0/5.0																																																																																							
ET	4.0/5.0	5.0/6.0	—																																																																																							
					Selectable combat flaps. If selected and speed ≤ 4.5, use higher drag and reduce minimum speeds by 0.5.																																																																																					
<table border="1"> <thead> <tr> <th colspan="5">Speeds and Ceilings</th><th colspan="5">Climb Capabilities</th></tr> <tr> <th>Alt. Band</th><th>Conf. Ceil.</th><th>CL</th><th>1/2</th><th>DT</th><th>Dive Speed</th><th>CL AB Oth</th><th>1/2 AB Oth</th><th>DT AB Oth</th><th>Alt. Band</th></tr> </thead> <tbody> <tr> <td>EH+</td><td>46+</td><td>4.0 – 11.0</td><td>4.5 – 10.0</td><td>—</td><td>12.0</td><td>1.0 0.5</td><td>1.0 0.5</td><td>— —</td><td>EH+</td></tr> <tr> <td>VH</td><td>36–45</td><td>3.5 – 12.0</td><td>4.0 – 11.0</td><td>5.0 – 9.0</td><td>12.0</td><td>1.0 0.5</td><td>1.0 0.5</td><td>1.0 0.5</td><td>VH</td></tr> <tr> <td>HI</td><td>26–35</td><td>3.0 – 10.5</td><td>3.5 – 9.0</td><td>4.0 – 8.0</td><td>12.0</td><td>2.0 0.5</td><td>1.0 0.5</td><td>1.0 0.5</td><td>HI</td></tr> <tr> <td>MH</td><td>17–25</td><td>2.5 – 9.0</td><td>3.0 – 8.0</td><td>3.0 – 7.0</td><td>10.0</td><td>3.0 1.0</td><td>2.0 1.0</td><td>1.5 0.5</td><td>MH</td></tr> <tr> <td>ML</td><td>8–16</td><td>2.0 – 8.5</td><td>2.5 – 7.5</td><td>2.5 – 6.5</td><td>9.0</td><td>4.0 1.0</td><td>3.0 1.0</td><td>1.5 0.5</td><td>ML</td></tr> <tr> <td>LO</td><td>0–7</td><td>2.0 – 8.0</td><td>2.0 – 7.0</td><td>2.5 – 6.0</td><td>8.5</td><td>4.0 2.0</td><td>3.0 1.0</td><td>2.0 1.0</td><td>LO</td></tr> </tbody> </table>	Speeds and Ceilings									Climb Capabilities					Alt. Band	Conf. Ceil.	CL	1/2	DT	Dive Speed	CL AB Oth	1/2 AB Oth	DT AB Oth	Alt. Band	EH+	46+	4.0 – 11.0	4.5 – 10.0	—	12.0	1.0 0.5	1.0 0.5	— —	EH+	VH	36–45	3.5 – 12.0	4.0 – 11.0	5.0 – 9.0	12.0	1.0 0.5	1.0 0.5	1.0 0.5	VH	HI	26–35	3.0 – 10.5	3.5 – 9.0	4.0 – 8.0	12.0	2.0 0.5	1.0 0.5	1.0 0.5	HI	MH	17–25	2.5 – 9.0	3.0 – 8.0	3.0 – 7.0	10.0	3.0 1.0	2.0 1.0	1.5 0.5	MH	ML	8–16	2.0 – 8.5	2.5 – 7.5	2.5 – 6.5	9.0	4.0 1.0	3.0 1.0	1.5 0.5	ML	LO	0–7	2.0 – 8.0	2.0 – 7.0	2.5 – 6.0	8.5	4.0 2.0	3.0 1.0	2.0 1.0	LO						
Speeds and Ceilings					Climb Capabilities																																																																																					
Alt. Band	Conf. Ceil.	CL	1/2	DT	Dive Speed	CL AB Oth	1/2 AB Oth	DT AB Oth	Alt. Band																																																																																	
EH+	46+	4.0 – 11.0	4.5 – 10.0	—	12.0	1.0 0.5	1.0 0.5	— —	EH+																																																																																	
VH	36–45	3.5 – 12.0	4.0 – 11.0	5.0 – 9.0	12.0	1.0 0.5	1.0 0.5	1.0 0.5	VH																																																																																	
HI	26–35	3.0 – 10.5	3.5 – 9.0	4.0 – 8.0	12.0	2.0 0.5	1.0 0.5	1.0 0.5	HI																																																																																	
MH	17–25	2.5 – 9.0	3.0 – 8.0	3.0 – 7.0	10.0	3.0 1.0	2.0 1.0	1.5 0.5	MH																																																																																	
ML	8–16	2.0 – 8.5	2.5 – 7.5	2.5 – 6.5	9.0	4.0 1.0	3.0 1.0	1.5 0.5	ML																																																																																	
LO	0–7	2.0 – 8.0	2.0 – 7.0	2.5 – 6.0	8.5	4.0 2.0	3.0 1.0	2.0 1.0	LO																																																																																	
Radar: RP-21MA Sapfir			ECM:	IFF	Weapon Stations Diagram:																																																																																					
ECCM:	0		RWR:	A																																																																																						
Arcts:	180+		DDS:	—																																																																																						
Search:	35–8		DJM:	—																																																																																						
Track:	24–8		AJM:	—																																																																																						
Lock-On:	7		BJM:	—																																																																																						
Guns: 23 mm GSh-23			Technology: None		Load Point Limits:					CL : 0–4																																																																																
To Hit:	7/4/2				1/2: 5–6																																																																																					
Ammunition:	2.0				Weight Limit: 4,400					DT : 7+																																																																																
Gunsight:	TT+0/HT+2/BT+3																																																																																									
Ranging:	RE				Station					Allowed Loads																																																																																
AtA/AtG:	5/5				1 and 5	550	BB	RP	RK	EP	FT	IRM																																																																														
Bomb System: Manual					2 and 4	1,100	BB	RP	RK	FT	DR	IRM																																																																														
										3	1,100	EP	PP	FT																																																																												
Notes:										Load Notes:																																																																																
1. The Mikoyan-Gurevich MiG-21M is an all-weather interceptor. It is an export version of the MiG-21S, with the RP-21MA radar instead of the RP-22 and armed with an internal GSh-23L gun and AA-2 IRMs. The NATO reporting name for the aircraft is Fishbed-J and for the radar is Spin Scan-B.										1. From 1961, may use AA-2 IRMs.																																																																																
2. The thick front canopy gives a +1 modifier to sighting rolls for targets in the 180+ arc.																																																																																										
										VPs: 22/15/7/4																																																																																
										v1.0000000 0000-00-00T00:00:00																																																																																

MiG-21SM					Crew: Pilot										
					Maneuver HFPs/DPs:										
Power APs/DPs/FPs: ○					LR/DR	1.0	1.0								
CL 1/2 DT Fuel					VR	0.0									
AB	3.5	2.5	2.5	6.0											
M	1.5	1.0	1.0	2.0											
N	0.0	0.0	0.0	1.0											
I	0.5	0.5	1.0	0.0											
SPBR	0.5	1.0	1.0	—											
					Cruise Speed:	6.0	Restr. Arcs:	180L 60–							
					Climb Speed:	4.5	Blind Arcs:	30–							
					Visibility:	5	Internal Fuel:	220							
					Size:	+0	AtA Refuel:	No							
					Vulnerability:	-2	Ejection Seat:	Std							
					Selectable combat flaps. If selected and speed ≤ 4.5, use higher drag and reduce minimum speeds by 0.5.										
Speeds and Ceilings															
Alt. Band	Conf. Ceil.	CL 56	1/2 50	DT 44	Dive Speed	CL AB Oth	1/2 AB Oth	DT AB Oth	Alt. Band						
EH+	46+	4.0 – 11.0	4.5 – 10.0	—	12.0	1.0 0.5	1.0 0.5	— —	EH+						
VH	36–45	3.5 – 12.0	4.0 – 11.0	5.0 – 9.0	12.0	1.0 0.5	1.0 0.5	1.0 0.5	VH						
HI	26–35	3.0 – 10.5	3.5 – 9.0	4.0 – 8.0	12.0	2.0 0.5	1.0 0.5	1.0 0.5	HI						
MH	17–25	2.5 – 9.0	3.0 – 8.0	3.0 – 7.0	10.0	3.0 1.0	2.0 1.0	1.5 0.5	MH						
ML	8–16	2.0 – 8.5	2.5 – 7.5	2.5 – 6.5	9.0	4.0 1.0	3.0 1.0	1.5 0.5	ML						
LO	0–7	2.0 – 8.0	2.0 – 7.0	2.5 – 6.0	8.5	4.0 2.0	3.0 1.0	2.0 1.0	LO						
Radar: RP-22 Saphir			ECM:	IFF	Weapon Stations Diagram:										
ECCM:	0		RWR:	A											
Arcts:	180+		DDS:	—											
Search:	48–12		DJM:	—											
Track:	30–8		AJM:	—											
Lock-On:	7		BJM:	—											
Guns: 23 mm GSh-23			Technology:		Load Point Limits:										
To Hit:	7/4/2		None		CL : 0–4										
Ammunition:	2.0				1/2: 5–6										
Gunsight:	TT+0/HT+2/BT+3				Weight Limit: 4,400										
Ranging:	RE				DT : 7+										
AtA/AtG:	5/5				Station	Limit	Allowed Loads								
Bomb System:	Manual				1 and 5	550	BB	RP	RK EP FT IRM RHM						
Notes:					2 and 4	1,100	BB	RP	RK FT DR IRM						
1. The Mikoyan-Gurevich MiG-21SM is an all-weather interceptor. It is an improved version of the MiG-21S, with a new engine and an internal GSh-21L cannon. The NATO reporting name for the aircraft is Fishbed-J and for the radar is Jay Bird. 2. The thick front canopy gives a +1 modifier to sighting rolls for targets in the 180+ arc.					3	1,100	EP	PP	FT						
Load Notes:															
1. From 1961, may use AA-2 IRMs. From 1966, may use AA-2C RHMs.															
VPs: 24/16/8/4								v1.0000000 0000-00-00T00:00:00							

MiG-21MF										Crew: Pilot									
										Maneuver HFPs/DPs:									
Power APs/DPs/FPs: ○										LR/DR	1.0	1.0							
AB 3.5 2.5 2.5 6.0										VR	0.0								
M 1.5 1.0 1.0 2.0										Turn DPs:									
N 0.0 0.0 0.0 1.0										CL	1/2	DT							
I 0.5 0.5 1.0 0.0										TT	1.0/2.0	1.0/2.0	1.0/2.0						
SPBR 0.5 1.0 1.0 —										HT	2.0/3.0	2.0/3.0	3.0/4.0						
										BT	4.0/5.0	4.0/5.0	4.0/5.0						
										ET	4.0/5.0	5.0/6.0	—						
										Selectable combat flaps. If selected and speed ≤ 4.5, use higher drag and reduce minimum speeds by 0.5.									
Speeds and Ceilings												Climb Capabilities							
Alt. Band	Conf. Ceil.	CL 56	1/2 50	DT 44	Dive Speed	CL AB Oth	1/2 AB Oth	DT AB Oth	Alt. Band										
EH+	46+	4.0 – 11.0	4.5 – 10.0	—	12.0	1.0 0.5	1.0 0.5	— —	EH+										
VH	36–45	3.5 – 12.0	4.0 – 11.0	5.0 – 9.0	12.0	1.0 0.5	1.0 0.5	1.0 0.5	VH										
HI	26–35	3.0 – 10.5	3.5 – 9.0	4.0 – 8.0	12.0	2.0 0.5	1.0 0.5	1.0 0.5	HI										
MH	17–25	2.5 – 9.0	3.0 – 8.0	3.0 – 7.0	10.0	3.0 1.0	2.0 1.0	1.5 0.5	MH										
ML	8–16	2.0 – 8.5	2.5 – 7.5	2.5 – 6.5	9.0	4.0 1.0	3.0 1.0	1.5 0.5	ML										
LO	0–7	2.0 – 8.0	2.0 – 7.0	2.5 – 6.0	8.5	4.0 2.0	3.0 1.0	2.0 1.0	LO										
Radar: RP-22 Saphir				ECM: IFF		Weapon Stations Diagram:													
ECCM: 0				RWR: A															
Arcs: 180+				DDS: —															
Search: 48–12				DJM: —															
Track: 30–8				AJM: —															
Lock-On: 7				BJM: —															
Guns: 23 mm GSh-23				Technology: None		Load Point Limits:													
To Hit: 7/4/2						CL : 0–4													
Ammunition: 2.0						1/2: 5–6													
Gunsight: TT+0/HT+2/BT+3						Weight Limit: 4,400													
Ranging: RE						DT : 7+													
AtA/AtG: 5/5						Station Limit Allowed Loads													
Bomb System: Manual				1 and 5		1 and 5 550 BB RP RK EP FT MDR IRM													
				2 and 4		2 and 4 1,100 BB RP RK FT DR MDR IRM													
				3		3 1,100 EP PP FT													
Notes:																			
1. The Mikoyan-Gurevich MiG-21MF is an all-weather interceptor. It is an export version of the MiG-21SM. The NATO reporting name for the aircraft is Fishbed-J and for the radar is Jay Bird.																			
2. The thick front canopy gives a +1 modifier to sighting rolls for targets in the 180+ arc.																			
VPs: 24/16/8/4										v1.0000000 0000-00-00T00:00:00									

MiG-21bis					Crew: Pilot										
					Maneuver HFPs/DPs:										
Power APs/DPs/FPs: ○					LR/DR	1.0	1.0								
					VR	0.0									
					Turn DPs:										
					CL	1/2	DT								
					TT	1.0/2.0	1.0/2.0	2.0/3.0							
					HT	2.0/3.0	2.0/3.0	3.0/4.0							
					BT	4.0/5.0	4.0/5.0	—							
					ET	4.0/5.0	—	—							
					Selectable combat flaps. If selected and speed ≤ minimum + 2.5, use higher drag and reduce minimum speeds by 0.5.										
Speeds and Ceilings															
Alt. Band	Conf. Ceil.	CL 56	1/2 48	DT 44	Dive Speed	CL AB Oth	1/2 AB Oth	DT AB Oth	Alt. Band						
EH+	46+	4.5 – 13.5	5.0 – 10.5	—	13.5	2.0 1.0	1.0 0.5	— —	EH+						
VH	36–45	3.5 – 13.0	4.0 – 11.0	4.0 – 6.5	13.5	3.0 1.0	2.0 1.0	1.0 —	VH						
HI	26–35	3.0 – 13.0	3.0 – 11.5	3.5 – 6.5	13.5	5.0 1.5	4.0 1.0	1.5 0.5	HI						
MH	17–25	2.5 – 11.5	3.0 – 11.0	3.0 – 6.5	11.0	6.0 2.0	5.0 2.0	2.0 1.0	MH						
ML	8–16	2.5 – 9.5	2.5 – 9.5	2.5 – 7.0	9.5	6.0 2.0	6.0 2.0	3.0 1.0	ML						
LO	0–7	2.0 – 8.5	2.0 – 8.0	2.5 – 7.5	8.5	7.0 3.0	6.0 3.0	4.0 1.5	LO						
Radar: RP-22 Saphir-21		ECM:	IFF	Weapon Stations Diagram:											
ECCM:	0	RWR:	B												
Arcs:	180+	DDS:	—												
Search:	54–12	DJM:	—												
Track:	36–8	AJM:	—												
Lock-On:	7	BJM:	—												
Guns: 23 mm GSh-23		Technology:			Load Point Limits:										
To Hit:	6/3/1	None			CL : 0–2 1/2: 3–4										
Ammunition:	2.0				Weight Limit: 3,930 DT : 5+										
Gunsight:	TT+0/HT+1/BT+2				Station	Limit	Allowed Loads								
Ranging:	RE				1 and 5	1,100	BB RP RK MDR IRM RHM FT								
AtA/AtG:	5/5				2 and 4	550	BB RP RK MDR IRM RHM								
Bomb System: Manual					3	1,100	GP FT								
Notes:															
1. The Mikoyan-Gurevich MiG-21bis is an all-weather interceptor. It is a development of the MiG-21SM with an improved engine. The NATO reporting name for the aircraft is Fishbed-L/N and for the radar is Jay Bird.															
2. Low transonic drag (LTD).															
3. The thick front canopy gives a +1 modifier to sighting rolls for targets in the 180+ arc.															
4. Emergency AB (ChR AB) may be used if speed is at least high transonic and altitude is 13 or less. When used, the AB power is 5.0/4.5/4.0 and the fuel use is 7.5. Emergency AB cannot be used for more than two consecutive game turns or more than eight game turns in total.															
VPs: 24/16/8/4								v1.0000000 0000-00-00T00:00:00							