

Instructions for User

INSTRUCTION FOR CLEANING AND DRYING:

To ensure the durability and uncompromised performance of this footwear

Footwear should always be kept as clean as possible.

Use a brush to remove any dust or dirt.

Footwear with leather upper should be regularly cleaned and polished with shoe polish.

Please note that footwear must be used correctly, cared for properly, and stored in a dry, ventilated condition for a good wear life and to prevent premature failure of the outsole.

INSTRUCTION FOR STORAGE AND MAINTENANCE:

To maintain safety shoes at their best, you can keep your shoes stored in a cool and dry place

Limitation: - Footwear is not for use in fire hazard/explosion prone areas/hot contact/electric resistance purpose

Performance against Vital Compliances

Component	Description	Requirement IS 15298-2:2016	Hillson Performance
Leather Upper	Upper Tear Strength (in N)	≥120	315
	Upper Tensile Strength (in N/mm ²)	≥15	18.5
	Water Vapor Permeability (in mg/cm ² /hr)	≥0.8	0.99
	Water Vapor Coefficient (In mg/cm ²)	≥15	16.6
	Chromium VI (in mg/kg)	<3	Not Detected
Lining	Tear Strength (in N)	≥15	85N
	Abrasion resistance (No of Rubs)	Dry- No hole till 25,600 Wet- No holes till 12,800	No holes
	Water Vapor Permeability (in mg/cm ² /hr)	≥2	>2
	Water Vapor Coefficient (In mg/cm ²)	≥20	>20
	Heel Grip Abrasion Resistance (No of Rubs)	Dry- No hole till 51,200 Wet- No holes till 25,600	No holes
In-sock	Water Absorption (in mg/cm ²)	≥70	70
	Water Desorption (in %)	≥80	100
	Abrasion resistance (No of Rubs)	Dry- No hole till 25,600 Wet- No holes till 12,800	No holes
Toe Cap	Impact Resistance (clearance in mm after impact 200j)	≥14 for size 08 & Toe cap should not crack	18 mm with no crack
	Compression Resistance (clearance in mm after compression 15kN)	≥14 for size 08	17 mm
Outsole	Abrasion Resistance (mm ³)	≤150	57
	Flexing Resistance (Cut Growth in mm)	@30,000 max cut growth 4mm	No cut growth
	Upper/Sole Bond Strength (in N/mm)	≥4	4.8
	Antistatic Resistance (in Mega Ohm)	>100kohm to ≤1000Mohm	390
	Hydrolysis (Cut growth in mm)	@150,000 max cut growth 6mm	No cut growth



CLAWZ CL-03

SAFETY SHOES CLAWZ

Clawz, the latest innovation from Hillson. Designed for those who value both fashion and functionality, Clawz offers unmatched comfort and superior slip resistance.

Crafted with lightweight, climate-optimized high-tech materials, Clawz keeps your feet cool and comfortable all day long. The ergonomically designed outsole ensures maximum support and stability, making Clawz the perfect partner for your busy workday and your adventures beyond.

Discover the perfect blend of youthful style and first-class comfort with Clawz — because you deserve shoes that work as hard as you do.



HILLSON FOOTWEAR PVT.LTD.
C.C. NO. 958185772
E-mail : info@hillsonshoes.com

INDUSTRIAL
PROFESSIONAL
OCCUPATIONAL



IS : 15298 : PART 2
CM/L-9954209
FOR BIS Certification details
Please visit www.bis.gov.in



HILLSON SAFETY SHOES
CLAWZ

Clawz is both youthful and stylish combined with first-class wearer comfort and highest slip resistance, thanks to its light weight design, climate-optimized high-tech materials, and ergonomically designed outsole.

Clawz the ideal companion for the working day and beyond.




Sizes							
US	5	6	7	8	9	10	11
UK	39	40	41	42	43	44	45

Application

General Safety at Workplace

Industries

Construction, Engineering, Automobile etc.



Material Specifications			
Component	Name	Technical Details	Benefits
Upper	Real Leather	Minimum 1.8 mm Real Buff leather in Tango Print	Thickness ensures durability All-weather softness for flexibility Breathability
Upper	D Ring Eyelet	Black Passivated coated	Coating ensures Non-corrosive performance required for longevity
Upper	Collar	Reach Compliance Synthetic Leather	Fabric and cushion together enhance comfort Thick and High-density inside foam ensures the same level of comfort throughout shoe life PVC material assured anti-peel-off property throughout shoe life
Upper	Laces	Polyester reflective laces	Polyester material ensures the longevity of laces and also the knot does not loosens for safety Reflective Material of laces for visual in dark areas to enhance safety
Upper	Safety Loop	Reflective Loop	Loop makes it easy to wear Saves the counter from damaging by disallowing wrong use Reflective material ensures visual in dark areas to enhance safety
Upper	Safety Reflective Tape at Quarter Area	High Visiblity Reflective Safety Fabrc Piping	Reflective Material ensures visual in dark areas to enhance safety
Upper	Safety Toe cap	EN 22568 Marked Steel toe cap	Assured 200J Impact resistance Assured compression load resistance @15kN Assured corrosion resistance
Upper	Comfort Vamp	Polysoft Material Foam	Anti Abrasive fabric ensures longevity in performance Comfortable inside foam reduces fatigue Increase the Gap between user feel and Toe Cap
Upper	Comfort Quarter Lining	Cushioned Fabric Lining	The smooth silicon finish of fabric ensures the feet to slip inside smoothly The extra layer of cushion gives more comfort The wet abrasion tested fabric ensures longevity in performance
Upper	Heel Grip	Non-Woven	Holds the heel from jumping while wearing Restricts users from wearing the wrong way
Sole	Outsole	High-Density Polyurethane	Rubber Touch enhances anti-abrasion properties Cleat designed for slip resistance and quick liquid dispersion
Sole	Midsole	Low-Density Polyurethane	Low density reduces the weight Enhanced energy absorption at the seat region Low density gives rebound
Sole	Insole	Non-Woven	High level humidity absorption and evacuation Good dimentional stability in both dry and humid conditions
Sole	Insocks	Ortho Bounce Insocks for complete feet	Orthobounce is a high density open cell footbed It gives continuous comfort, Rebound, resilience in prolonged use
Sole	Insocks	Neoprene For Heel & Arch Support	Body Balance Distribute body weight and pressure Significantly reduces fatigue