Parallel Computing Workshop


Adam Larios




26 Feb 2015




Serial Computing



Serial Computing



Parallel Computing



1 / 16

Major Uses

• Solve many small problems at the same time.

Major Uses


- Solve many small problems at the same time.
- Solve one big problem quickly by breaking it into small pieces.

Major Uses

- Solve many small problems at the same time.
- Solve one big problem quickly by breaking it into small pieces.


Major Uses


- Solve many small problems at the same time.
- Solve one big problem quickly by breaking it into small pieces.



Major Uses


- Solve many small problems at the same time.
- Solve one big problem quickly by breaking it into small pieces.






Major Uses

- Solve many small problems at the same time.
- Solve one big problem quickly by breaking it into small pieces.






2 / 16

- Repeated associative binary operations (addition, multiplication, maximization)
- Matrix-vector multiplication

Supercomputers



Titan



Processors Assembly



Blue Gene



Simulations

Why do parallel computing?

Good Reasons

- Massive speed up.
- Massive increase in problem size.
- Concurrency (the universe is inherently parallel in space)

Why do parallel computing?

Good Reasons

- Massive speed up.
- Massive increase in problem size.
- Concurrency (the universe is inherently parallel in space)



What is the bad news?

Not as useful when

• Iteration is required.

What is the bad news?

Not as useful when

- Iteration is required.
- Global communication is very frequent.

What is the bad news?

Not as useful when

- Iteration is required.
- Global communication is very frequent.

What is the bad news?

Not as useful when

- Iteration is required.
- Global communication is very frequent.

Difficulties

Often harder to think about.

What is the bad news?

Not as useful when

- Iteration is required.
- Global communication is very frequent.

Difficulties

- Often harder to think about.
- Often harder to program.

What is the bad news?

Not as useful when

- Iteration is required.
- Global communication is very frequent.

Difficulties

- Often harder to think about.
- Often harder to program.
- More problem dependent.

What is the bad news?

Not as useful when

- Iteration is required.
- Global communication is very frequent.

Difficulties

- Often harder to think about.
- Often harder to program.
- More problem dependent.
- Scalability and overhead costs.

What is the bad news?

Not as useful when

- Iteration is required.
- Global communication is very frequent.

Difficulties

- Often harder to think about.
- Often harder to program.
- More problem dependent.
- Scalability and overhead costs.

What is the bad news?

Not as useful when

- Iteration is required.
- Global communication is very frequent.

Difficulties

- Often harder to think about.
- Often harder to program.
- More problem dependent.
- Scalability and overhead costs.

Is it right for you?

It depends...

What is the bad news?

Not as useful when

- Iteration is required.
- Global communication is very frequent.

Difficulties

- Often harder to think about.
- Often harder to program.
- More problem dependent.
- Scalability and overhead costs.

Is it right for you?

- It depends...
- ... but probably yes!

What is the bad news?

Not as useful when

- Iteration is required.
- Global communication is very frequent.

Difficulties

- Often harder to think about.
- Often harder to program.
- More problem dependent.
- Scalability and overhead costs.

Is it right for you?

- It depends...
- ... but probably yes!
- E.g., do you have even one parameter in your problem?

Parallel Machines

• Your own multi-core laptop or desktop

Parallel Machines

- Your own multi-core laptop or desktop
- A cluster. like at the HCC


Parallel Machines

- Your own multi-core laptop or desktop
- A cluster, like at the HCC
- "Cloud computing", Amazon HPC, etc.

Parallel Machines


- Your own multi-core laptop or desktop
- A cluster, like at the HCC
- "Cloud computing", Amazon HPC, etc.
- Open Science Grid

How does it work?




How does it work?

Serial Logic




Parallel Logic




8 / 16

Memory


Shared Memory




Distributed Memory



Hybrid Memory



Non-Uniform Memory



What do you need?

• Libraries: OpenMPI, MPICH (Open Source)

What do you need?

- Libraries: OpenMPI, MPICH (Open Source)
- A parallel compiler (mpif90, mpicc, etc.)

What do you need?

- Libraries: OpenMPI, MPICH (Open Source)
- A parallel compiler (mpif90, mpicc, etc.)
- Some knowledge of Linux/Unix (probably)

What do you need?

- Libraries: OpenMPI, MPICH (Open Source)
- A parallel compiler (mpif90, mpicc, etc.)
- Some knowledge of Linux/Unix (probably)

What do you need?

- Libraries: OpenMPI, MPICH (Open Source)
- A parallel compiler (mpif90, mpicc, etc.)
- Some knowledge of Linux/Unix (probably)

Other notes

- Vendors: MPI, Intel MPI, Scali MP
- Matlab parallel programming

A basic MPI program

```
program who_am_I
    use mpi
    implicit none
    integer :: nb_procs,rank,code

call MPI_INIT(code)
    call MPI_COMM_SIZE(MPI_COMM_WORLD ,nb_procs,code)
    call MPI_COMM_RANK(MPI_COMM_WORLD ,rank,code)

print *,'I am the process ',rank,' of ',nb_procs
    call MPI_FINALIZE (code)
end program who_am_I
```

Communications

```
program point_to_point
use mpi
implicit none
integer, dimension (MPI STATUS SIZE) :: status
integer, parameter :: tag=100
integer :: rank.value.code
call MPI INIT(code)
call MPI COMM RANK (MPI COMM WORLD , rank, code)
if (rank == 2) then
  value = 1000
  call MPI_SEND(value,1,MPI_INTEGER,5,tag,MPI_COMM_WORLD,code)
elseif (rank == 5) then
  call MPI RECV (value, 1, MPI INTEGER, 2, tag, MPI COMM WORLD, status, code)
  print *,'I, process 5, have received value ',value,'&
           from process 2'
end if
call MPI FINALIZE (code)
```

end program point_to_point


Communications

```
> mpiexec -n 7 point_to_point
I, process 5 , have received value 1000 from process 2
```


Communication Overhead

- Boundary node
- Interior node
- Interface node

Proc 0 Proc 1 Proc 2 Proc 3 Proc 4 Proc 5 Proc 6 Proc 7



Scaling Tests



Resources

- "Introduction to Parallel Computing", Blaise Barney https://computing.llnl.gov/tutorials/parallel_comp
- "A Parallel Multigrid Tutorial", Jim Jones
 https://computing.llnl.gov/casc/linear_solvers/present.html
- "Introduction to Parallel Computing, Design and Analysis of Algorithms", Vipin Kumar, Ananth Grama, Anshul Gupta, George Karypis
- IDRIS tutorial with great coding examples: http://www.idris.fr/data/cours/parallel/openmp/

Thank you, and have fun!