

Doom rspress Alauda

□ □ □ □

- □□□□□□□□□□□□□□□□□□
- □□□□□□□□
- □□□□□

MDX ██████████ Markdown ████████ Markdown █████
██████ React ███



0000000000 MDX 000

0000

0000000000 Doom 00

00

00

0000

000000

00

MDX

📄 MDX 📄📄📄📄📄📄📄📄📄📄

rspress 📄

doom 📄

📄📄📄📄📄

📄📄📄

📄📄📄📄📄📄📄📄📄📄

i18n.json

.ts/.tsx

.mdx

API 📄

📄 API

CRD

📄📄📄

📄 openapi 📄

📄📄📄📄📄

props

📄

📄📄📄

📄📄📄📄📄

00

00000000000000000000 ACP 00

00000

0000

000 ACP

📄📄

📄📄

📄📄📄

📄📄📄📄

📄📄📄📄📄

📄📄📄📄📄

📄📄📄

📄📄📄📄📄📄

📄📄📄


📄📄 PDF

📄📄📄📄

📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄

```
mkdir my-docs && cd my-docs
```

📄 `npm init -y` 📄📄📄📄📄📄📄📄📄📄📄 `npm`📄`yarn` 📄 `pnpm` 📄 `doom:`



```
npm install -D @alauda/doom typescript
```

📄📄📄📄📄📄📄📄:

```
# 📄📄 docs 📄📄📄📄📄📄📄📄
```

```
mkdir docs/en && echo '# Hello World' > docs/en/index.md
```

```
mkdir docs/zh && echo '# 文档' > docs/zh/index.md
```

package.json 配置:

```
{
  "scripts": {
    "dev": "doom dev",
    "build": "doom build",
    "new": "doom new",
    "serve": "doom serve",
    "translate": "doom translate",
    "export": "doom export"
  }
}
```

doom.config.yml:

```
title: My Docs
```

tsconfig.json 配置:

```
{
  "compilerOptions": {
    "jsx": "react-jsx",
    "module": "NodeNext",
    "moduleResolution": "NodeNext",
    "noUnusedLocals": true,
    "noUnusedParameters": true,
    "resolveJsonModule": true,
    "skipLibCheck": true,
    "strict": true,
    "target": "ESNext",
  },
  "mdx": {
    "checkMdx": true,
  },
}
```

global.d.ts

```
/// <reference types="@alauda/doom/runtime" />
```

.mdx doom

doom -h

output

Usage: doom [options] [command]

Doctor Doom making docs.

Options:

- | | |
|-------------------------------|---|
| -V, --version | output the version number |
| -c, --config <config> | Specify the path to the config file |
| -v <version> | Specify the version of the documentation, c |
| -b, --base <base> | Override the base of the documentation |
| -p, --prefix <prefix> | Specify the prefix of the documentation bas |
| -f, --force [boolean] | Force to |
| | 1. fetch latest reference remotes or scaffo |
| | 2. translate ignore hash equality check and |
| -i, --ignore [boolean] | Ignore internal routes (default: false) |
| -d, --download [boolean] | Display download pdf link on nav bar (defau |
| -e, --export [boolean] | Run or build in exporting PDF mode, `apis/* |
| -I, --include <language...> | Include only the specific language(s), |
| -E, --exclude <language...> | Include all languages except the specific l |
| -o, --out-dir <path> | Override the `outDir` defined in the config |
| -r, --redirect <enum> | Whether to redirect to the locale closest t |
| -R, --edit-repo [boolean url] | Whether to enable or override the `editRepo |
| -n, --no-open [boolean] | Do not open the browser after starting the |
| -h, --help | display help for command |

Commands:

- | | |
|----------------------|------------------------------|
| dev [options] [root] | Start the development server |
| build [root] | Build the documentation |

<code>preview serve</code> [options] [root]	Preview the built documentation
<code>new</code> [template]	Generate scaffolding from templates
<code>translate</code> [options] [root]	Translate the documentation
<code>export</code> [options] [root]	Export the documentation as PDF, <code>`apis/**`</code>
<code>help</code> [command]	display help <code>for</code> command

📄📄📄📄📄

📄 `yarn dev` 📄📄📄📄📄📄📄📄📄📄📄📄📄📄

`doom dev -h`

output

Usage: `doom dev` [options] [root]

Start the development server

Arguments:

<code>root</code>	Root directory of the documentation
-------------------	-------------------------------------

Options:

<code>-H, --host</code> [host]	Dev server host name
<code>-P, --port</code> [port]	Dev server port number
<code>-l, --lazy</code> [boolean]	Whether to enable <code>`lazyCompilation`</code> which could i
<code>-h, --help</code>	display help for command

📄📄📄📄📄

📄 `yarn build` 📄📄📄📄📄📄📄📄📄📄 `dist` 📄📄📄📄📄

📄📄📄📄

📄 `yarn serve` 📄📄📄📄📄📄📄📄📄📄 `-b` , `-p` 📄📄📄📄📄📄📄📄 `-b` , `-p` 📄
📄

📄📄📄📄📄📄

📄 `yarn new` 📄📄📄📄📄📄📄📄📄📄

□□□□

`doom translate -h`

output

`Usage: doom translate [options] [root]``Translate the documentation``Arguments:``root Root directory of the documentation``Options:`

`-s, --source <language>` Document source language, one of en, zh, ru (default)

`-t, --target <language>` Document target language, one of en, zh, ru (default)

`-g, --glob <path...>` Glob patterns for source dirs/files

`-C, --copy [boolean]` Whether to copy relative assets to the target directory

`-h, --help` display help for command

- `-g, --glob` 指定源文件的路径模式，支持 glob 模式。例如：
`doom translate -g '*/assets/*' <root>`

1. `yarn translate -g abc xyz <root>/<source>/abc , <root>/<source>/xyz`
 将源文件复制到目标目录，并生成目标文件。

2. `yarn translate -g '*' <root>/<source>` 将源文件复制到目标目录。

- `-C, --copy` 是否将源文件复制到目标目录。默认为 `false`。

- 示例

1. `<root>/<source>/abc.jpg` 复制到 `<root>/public/<source>/abc.jpg`，并生成 `<root>/public/<target>/abc.jpg`。
2. `<root>/<source>/assets/xyz.jpg` 复制到 `<root>/<source>/assets/xyz.jpg`，并生成 `<root>/<target>/assets/xyz.jpg`。
3. `<root>/<source>/assets/xyz.jpg` 复制到 `<root>/<source>/assets/xyz.jpg`，并生成 `<root>/<source>/assets/xyz.jpg`。

```
<root>/<target>/assets/<target>/xyz.jpg
./assets/<target>/xyz.jpg
```

- - 1. `/<source>/abc.jpg` `<root>/public/<target>/abc.jpg`
`/<target>/abc.jpg`
 - 2. `<root>/<source>/abc.mdx` `./assets/<source>/xyz.jpg`
`<root>/<target>/assets/<target>/xyz.jpg`
`./assets/<target>/xyz.jpg`
`../<source>/assets/<target>/xyz.jpg`

WARNING

`-g '*'` `source` `target`
`internalRoutes` `target`

TIP

`AZURE_OPENAI_API_KEY` `Leader`

```
i18n:
  title:
    en: DevOps Connectors
  additionalPrompts: 'Connectors'
  disableAutoTranslation: false
title: DevOps
```

PDF

WARNING

`yarn build`

```
doom export -h
```

```
# output
```

```
Usage: doom export [options] [root]
```

```
Export the documentation as PDF, `apis/**` and `*/apis/**` routes will be ign
```

```
Arguments:
```

```
  root                Root directory of the documentation
```

```
Options:
```

```
  -H, --host [host]  Serve host name
```

```
  -P, --port [port]  Serve port number (default: "4173")
```

```
  -h, --help          display help for command
```

```
❯ yarn export 📄📄📄 PDF 📄📄📄📄📄📄📄 -b , -p 📄📄📄📄📄📄📄📄 -b , -p
❯
```

```
📄📄📄📄 playwright 📄📄📄📄📄 build-harbor.alauda.cn/frontend/playwright-
runner:doom 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄
```

```
.env.yarn
```

```
PLAYWRIGHT_DOWNLOAD_HOST="https://cdn.npmmirror.com/binaries/playwright"
```



📄

📄 `doom` 📄📄

📄📄

📄📄

API 📄📄

📄📄📄📄📄

📄📄📄

📄📄📄

📄📄📄

📄📄📄

📄📄📄📄📄

`sites.yaml` 📄

📄📄

📄📄📄📄📄

📄

📄“📄📄📄📄”📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄

📄📄

📄📄

📄

📄

Markdown

Callouts

Mermaid

MDX

📄 MDX 📄📄📄📄📄📄📄📄📄📄

rspress 📄

doom 📄

📄📄📄📄📄

📄📄

📄📄📄📄📄📄📄📄📄

i18n.json

.ts/.tsx

.mdx

API 📄

📄 API

CRD

📄📄📄

📄 openapi 📄

📄📄📄📄📄

props

📄


```
import { defineConfig } from '@alauda/doom/config'
```


- `lang` 指定生成文档的语言 `en` 指定生成文档的语言
`public` 指定生成文档是否公开
- `title` 指定生成文档的标题
- `logo` 指定生成文档的 logo `public` 指定生成文档是否公开
`doom` 指定生成文档的 logo 为 `alauda logo`
- `logoText` 指定生成文档的 logo 文本
- `icon` 指定生成文档的 icon `logo`
- `base` 指定生成文档的 base 路径 `product-docs` 指定生成文档的 base 路径 `/`
- `outDir` 指定生成文档的输出目录 `dist/{base}/{version}` 指定生成文档的输出目录
`dist/{outDir}/{version}` 指定生成文档的输出目录 `version` 指定生成文档的版本

```
api:
  # CRD  doom.config.*  glob  json/yaml
  crds:
    - docs/shared/crds/*.yaml
  # OpenAPI  doom.config.*  glob  json/yaml
  openapis:
    - docs/shared/openapis/*.json
  #  openapi
  #  https://doom.alauda.cn/apis/references/CodeQuality.html#v1alpha1.CodeQ
  references:
    v1alpha1.CodeQualityBranch: /apis/references/CodeQualityBranch#v1alpha1.C
  #  API  gateway
  pathPrefix: /apis
```

API

```
# doom.config.* glob json/yaml
permission:
  functionresources:
    # `kubectl get functionresources`
    - docs/shared/functionresources/*.yaml
  roletemplates:
    # `kubectl get roletemplates -l auth.cpaas.io/roletemplate.official=true`
    - docs/shared/roletemplates/*.yaml
```

```
reference:
- repo: alauda-public/product-doc-guide #
  branch: # [string]
  publicBase: # [string] /images/xx.png do
sources:
- name: anchor #
  path: docs/index.mdx# # doom.conf
  ignoreHeading: # [boolean] true
  processors: #
    - type: ejsTemplate
      data: # ejs `<%= data.xx %>`
  frontmatterMode: merge # frontmatter ignore ign
```

frontmatterMode

- ignore frontmatter frontmatter

- `merge` `frontmatter` `key`
- `replace` `frontmatter` `frontmatter`
- `remove` `frontmatter`

--	--	--	--	--	--

```
releaseNotes:  
  queryTemplates:  
    fixed: # npm ejc npm jql nm  
    unfixed:
```

release-notes.md

```
<!-- release-notes-for-bugs?template=fixed&project=DevOps -->
```

release-notes.mdx

```
{/* release-notes-for-bugs?template=fixed&project=DevOps */}
```

```
template=fixed&project=DevOps fixed queryTemplates
query project=DevOps ejjs fixed jira jql
https://jira.alauda.cn/rest/api/2/search?jql=<jql> API
JIRA_USERNAME JIRA_PASSWORD
```

--	--	--	--	--

sidebar:

```
collapsed: false # ..... false
```

--	--	--	--	--	--

```
internalRoutes: # glob docs cli -i, --ignore`
- '*/internal/**/*'
```

--	--	--	--	--	--	--	--

```
shiki:
  theme: # optional, https://shiki.style/themes
  langs: # optional, https://shiki.style/languages
  transformers: # optional, only available in js/ts config, https://shiki.sty
```

WARNING

plaintext

`sites.yaml` ☐ ☐

`sites.yaml`

```
- name: connectors # 000000
  base: /devops-connectors # 00000000
  version: v1.1 # 00000000 ExternalSite/ExternalSiteLink 0000
  displayName: # 00000000000000000000000000000000 name
```

en: DevOps Connectors

zh: DevOps 连接器

连接器

连接器

repo: <https://github.com/AlaudaDevops/connectors-operator> # 连接器

image: devops/connectors-docs # 连接器

🌑🌑🌑🌑

translate:

```
# 连接器 `sourceLang`, `targetLang`, `userPrompt` 或 `additionalPrompts`
# 或 `sourceLang` 或 `targetLang` 或 `sourceLang` 或 `targetLang`
# `userPrompt` 连接器
# `additionalPrompts` 连接器 `frontmatter.i18n` 连接器 `additionalPrompts` 连接器
# 连接器
```

systemPrompt: |

连接器

连接器<%= targetLang %>连接器<%= sourceLang %>连接器<%=

连接器

```
- 连接器<%= sourceLang %>连接器<%= targetLang %>连接器
- 连接器 MDX 连接器 MDX 连接器 jsx 连接器 <Overview />连接器
- 连接器
- MDX 连接器MDX 连接器 MDX 连接器
  - <Overview /> 连接器 Overview 连接器
  - <Tab label="value">连接器</Tab>连接器 label 连接器 key 连接器"value" 连接器
<%= terms %>
- 连接器
  - {/* release-notes-for-bugs */}
  - <!-- release-notes-for-bugs -->
- 连接器
  - {/* reference-start */}
  - {/* reference-end */}
  - <!-- reference-start -->
  - <!-- reference-end -->
- 连接器 \< 连接器 \{ 连接器
- 连接器 Markdown 连接器 frontmatter, 连接器 frontmatter.i18n 连接器
```

```
## 📄

📄📄📄📄📄📄📄📄

1. 📄📄<%= sourceLang %>📄📄📄📄<%= targetLang %>📄📄📄📄📄📄📄📄📄📄
2. 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄
   - 📄📄📄<%= targetLang %>📄📄📄📄📄📄📄📄
   - 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄
   - 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄
3. 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄<%= targetLang %>📄📄📄📄
4. 📄📄📄📄📄📄📄<%= targetLang %>📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄<%= targetLang %>📄📄📄📄📄📄📄📄

📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄

<%= userPrompt %>

<%= additionalPrompts %>
  userPrompt: # 📄📄📄📄📄📄📄 `systemPrompt` 📄📄 `ejs` 📄📄📄📄
```

📄📄📄📄📄📄📄📄

editRepoBaseUrl: [alauda/doom/tree/main/docs](https://github.com/lauda/doom/tree/main/docs) # [https://github.com/](https://github.com/lauda/doom/tree/main/docs) 📄📄📄📄📄📄📄📄

11

11

index.mdx Overview

```
#  
  
<Overview />
```

Markdown

000000 [gfm](#) 000000Doom 000000000000 Markdown 000000

00

Callouts

Mermaid

Callouts

00000000

NOTE

- 000000000000000000000000 ; , % , # , // , /** */ , -- 0 <!-- --> 0
- 000000000000000000000000 [\ ! code callout] 00000
- 0000 :::callouts 000000000000000000000000 <div class="doom-callouts"> 0
<Callouts> 00000

```
```sh
Memory overhead per virtual machine ≈ (1.002 × requested memory) \
 + 218 MiB \ 1
 + 8 MiB × (number of vCPUs) \ 2
 + 16 MiB × (number of graphics devices) \ 3
 + (additional memory overhead) 4
```

:::callouts
```

- 1. Required for the processes that run in the ``virt-launcher`` pod.
- 2. Number of virtual CPUs requested by the virtual machine.
- 3. Number of virtual graphics cards requested by the virtual machine.
- 4. Additional memory overhead:
 - If your environment includes a Single Root I/O Virtualization (SR-IOV) n
 - If Secure Encrypted Virtualization (SEV) is enabled, add 256 MiB.
 - If Trusted Platform Module (TPM) is enabled, add 53 MiB.

...

Memory overhead per virtual machine $\approx (1.002 \times \text{requested memory}) \setminus$

+ 218 MiB \setminus ①

+ 8 MiB \times (number of vCPUs) \setminus ②

+ 16 MiB \times (number of graphics devices) \setminus ③

+ (additional memory overhead) ④


- ① Required for the processes that run in the `virt-launcher` pod.
- ② Number of virtual CPUs requested by the virtual machine.
- ③ Number of virtual graphics cards requested by the virtual machine.
- ④ Additional memory overhead:
 - If your environment includes a Single Root I/O Virtualization (SR-IOV) network device or a Graphics Processing Unit (GPU), allocate 1 GiB additional memory overhead for each device.
 - If Secure Encrypted Virtualization (SEV) is enabled, add 256 MiB.
 - If Trusted Platform Module (TPM) is enabled, add 53 MiB.

Shiki Transformers

Mermaid

```
mermaid
graph TD;
  A-->B;
  A-->C;
  B-->D;
  C-->D;

```



MDX

[MDX](#) [Markdown](#) [Markdown](#) [JSX](#) [rspress MDX](#)

rspress

doom

Overview

Directive

ExternalSite

ExternalSiteLink

AcpApisOverview ExternalApisOverview

Term

props

TermsTable

props

JsonViewer

rspress

rspress [.mdx](#)

- Badge
- Card
- LinkCard

- [PackageManagerTabs](#)
- [Steps](#)
- [Tab/Tabs](#)
- [Toc](#)

在 `preview.mdx` 文件中，从 `@rspress/core/theme` 包中引入 `SourceCode` 组件。

```
preview.mdx

import { SourceCode } from '@rspress/core/theme'

<SourceCode href="/" />
```

doom 文档

`doom` 是一个用于生成文档的工具，它支持 MDX 格式，并提供了丰富的组件和 API 来帮助你快速搭建文档网站。

Overview

本文将介绍 `doom` 的基本用法和核心概念。

Directive

在 MDX 文件中，你可以使用 `Directive` 组件来添加元数据或控制文档的渲染。

```
- 在 `doc/en` 目录下创建 `doc/zh` 目录，用于存放中文文档。

<Directive type="danger" title="警告">
  这是一个警告信息，请仔细阅读。
</Directive>
```

- [illegible]

11

doc/zh

11

ExternalSite

--	--	--	--	--	--	--	--

```
<ExternalSite name="connectors" />
```

Note

[illegible]

DevOps ☐ ☐ ☐ ☒

ExternalSiteLink

□ □ □ □ □ □ □ □ □ □

```
<ExternalSiteLink name="connectors" href="link.mdx#hash" children="Content" /
```

[Content ↗](#)

TIP

```
mdx <ExternalSiteLink name="connectors" href="link" children="Content" />
```

```
<ExternalSiteLink name="connectors" href="link">
  Content {/* □□□□ `p` □□□ */}
```

```
</ExternalSiteLink>
```

children

AcpApisOverview ☐ ExternalApisOverview

API

```

<AcpApisOverview />
{/* same as following */}
<ExternalApisOverview name="acp" />

<ExternalApisOverview name="connectors" />

```

Note

ACP APIs [ACP APIs](#)

Note

DevOps APIs [DevOps APIs](#)

Term

```

<Term name="company" textCase="capitalize" />
<Term name="product" textCase="lower" />
<Term name="productShort" textCase="upper" />

```

ACP

props

- name :
- textCase : lower , upper , capitalize

TermsTable

```
<TermsTable />
```

company		-	Alauda	-	
product		-	Alauda Container Platform	-	
productShort	ACP	-	ACP	-	

props

- terms : NormalizedTermItem[]

JsonViewer

```
<JsonViewer value={{ key: 'value' }} />
```

```
yaml    json
key: value
```

shared

```
import CommonContent from './shared/CommonContent.mdx'
```

```
<CommonContent />
```

runtime API .jsx/.tsx .mdx

```
// shared/CommonContent.tsx
```

```
export const CommonContent = () => {
  const { page } = usePageData()
  return <div>{page.title}</div>
}
```

```
// showcase/content.mdx
```

```
import { CommonContent } from './shared/CommonContent'
; <CommonContent />
```

WARNING

.mdx props issue props .jsx/.tsx

--	--	--

[illegible]

11

i18n.json

```
.ts/.tsx
```

.mdx

i18n.json

```

// docs
// i18n.json
// useI18n

```

docs/i18n.json

```
{
  "title": {
    "zh": "标题",
    "en": "Title"
  },
  "description": {
    "zh": "描述",
    "en": "description"
  }
}
```

.ts/.tsx

```
import { useI18n } from '@rspress/runtime'

export const CommonContent = () => {
  const t = useI18n()
  return <h1>{t('title')}</h1>
}
```

.mdx

```
import { useI18n } from '@rspress/runtime'

# {useI18n()('title')}

{useI18n()('description')}
```

API 文档

本页面提供 API 文档 API 文档 CRD (Custom Resource Definition) 文档文档文档文档文档文档文档

```
├─ apis
│   └─ advanced-apis # 高级 API
│   └─ crds # CRDs
│   └─ references # 参考
```

文档

- API 文档
 - props
- CRD
 - props
- 文档文档
 - props
- openapi 文档

API 文档

```
advanced-apis/codeQualityTaskSummary.mdx

# CodeQualityTaskSummary

<OpenAPIPath path="/plugins/v1alpha1/template/codeQuality/task/{task-id}/summ
```

CodeQualityTaskSummary

props

- path : OpenAPI schema paths
- pathPrefix : api.pathPrefix
- openapiPath : openapi

CRD

```
crds/ArtifactCleanupRun.mdx

# ArtifactCleanupRun

<K8sCrd name="artifactcleanupruns.artifacts.katanomi.dev" />
```

ArtifactCleanupRun

props

- name : CRD metadata.name
- crdPath : openapi CRD

```
references/CodeQuality.mdx

# CodeQuality

<OpenAPIRef schema="v1alpha1.CodeQuality" />
```

props

- schema : OpenAPI schema definitions (v2) or component/schemas (v3)
- openapiPath : openapi

openapi

OpenAPIPath OpenAPIRef openapi
openapi openapiPath

```
<OpenAPIPath
  path="/plugins/v1alpha1/template/codeQuality/task/{task-id}/summary"
  openapiPath="shared/openapis/katanomi.json"
/>
```

权限管理

```
<K8sPermissionTable functions={['devops-testplans', 'devops-testmodules']} />
```

权限

props

权限

props

- functions: string[] - 权限资源 FunctionResource 列表

权限

权限	权限	权限 资源	权限 资源	权限 资源	权限 资源	权限 资源	权限 资源
权限 devops- testplans	权限	✓	✓	✓	✓	✓	✗
	权限	✓	✗	✓	✓	✓	✗
	权限	✓	✗	✓	✓	✓	✗
	权限	✓	✗	✓	✓	✓	✗
权限 devops-	权限	✓	✓	✓	✓	✓	✗

模块	测试	测试用例 通过	测试用例 失败	测试用例 通过	测试用例 通过	测试用例 通过	测试用例 通过
testmodules	测试	✓	✗	✓	✓	✓	✗
	测试	✓	✗	✓	✓	✓	✗
	测试	✓	✗	✓	✓	✓	✗

--	--	--	--

☐ Markdown ☐☐☐☐

```
<!-- reference-start#name -->
```

```
<!-- reference-end -->
```

MDX

```
{/* reference-start#name */}
```

```
{/* reference-end */}
```

name

```
□□□□□□ <root>/public/_remotes/<name> □□□□
```

```
□□□□□ <!-- reference-start#ref --> □□□□□
```

--	--	--	--	--	--

frontmatterMode

--	--	--	--	--	--

reference:

```
- repo: alauda-public/product-doc-guide # 
branch: # [string]
```

```
publicBase: # [string] /images/xx.png do
sources:
- name: anchor #
  path: docs/index.mdx# # doom.conf
  ignoreHeading: # [boolean] true
  processors: #
    - type: ejstemplate
      data: # ejs `<%= data.xx %>`
  frontmatterMode: merge # frontmatter ignore ign
```

frontmatterMode

- **ignore** frontmatter frontmatter
- **merge** frontmatter key
- **replace** frontmatter frontmatter
- **remove** frontmatter

□ □ □ □ □ □ □ □

doom serve # □□□□□□□□□□

```
WORKDIR /docs
```

```
COPY . dist
```

ACP

`doom build` `dist` `-v`

```
# release-4.0 4.0
```

```
doom build -v 4.0 # 4.0 dist/4.0 {base}/4.0
```

```
doom build -v master # master dist/master {base}/master
```

```
doom build -v {other} # dist/{other} {base}/{other}
```

```
# unversioned unversioned-x.y
```

```
doom build -v unversioned # dist/unversioned {base}
```

```
doom build -v unversioned-4.0 # 4.0 dist/unversioned-4.0
```

```
├─ console-platform
│   ├── 4.0
│   ├── 4.1
│   ├── index.html
│   ├── overrides.yaml
│   └─ versions.yaml
├─ console-devops-docs
│   ├── 4.0
│   ├── 4.1
│   ├── index.html
│   ├── overrides.yaml
│   └─ versions.yaml
├─ console-tekton-docs
│   └─ 1.0
```

```
|   ├── 1.1
|   ├── index.html
|   ├── overrides.yaml
|   └── versions.yaml
```

index.html

```
<!DOCTYPE html>
<html>
  <head>
    <title>Redirecting...</title>
    <meta http-equiv="refresh" content="0; url=/console-docs/4.1" />
  </head>
  <body>
    <p>Redirecting to <a href="/console-docs/4.1">/console-docs/4.1</a></p>
  </body>
</html>
```

目录

overrides.yaml

```
# console-platform
# https://gitlab-ce.alauda.cn/idp/Doom/-/blob/master/src/terms.ts#L11
terms:
  company:
    en: Alauda
    zh: 奥达
  product:
    en: Alauda Container Platform
    zh: 奥达容器平台
  productShort:
    en: ACP

#
title:
  en: Doom - Alauda
  zh: Doom - 奥达
logoText:
```

en: Doom - Alauda
zh: Doom - 文档

versions.yaml

- '4.1'
- '4.0'

📄📄📄📄📄📄📄

📄📄📄📄📄 [chart-frontend](#) 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄 [alauda-docs](#) 📄📄📄📄📄
📄📄📄
📄📄

📄📄📄📄📄📄📄

📄📄📄
📄📄📄

INFO

📄📄📄📄 PR 📄📄📄gitops 📄📄📄📄