

--	--	--	--

Doom  [rspress](#)  Alauda  [rspress](#)

11

□ □ □ □

□□ Markdown □□□□ MDX

□ □ □ □

□ □ □ □

- □□□□□□□□□□□□□□□□
- □□□□□□□
- □□□□□

□□ **Markdown** □□□□ **MDX**

**MDX** ██████████**Markdown** ████████**Markdown** ██████████**React** ██████████



0000000000 MDX 00 ↗ 0

0000

0000000000 Doom 00

00

00

0000

000000

00

11

□□ `doom` □□□□

4/4

□ □ □ □

## API □□□□

Page 10 of 10

Page 1 of 1

6/6/2019

□ □ □ □ □

Page 10

□ □ □ □ □ □ □ □ □

--	--	--	--	--	--	--	--

sites.yaml

□ □ □ □

□ □ □ □ □ □ □ □ □

□ □ □ □ □ □

Algolia ☐ ☐ ☐ ☐

Sitemap ☐ ☐

11

[illegible]

□ □ □ □

333

11

11

## Markdown

## Callouts

Mermaid

MDX

00 MDX 000000000000000000

rspress 00

doom 00

00000000

000

0000000000000000

i18n.json

.ts/.tsx

.mdx

API 00

00 API

CRD

0000

00 openapi 00

000000

props

00

0000

000000

00

000000000000000000000000 ACP 00

000000

000000

0000000

000000000

📄📄

📄📄

📄📄📄

📄📄📄📄

📄📄📄📄📄

📄📄📄📄📄

📄📄📄

📄📄📄📄📄📄

📄📄📄

📄📄 PDF

📄📄📄

📄📄📄📄

📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄

```
mkdir my-docs && cd my-docs
```

📄 `npm init -y` 📄📄📄📄📄📄📄📄📄📄📄 `npm`📄`yarn` 📄 `pnpm` 📄📄 `doom:`



```
npm install -D @alauda/doom typescript
```

📄📄📄📄📄📄📄📄:

```
# 创建 docs 目录
```

```
mkdir docs/en && echo '# Hello World' > docs/en/index.md
```

```
mkdir docs/zh && echo '# 你好' > docs/zh/index.md
```

在 `package.json` 中添加脚本:

```
{
  "scripts": {
    "dev": "doom dev",
    "build": "doom build",
    "new": "doom new",
    "serve": "doom serve",
    "translate": "doom translate",
    "export": "doom export"
  }
}
```

在 `doom.config.yml` 中添加:

```
title: My Docs
```

在 `tsconfig.json` 中添加:

```
{
  "compilerOptions": {
    "jsx": "react-jsx",
    "module": "NodeNext",
    "moduleResolution": "NodeNext",
    "noUnusedLocals": true,
    "noUnusedParameters": true,
    "resolveJsonModule": true,
    "skipLibCheck": true,
    "strict": true,
    "target": "ESNext",
  },
  "mdx": {
    "checkMdx": true,
  },
}
```

global.d.ts

```
/// <reference types="@alauda/doom/runtime" />
```

.mdx doom



```
doom -h
```

```
# output
```

```
Usage: doom [options] [command]
```

```
Doctor Doom making docs.
```

### Options:

-V, --version	output the version number
-c, --config <config>	Specify the path to the config file
-v <version>	Specify the version of the documentation, c
-b, --base <base>	Override the base of the documentation
-p, --prefix <prefix>	Specify the prefix of the documentation bas
-f, --force [boolean]	Force to
	1. fetch latest reference remotes or scaffo
	2. translate ignore hash equality check and
-i, --ignore [boolean]	Ignore internal routes (default: false)
-d, --download [boolean]	Display download pdf link on nav bar (defau
-e, --export [boolean]	Run or build in exporting PDF mode, `apis/*
-I, --include <language...>	Include <b>only</b> the specific language(s),
-E, --exclude <language...>	Include all languages except the specific l
-o, --out-dir <path>	Override the `outDir` defined in the config
-r, --redirect <enum>	Whether to redirect to the locale closest t
-R, --edit-repo [boolean url]	Whether to enable or override the `editRepo
-a, --algolia [boolean alauda]	Whether to enable or use the alauda (docs.a
-S, --site-url	Whether to enable the siteUrl for sitemap g
-n, --no-open [boolean]	Do not open the browser after starting the
-h, --help	display help for command

### Commands:

dev [options] [root]	Start the development server
build [root]	Build the documentation
preview serve [options] [root]	Preview the built documentation
new [template]	Generate scaffolding from templates
translate [options] [root]	Translate the documentation
export [options] [root]	Export the documentation as PDF, `apis/**`
lint [root]	Lint the documentation
help [command]	display help for command

📄📄📄📄📄

📄 yarn dev 📄📄📄📄📄📄📄📄📄📄📄📄📄📄

```
doom dev -h
```

```
# output
```

```
Usage: doom dev [options] [root]
```

```
Start the development server
```

```
Arguments:
```

```
  root
```

```
Root directory of the documentation
```

```
Options:
```

```
-H, --host [host]
```

```
Dev server host name
```

```
-P, --port [port]
```

```
Dev server port number
```

```
-l, --lazy [boolean]
```

```
Whether to enable `lazyCompilation` which could i
```

```
-h, --help
```

```
display help for command
```

📄📄📄📄📄

📄 yarn build 📄📄📄📄📄📄📄📄📄 dist 📄📄📄📄📄

📄📄📄📄

📄 yarn serve 📄📄📄📄📄📄📄📄📄📄 -b , -p 📄📄📄📄📄📄📄📄 -b , -p 📄

📄

📄📄📄📄📄📄

📄 yarn new 📄📄📄📄📄📄📄📄📄📄

📄📄📄📄

```
doom translate -h
```

```
# output
```

```
Usage: doom translate [options] [root]
```

Translate the documentation

Arguments:

root Root directory of the documentation

Options:

-s, --source <language> Document source language, one of en, zh, ru (default en)

-t, --target <language> Document target language, one of en, zh, ru (default en)

-g, --glob <path...> Glob patterns for source dirs/files

-C, --copy [boolean] Wether to copy relative assets to the target directory

-h, --help display help for command

- -g, --glob 指定源文件的路径 glob 指定源文件的路径

1. yarn translate -g abc xyz 将 <root>/<source>/abc 文件复制到 <root>/<target>/xyz 目录

2. yarn translate -g '\*' 将 <root>/<source> 目录下的所有文件复制到 <root>/<target>

- -C, --copy 是否复制源文件中的相对路径文件到目标目录 false 不复制

- 示例

1. /<source>/abc.jpg 复制到 <root>/public/<source>/abc.jpg 文件

<root>/public/<target>/abc.jpg 文件复制到 <root>/<target>/abc.jpg 文件

2. <root>/<source>/abc.mdx 复制到 ./assets/xyz.jpg 文件

<root>/<source>/assets/xyz.jpg 文件复制到 <root>/<target>/assets/xyz.jpg 文件

3. <root>/<source>/abc.mdx 复制到 ./assets/<source>/xyz.jpg 文件

<root>/<source>/assets/<source>/xyz.jpg 文件复制到 <root>/<target>/assets/<target>/xyz.jpg 文件

./assets/<target>/xyz.jpg

- 📄📄📄📄📄📄
  1. `/<source>/abc.jpg` 📄📄📄 `<root>/public/<target>/abc.jpg` 📄📄📄📄📄  
📄📄📄📄 `/<target>/abc.jpg` 📄📄📄📄📄📄📄📄📄
  2. `<root>/<source>/abc.mdx` 📄📄 `./assets/<source>/xyz.jpg` 📄📄📄  
`<root>/<target>/assets/<target>/xyz.jpg` 📄📄📄📄📄📄📄📄📄  
`./assets/<target>/xyz.jpg` 📄📄📄📄  
`../<source>/assets/<target>/xyz.jpg`

**WARNING**

📄📄📄📄📄 `-g '*'` 📄📄📄📄📄📄 `source` 📄 `target` 📄📄📄📄📄  
`internalRoutes` 📄📄📄📄 `target` 📄📄📄📄📄

**TIP**

📄📄📄📄📄📄 `AZURE_OPENAI_API_KEY` 📄📄📄📄📄📄📄 `Leader` 📄

📄📄📄📄📄📄📄📄📄📄📄

```
i18n:
  title:
    en: DevOps Connectors
  additionalPrompts: '📄📄📄 Connectors 📄📄📄📄📄📄'
  disableAutoTranslation: false
title: DevOps 📄📄
```

📄📄📄📄📄📄📄📄📄

📄📄 **PDF**

**WARNING**

📄📄📄📄📄📄📄📄 `yarn build` 📄📄📄

```
doom export -h
```

```
# output
```

Usage: doom export [options] [root]

Export the documentation as PDF, ``apis/**`` and ``*/apis/**`` routes will be ign

### Arguments:

```
root      Root directory of the documentation
```

Options:

`-H, --host [host]` Serve host name

```
-P, --port [port]  Serve port number (default: "4173")
```

```
-h, --help      display help for command
```

```
yarn export [options] PDF [options] -b , -p [options] -b , -p
```

11

playwright [build-harbor.alauda.cn/frontend/playwright-](https://build-harbor.alauda.cn/frontend/playwright-)

runner:doom □□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□

`.env.yarn`

```
PLAYWRIGHT_DOWNLOAD_HOST="https://cdn.npmmirror.com/binaries/playwright"
```

--	--	--	--

```
doom lint -h
```

```
# output
```

```
Usage: doom lint [options] [root]
```

```
Lint the documentation
```

```
Arguments:
```

```
  root          Root directory of the documentation
```

```
Options:
```

```
  -h, --help    display help for command
```



📄

📄 `doom` 📄📄

📄📄

📄📄

API 📄📄

📄📄📄📄

📄📄📄

📄📄📄

📄📄📄

📄📄📄📄

📄📄📄📄📄

📄📄📄📄

`sites.yaml` 📄

📄📄

📄📄📄📄📄

📄📄📄

Algolia 📄📄

Sitemap 📄





API 00

00 API

CRD

0000

00 openapi 00

000000

props

00

0000

000000

00

000000000000000000000000 ACP 00

00000

00000

000000

00000000

11

Sitemap ☐ ☐

--	--	--	--

```
doom.config.yml  rspress  js/ts
```

```
□□□□ .js/.ts/.mjs/.mts/.cjs/.cts □□□□□□□□
```

```

js/ts @alauda/doom/config defineConfig

```

```
import { defineConfig } from '@alauda/doom/config'

export default defineConfig({})
```

- `lang` `en` `null` `undefined`
- `title`
- `logo` `public` `doom` `alauda logo`
- `logoText` `logo`
- `icon` `favicon` `logo`
- `base` `product-docs` `/`
- `outDir` `dist/{base}/{version}` `dist/{outDir}/{version}` `version`

API ☐ ☐ ☐ ☐

**api:**

```
# CRD 配置 doom.config.* 文件 glob 模式 json/yaml 文件
```

**crds:**

```
- docs/shared/crds/*.yaml
```

```
# OpenAPI 配置 doom.config.* 文件 glob 模式 json/yaml 文件
```

**openapis:**

```
- docs/shared/openapis/*.json
```

```
# 配置 openapi 文件
```

```
# 配置 https://doom.alauda.cn/apis/references/CodeQuality.html#v1alpha1.CodeQ
```

**references:**

```
  v1alpha1.CodeQualityBranch: /apis/references/CodeQualityBranch#v1alpha1.C
```

```
# 配置 API 网关 gateway 文件
```

```
pathPrefix: /apis
```

配置 API 文件

配置 API 文件

```
# 配置 doom.config.* 文件 glob 模式 json/yaml 文件
```

**permission:****functionresources:**

```
# `kubectl get functionresources`
```

```
- docs/shared/functionresources/*.yaml
```

**roletemplates:**

```
# `kubectl get roletemplates -l auth.cpaas.io/roletemplate.official=true`
```

```
- docs/shared/roletemplates/*.yaml
```

配置 API 文件

配置 API 文件

**reference:**

```

- repo: alauda-public/product-doc-guide # 
branch: # [string] 
publicBase: # [string] /images/xx.png do
sources:
  - name: anchor # 
    path: docs/index.mdx# # doom.conf
    ignoreHeading: # [boolean] true
    processors: 
      - type: ejsTemplate
        data: # ejs `<%= data.xx %>` 
    frontmatterMode: merge # frontmatter ignore ign

```

**frontmatterMode**

- **ignore** frontmatter frontmatter
- **merge** frontmatter key
- **replace** frontmatter frontmatter
- **remove** frontmatter

**releaseNotes:****queryTemplates:**

**fixed:** # ejs jql

**unfixed:**

release-notes.md

```
<!-- release-notes-for-bugs?template=fixed&project=DevOps -->
```

□ □ □ □ □

```
sidebar:  
  collapsed: false # [] false
```



```
internalRoutes: # 匹配 glob 匹配的 docs 下的 cli 子目录，忽略 `
  - '*/internal/**'
```

--	--	--	--	--	--	--	--	--

```
onlyIncludeRoutes: # 匹配 glob 匹配的 docs 下的 cli 的 -i, --ignore 匹配的
  - '*/internal/**'
internalRoutes:
  - '*/internal/overview.mdx'
```

```
theme: # optional, https://shiki.style/themes
langs: # optional, https://shiki.style/languages
transformers: # optional, only available in js/ts config, https://shiki.sty
```

plaintext

```
- name: connectors # []  
  
base: /devops-connectors # []  
  
version: v1.1 # [] ExternalSite/ExternalSiteLink []  
  
displayName: # [] name  
    en: DevOps Connectors  
    zh: DevOps []  
  
# []  
# []  
  
repo: https://github.com/AlaudaDevops/connectors-operator # [] gi  
image: devops/connectors-docs # []
```

translate:

```
# =====ejs ===== `sourceLang`, `targetLang`, `userPrompt`, `additional
#  `sourceLang`  `targetLang`  ` `  ` `
#    `userPrompt` =====
#    `additionalPrompts`  `frontmatter.i18n`  `additionalPrompts`
#    `terms`  `titleTranslationPrompt` ===== AI
# =====
```

systemPrompt: |

You are a professional technical documentation engineer, skilled in writing h

## Baseline Requirements

- Sentences should be fluent and conform to the expression habits of the <%=
- Input format is MDX; output format must also retain the original MDX format
- **\*\*CRITICAL\*\***: Do not translate or modify ANY link content in the document.
  - URLs in markdown links: [text](URL) - keep URL exactly as is
  - Reference-style links: [text][ref] and [ref]: URL - keep both ref and URL
  - Inline URLs: https://example.com - keep completely unchanged
  - Image links: ![alt](src) - keep src unchanged, but alt text can be transl
  - Anchor links: [text](#anchor) - keep #anchor unchanged
  - Any href attributes in HTML tags - keep unchanged
- Do not translate professional technical terms and proper nouns, including b
- The title field and description field in frontmatter should be translated,
- Content within MDX components needs to be translated, whereas MDX component
- Do not modify or translate any placeholders in the format of \_\_ANCHOR\_N\_\_ (
- Keep original escape characters like backslash, angle brackets, etc. unchan
- Do not add any escape characters to special characters like [], (), {}, etc
  - If source has "Architecture [Optional]", keep it as "Architecture [Option
  - If source has "Function (param)", keep it as "Function (param)" (not "Fun
  - Only add escape characters if they were present in the original text
- Preserve and do not translate the following comments, nor modify their cont
  - {/\* release-notes-for-bugs \*/}
  - <!-- release-notes-for-bugs -->
- Remove and do not retain the following comments:
  - {/\* reference-start \*/}
  - {/\* reference-end \*/}
  - <!-- reference-start -->
  - <!-- reference-end -->
- Ensure the original Markdown format remains intact during translation, such
- Do not translate the content of the code block.

<% if (titleTranslationPrompt) { %>

<%- titleTranslationPrompt %>

<% } %>

<% if (terms) { %>



```
<%- terms %>
<% } %>

<% if (userPrompt || additionalPrompts) { %>
## Additional Requirements
These are additional requirements for the translation. They should be met also

The text for translation is provided below, within triple quotes:
"""
<% if (userPrompt) { %>
<%- userPrompt %>
<% } %>

<% if (additionalPrompts) { %>
<%- additionalPrompts %>
<% } %>
"""
<% } %>
```

📄📄📄📄📄📄📄📄

**editRepoBaseUrl:** [alauda/doom/tree/main/docs](https://github.com/lauda/doom/tree/main/docs) # <https://github.com/lauda/doom/tree/main/docs> 📄📄📄📄📄📄📄📄

📄📄📄📄📄📄

**lint:**  
**cspellOptions:** # 📄📄📄cspell 📄📄📄📄 <https://github.com/streetsidesoftware/cspell>

**Algolia** 📄📄📄📄

```
algolia: # 📄Algolia 📄📄📄📄📄📄📄 `--a, --algolia` 📄📄📄📄📄  
  appId: # Algolia 📄 ID  
  apiKey: # Algolia API Key  
  indexName: # Algolia 📄📄📄
```

📄📄 `public/robots.txt` 📄 Algolia 📄📄📄

## INFO

📄 `rspress` 📄📄📄📄📄 Algolia 📄📄📄📄📄 [📄📄📄📄📄](#) 📄📄📄📄📄📄📄📄📄📄📄📄📄📄  
`@alauda/doom/theme` 📄📄📄📄📄📄📄📄📄📄📄📄📄📄

```
export * from '@alauda/doom/theme'
```

## Sitemap 📄📄

```
siteUrl: https://docs.alauda.cn # 📄📄📄 URL📄📄📄 sitemap📄📄📄 `--S, --site-url
```

11

--	--	--	--

```

index
index.md index.mdx

```

```
├─ index.md
├─ start.mdx
└─ usage
    ├─ index.mdx
    └─ convention.md
```

--	--	--	--	--	--

1. `public` □□□□□□□□□□□□□□□□
2. `public/_remotes` □□□□□□□□□□□□□□□□□□□□□□□□□□□□  
`*/public/_remotes` □□ `.gitignore` □□□□□□□□□□
3. `shared` □□□□□□□□□□□□□□□□□□□□□□□□□□□□

🐱🐱

🐱🐱🐱🐱🐱🐱 `frontmatter` 🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱

```
---
title: 🐱
description: 🐱
author: 🐱
category: 🐱
---
```

🐱🐱🐱🐱🐱🐱 `MDX` 🐱 `.mdx` 🐱🐱🐱🐱 `frontmatter` 🐱🐱🐱🐱🐱🐱

🐱🐱

🐱 `index.md` 🐱 `index.mdx` 🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱 `frontmatter` 🐱  
`weight` 🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱 `weight` 🐱🐱🐱🐱🐱🐱

```
---
weight: 1
---
```

### WARNING

🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱

🐱🐱

index.mdx Overview

```
#  
  
<Overview />
```

# Markdown

[gfm](#) [Doom](#) [Markdown](#)

11

## Callouts

Mermaid

## Callouts

□ □ □ □ □ □

## NOTE

1. `;;, %, #, //, /** */, -- <!-- -->`
2. `[!\code callout]`
3. `:::callouts <div class="doom-callouts"> <Callouts>`

```
```sh
```

```
Memory overhead per virtual machine ≈ (1.002 × requested memory) \
    + 218 MiB \
    + 8 MiB × (number of vCPUs) \
    + 16 MiB × (number of graphics devices) \
    + (additional memory overhead)
```

```
```
```

```
:::callouts
```

1. Required for the processes that run in the `virt-launcher` pod.
2. Number of virtual CPUs requested by the virtual machine.
3. Number of virtual graphics cards requested by the virtual machine.
4. Additional memory overhead:
  - If your environment includes a Single Root I/O Virtualization (SR-IOV) network device or a Graphics Processing Unit (GPU), allocate 1 GiB additional memory overhead for each device.
  - If Secure Encrypted Virtualization (SEV) is enabled, add 256 MiB.
  - If Trusted Platform Module (TPM) is enabled, add 53 MiB.

```
:::
```

```
Memory overhead per virtual machine ≈ (1.002 × requested memory) \
    + 218 MiB \
    + 8 MiB × (number of vCPUs) \
    + 16 MiB × (number of graphics devices) \
    + (additional memory overhead)
```

- ① Required for the processes that run in the `virt-launcher` pod.
- ② Number of virtual CPUs requested by the virtual machine.
- ③ Number of virtual graphics cards requested by the virtual machine.
- ④ Additional memory overhead:
  - If your environment includes a Single Root I/O Virtualization (SR-IOV) network device or a Graphics Processing Unit (GPU), allocate 1 GiB additional memory overhead for each device.
  - If Secure Encrypted Virtualization (SEV) is enabled, add 256 MiB.
  - If Trusted Platform Module (TPM) is enabled, add 53 MiB.

# Mermaid ↗

```
```mermaid
graph TD;
  A-->B;
  A-->C;
  B-->D;
  C-->D;
```
```



[Markdown Preview Mermaid ↗](#) VSCode



# MDX

[MDX](#) [Markdown](#) [Markdown](#) [JSX](#) [rspress MDX](#)

rspress

doom

Overview

Directive

ExternalSite

ExternalSiteLink

AcpApis0overview ExternalApis0overview

Term

props

TermsTable

props

JsonViewer

## rspress

rspress [.mdx](#)

- Badge

- [Card](#)
- [LinkCard](#)
- [PackageManagerTabs](#)
- [Steps](#)
- [Tab/Tabs](#)
- [Toc](#)

安装 @rspress/core/theme 包

preview.mdx

```
import { SourceCode } from '@rspress/core/theme'

<SourceCode href="/" />
```

## doom 文档

doom 是一个基于 MDX 的文档生成工具，它可以帮助你快速生成文档。

### Overview

doom 支持多种文档格式，包括 MDX、MD 和 HTML。

### Directive

doom 提供了多种 Directive，用于控制文档的生成和输出。

```
- 使用 `doc/en` 生成英文文档，使用 `doc/zh` 生成中文文档。

<Directive type="danger" title="警告">
  这是一个警告信息。
  `doc/zh` 生成中文文档。
</Directive>
```

- 在 `( doc/en )` 中指定语言 `doc/zh` 以指定文档语言。默认语言为 `doc/en`。

注意

在 `doc/zh` 中指定语言。

## ExternalSite

在文档中指定外部网站。

```
<ExternalSite name="connectors" />
```

### Note

在 `DevOps` 文档中指定外部网站。在 `DevOps` 文档中指定外部网站。  
[DevOps 文档](#) [↗](#)

## ExternalSiteLink

在文档中指定外部网站链接。

```
<ExternalSiteLink name="connectors" href="link.mdx#hash" children="Content" />
```

[Content](#) [↗](#)

### TIP

在 `mdx` 中指定 `<ExternalSiteLink name="connectors" href="link" children="Content" />`。  
在文档中指定外部网站链接。

```
<ExternalSiteLink name="connectors" href="link">
  Content {/*   `p`   */}
</ExternalSiteLink>
```

p children

## AcpApisOverview ExternalApisOverview

API

```
<AcpApisOverview />
{/* same as following */}
<ExternalApisOverview name="acp" />

<ExternalApisOverview name="connectors" />
```

### Note

ACP APIs [ACP APIs](#)

### Note

DevOps APIs [DevOps APIs](#)

## Term

```
<Term name="company" textCase="capitalize" />
<Term name="product" textCase="lower" />
<Term name="productShort" textCase="upper" />
```

ACP

props

- `name` :
- `textCase` : `lower` , `upper` , `capitalize`

## TermsTable

```
<TermsTable />
```

company		-	Alauda	-	
product		-	Alauda Container Platform	-	
productShort	ACP	-	ACP	-	

## props

- `terms` : `NormalizedTermItem[]`

## JsonViewer

```
<JsonViewer value={{ key: 'value' }} />
```

```
yaml    json
key: value
```

□□□□□□□□

□□□□□□□□□□□□□□□□□□ `shared` □□□□□□□□□□□□□□□□□□□□

```
import CommonContent from './shared/CommonContent.mdx'

<CommonContent />
```

□□□□□□□□ `runtime` ↗ □□□ API□□□□□□ `.jsx/.tsx` □□□□□□□□ `.mdx` □□□□□□□□

```
// shared/CommonContent.tsx
export const CommonContent = () => {
  const { page } = usePageData()
  return <div>{page.title}</div>
}

// showcase/content.mdx
import { CommonContent } from './shared/CommonContent'
;<CommonContent />
```

## WARNING

□□□□□□ `.mdx` □□□□□□□□□□ `props` □□□□□□ issue ↗ □□□□□□□□ `props` □□□□□□□□  
`.jsx/.tsx` □□□□□□□□

📄 📄 📄

`alauda` 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄 `en / zh` 📄📄📄📄📄📄📄📄📄📄📄📄  
📄 `public` 📄📄📄 `en / zh` 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄

📄 📄

- `i18n.json`
- `.ts/.tsx`
- `.mdx`

## `i18n.json`

📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄 `docs` 📄📄📄 `i18n.json` 📄📄  
📄📄📄📄📄 `useI18n` 📄📄📄📄📄📄📄📄

docs/i18n.json

```
{
  "title": {
    "zh": "标题",
    "en": "Title"
  },
  "description": {
    "zh": "描述",
    "en": "description"
  }
}
```

## .ts/.tsx

```
import { useI18n } from '@rspress/runtime'

export const CommonContent = () => {
  const t = useI18n()
  return <h1>{t('title')}</h1>
}
```

## .mdx

```
import { useI18n } from '@rspress/runtime'

# {useI18n()('title')}

{useI18n()('description')}
```



# API 文档

API 文档 API 文档 CRD (Custom Resource Definition) 文档

```
├─ apis
│   ├── advanced-apis # API
│   ├── crds # CRDs
│   └── references # 文档
```

文档

API

props

CRD

props

文档

props

openapi 文档

## API

advanced-apis/codeQualityTaskSummary.mdx

```
# CodeQualityTaskSummary

<OpenAPIPath path="/plugins/v1alpha1/template/codeQuality/task/{task-id}/summ
```

CodeQualityTaskSummary

props

- path : OpenAPI schema paths
- pathPrefix : api.pathPrefix
- openapiPath : openapi

CRD

crds/ArtifactCleanupRun.mdx

```
# ArtifactCleanupRun

<K8sCrd name="artifactcleanupruns.artifacts.katanomi.dev" />
```

ArtifactCleanupRun

props

- name : CRD metadata.name
- crdPath : openapi CRD

references/CodeQuality.mdx

# CodeQuality

```
<OpenAPIRef schema="v1alpha1.CodeQuality" />
```

仕様 CodeQuality 仕様

## props

- `schema` : OpenAPI schema `definitions` (v2) or `component/schemas` (v3) 参照
- `openapiPath` : 参照 `openapi` 参照

## 仕様 openapi 仕様

参照 `OpenAPIPath` 参照 `OpenAPIRef` 参照 `openapi` 参照

参照 `openapi` 参照 `openapiPath` 参照

```
<OpenAPIPath
  path="/plugins/v1alpha1/template/codeQuality/task/{task-id}/summary"
  openapiPath="shared/openapis/katanomi.json"
/>
```

权限管理

```
<K8sPermissionTable functions={['devops-testplans', 'devops-testmodules']} />
```

权限

props

权限

props

- functions: string[] - 权限资源 FunctionResource 列表

权限

权限	权限	权限 名称	权限 名称	权限 名称	权限 名称	权限 名称	权限 名称
权限 devops- testplans	权限	✓	✓	✓	✓	✓	✗
	权限	✓	✗	✓	✓	✓	✗
	权限	✓	✗	✓	✓	✓	✗
	权限	✓	✗	✓	✓	✓	✗

00	00	000 00	000 000	000 00	0000 000	00 00	000 00
0000 devops- testmodules	00	✓	✓	✓	✓	✓	×
	00	✓	×	✓	✓	✓	×
	00	✓	×	✓	✓	✓	×
	00	✓	×	✓	✓	✓	×

☐ Markdown ☐☐☐☐

```
<!-- reference-end -->
```

```
{/* reference-end */}
```

```
□□□□□□ <root>/public/_remotes/<name> □□□□
```

```
□□□□□ <!-- reference-start#ref --> □□□□□
```

11

## frontmatterMode

--	--	--	--	--	--

**reference:**

```

- repo: alauda-public/product-doc-guide # 
branch: # [string] 
publicBase: # [string] /images/xx.png do
sources:
  - name: anchor # 
    path: docs/index.mdx# # doom.conf
    ignoreHeading: # [boolean] true
    processors: 
      - type: ejTemplate
        data: # ejs `<%= data.xx %>` 
    frontmatterMode: merge # frontmatter ignore ign

```

**frontmatterMode**

- **ignore** frontmatter frontmatter
- **merge** frontmatter key
- **replace** frontmatter frontmatter
- **remove** frontmatter

0000000000

□ □ □ □ □

--	--	--	--	--	--



--	--	--	--	--

[illegible]

```
doom build # ████████
doom serve # ██████████
```

--	--	--	--	--

```
doom build dist -v
```



```
# ===== release-4.0 == 4.0 ==
doom build -v 4.0 # == 4.0 ===== dist/4.0===== {base}/4.0
doom build -v master # == master ===== dist/master===== {base}/master
doom build -v {other} # ===== dist/{other}===== {base}/{other}

# unversioned = unversioned-x.y =====
doom build -v unversioned # ===== dist/unversioned===== {base}
doom build -v unversioned-4.0 # ===== 4.0 ===== dist/unversio
```

□□□□□□

```
|— console-platform
|   |— 4.0
|   |— 4.1
|   |— index.html
|   |— overrides.yaml
|   └— versions.yaml
|— console-devops-docs
|   |— 4.0
|   |— 4.1
|   |— index.html
|   |— overrides.yaml
|   └— versions.yaml
|— console-tekton-docs
|   |— 1.0
|   |— 1.1
|   |— index.html
|   |— overrides.yaml
|   └— versions.yaml
```

index.html

