

--	--	--	--

Doom  [rspress](#)   Alauda                  

--	--	--	--

- □□□□□□□□□□□□□□□□□□
- □□□□□□□□
- □□□□□

□□ **Markdown** □□□□ **MDX**

MDX                                 



🐼🐼🐼🐼🐼 MDX🐼 🐼🐼🔗🐼

🐼🐼🐼🐼

🐼🐼🐼🐼🐼🐼🐼 Doom 🐼🐼

🐼🐼

🐼🐼

🐼🐼🐼🐼

🐼🐼🐼🐼🐼

🐼🐼

MDX

📄 MDX 📄📄📄📄📄📄📄📄📄📄📄📄📄

rspress 📄

doom 📄

📄📄📄📄📄

📄📄📄

📄📄📄📄📄📄📄📄📄📄📄📄

i18n.json

.ts/.tsx

.mdx

API 📄

📄 API

CRD

📄📄📄

📄 openapi 📄

📄📄📄📄📄

props

📄

📄📄📄

📄📄📄📄📄

00

000000000000000000000000 ACP 00

000000

000000

0000000

000000000

🐼



🐼

🐼🐼🐼🐼

🐼🐼🐼🐼🐼🐼🐼🐼🐼🐼🐼🐼🐼🐼🐼🐼

```
mkdir my-docs && cd my-docs
```

🐼 `npm init -y` 🐼🐼🐼🐼🐼🐼🐼🐼🐼🐼 `npm`🐼`yarn` 🐼 `pnpm` 🐼 `doom:`

 `npm`  `yarn`  `pnpm`  `bun`

```
npm install -D @alauda/doom typescript
```

🐼🐼🐼🐼🐼🐼🐼🐼:

```
# 🐼 docs 🐼🐼🐼🐼🐼🐼🐼🐼🐼🐼  
mkdir docs/en && echo '# Hello World' > docs/en/index.md  
mkdir docs/zh && echo '# 🐼🐼🐼' > docs/zh/index.md
```

🐼 `package.json` 🐼🐼🐼🐼🐼🐼:

```
{
  "scripts": {
    "dev": "doom dev",
    "build": "doom build",
    "new": "doom new",
    "serve": "doom serve",
    "translate": "doom translate",
    "export": "doom export"
  }
}
```

doom.config.yml:

```
title: My Docs
```

tsconfig.json

```
{
  "compilerOptions": {
    "jsx": "react-jsx",
    "module": "NodeNext",
    "moduleResolution": "NodeNext",
    "noUnusedLocals": true,
    "noUnusedParameters": true,
    "resolveJsonModule": true,
    "skipLibCheck": true,
    "strict": true,
    "target": "ESNext",
  },
  "mdx": {
    "checkMdx": true,
  },
}
```

global.d.ts

```
/// <reference types="@alauda/doom/runtime" />
```

📄📄📄📄📄 .mdx 📄📄📄📄📄📄📄 doom 📄📄📄📄📄📄

📄📄📄📄📄

doom -h

output

Usage: doom [options] [command]

Doctor Doom making docs.

Options:

-V, --version

output the version number

-c, --config <config>

Specify the path to the config file

-v <version>

Specify the version of the documentation, c

-b, --base <base>

Override the base of the documentation

-p, --prefix <prefix>

Specify the prefix of the documentation bas

-f, --force [boolean]

Force to

1. fetch latest reference remotes or scaffo

2. translate ignore hash equality check and

-i, --ignore [boolean]

Ignore internal routes (default: false)

-d, --download [boolean]

Display download pdf link on nav bar (defau

-e, --export [boolean]

Run or build in exporting PDF mode, `apis/*

-I, --include <language...>

Include **only** the specific language(s),

-E, --exclude <language...>

Include all languages except the specific l

-o, --out-dir <path>

Override the `outDir` defined in the config

-r, --redirect <enum>

Whether to redirect to the locale closest t

-R, --edit-repo [boolean|url]

Whether to enable or override the `editRepo

-n, --no-open [boolean]

Do not open the browser after starting the

-h, --help

display help for command

Commands:

dev [options] [root]

Start the development server

build [root]

Build the documentation

preview|serve [options] [root]

Preview the built documentation

new [template]

Generate scaffolding from templates

translate [options] [root]

Translate the documentation

export [options] [root]

Export the documentation as PDF, `apis/**`

help [command]

display help for command

Install the package

Install the package

Run `yarn dev` to start the development server

```
doom dev -h
```

```
# output
```

```
Usage: doom dev [options] [root]
```

```
Start the development server
```

```
Arguments:
```

```
  root
```

```
    Root directory of the documentation
```

```
Options:
```

```
  -H, --host [host]
```

```
    Dev server host name
```

```
  -P, --port [port]
```

```
    Dev server port number
```

```
  -l, --lazy [boolean]
```

```
    Whether to enable `lazyCompilation` which could improve  
    display help for command
```

```
  -h, --help
```

Install the package

Run `yarn build` to build the documentation to `dist` directory

Install the package

Run `yarn serve` to start the development server with `-b`, `-p` options to specify the host and port

Install the package

Run `yarn new` to create a new project

Install the package

```
doom translate -h
```

```
# output
```

```
Usage: doom translate [options] [root]
```

```
Translate the documentation
```

```
Arguments:
```

```
  root                                Root directory of the documentation
```

```
Options:
```

```
  -s, --source <language> Document source language, one of en, zh, ru (default: en)
  -t, --target <language> Document target language, one of en, zh, ru (default: en)
  -g, --glob <path...>     Glob patterns for source dirs/files
  -C, --copy [boolean]      Whether to copy relative assets to the target directory
  -h, --help                display help for command
```

- `-g, --glob` `<glob>` Glob patterns for source dirs/files

```
1. yarn translate -g abc xyz <root>/<source>/abc , <root>/<source>/xyz
   <root>/<target>/abc , <root>/<target>/xyz
```

```
2. yarn translate -g '*' <root>/<source>
```

- `-C, --copy` `<boolean>` Whether to copy relative assets to the target directory

- `<boolean>`

```
1. /<source>/abc.jpg <root>/public/<source>/abc.jpg
   <root>/public/<target>/abc.jpg /<target>/abc.jpg
```

```
2. <root>/<source>/abc.mdx ./assets/xyz.jpg
   <root>/<source>/assets/xyz.jpg <root>/<target>/assets/xyz.jpg
   <root>/<target>/assets/xyz.jpg
```

```
3. <root>/<source>/abc.mdx ./assets/<source>/xyz.jpg
   <root>/<source>/assets/<source>/xyz.jpg
   <root>/<target>/assets/<target>/xyz.jpg
   ./assets/<target>/xyz.jpg
```

- `0000000000`
 1. `/<source>/abc.jpg` `00000` `<root>/public/<target>/abc.jpg` `0000000000`
`00000000` `/<target>/abc.jpg` `000000000000000000`
 2. `<root>/<source>/abc.mdx` `0000` `./assets/<source>/xyz.jpg` `000000`
`<root>/<target>/assets/<target>/xyz.jpg` `000000000000000000`
`./assets/<target>/xyz.jpg` `00000000`
`../<source>/assets/<target>/xyz.jpg`

WARNING

当使用 `-g '*'` 时，`source` 与 `target` 必须为 `internalRoutes` 中的 `target`。

TIP

□□□□□□□□ □□□□□□□□□□ `AZURE_OPENAI_API_KEY` □□□□□□□□□□□□□□ Leader □□

TIP

□□□□□□□□ `AZURE_OPENAI_API_KEY` □□□□□□□□□□□□□□ Leader □□

□□□□□□□□□□□□□□

```
i18n:
  title:
    en: DevOps Connectors
  additionalPrompts: '#### Connectors #####'
  disableAutoTranslation: false
title: DevOps ###
```

PDF

WARNING

■■■■■■■■■■■■■■■ yarn build ■■■■

WARNING

■■■■■■■■■■■■■■■ yarn build ■■■■

```
doom export -h
```

```
# output
```

```
Usage: doom export [options] [root]
```

```
Export the documentation as PDF, `apis/**` and `*/apis/**` routes will be ign
```

```
Arguments:
```

```
  root                Root directory of the documentation
```

```
Options:
```

```
-H, --host [host]  Serve host name
-P, --port [port]  Serve port number (default: "4173")
-h, --help         display help for command
```

```
❯ yarn export 📄📄📄 PDF 📄📄📄📄📄📄 -b , -p 📄📄📄📄📄📄📄📄 -b , -p
❯
```

```
📄📄📄📄 playwright ↗📄📄📄📄📄 build-harbor.alauda.cn/frontend/playwright-
runner:doom 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄
```

```
.env.yarn
```

```
PLAYWRIGHT_DOWNLOAD_HOST="https://cdn.npmmirror.com/binaries/playwright"
```

```
📄📄📄📄
```

```
doom lint -h
```

```
# output
```

```
Usage: doom lint [options] [root]
```

```
Lint the documentation
```

```
Arguments:
```

```
  root          Root directory of the documentation
```

```
Options:
```

```
  -h, --help  display help for command
```

```
0000000000000000
```



11

□□ `doom` □□□□

4/4

□ □ □ □

API □□□□

Page 10

Page 10 of 10

Page 1 of 1

5/5/2019

Page 10

Page 10

sites.yaml

□ □ □ □

□ □ □ □ □ □ □ □ □

Page 10

11

4/4

333

11

11

Markdown

Callouts

Mermaid

MDX

📄 MDX 📄📄📄📄📄📄📄📄📄📄

rspress 📄

doom 📄

📄📄📄📄📄

📄📄

📄📄📄📄📄📄📄📄📄

i18n.json

.ts/.tsx

.mdx

API 📄

📄 API

CRD

📄📄📄

📄 openapi 📄

📄📄📄📄📄

props

📄

0000

000000

00

000000000000000000000000 ACP 00

00000

00000

000000

00000000

--	--	--	--

```

##### yaml ##### doom.config.yaml
doom.config.yaml ##### rspress ##### js/ts #####
##### .js/.ts/.mjs/.mts/.cjs/.cts #####

js/ts ##### @alauda/doom/config ##### defineConfig
#####

```

```
import { defineConfig } from '@alauda/doom/config'

export default defineConfig({})
```

--	--	--	--

- lang `en` `null` `undefined`
- title
- logo `public` `doom` `alauda logo`
- logoText `logo`
- icon `favicon` `logo`

- `base` `product-docs` `/`
- `outDir` `dist/{base}/{version}` `dist/{outDir}/{version}` `version`

API ☐ ☐ ☐ ☐

```
api:
  # CRD  doom.config.*  glob  json/yaml
  crds:
    - docs/shared/crds/*.yaml
  # OpenAPI  doom.config.*  glob  json/yaml
  openapis:
    - docs/shared/openapis/*.json
  #  openapi
  #  https://doom.alauda.cn/apis/references/CodeQuality.html#v1alpha1.CodeQ
  references:
    v1alpha1.CodeQualityBranch: /apis/references/CodeQualityBranch#v1alpha1.C
  #  API  gateway
  pathPrefix: /apis
```

□□□□□□ API □□

--	--	--	--	--	--	--	--

```
# doo.config.* glob json/yaml
permission:
  functionresources:
    # `kubectl get functionresources`
    - docs/shared/functionresources/*.yaml
  roletemplates:
    # `kubectl get roletemplates -l auth.cpaas.io/roletemplate.official=true`
    - docs/shared/roletemplates/*.yaml
```

reference:

- repo: `alauda-public/product-doc-guide` #
- branch: # [string]
- publicBase: # [string] /images/xx.png do
- sources:
 - name: `anchor` #
 - path: `docs/index.mdx#` #
 - ignoreHeading: # [boolean] true
 - processors: #
 - type: `ejsTemplate`
 - data: # `ejs` `<%= data.xx %>`
 - frontmatterMode: `merge` # frontmatter ignore ign

frontmatterMode

- `ignore` frontmatter frontmatter
- `merge` frontmatter key
- `replace` frontmatter frontmatter
- `remove` frontmatter

releaseNotes:

queryTemplates:

fixed: # `ejs` `jq`

unfixed:

release-notes.md

```
<!-- release-notes-for-bugs?template=fixed&project=DevOps -->
```

release-notes.mdx

```
{/* release-notes-for-bugs?template=fixed&project=DevOps */}
```

template=fixed&project=DevOps fixed queryTemplates
query project=DevOps [ejs](#) fixed [jira](#) [jql](#)
<https://jira.alauda.cn/rest/api/2/search?jql=<jql>> API
JIRA_USERNAME JIRA_PASSWORD

🐞🐞🐞🐞

```
sidebar:  
  collapsed: false # false
```

🐞🐞🐞🐞🐞🐞

```
internalRoutes: # docs cli -i, --ignore`  
  - '*/internal/**'
```

🐞🐞🐞🐞🐞🐞

```
onlyIncludeRoutes: # 匹配 glob 匹配 docs 下的 cli 子目录，忽略子目录
  - '*/internal/**'

internalRoutes:
  - '*/internal/overview.mdx'
```



```
shiki:
  theme: # optional, https://shiki.style/themes
  langs: # optional, https://shiki.style/languages
  transformers: # optional, only available in js/ts config, https://shiki.sty
```

WARNING

plaintext

sites.yaml

sites.yaml [View](#) [Raw](#) [Download](#)



translate:

```
# #####ejs ##### `sourceLang`, `targetLang`, `userPrompt` □ `additionalPrompts`
# □□ `sourceLang` □ `targetLang` □ `##` □ `##` #####
#   `userPrompt` #####
#   `additionalPrompts` □□□ `frontmatter.i18n` □□ `additionalPrompts` □□□
# #####
```

```
systemPrompt: |
```

□□

```

#####<%= targetLang %>#####<%= sourceLang %>###<%=

```

□□

```
- =====<%= sourceLang %>=====<%= targetLang %>=====
-      MDX      MDX      jsx      <Overview />=====
-      =====
-      MDX      MDX      MDX      MDX
-      - <Overview />  Overview
-      - <Tab label="value">=</Tab>  label  key  "value"  =====
```

<%= terms %>

```
- ████████████████████████████████████████████████████  
- { /* release-notes-for-bugs */}  
- <!-- release-notes-for-bugs -->  
  
- ████████████████████████████████████████████████████  
- { /* reference-start */}  
- { /* reference-end */}  
- <!-- reference-start -->  
- <!-- reference-end -->  
  
- ███████████████████ \\  
- ███████████████████ \{ ████████████████████  
  
- ███████████████████ Markdown █████ frontmatter, ███████████████████ frontmatter.ii8n █████
```

□□

□ □ □ □ □ □ □ □ □ □

```
1.   sourceLang %>% summarise(targetLang %)
2. 
-   targetLang %>% 
-   summarise(
-   )
3.   summarise(targetLang %)
4.   summarise(targetLang %, targetLang %)
```

□ □

```
<%= userPrompt %>
```

```
<%= additionalPrompts %>
```

```
userPrompt: # 🐙🐙🐙🐙🐙🐙🐙 `systemPrompt` 🐙🐙 `ejs` 🐙🐙🐙🐙
```

🐙🐙🐙🐙🐙🐙🐙🐙

```
editRepoBaseUrl: alauda/doom/tree/main/docs # https://github.com/ 🐙🐙🐙🐙🐙🐙🐙🐙
```

🐙🐙🐙🐙🐙🐙

```
lint:
```

```
cspellOptions: # 🐙🐙🐙cspell 🐙🐙🐙🐙🐙 https://github.com/streetsidesoftware/csp
```


--	--	--	--

```

index
index.md index.mdx

```

```
├─ index.md
├─ start.mdx
└─ usage
    ├─ index.mdx
    └─ convention.md
```

□ □ □ □ □ □

1. `public` `xxxxxxxxxxxxxxxxxxxx`
2. `public/_remotes` `xxxx` `xxxxxx` `xx`
`*/public/_remotes` `xx` `.gitignore` `xxxxxxxxxx`
3. `shared` `xx`

□□□□□□□□ frontmatter □□□□□□□□□□□□□□□□□□□□

```

--
title:  []
description:  []
author:  []
category:  []
--

```

□□□□□□□□ MDX □□ .mdx □□□□□□□□ frontmatter □□□□□□□□

□ □

index.md index.mdx frontmatter weight

```

- - -
weight: 1
- - -

```

WARNING

[illegible]

11

index.mdx Overview

□ □

<Overview />

0000000000

Markdown

[gfm](#)
Doom
Markdown

Callouts

NOTE

- 1. ; , % , # , // , /** */ , -- <!-- -->
- 2. [\\!code callout]
- 3. :::callouts <div class="doom-callouts"> <Callouts>

```
```sh
```

```
Memory overhead per virtual machine ≈ (1.002 × requested memory) \
 + 218 MiB \
 + 8 MiB × (number of vCPUs) \
 + 16 MiB × (number of graphics devices) \
 + (additional memory overhead)
```

```
```
```

```
:::callouts
```

1. Required for the processes that run in the `virt-launcher` pod.
2. Number of virtual CPUs requested by the virtual machine.
3. Number of virtual graphics cards requested by the virtual machine.
4. Additional memory overhead:
 - If your environment includes a Single Root I/O Virtualization (SR-IOV) network device or a Graphics Processing Unit (GPU), allocate 1 GiB additional memory overhead for each device.
 - If Secure Encrypted Virtualization (SEV) is enabled, add 256 MiB.
 - If Trusted Platform Module (TPM) is enabled, add 53 MiB.

```
:::
```

```
Memory overhead per virtual machine ≈ (1.002 × requested memory) \
    + 218 MiB \
    + 8 MiB × (number of vCPUs) \
    + 16 MiB × (number of graphics devices) \
    + (additional memory overhead)
```

- ① Required for the processes that run in the `virt-launcher` pod.
- ② Number of virtual CPUs requested by the virtual machine.
- ③ Number of virtual graphics cards requested by the virtual machine.
- ④ Additional memory overhead:
 - If your environment includes a Single Root I/O Virtualization (SR-IOV) network device or a Graphics Processing Unit (GPU), allocate 1 GiB additional memory overhead for each device.
 - If Secure Encrypted Virtualization (SEV) is enabled, add 256 MiB.
 - If Trusted Platform Module (TPM) is enabled, add 53 MiB.

Mermaid ↗

□□□□□□

```
```mermaid
graph TD;
 A-->B;
 A-->C;
 B-->D;
 C-->D;
```
```

□□ [Markdown Preview Mermaid ↗](#) □□□ VSCode □□□□□□

MDX

[MDX](#) [↗](#) [Markdown](#) [Markdown](#) [JSX](#) [rspress MDX](#) [↗](#)

rspress

rspress [↗](#) .mdx

- Badge
- Card
- LinkCard
- PackageManagerTabs
- Steps
- Tab/Tabs
- Toc

@rspress/core/theme

preview.mdx

```
import { SourceCode } from '@rspress/core/theme'

<SourceCode href="/" />
```

doom

doom 是一个基于 React 的文档生成工具，它可以帮助你快速生成高质量的文档。

Overview

doom 是一个基于 React 的文档生成工具，它可以帮助你快速生成高质量的文档。

Directive

doom 支持使用 Directive 来生成文档，Directive 是一个用于生成文档的组件。

```
- 使用 Directive 生成文档时，需要在文档的开头添加 Directive 的声明。
```

```
<Directive type="danger" title="警告">
  这里是一个警告信息，请用户仔细阅读。
  `doc/zh` 文档中已经包含该警告。
</Directive>
```

- 使用 Directive 生成文档时，需要在文档的开头添加 Directive 的声明。

警告

这里是一个警告信息，请用户仔细阅读。`doc/zh` 文档中已经包含该警告。

警告

ExternalSite

doom 支持使用 ExternalSite 来生成文档，ExternalSite 是一个用于生成文档的组件。

```
<ExternalSite name="connectors" />
```


Note

ExternalSiteLink

□ □ □ □ □ □ □ □ □ □

```
<ExternalSiteLink name="connectors" href="link.mdx#hash" children="Content" />
```

TIP

```
mdx <ExternalSiteLink name="connectors" href="link" children="Content" />
```

```
<ExternalSiteLink name="connectors" href="link">
  Content {/* □□□□ `p` □□□ */}
</ExternalSiteLink>
```

□□□□□□□□ p □□□□□□□□□□□□□□ children □□□□

AcpApisOverview ☒ ExternalApisOverview

□□□□□□ API □□□□

```
<AcpApisOverview />
{ /* same as following */ }
<ExternalApisOverview name="acp" />

<ExternalApisOverview name="connectors" />
```

Note

□□ ACP APIs □□□□□□□□□□ □

Note

□□ DevOps □□□ APIs □□□□□□□□□□ □

Term

```
<Term name="company" textCase="capitalize" />
<Term name="product" textCase="lower" />
<Term name="productShort" textCase="upper" />
```

props

- `name` : `□□□□□□□□□□□□□□□□`
- `textCase` : `□□□□□□□□□□□□` `lower` , `upper` , `capitalize`

TermsTable

□ □ □ □ □ □ □ □ □ □

```
<TermsTable />
```

公司	名称	类型	名称	类型	名称
company	名称	-	Alauda	-	名称
product	名称 名称	-	Alauda Container Platform	-	名称
productShort	ACP	-	ACP	-	名称 名称

props

- terms : NormalizedTermItem[]

JsonViewer

```
<JsonViewer value={{ key: 'value' }} />
```

yaml json

--	--	--	--	--	--	--

□□□□□□□□□□□□□□□□ shared □□□□□□□□□□□□□□□□□□□□

```
import CommonContent from './shared/CommonContent.mdx'
```

<CommonContent />

runtime [↗](#) API `.jsx/.tsx` `.mdx`

```
// shared/CommonContent.tsx

export const CommonContent = () => {
  const { page } = usePageData()
  return <div>{page.title}</div>
}

// showcase/content.mdx

import { CommonContent } from './shared/CommonContent'
;<CommonContent />
```

WARNING

`.mdx` props issue props
`.jsx/.tsx`

📄📄📄

`alauda` 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄 `en / zh` 📄📄📄📄📄📄📄📄📄📄📄📄📄
📄 `public` 📄📄📄📄 `en / zh` 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄

📄📄

`i18n.json`

📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄 `docs` 📄📄📄📄 `i18n.json` 📄📄
📄📄📄📄📄📄 `useI18n` 📄📄📄📄📄📄📄📄📄

docs/i18n.json

```
{
  "title": {
    "zh": "📄📄",
    "en": "Title"
  },
  "description": {
    "zh": "📄📄",
    "en": "description"
  }
}
```

`.ts/.tsx`

```
import { useI18n } from '@rspress/runtime'

export const CommonContent = () => {
  const t = useI18n()
  return <h1>{t('title')}</h1>
}
```

.mdx

```
import { useI18n } from '@rspress/runtime'

# {useI18n()('title')}

{useI18n()('description')}
```

API 00

00000000000000000000 API 0000 API 0 CRD (Custom Resource Definition) 000000000000
00000000

```
└─ apis
  │   └─ advanced-apis # 00 API
  │   └─ crds # CRDs
  │   └─ references # 0000
```

00

00 API

```
advanced-apis/codeQualityTaskSummary.mdx

# CodeQualityTaskSummary

<OpenAPIPath path="/plugins/v1alpha1/template/codeQuality/task/{task-id}/summ
```

00 [CodeQualityTaskSummary](#)0

props

- path : OpenAPI schema paths 0000
- pathPrefix : 00000000000000000000 api.pathPrefix
- openapiPath : 0000 [openapi](#) 00

CRD

crds/ArtifactCleanupRun.mdx

```
# ArtifactCleanupRun
```

```
<K8sCrd name="artifactcleanupruns.artifacts.katanomi.dev" />
```

〇〇 [ArtifactCleanupRun](#) 〇

props

- `name` : CRD `metadata.name`
- `crdPath` : 〇〇〇〇 [openapi](#) 〇〇〇〇〇〇〇〇〇〇 CRD 〇〇

〇〇〇〇

references/CodeQuality.mdx

```
# CodeQuality
```

```
<OpenAPIRef schema="v1alpha1.CodeQuality" />
```

〇〇 [CodeQuality](#) 〇

props

- `schema` : OpenAPI schema `definitions` (v2) or `component/schemas` (v3) 〇〇〇〇
- `openapiPath` : 〇〇〇〇 [openapi](#) 〇〇

関数 openapi 関数

関数 `OpenAPIPath` 関数 `OpenAPIRef` 関数 `openapi` 関数 `openapiPath` 関数 `openapi` 関数 `openapiPath` 関数 `openapi`

```
<OpenAPIPath
  path="/plugins/v1alpha1/template/codeQuality/task/{task-id}/summary"
  openapiPath="shared/openapis/katanomi.json"
/>
```


权限管理

```
<K8sPermissionTable functions={['devops-testplans', 'devops-testmodules']} />
```

权限

props

- functions: string[] - 权限资源 FunctionResource 列表

权限

权限	权限	权限 名称	权限 名称	权限 名称	权限 名称	权限 名称	权限 名称
权限 devops- testplans	权限	✓	✓	✓	✓	✓	✗
	权限	✓	✗	✓	✓	✓	✗
	权限	✓	✗	✓	✓	✓	✗
	权限	✓	✗	✓	✓	✓	✗
权限 devops- testmodules	权限	✓	✓	✓	✓	✓	✗
	权限	✓	✗	✓	✓	✓	✗
	权限	✓	✗	✓	✓	✓	✗

□□	□□	□□□ □□	□□□ □□□	□□□ □□	□□□□ □□□	□□ □□	□□□ □□
	□□	✓	×	✓	✓	✓	×

--	--	--	--

☐ Markdown ☐☐☐☐

```
<!-- reference-end -->
```

MDX

```
{/* reference-end */}
```

name

```
□□□□□□ <root>/public/_remotes/<name> □□□□
```

```
□□□□□ <!-- reference-start#ref --> □□□□□
```

--	--	--	--	--	--

reference:

```
- repo: alauda-public/product-doc-guide # 
branch: # [string] 
publicBase: # [string] /images/xx.png do
sources:
  - name: anchor # 
    path: docs/index.mdx# # doom.conf
    ignoreHeading: # [boolean] true
    processors: # 
      - type: ejsTemplate
        data: # ejs `<%= data.xx %>` 
    frontmatterMode: merge # frontmatter ignore ign
```

frontmatterMode

- ignore frontmatter frontmatter
- merge frontmatter key
- replace frontmatter frontmatter
- remove frontmatter

0000000000

```
doom build # 
doom serve # 
```

doom build dist -v

```
# release-4.0  4.0 
doom build -v 4.0 #  4.0  dist/4.0{base}/4.0
doom build -v master #  master  dist/master{base}/master
doom build -v {other} #  dist/{other}{base}/{other}

# unversioned  unversioned-x.y 
doom build -v unversioned #  dist/unversioned{base}
doom build -v unversioned-4.0 #  4.0  dist/unversio
```

☐☐☐☐☐☐☐

```
|— console-platform
|   |— 4.0
|   |— 4.1
|   |— index.html
|   |— overrides.yaml
|   └─ versions.yaml
|— console-devops-docs
|   |— 4.0
|   |— 4.1
|   |— index.html
|   |— overrides.yaml
|   └─ versions.yaml
|— console-tekton-docs
|   |— 1.0
|   |— 1.1
|   |— index.html
|   |— overrides.yaml
|   └─ versions.yaml
```

index.html

```
<!DOCTYPE html>
<html>
  <head>
    <title>Redirecting...</title>
    <meta http-equiv="refresh" content="0; url=/console-docs/4.1" />
  </head>
  <body>
    <p>Redirecting to <a href="/console-docs/4.1">/console-docs/4.1</a></p>
  </body>
</html>
```

☐☐☐☐☐☐☐☐☐

overrides.yaml

```
# □□□□□□□□□□□□□□□□□□□□□□□□  
title:  
    en: Doom - Alauda  
    zh: Doom - □□□  
logoText:  
    en: Doom - Alauda  
    zh: Doom - □□□
```

versions.yaml

- '4.1'
- '4.0'