

Doom [rspress](#) [Alauda](#)

APIs

[illegible]



MDX

Doom

``doom`

“”

Markdown

Callouts

📄📄📄

📄📄📄

API 📄📄📄

📄📄📄📄📄📄

📄📄📄📄📄

📄📄📄📄📄

📄📄📄📄

📄📄📄📄📄

📄📄📄📄📄📄

📄📄📄📄📄📄

📄📄📄📄📄

`sites.yaml` 📄📄

📄📄📄📄

📄📄📄📄📄📄📄📄

📄📄📄📄📄

📄📄📄📄📄

Algolia 📄📄📄📄

Sitemap 📄📄

📄📄📄📄

📄📄📄

📄📄

📄📄

📄📄📄

📄📄📄📄📄📄📄📄📄📄📄📄

`i18n.json`

`.ts/.tsx`

`.mdx`

📄📄📄📄📄📄

`props`

📄📄

Mermaid

MDX

📄📄 MDX 📄📄📄📄

rspress 📄📄

API 📄📄

K8S API

📄📄📄📄

📄📄📄📄📄

📄📄

📄📄📄📄📄📄📄📄

📄📄📄📄

📄📄📄📄

📄📄📄📄📄

📄📄📄📄📄📄

APIs

Advanced APIs

CRDs

Kubernetes

Common References

📄📄

📄📄

📄📄📄📄

📄📄📄📄

📄📄📄📄

📄📄📄📄

📄📄📄

📄📄📄📄📄

📄📄📄

📄📄 PDF

📄📄📄

📄📄📄📄

📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄

`mkdir my-docs && cd my-docs`

📄 `npm init -y` 📄📄📄📄📄📄📄📄📄📄📄📄 `npm`📄`yarn` 📄 `pnpm` 📄📄 `doom:`

 `npm`

 `yarn`

 `pnpm`

 `bun`

 `deno`

```
npm install -D @alauda/doom typescript
```

创建文档目录:

```
# 创建 docs 目录
mkdir docs/en && echo '# Hello World' > docs/en/index.md
mkdir docs/zh && echo '# 文档' > docs/zh/index.md
```

在 `package.json` 中添加:

```
{
  "scripts": {
    "dev": "doom dev",
    "build": "doom build",
    "new": "doom new",
    "serve": "doom serve",
    "translate": "doom translate",
    "export": "doom export"
  }
}
```

创建配置文件 `doom.config.yml`:

```
title: My Docs
```

创建 `tsconfig.json` 文件

```
{
  "compilerOptions": {
    "jsx": "react-jsx",
    "module": "NodeNext",
    "moduleResolution": "NodeNext",
    "noUnusedLocals": true,
    "noUnusedParameters": true,
    "resolveJsonModule": true,
    "skipLibCheck": true,
    "strict": true,
    "target": "ESNext",
  },
  "mdx": {
    "checkMdx": true,
  },
}
```

📄📄📄 `global.d.ts` 📄📄📄📄📄📄

```
/// <reference types="@alauda/doom/runtime" />
```

📄📄📄📄📄 `.mdx` 📄📄📄📄📄📄📄 `doom` 📄📄📄📄📄📄📄

📄📄📄📄📄




```
doom -h
```

```
# output
```

```
Usage: doom [options] [command]
```

```
Doctor Doom making docs.
```

```
Options:
```

```
  -V, --version                output the version number
  -c, --config <config>       Specify the path to the config file
  -v <version>                 Specify the version of the document
                                ation, can also be `unversioned` or `unversioned-x.y`
  -b, --base <base>           Override the base of the documentat
                                ion
  -p, --prefix <prefix>       Specify the prefix of the documenta
                                tion base
  -f, --force [boolean]        Force to
                                1. fetch latest reference remotes o
                                r scaffolding templates, otherwise use local cache
                                2. translate ignore hash equality c
                                heck and original text (default: false)
  -i, --ignore [boolean]       Ignore internal routes (default: fa
                                lse)
  -d, --download [boolean]     Display download pdf link on nav ba
                                r (default: false)
  -e, --export [boolean]       Run or build in exporting PDF mode,
                                `apis/**` and `*/apis/**` routes will be ignored automatically (default:
                                false)
  -I, --include <language...> Include **only** the specific langu
                                age(s), `en ru` for example
  -E, --exclude <language...> Include all languages except the sp
                                ecific language(s), `ru` for example
  -o, --out-dir <path>         Override the `outDir` defined in th
                                e config file or the default `dist/{base}/{version}`, the resulting path
                                will be `dist/{outDir}/{version}`
  -r, --redirect <enum>        Whether to redirect to the locale c
                                losest to `navigator.language` when the user visits the site, could be `a
                                uto`, `never` or `only-default-lang` (default: "only-default-lang")
  -R, --edit-repo [boolean|url|lang] Whether to enable or override the `
                                editRepoBaseUrl` config feature, `https://github.com/` prefix could be om
                                itted; if a language code is provided, all other languages will use the s
                                ame repo but with the language code as sub-path (default: false)
  -a, --algolia [boolean|alauda] Whether to enable or use the alauda
```

```
(docs.alauda.io) preset for Algolia search (default: false)
  -S, --site-url <url>           Whether to enable the siteUrl for s
itemap generation (default: false)
  -n, --no-open                   Do not open the browser after start
ing the server
  --lang <language>              Specify the language of the documen
tation
  -h, --help                      display help for command
```

Commands:

```
dev [options] [root]             Start the development server
build [root]                     Build the documentation
preview|serve [options] [root]   Preview the built documentation
new [template]                  Generate scaffolding from templates
translate [options] [root]       Translate the documentation
export [options] [root]          Export the documentation as PDF, `a
pis/**` and `*/apis/**` routes will be ignored automatically
lint [options] [root]            Lint the documentation
help [command]                  display help for command
```

yarn dev

```
doom dev -h
```

```
# output
```

```
Usage: doom dev [options] [root]
```

```
Start the development server
```

```
Arguments:
```

```
  root                                Root directory of the documentation
```

```
Options:
```

```
  -H, --host [host]                  Dev server host name
  -P, --port [port]                  Dev server port number
  -l, --lazy [boolean]                Whether to enable `lazyCompilation` which could improve the compilation performance (default: true)
  --no-lazy                          Do not enable `lazyCompilation`
  -h, --help                          display help for command
```

📄📄📄📄📄📄

📄 `yarn build` 📄📄📄📄📄📄📄📄📄📄📄📄📄 `dist` 📄📄📄📄📄📄

📄📄📄📄

📄 `yarn serve` 📄📄📄📄📄📄📄📄📄📄📄📄📄 `-b`, `-p` 📄📄📄📄📄📄📄📄📄 `-b`, `-p`

📄📄

📄📄📄📄📄📄📄

📄 `yarn new` 📄📄📄📄📄📄📄📄📄📄📄📄📄

📄📄📄📄

```
doom translate -h
```

```
# output
```

```
Usage: doom translate [options] [root]
```

```
Translate the documentation
```

```
Arguments:
```

```
  root                                Root directory of the documentation
```

```
Options:
```

```
  -s, --source <language>  Document source language, one of en, zh, ru (default: "en")
```

```
  -t, --target <language>  Document target language, one of en, zh, ru (default: "zh")
```

```
  -g, --glob <path...>     Glob patterns of source dirs/files to translate
```

```
  -C, --copy [boolean]     Whether to copy relative assets to the target directory instead of following links (default: false)
```

```
  -h, --help                display help for command
```

- `-g, --glob` 指定要翻译的源目录/文件的glob模式 `glob` 模式支持通配符 `*` 和 `?`

1. `yarn translate -g abc xyz` 将 `<root>/<source>/abc` , `<root>/<source>/xyz` 复制到 `<root>/<target>/abc` , `<root>/<target>/xyz`

2. `yarn translate -g '*'` 将 `<root>/<source>` 下的所有文件复制到 `<root>/<target>`

- `-C, --copy` 是否复制相对资产到目标目录而不是跟随链接 `false` 表示不复制

- 示例

1. `/<source>/abc.jpg` 复制到 `<root>/public/<source>/abc.jpg` 并

复制到 `<root>/public/<target>/abc.jpg` 并复制到 `/<target>/abc.jpg`

2. `<root>/<source>/abc.mdx` 复制到 `./assets/xyz.jpg` 并复制到

`<root>/<source>/assets/xyz.jpg` 并复制到 `<root>/<target>/assets/xyz.jpg` 并复制到

`<root>/<target>/assets/xyz.jpg`

3. `<root>/<source>/abc.mdx` `./assets/<source>/xyz.jpg`
`<root>/<source>/assets/<source>/xyz.jpg`
`<root>/<target>/assets/<target>/xyz.jpg`
`./assets/<target>/xyz.jpg`

•

1. `/<source>/abc.jpg` `<root>/public/<target>/abc.jpg`
`/<target>/abc.jpg`
2. `<root>/<source>/abc.mdx` `./assets/<source>/xyz.jpg`
`<root>/<target>/assets/<target>/xyz.jpg`
`./assets/<target>/xyz.jpg`
`../<source>/assets/<target>/xyz.jpg`

WARNING

`-g '*'` `source` `target` `internalRoutes`
`target`

TIP

`AZURE_OPENAI_API_KEY` Leader

```
i18n:
  title:
    en: DevOps Connectors
  additionalPrompts: 'Connectors '
  disableAutoTranslation: false
title: DevOps
```

PDF

WARNING

```

□□□□□□□□□□□□□□ yarn build □□□□

```

```
doom export -h
```

```
# output
```

Usage: doom export [options] [root]

Export the documentation as PDF, ``apis/**`` and ``*/apis/**`` routes will be ignored automatically

Arguments:

```
root      Root directory of the documentation
```

Options:

`-H, --host [host]` Serve host name

```
-P, --port [port]  Serve port number (default: "4173")
```

```
-h, --help    display help for command
```

□□ yarn export □□□□ PDF □□□□□□□□□□ -b, -p □□□□□□□□□□□□□□ -b, -p □□

playwright ↗ build-harbor.alauda.cn/frontend/playwright-runner:doom

`.env.yarn`

```
PLAYWRIGHT_DOWNLOAD_HOST="https://cdn.npmmirror.com/binaries/playwright"
```

□□□□□□□□ pdf □□□ doom □□□□□□□□□□ pdf □□□□□□□□□□□□□□□□□□□□□□□□

--	--	--	--

```
doom lint -h
```

```
# output
```

```
Usage: doom lint [options] [root]
```

```
Lint the documentation
```

```
Arguments:
```

```
  root                Root directory of the documentation
```

```
Options:
```

```
  -g, --glob <path...>  Glob patterns of source dirs/files to lint (default: "**/*.{js,jsx,ts,tsx,md,mdx}")
  --no-cspell            Disable cspell linting
  -h, --help            display help for command
```

```
doom lint ESLint cspell
```

[ESLint](#) / [CSpell](#):

- `eslint.config.mjs`:

```
import doom from '@alauda/doom/eslint'

export default doom(new URL('docs', import.meta.url))
```

- `cspell.config.mjs`:

```
export { default } from '@alauda/doom/cspell'
```

`CWD` `.cspell` `CSpell` `.cspell/k8s.txt`

```
k8s
kubernetes
```

🐙🐙

🐙🐙

🐙🐙 `doom` 🐙🐙🐙

🐙🐙🐙🐙

🐙🐙🐙🐙

API 🐙🐙🐙

🐙🐙🐙🐙🐙🐙

🐙🐙🐙🐙🐙

🐙🐙🐙🐙🐙

🐙🐙🐙🐙

🐙🐙🐙🐙🐙🐙

🐙🐙🐙🐙🐙🐙

🐙🐙🐙🐙🐙🐙

`sites.yaml` 🐙🐙

🐙🐙🐙🐙

🐙🐙🐙🐙🐙🐙🐙

🐙🐙🐙🐙🐙

🐙🐙🐙🐙🐙

Algolia 🐙🐙🐙

Sitemap 🐙🐙

🐙🐙

🐙🐙“🐙🐙🐙🐙🐙🐙”🐙🐙🐙🐙🐙🐙🐙🐙🐙🐙🐙🐙

🐙🐙🐙🐙

🐙🐙🐙

🐙🐙

🐙🐙

🐙🐙🐙

🐙🐙🐙🐙🐙🐙🐙🐙🐙🐙🐙🐙

`i18n.json`

`.ts/.tsx`

`.mdx`

🐙🐙🐙🐙🐙🐙

`props`

🐙🐙

Markdown

Callouts

Mermaid

MDX

🐙🐙 MDX 🐙🐙🐙

rspress 🐙🐙

API 🐙🐙

K8S API

🐙🐙🐙🐙

🐙🐙🐙🐙🐙

🐙🐙

🐙🐙🐙🐙🐙🐙🐙

🐙🐙🐙🐙

📄📄

📄📄

|

📄📄📄📄	
📄📄📄📄	
API 📄📄📄📄	
📄📄📄📄📄📄📄📄	
📄📄📄📄📄📄	
frontmatterMode	
📄📄📄📄📄📄	
📄📄📄📄📄	
📄📄📄📄📄📄📄📄	
📄📄📄📄📄📄📄📄	
📄📄📄📄📄📄📄	
sites.yaml	📄📄
📄📄📄📄	
📄📄📄📄📄📄📄📄📄📄📄	
📄📄📄📄📄📄	
📄📄📄📄📄📄	
Algolia 📄📄📄📄	
Sitemap 📄📄	

--	--	--	--

```
yaml doom.config.yaml  
doom.config.yaml rspress js/ts  
.js/.ts/.mjs/.mts/.cjs/.cts
```

```

js/ts  @alauda/doom/config  defineConfig

```

```
import { defineConfig } from '@alauda/doom/config'

export default defineConfig({})
```


- `lang` `en` `null` `undefined`
- `title`
- `logo` `public` `doom` `alauda logo`
- `logoText` `logo`
- `icon` `favicon` `logo`
- `base` `product-docs` `/`
- `outDir` `dist/{base}/{version}` `dist/{outDir}/{version}` `version`

API ☐ ☐ ☐ ☐

api:

```
# CRD 配置 doom.config.* 文件 glob 模式 json/yaml 文件
```

crds:

```
- docs/shared/crds/*.yaml
```

```
# OpenAPI 配置 doom.config.* 文件 glob 模式 json/yaml 文件
```

openapis:

```
- docs/shared/openapis/*.json
```

```
# 配置 openapi 文件
```

```
# 配置 https://doom.alauda.cn/apis/references/CodeQuality.html#v1alpha1.CodeQualitySpec
```

references:

```
  v1alpha1.CodeQualityBranch: /apis/references/CodeQualityBranch#v1alpha1.CodeQualityBranch
```

```
# 配置 API 网关
```

```
pathPrefix: /apis
```

配置 API 文件

配置 API 文件

```
# 配置 doom.config.* 文件 glob 模式 json/yaml 文件
```

permission:**functionresources:**

```
# `kubectl get functionresources`
```

```
- docs/shared/functionresources/*.yaml
```

roletemplates:

```
# `kubectl get roletemplates -l auth.cpaas.io/roletemplate.official=true`
```

```
- docs/shared/roletemplates/*.yaml
```

配置 API 文件

配置 API 文件

reference:

```
- repo: alauda-public/product-doc-guide # 

```

frontmatterMode

- `ignore` 忽略 frontmatter 内容
- `merge` 合并 frontmatter 内容
- `replace` 替换 frontmatter 内容
- `remove` 移除 frontmatter 内容

📄📄📄📄📄

📄📄📄📄📄

releaseNotes:

queryTemplates:

```
fixed: # 使用 ejs 模板
unfixed:
```

release-notes.md

```
<!-- release-notes-for-bugs?template=fixed&project=DevOps -->
```

release-notes.mdx

```
{/* release-notes-for-bugs?template=fixed&project=DevOps */}
```

```

template=fixed&project=DevOps  fixed  queryTemplates 
query  project=DevOps  ejts  fixed  jira  jql
https://jira.alauda.cn/rest/api/2/search?jql=<jql>  API 
JIRA_USERNAME  JIRA_PASSWORD 

```

🌑🌑🌑🌑🌑

```

sidebar:
  collapsed: false # 

```

🌑🌑🌑🌑🌑🌑🌑

```

internalRoutes: #  glob  docs  cli  -i, --ignore` 
/
- '*/internal/**'

```

🌑🌑🌑🌑🌑🌑🌑

```

onlyIncludeRoutes: #  glob  docs  cli  -i, --ignore` 
/` 
- '*/internal/**'
internalRoutes:
- '*/internal/overview.mdx'

```



```
shiki:
  theme: # optional, https://shiki.style/themes
  langs: # optional, https://shiki.style/languages
  transformers: # optional, only available in js/ts config, https://shiki.style/guide/transformers
```

WARNING

plaintext

sites.yaml

sites.yaml □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□

```
- name: connectors # 
base: /devops-connectors # 
version: v1.1 # ExternalSite/ExternalSiteLink 

displayName: #  name
    en: DevOps Connectors
    zh: DevOps 

# 
# 

repo: https://github.com/AlaudaDevops/connectors-operator # 
gitlab slug `alauda/product-docs`
image: devops/connectors-docs # 
```

--	--	--	--



translate:

```
# =====ejs ===== `sourceLang`, `targetLang`, `userPrompt`, `additionalPrompts`, `terms`, `titleTranslationPrompt`
# == `sourceLang` == `targetLang` == `` == `` =====
# `userPrompt` =====
# `additionalPrompts` == `frontmatter.i18n` == `additionalPrompts`
=====
# `terms` == `titleTranslationPrompt` ===== AI
=====
# =====
```

systemPrompt: |

You are a professional technical documentation engineer, skilled in writing high-quality technical documentation in <%= targetLang %>. Please accurately translate the following text from <%= sourceLang %> to <%= targetLang %>, maintaining the style consistent with technical documentation in <%= sourceLang %>.

Baseline Requirements

- Sentences should be fluent and conform to the expression habits of the <%= targetLang %> language.
- Input format is MDX; output format must also retain the original MDX format. Do not translate the names of jsx components such as <Overview />, and do not wrap output in unnecessary code blocks.
- ****CRITICAL****: Do not translate or modify ANY link content in the document. This includes:
 - **URLs in markdown links**: [text](URL) - keep URL exactly as is
 - **Reference-style links**: [text][ref] and [ref]: URL - keep both ref and URL unchanged
 - **Inline URLs**: https://example.com - keep completely unchanged
 - **Image links**: ![alt](src) - keep src unchanged, but alt text can be translated
 - **Anchor links**: [text](#anchor) - keep #anchor unchanged
 - Any href attributes in HTML tags - keep unchanged
- **Do not translate professional technical terms and proper nouns, including but not limited to**: Kubernetes, Docker, CLI, API, REST, GraphQL, JSON, YAML, Git, GitHub, GitLab, AWS, Azure, GCP, Linux, Windows, macOS, Node.js, React, Vue, Angular, TypeScript, JavaScript, Python, Java, Go, Rust, etc. Keep these terms in their original form.
- The title field and description field in frontmatter should be translated, other frontmatter fields should retain and do not translate.
- Content within MDX components needs to be translated, whereas MDX component names and parameter keys do not.
- Do not modify or translate any placeholders in the format of __ANCHOR_N

__ (where N is a number). These placeholders must be kept exactly as they appear in the source text.

- Keep original escape characters like backslash, angle brackets, etc. unchanged during translation.

- Do not add any escape characters to special characters like [], (), {}, etc. unless they were explicitly present in the source text. For example:

- If source has "Architecture [Optional]", keep it as "Architecture [Optional]" (not "Architecture \[Optional]")

- If source has "Function (param)", keep it as "Function (param)" (not "Function \ (param)")

- Only add escape characters if they were present in the original text

- Preserve and do not translate the following comments, nor modify their content:

- { /* release-notes-for-bugs */ }

- <!-- release-notes-for-bugs -->

- Remove and do not retain the following comments:

- { /* reference-start */ }

- { /* reference-end */ }

- <!-- reference-start -->

- <!-- reference-end -->

- Ensure the original Markdown format remains intact during translation, such as frontmatter, code blocks, lists, tables, etc.

- Do not translate the content of the code block.

```
<% if (titleTranslationPrompt) { %>
```

```
<%- titleTranslationPrompt %>
```

```
<% } %>
```

```
<% if (terms) { %>
```

```
<%- terms %>
```

```
<% } %>
```

```
<% if (userPrompt || additionalPrompts) { %>
```

```
## Additional Requirements
```

These are additional requirements for the translation. They should be met along with the baseline requirements, and in case of any conflict, the baseline requirements should take precedence.

The text for translation is provided below, within triple quotes:

```
"""
```

```
<% if (userPrompt) { %>
```

```
<%- userPrompt %>
```

```
<% } %>
```

```
<% if (additionalPrompts) { %>
```

```
<%- additionalPrompts %>
```

```
<% } %>
""
<% } %>
```

📄📄📄📄📄📄📄📄

```
editRepoBaseUrl: alauda/doom/tree/main/docs # https://github.com/ 📄📄📄📄
📄📄📄 -R, --edit-repo` 📄📄📄📄📄📄
```

📄📄📄📄📄📄

```
export:
  - name: Concepts # 📄📄📄📄 pdf 📄📄📄📄📄📄
    scope: '*/concepts' # 📄📄📄📄📄📄📄📄📄📄 glob 📄📄📄📄 docs 📄
```

📄📄📄📄📄📄

```
lint:
  cspellOptions: # 📄📄📄cspell 📄📄📄📄 https://github.com/streetsidesoftware/cspell/tree/main/packages/cspell-eslint-plugin#options
```

Algolia 📄📄📄📄

```
algolia: # 📄📄📄Algolia 📄📄📄📄📄📄 -a, --algolia` 📄📄📄📄📄
appId: # Algolia 📄 ID
apiKey: # Algolia API Key
indexName: # Algolia 📄📄📄
```

📄📄📄 `public/robots.txt` 📄📄 Algolia 📄📄📄📄

📄 `rspress` 📄📄📄📄📄📄 `Algolia` 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄
📄`@alauda/doom/theme` 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄

theme/index.ts

```
export * from '@alauda/doom/theme'
```

Sitemap 📄📄

```
siteUrl: https://docs.alauda.cn # 📄📄📄 URL📄📄📄 sitemap📄📄📄 ` -S, --site  
-url` 📄📄📄📄📄📄
```

11

1. `public` □□□□□□□□□□□□□□□□
2. `public/_remotes` □□□□□□□□□□□□□□□□□□□□□□□□□□□□
`*/public/_remotes` □□ `.gitignore` □□□□□□□□

shared

frontmatter

MDX

frontmatter

index.md

index.mdx

frontmatter

weight

weight

index.mdx

Overview

#

<Overview />

Markdown

[gfm](#) Doom Markdown

Callouts

Mermaid

Callouts

Note

1. ; , % , # , // , /** */ , -- <!-- -->
2. [\\!code callout]
3. :::callouts <div class="doom-callouts"> <Callouts>


```

```sh
Memory overhead per virtual machine ≈ (1.002 × requested memory) \
 + 218 MiB \ # [!code callout]
 + 8 MiB × (number of vCPUs) \ # [!code callout]
 + 16 MiB × (number of graphics devices) \ # [!code callou
t]
 + (additional memory overhead) # [!code callout]
```

```

:::callouts

1. Required for the processes that run in the `virt-launcher` pod.
2. Number of virtual CPUs requested by the virtual machine.
3. Number of virtual graphics cards requested by the virtual machine.
4. Additional memory overhead:
 - If your environment includes a Single Root I/O Virtualization (SR-IOV) network device or a Graphics Processing Unit (GPU), allocate 1 GiB additional memory overhead for each device.
 - If Secure Encrypted Virtualization (SEV) is enabled, add 256 MiB.
 - If Trusted Platform Module (TPM) is enabled, add 53 MiB.

:::

```

Memory overhead per virtual machine ≈ (1.002 × requested memory) \
    + 218 MiB \ ①
    + 8 MiB × (number of vCPUs) \ ②
    + 16 MiB × (number of graphics devices) \ ③
    + (additional memory overhead) ④

```

- ① Required for the processes that run in the `virt-launcher` pod.
- ② Number of virtual CPUs requested by the virtual machine.
- ③ Number of virtual graphics cards requested by the virtual machine.
- ④ Additional memory overhead:
 - If your environment includes a Single Root I/O Virtualization (SR-IOV) network device or a Graphics Processing Unit (GPU), allocate 1 GiB additional memory overhead for each device.
 - If Secure Encrypted Virtualization (SEV) is enabled, add 256 MiB.


- If Trusted Platform Module (TPM) is enabled, add 53 MiB.

Shiki Transformers ↗

Mermaid ↗

```
mermaid
graph TD;
    A-->B;
    A-->C;
    B-->D;
    C-->D;

```



Markdown Preview Mermaid ↗ VSCode

MDX

[MDX](#)   Markdown  Markdown  JSX  [rspress MDX](#)  

[rspress](#)  

doom  

Overview

Directive

ExternalSite

ExternalSiteLink

AcpApisOverview  ExternalApisOverview

Term

props

TermsTable

props

JsonViewer

rspress

[rspress](#)                 

- [Badge](#)
- [Card](#)
- [LinkCard](#)
- [PackageManagerTabs](#)
- [Steps](#)
- [Tab/Tabs](#)
- [Toc](#)

[rspress/theme](#)

preview.mdx

```
import { SourceCode } from '@rspress/core/theme'  
  
<SourceCode href="/" />
```

doom

[doom](#)

Overview

Directive

[Directive](#)

- 文档(`doc/en`) 文档 `doc/zh` 文档

```
<Directive type="danger" title="危险">
  文档
  `doc/zh` 文档
</Directive>
```

- 文档(doc/en) 文档 doc/zh 文档

文档

文档 doc/zh 文档

文档

ExternalSite

文档

```
<ExternalSite name="connectors" />
```

Note

文档 DevOps 文档 DevOps 文档

[DevOps 文档](#)

ExternalSiteLink

文档

```
<ExternalSiteLink name="connectors" href="link.mdx#hash" children="Content" />
```

[Content](#)

TIP

`mdx`
`<ExternalSiteLink name="connectors" href="link" children="Content" />`

```

<ExternalSiteLink name="connectors" href="link">
  Content { /*   `p`   */ }
</ExternalSiteLink>

```

`p`
`children`

AcpApisOverview**ExternalApisOverview**

API

```

<AcpApisOverview />
{ /* same as following */ }
<ExternalApisOverview name="acp" />

<ExternalApisOverview name="connectors" />

```

Note

ACP APIs [ACP APIs](#)

Note

DevOps APIs [DevOps APIs](#)

Term

```
<Term name="company" textCase="capitalize" />
<Term name="product" textCase="lower" />
<Term name="productShort" textCase="upper" />
<Term name="alaudaCloudLink" />
```

ACP [Alauda Cloud](#)

props

- `name`:
- `textCase`: `lower` , `upper` , `capitalize`

TermsTable

```
<TermsTable />
```

company		-	Alauda	-	
product		-	Alauda Container Platform	-	
productShort	ACP	-	ACP	-	

alaudaCloudLink	Alauda Cloud ↗	-	Alauda Cloud ↗	-	-

props

- `terms`: `NormalizedTermItem[]`

JsonViewer

```
<JsonViewer value={{ key: 'value' }} />
```

yamljson

```
key: value
```

`shared`

```
import CommonContent from './shared/CommonContent.mdx'

<CommonContent />
```

runtime ↗ API `.jsx/.tsx` `.mdx`


```
// shared/CommonContent.tsx
export const CommonContent = () => {
  const { page } = usePageData()
  return <div>{page.title}</div>
}

// showcase/content.mdx
import { CommonContent } from './shared/CommonContent'
<CommonContent />
```

WARNING

000000 .mdx 000000000 props 000000 issue ^00000000 props 0000000
.jsx/.tsx 0000000

Docs

`alauda` Docs `en / zh` Docs
`public` Docs `en / zh` Docs

Docs

`i18n.json`

`.ts/.tsx`

`.mdx`

`i18n.json`

Docs `docs` Docs `i18n.json` Docs
`useI18n` Docs

docs/i18n.json

```
{
  "title": {
    "zh": "标题",
    "en": "Title"
  },
  "description": {
    "zh": "描述",
    "en": "description"
  }
}
```

.ts/.tsx

```
import { useI18n } from '@rspress/core/runtime'

export const CommonContent = () => {
  const t = useI18n()
  return <h1>{t('title')}</h1>
}
```

.mdx

```
import { useI18n } from '@rspress/core/runtime'

# {useI18n()('title')}

{useI18n()('description')}
```

API 文档

本文档提供了关于 API 文档的 K8S API, 以及 API 以及 CRD (Custom Resource Definition) 文档的概述。

```
├─ apis
│   ├── advanced_apis # 高级 API
│   ├── crds # CRDs
│   ├── kubernetes_apis # K8S API
│   └─ references # 参考
```

目录

K8S API

props

API 文档

props

CRD (deprecated)

props

文档

props

API 文档

K8S API

kubernetes_apis/workload/daemonset.mdx

```
# DaemonSet [apps/v1]

<K8sAPI
  name="io.k8s.api.apps.v1.DaemonSet"
  pathPrefix="/kubernetes/{cluster}"
/>
```

00 [DaemonSet](#)0

crds/ArtifactCleanupRun.mdx

```
# ArtifactCleanupRun

<K8sAPI name="artifactcleanupruns.artifacts.katanomi.dev" />
```

00 [ArtifactCleanupRun](#)0

props

- `name`: OpenAPI schema `definitions` (v2) or `components/schemas` (v3) 00000000
CRD `metadata.name`
- `namespaced`: 00000000000000000000 `true` 00 API Endpoints 00000000000000
`namespaces/{namespace}`
- `pathPrefix`: 0000000000000000 `api.pathPrefix`
- `filepath`: 0000 `openapi` 000000000000 `openapi` 0 CRD 00
- `apiGroup`: 00000 API 00`openapi` 0000000000 `x-kubernetes-group-version-kind` 0000
- `apiVersion`: 00000 API 0000CRD 000000 `spec.versions` 0000000
- `apiKind`: 00000 API 00000

00 **API**

```
advanced_apis/codeQualityTaskSummary.mdx

# CodeQualityTaskSummary

<OpenAPIPath path="/plugins/v1alpha1/template/codeQuality/task/{task-id}/summary" />
```

CodeQualityTaskSummary

props

- path: OpenAPI schema paths
- pathPrefix: api.pathPrefix
- openapiPath: openapi

CRD (deprecated)

WARNING

CRD K8sAPI CRD K8sCrd CRD K8sCrd

```
crds/ArtifactCleanupRun-K8sCrd.mdx

# ArtifactCleanupRun - K8sCrd

<K8sCrd name="artifactcleanupruns.artifacts.katanomi.dev" />
```

ArtifactCleanupRun-K8sCrd

props

- name: CRD metadata.name
- crdPath: openapi CRD

□□□□

```
references/CodeQuality.mdx

# CodeQuality

<OpenAPIRef schema="v1alpha1.CodeQuality" />
```

□□ [CodeQuality](#)□

props

- `schema` : OpenAPI schema `definitions` (v2) or `components/schemas` (v3) □□□□□
- `openapiPath` : □□□□ [openapi](#) □□

□□ **openapi** □□

□□ `OpenAPIPath` □ `OpenAPIRef` □□□□□□□□ `openapi` □□□□□□□□□□□□□□□□□□□□
□ `openapi` □□□□□□□ `openapiPath` □□□□□

```
<OpenAPIPath
  path="/plugins/v1alpha1/template/codeQuality/task/{task-id}/summary"
  openapiPath="shared/openapis/katanomi.json"
/>
```

```
<K8sPermissionTable functions={['devops-testplans', 'devops-testmodule  
s']] />
```

11

- `functions`: `string[]` - `FunctionResource`

	□□	□□ □□ □	□□□ □□□	□□ □□ □	□□□ □□□ □	□□ □□	□□ □□ □
□□□□	□□	✓	✓	✓	✓	✓	✗
devops- testplans	□□	✓	✗	✓	✓	✓	✗



reference:

```

- repo: alauda-public/product-doc-guide # 
  branch: # [string] 
  publicBase: # [string] /images/xx.png 
  docs/public
    sources:
      - name: anchor # 
        path: docs/index.mdx# # doom.c
onfig.* 
  ignoreHeading: # [boolean] true
  processors: # 
    - type: ejsTemplate
      data: # ejs `<%= data.xx %>` 
  frontmatterMode: merge # frontmatter ignore
ignore/merge/replace/remove

```

frontmatterMode

- **ignore** frontmatter frontmatter
- **merge** frontmatter key
- **replace** frontmatter frontmatter
- **remove** frontmatter

[frontmatterMode](#)

□ □ □ □ □ □ □ □

[illegible]

```
doom build # ████████
doom serve # ████████████████
```



```
doom build dist -v
```

```
# ===== release-4.0 == 4.0 ==
doom build -v 4.0 # == 4.0 ===== dist/4.0===== {base}/4.0
doom build -v master # == master ===== dist/master===== {base}/master
doom build -v {other} # ===== dist/{other}===== {base}/{other}

# unversioned = unversioned-x.y =====
doom build -v unversioned # ===== dist/unversioned===== {base}
doom build -v unversioned-4.0 # ===== 4.0 ===== dist/unversioned===== {base}
```

□□□□□□

```
|— console-platform
|   |— 4.0
|   |— 4.1
|   |— index.html
|   |— overrides.yaml
|   |— versions.yaml
|— console-devops-docs
|   |— 4.0
|   |— 4.1
|   |— index.html
|   |— overrides.yaml
|   |— versions.yaml
|— console-tekton-docs
|   |— 1.0
|   |— 1.1
|   |— index.html
|   |— overrides.yaml
|   |— versions.yaml
```

index.html

```
<!DOCTYPE html>
<html>
  <head>
    <title>Redirecting...</title>
    <meta http-equiv="refresh" content="0; url=/console-docs/4.1" />
  </head>
  <body>
    <p>Redirecting to <a href="/console-docs/4.1">/console-docs/4.1</a></p>
  </body>
</html>
```

🐛🐛🐛🐛🐛🐛🐛

overrides.yaml

```
# 🐛🐛🐛🐛🐛🐛🐛🐛
title:
  en: Doom - Alauda
  zh: Doom - 🐛🐛
logoText:
  en: Doom - Alauda
  zh: Doom - 🐛🐛
```

versions.yaml

- '4.1'
- '4.0'