

□□□□ >

Doom  [rspress](#)  Alauda          

□ □ □ □

- □□□□□□□□□□□□□□□□
- □□□□□□□□
- □□□□□

MDX ██████████ Markdown ████████ Markdown █████
██████ React ███



0000000000 MDX 00 00 ↗ 0

0000

000000000000 Doom 00

00

00

0000

000000

00

Sitemap ☐ ☐

11

Markdown

Callouts

Mermaid

📄📄📄

MDX

📄 MDX 📄📄📄📄📄📄📄📄📄📄

rspress 📄

doom 📄

📄📄📄📄📄

📄📄

📄📄📄📄📄📄📄📄📄

i18n.json

.ts/.tsx

.mdx

API 📄

📄 API

CRD

📄📄📄

📄 openapi 📄

📄📄📄📄📄

props

📄

0000

000000

00

000000000000000000000000 ACP 00

00000

00000

000000

00000000

📄📄

📄📄

📄📄📄

📄📄📄📄

📄📄📄📄📄

📄📄📄📄📄

📄📄📄

📄📄📄📄📄📄

📄📄📄

📄📄 PDF

📄📄📄

📄📄📄📄

📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄

```
mkdir my-docs && cd my-docs
```

📄 `npm init -y` 📄📄📄📄📄📄📄📄📄📄📄 `npm`📄`yarn` 📄 `pnpm` 📄📄 `doom:`



```
npm install -D @alauda/doom typescript
```

📄📄📄📄📄📄📄📄:

```
# 创建 docs 目录
mkdir docs/en && echo '# Hello World' > docs/en/index.md
mkdir docs/zh && echo '# 你好' > docs/zh/index.md
```

在 `package.json` 中添加:

```
{
  "scripts": {
    "dev": "doom dev",
    "build": "doom build",
    "new": "doom new",
    "serve": "doom serve",
    "translate": "doom translate",
    "export": "doom export"
  }
}
```

在 `doom.config.yml` 中添加:

```
title: My Docs
```

在 `tsconfig.json` 中添加:

```
{
  "compilerOptions": {
    "jsx": "react-jsx",
    "module": "NodeNext",
    "moduleResolution": "NodeNext",
    "noUnusedLocals": true,
    "noUnusedParameters": true,
    "resolveJsonModule": true,
    "skipLibCheck": true,
    "strict": true,
    "target": "ESNext",
  },
  "mdx": {
    "checkMdx": true,
  },
}
```

📄📄📄 global.d.ts 📄📄📄📄📄

```
/// <reference types="@alauda/doom/runtime" />
```

📄📄📄📄📄 .mdx 📄📄📄📄📄📄📄 doom 📄📄📄📄📄📄

📄📄📄📄📄

```
doom -h
```

```
# output
```

```
Usage: doom [options] [command]
```

```
Doctor Doom making docs.
```

Options:

-V, --version	output the version number
-c, --config <config>	Specify the path to the config file
-v <version>	Specify the version of the documentation, c
-b, --base <base>	Override the base of the documentation
-p, --prefix <prefix>	Specify the prefix of the documentation bas
-f, --force [boolean]	Force to 1. fetch latest reference remotes or scaffo 2. translate ignore hash equality check and Ignore internal routes (default: false)
-i, --ignore [boolean]	
-d, --download [boolean]	Display download pdf link on nav bar (defau
-e, --export [boolean]	Run or build in exporting PDF mode, `apis/*
-I, --include <language...>	Include only the specific language(s),
-E, --exclude <language...>	Include all languages except the specific l
-o, --out-dir <path>	Override the `outDir` defined in the config
-r, --redirect <enum>	Whether to redirect to the locale closest t
-R, --edit-repo [boolean url]	Whether to enable or override the `editRepo
-a, --algolia [boolean alauda]	Whether to enable or use the alauda (docs.a
-S, --site-url	Whether to enable the siteUrl for sitemap g
-n, --no-open	Do not open the browser after starting the
-h, --help	display help for command

Commands:

dev [options] [root]	Start the development server
build [root]	Build the documentation
preview serve [options] [root]	Preview the built documentation
new [template]	Generate scaffolding from templates
translate [options] [root]	Translate the documentation
export [options] [root]	Export the documentation as PDF, `apis/**`
lint [root]	Lint the documentation
help [command]	display help for command

000000

00 yarn dev 00000000000000000000

```
doom dev -h
```

```
# output
```

```
Usage: doom dev [options] [root]
```

```
Start the development server
```

```
Arguments:
```

```
  root                                Root directory of the documentation
```

```
Options:
```

```
  -H, --host [host]                  Dev server host name
  -P, --port [port]                  Dev server port number
  -l, --lazy [boolean]               Whether to enable `lazyCompilation` which could i
  --no-lazy                          Do not enable `lazyCompilation`
  -h, --help                         display help for command
```

000000

00 yarn build 000000000000000000 dist 00000000

0000

00 yarn serve 00000000000000000000 -b , -p 0000000000000000 -b , -p 00000000000000000000

00000000

00 yarn new 00000000000000000000

0000

```
doom translate -h
```

```
# output
```

```
Usage: doom translate [options] [root]
```

```
Translate the documentation
```

```
Arguments:
```

```
  root                                Root directory of the documentation
```

```
Options:
```

```
  -s, --source <language> Document source language, one of en, zh, ru (default: en)
  -t, --target <language> Document target language, one of en, zh, ru (default: en)
  -g, --glob <path...>    Glob patterns of source dirs/files to translate
  -C, --copy [boolean]    Whether to copy relative assets to the target directory
  -h, --help              display help for command
```

- `-g, --glob` 指定要翻译的源文件的路径模式 `glob` 指定要翻译的目标文件的路径模式

1. `yarn translate -g abc xyz` 指定 `<root>/<source>/abc` ,
`<root>/<source>/xyz` 指定要翻译的源文件的路径模式 `<root>/<target>/abc` ,
`<root>/<target>/xyz` 指定要翻译的目标文件的路径模式

2. `yarn translate -g '*'` 指定 `<root>/<source>` 指定要翻译的源文件的路径模式

- `-C, --copy` 指定是否将源文件复制到目标文件的路径模式 `false` 指定不复制

- 指定要翻译的源文件的路径模式

1. `/<source>/abc.jpg` 指定要翻译的源文件的路径模式 `<root>/public/<source>/abc.jpg` 指定要翻译的源文件的路径模式 `<root>/public/<target>/abc.jpg` 指定要翻译的目标文件的路径模式 `/<target>/abc.jpg`

2. `<root>/<source>/abc.mdx` 指定要翻译的源文件的路径模式 `./assets/xyz.jpg` 指定要翻译的源文件的路径模式 `<root>/<source>/assets/xyz.jpg` 指定要翻译的源文件的路径模式 `<root>/<target>/assets/xyz.jpg` 指定要翻译的目标文件的路径模式

3. `<root>/<source>/abc.mdx` 指定要翻译的源文件的路径模式 `./assets/<source>/xyz.jpg` 指定要翻译的源文件的路径模式 `<root>/<source>/assets/<source>/xyz.jpg` 指定要翻译的源文件的路径模式 `<root>/<target>/assets/<target>/xyz.jpg` 指定要翻译的目标文件的路径模式 `./assets/<target>/xyz.jpg`

- 📄📄📄📄📄📄

1. `</source>/abc.jpg` 📄📄📄📄 `<root>/public/<target>/abc.jpg` 📄📄📄📄📄
📄📄📄📄📄📄 `</target>/abc.jpg` 📄📄📄📄📄📄📄📄📄📄
2. `<root>/<source>/abc.mdx` 📄📄📄 `./assets/<source>/xyz.jpg` 📄📄📄📄
`<root>/<target>/assets/<target>/xyz.jpg` 📄📄📄📄📄📄📄📄📄📄
`./assets/<target>/xyz.jpg` 📄📄📄📄📄
`../<source>/assets/<target>/xyz.jpg`

::: WARNING 📄📄📄📄📄📄 ``-g '*'`` 📄📄📄📄📄📄📄📄 ``source`` 📄 ``target`` 📄📄📄📄📄
``internalRoutes`` 📄📄📄📄📄 ``target`` 📄📄📄📄📄 ::: ::: TIP 📄📄📄📄📄📄
``AZURE_OPENAI_API_KEY`` 📄📄📄📄📄📄📄📄📄📄 Leader 📄 :::

📄📄📄📄📄📄📄📄📄📄

```
i18n:
  title:
    en: DevOps Connectors
  additionalPrompts: '📄📄📄 Connectors 📄📄📄📄📄📄'
  disableAutoTranslation: false
  title: DevOps 📄📄
```

📄📄📄📄📄📄📄📄

📄📄 PDF

::: WARNING 📄📄📄📄📄📄📄📄 ``yarn build`` 📄📄📄 :::

```
doom export -h
```

```
# output
```

Usage: doom export [options] [root]

Export the documentation as PDF, ``apis/**`` and ``*/apis/**`` routes will be ign

Arguments:

root

Root directory of the documentation

Options:

`-H, --host [host]` Serve host name

```
-P, --port [port]  Serve port number (default: "4173")
```

```
-h, --help      display help for command
```

```
yarn export PDF -b , -p -b , -p
```

11

playwright build-harbor.alauda.cn/frontend/playwright-

runner:doom □□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□

`.env.yarn`

```
PLAYWRIGHT_DOWNLOAD_HOST="https://cdn.npmmirror.com/binaries/playwright"
```

□□□□□□□□ pdf □□□ doom □□□□□□□□ pdf □□□□□□□□□□□□□□□□

--	--	--	--

```
doom lint -h
```

```
# output
```

```
Usage: doom lint [options] [root]
```

```
Lint the documentation
```

```
Arguments:
```

```
  root                Root directory of the documentation
```

```
Options:
```

```
  -g, --glob <path...>  Glob patterns of source dirs/files to lint (default:
  --no-cspell            Disable cspell linting
  -h, --help            display help for command
```

```
doom lint ESLint cspell ESLint
/ CSpell
```

- `eslint.config.mjs` :

```
import doom from '@alauda/doom/eslint'

export default doom(new URL('docs', import.meta.url))
```

- `cspell.config.mjs` :

```
export { default } from '@alauda/doom/cspell'
```

```
CWD .cspell CSpell .cspell/k8s.txt
```

```
k8s
kubernetes
```



📄

📄 `doom` 📄📄

📄📄

📄📄

API 📄📄

📄📄📄📄📄

📄📄📄

📄📄📄

📄📄📄

📄📄📄📄📄

📄📄📄📄📄📄

📄📄📄📄📄

`sites.yaml` 📄

📄📄

📄📄📄📄📄📄

📄📄📄

📄📄📄

Algolia 📄📄

Sitemap 📄

11

□ □ □ □

□ □ □ □ □ □ □

.mdx

API 00

00 API

CRD

0000

00 openapi 00

000000

props

00

0000

000000

00

00000000000000000000 ACP 00

00000

00000

000000

00000000

📄📄

📄📄

🔗🔗🔗

🔗🔗🔗

API 🔗🔗🔗

🔗🔗🔗🔗🔗🔗

🔗🔗🔗🔗🔗

frontmatterMode

🔗🔗🔗🔗🔗

🔗🔗🔗🔗

🔗🔗🔗🔗🔗🔗

🔗🔗🔗🔗🔗🔗🔗

🔗🔗🔗🔗🔗🔗

sites.yaml 🔗🔗

🔗🔗🔗🔗

🔗🔗🔗🔗🔗🔗🔗

🔗🔗🔗🔗🔗

🔗🔗🔗🔗🔗

Algolia 🔗🔗🔗🔗

Sitemap 🔗🔗

📄📄📄📄

```

0000000000000000 yml 00000000 doom.config.yml 

```

```
doom.config.yml  rspress  js/ts
.js/.ts/.mjs/.mts/.cjs/.cts
```

```

js/ts @alauda/doom/config defineConfig

```

```
import { defineConfig } from '@alauda/doom/config'

export default defineConfig({})
```

--	--	--	--

- `lang` 指定生成文档的语言 `en` 指定生成文档的语言
`null` 或 `undefined`
- `title` 指定生成文档的标题
- `logo` 指定生成文档的 logo `public` 指定生成文档的 logo
指定生成文档的 logo `doom` 指定生成文档的 logo
- `logoText` 指定生成文档的 logo 文本
- `icon` 指定生成文档的 icon `logo`
- `base` 指定生成文档的 base `product-docs` 指定生成文档的 base `/`
- `outDir` 指定生成文档的输出目录 `dist/{base}/{version}` 指定生成文档的输出目录
`dist/{outDir}/{version}` 指定生成文档的输出目录 `version` 指定生成文档的版本

API ☐ ☐ ☐ ☐

api:

```
# CRD 配置 doom.config.* 文件 glob 模式 json/yaml 文件
```

crds:

```
- docs/shared/crds/*.yaml
```

```
# OpenAPI 配置 doom.config.* 文件 glob 模式 json/yaml 文件
```

openapis:

```
- docs/shared/openapis/*.json
```

```
# 配置 openapi 文件
```

```
# 配置 https://doom.alauda.cn/apis/references/CodeQuality.html#v1alpha1.CodeQ
```

references:

```
v1alpha1.CodeQualityBranch: /apis/references/CodeQualityBranch#v1alpha1.C
```

```
# 配置 API 网关 gateway 文件
```

```
pathPrefix: /apis
```

配置 API 文件

配置 API 文件

```
# 配置 doom.config.* 文件 glob 模式 json/yaml 文件
```

permission:**functionresources:**

```
# `kubectl get functionresources`
```

```
- docs/shared/functionresources/*.yaml
```

roletemplates:

```
# `kubectl get roletemplates -l auth.cpaas.io/roletemplate.official=true`
```

```
- docs/shared/roletemplates/*.yaml
```

配置 API 文件

配置 API 文件

reference:

```
- repo: alauda-public/product-doc-guide # 
branch: # [string] 
publicBase: # [string] /images/xx.png do
sources:
  - name: anchor # 
    path: docs/index.mdx# # doom.conf
    ignoreHeading: # [boolean] true
    processors: # 
      - type: ejsTemplate
        data: # ejs `<%= data.xx %>` 
    frontmatterMode: merge # frontmatter ignore ign
```

frontmatterMode

- `ignore` `frontmatter` `frontmatter`
- `merge` `frontmatter` `key`
- `replace` `frontmatter` `frontmatter`
- `remove` `frontmatter`

--	--	--	--	--	--

```
releaseNotes:
```

queryTemplates:

fixed: # 000 ejs 000 jq1 00

unfixed:

release-notes.md

```
<!-- release-notes-for-bugs?template=fixed&project=DevOps -->
```

release-notes.mdx

```
{/* release-notes-for-bugs?template=fixed&project=DevOps */}
```

```

template=fixed&project=DevOps  fixed  queryTemplates 
query  project=DevOps  ejc  fixed  jira  jql 
https://jira.alauda.cn/rest/api/2/search?jql=<jql>  API 
JIRA_USERNAME  JIRA_PASSWORD 

```

--	--	--	--	--

```
sidebar:
  collapsed: false # oooooooooooooooooooooooooooooooooooooo false
```

--	--	--	--	--	--	--	--

```
internalRoutes: # glob docs cli -i, --ignore`
- '*/internal/**'
```

□ □ □ □ □ □ □ □ □

```
onlyIncludeRoutes: # 匹配 glob 匹配 docs 匹配 cli 匹配 -i, --ignore` 匹配
  - '*/internal/**'

internalRoutes:
  - '*/internal/overview.mdx'
```

```
::: WARNING [redacted] `plaintext` [redacted] :::
```

```
sites.yaml
```

□ □ □ □

translate:

```
# =====ejs ===== `sourceLang`, `targetLang`, `userPrompt`, `additional
#  `sourceLang`  `targetLang`  ` `  ` `  =====
#    `userPrompt` =====
#    `additionalPrompts`  `frontmatter.i18n`  `additionalPrompts`  ==
#    `terms`  `titleTranslationPrompt` ===== AI ==
# =====
```

systemPrompt: |

You are a professional technical documentation engineer, skilled in writing h

Baseline Requirements

- Sentences should be fluent and conform to the expression habits of the <%=
- Input format is MDX; output format must also retain the original MDX format
- ****CRITICAL****: Do not translate or modify ANY link content in the document.
 - URLs in markdown links: [text](URL) - keep URL exactly as is
 - Reference-style links: [text][ref] and [ref]: URL - keep both ref and URL
 - Inline URLs: https://example.com - keep completely unchanged
 - Image links: ![alt](src) - keep src unchanged, but alt text can be transl
 - Anchor links: [text](#anchor) - keep #anchor unchanged
 - Any href attributes in HTML tags - keep unchanged
- Do not translate professional technical terms and proper nouns, including b
- The title field and description field in frontmatter should be translated,
- Content within MDX components needs to be translated, whereas MDX component
- Do not modify or translate any placeholders in the format of __ANCHOR_N__ (
- Keep original escape characters like backslash, angle brackets, etc. unchan
- Do not add any escape characters to special characters like [], (), {}, etc
 - If source has "Architecture [Optional]", keep it as "Architecture [Option
 - If source has "Function (param)", keep it as "Function (param)" (not "Fun
 - Only add escape characters if they were present in the original text
- Preserve and do not translate the following comments, nor modify their cont
 - {/* release-notes-for-bugs */}
 - <!-- release-notes-for-bugs -->
- Remove and do not retain the following comments:
 - {/* reference-start */}
 - {/* reference-end */}
 - <!-- reference-start -->
 - <!-- reference-end -->
- Ensure the original Markdown format remains intact during translation, such
- Do not translate the content of the code block.

<% if (titleTranslationPrompt) { %>

<%- titleTranslationPrompt %>

<% } %>

<% if (terms) { %>

```
<%- terms %>
<% } %>

<% if (userPrompt || additionalPrompts) { %>
## Additional Requirements
These are additional requirements for the translation. They should be met also

The text for translation is provided below, within triple quotes:
"""
<% if (userPrompt) { %>
<%- userPrompt %>
<% } %>

<% if (additionalPrompts) { %>
<%- additionalPrompts %>
<% } %>
"""
<% } %>
```

📄📄📄📄📄📄📄📄

editRepoBaseUrl: [alauda/doom/tree/main/docs](#) # <https://github.com/> 📄📄📄📄📄📄📄📄

📄📄📄📄📄📄

```
export:
- name: Concepts # 📄📄📄📄 pdf 📄📄📄📄📄📄
  scope: '*/concepts' # 📄📄📄📄📄📄📄📄📄 glob 📄📄📄📄 docs 📄
```

📄📄📄📄📄📄

```
lint:
  cspellOptions: # 🐼cspell 🐼🐼🐼 https://github.com/streetsidesoftware/csp
```

Algolia 🐼🐼🐼

```
algolia: # 🐼Algolia 🐼🐼🐼🐼 -a, --algolia` 🐼🐼🐼🐼
  appId: # Algolia 🐼 ID
  apiKey: # Algolia API Key
  indexName: # Algolia 🐼🐼
```

🐼🐼 public/robots.txt 🐼 Algolia 🐼🐼

```
::: INFO 🐼 `rspress` 🐼🐼🐼🐼🐼 Algolia 🐼🐼🐼🐼[🐼🐼🐼🐼]
(https://rspress.dev/zh/guide/advanced/custom-theme) 🐼🐼🐼🐼🐼🐼🐼🐼🐼🐼🐼
`@alauda/doom/theme` 🐼🐼🐼🐼🐼🐼🐼🐼🐼🐼🐼🐼🐼`ts title="theme/index.ts" export *
from '@alauda/doom/theme' `` :::
```

Sitemap 🐼🐼

```
siteUrl: https://docs.alauda.cn # 🐼🐼🐼 URL🐼🐼🐼 sitemap🐼🐼🐼 -S, --site-url
```

□ □ □ □

100

11

11

--	--	--	--

index

index.md index.mdx

```
├─ index.md
├─ start.mdx
└─ usage
    ├─ index.mdx
    └─ convention.md
```

--	--	--	--	--	--

1. `public` `□□□□□□□□□□□□□□□□`
2. `public/_remotes` `□□□□□□□□□□□□□□□□□□□□□□□□□□□□`
`*/public/_remotes` `□□` `.gitignore` `□□□□□□□□□□`
3. `shared` `□□□□□□□□□□□□□□□□□□□□□□□□□□□□`

📄📄

📄📄📄📄📄📄📄 `frontmatter` 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄

```
---
title: 📄
description: 📄
author: 📄
category: 📄
---
```

📄📄📄📄📄📄 `MDX` 📄 `.mdx` 📄📄📄📄📄 `frontmatter` 📄📄📄📄📄📄

📄📄

📄 `index.md` 📄 `index.mdx` 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄 `frontmatter` 📄
`weight` 📄📄📄📄📄📄📄📄📄📄 `weight` 📄📄📄📄📄📄📄

```
---
weight: 1
---
```

:: WARNING 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄 ::

📄📄

📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄 `index.mdx` 📄📄📄📄 `Overview` 📄📄📄📄📄
📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄

#

<Overview />

Markdown

gfm ↗ Doom Markdown

11

Callouts

Mermaid

□ □ □ □

Callouts

□ □ □ □ □ □

:: NOTE 1. `;;` `%`` `#`` `//`` `/** */`` `--`` `<!-- -->` 2. `[!code callout]` 3. `:::callouts`` `<div class="doom-callouts">` `<Callouts>` `::`

```
```sh
```

```
Memory overhead per virtual machine ≈ (1.002 × requested memory) \
 + 218 MiB \ # [\\!code callout]
 + 8 MiB × (number of vCPUs) \ # [\\!code callout]
 + 16 MiB × (number of graphics devices) \ # [\\!code callout]
 + (additional memory overhead) # [\\!code callout]
```

```
```
```

```
:::callouts
```

1. Required for the processes that run in the `virt-launcher` pod.
2. Number of virtual CPUs requested by the virtual machine.
3. Number of virtual graphics cards requested by the virtual machine.
4. Additional memory overhead:
 - If your environment includes a Single Root I/O Virtualization (SR-IOV) network device or a Graphics Processing Unit (GPU), allocate 1 GiB additional memory overhead for each device.
 - If Secure Encrypted Virtualization (SEV) is enabled, add 256 MiB.
 - If Trusted Platform Module (TPM) is enabled, add 53 MiB.


```
:::
```

```
Memory overhead per virtual machine ≈ (1.002 × requested memory) \
    + 218 MiB \ ❶
    + 8 MiB × (number of vCPUs) \ ❷
    + 16 MiB × (number of graphics devices) \ ❸
    + (additional memory overhead) ❹
```

- ❶ Required for the processes that run in the `virt-launcher` pod.
- ❷ Number of virtual CPUs requested by the virtual machine.
- ❸ Number of virtual graphics cards requested by the virtual machine.
- ❹ Additional memory overhead:
 - If your environment includes a Single Root I/O Virtualization (SR-IOV) network device or a Graphics Processing Unit (GPU), allocate 1 GiB additional memory overhead for each device.
 - If Secure Encrypted Virtualization (SEV) is enabled, add 256 MiB.
 - If Trusted Platform Module (TPM) is enabled, add 53 MiB.

Mermaid ↗

```
```mermaid
graph TD;
 A-->B;
 A-->C;
 B-->D;
 C-->D;
```
```



[Markdown Preview Mermaid](#) VSCode

::: WARNING `.md` [issue](https://github.com/web-infra-dev/rspress/issues/2215#issuecomment-3018371927) :::

```
{width="100" height="100"}
```



MDX

[MDX](#) [Markdown](#) [Markdown](#) [JSX](#) [rspress MDX](#)

rspress

doom

Overview

Directive

ExternalSite

ExternalSiteLink

AcpApis0overview ExternalApis0overview

Term

props

TermsTable

props

JsonViewer

rspress

rspress [.mdx](#)

- Badge

- [Card](#)
- [LinkCard](#)
- [PackageManagerTabs](#)
- [Steps](#)
- [Tab/Tabs](#)
- [Toc](#)

在 `rspress/theme` 中配置

preview.mdx

```
import { SourceCode } from 'rspress/theme'

<SourceCode href="/" />
```

doom 文档

doom 文档

Overview

文档概述

Directive

在文档中插入 Directive 组件

```
- 在 `doc/en` 中插入 `doc/zh` 内容

<Directive type="danger" title="警告">
  在 `doc/zh` 中插入内容
</Directive>
```

- doc/zh

```
<ExternalSite name="connectors" />
```

Note

□□ DevOps □□□□□□□□□□□□□□□□□□□□□□□□ DevOps □□□□□□□□□□□□□□□□□□□□

[DevOps](#) □□□ ↗ □

```
<ExternalSiteLink name="connectors" href="link.mdx#hash" children="Content" />
```

```
<AcpApisOverview />
{/* same as following */}
<ExternalApisOverview name="acp" />

<ExternalApisOverview name="connectors" />
```

Note

00 ACP APIs 000000000000 [ACP APIs 00 ↗](#)

Note

00 DevOps 000 APIs 000000000000 [DevOps 000 APIs 00 ↗](#)

Term

000000000000000000

```
<Term name="company" textCase="capitalize" />
<Term name="product" textCase="lower" />
<Term name="productShort" textCase="upper" />
```

000 00000000 ACP

props

- `name` : 000000000000000000
- `textCase` : 00000000000000 `lower` , `upper` , `capitalize`

TermsTable

000000000000

```
<TermsTable />
```

company		-	Alauda	-	
product		-	Alauda Container Platform	-	
productShort	ACP	-	ACP	-	

props

- `terms` : `NormalizedTermItem[]`

JsonViewer

```
<JsonViewer value={{ key: 'value' }} />
```

```
yaml      json
key: value
```

shared

```
import CommonContent from './shared/CommonContent.mdx'

<CommonContent />
```

runtime ↗ API .jsx/.tsx .mdx

```
// shared/CommonContent.tsx
export const CommonContent = () => {
  const { page } = usePageData()
  return <div>{page.title}</div>
}

// showcase/content.mdx
import { CommonContent } from './shared/CommonContent'
;<CommonContent />
```

::: WARNING 在`.mdx` 中，`props` 属性[issue](https://github.com/web-infra-dev/rspress/issues/1555)中，`props` 属性在`.jsx/.tsx` 中，:::

📄 📄 📄

`alauda` 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄 `en / zh` 📄📄📄📄📄📄📄📄📄📄📄📄
📄 `public` 📄📄📄📄 `en / zh` 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄

📄 📄

- `i18n.json`
- `.ts/.tsx`
- `.mdx`

`i18n.json`

📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄 `docs` 📄📄📄📄 `i18n.json` 📄📄
📄📄📄📄📄📄 `useI18n` 📄📄📄📄📄📄📄📄📄

docs/i18n.json

```
{
  "title": {
    "zh": "📄",
    "en": "Title"
  },
  "description": {
    "zh": "📄",
    "en": "description"
  }
}
```

.ts/.tsx

```
import { useI18n } from '@rspress/runtime'

export const CommonContent = () => {
  const t = useI18n()
  return <h1>{t('title')}</h1>
}
```

.mdx

```
import { useI18n } from '@rspress/runtime'

# {useI18n()('title')}

{useI18n()('description')}
```

API 文档

文档中定义了 API 文档 API 文档 CRD (Custom Resource Definition) 文档文档文档文档文档文档文档

```
├─ apis
│   ├── advanced-apis # 文档 API
│   ├── crds # CRDs
│   └── references # 文档文档文档
```

文档

文档 API

props

CRD

props

文档文档

props

文档 openapi 文档

文档 API

advanced-apis/codeQualityTaskSummary.mdx

```
# CodeQualityTaskSummary

<OpenAPIPath path="/plugins/v1alpha1/template/codeQuality/task/{task-id}/summ
```

CodeQualityTaskSummary

props

- path : OpenAPI schema paths
- pathPrefix : api.pathPrefix
- openapiPath : openapi

CRD

crds/ArtifactCleanupRun.mdx

```
# ArtifactCleanupRun

<K8sCrd name="artifactcleanupruns.artifacts.katanomi.dev" />
```

ArtifactCleanupRun

props

- name : CRD metadata.name
- crdPath : openapi CRD

references/CodeQuality.mdx

CodeQuality

```
<OpenAPIRef schema="v1alpha1.CodeQuality" />
```

CodeQuality

props

- `schema` : OpenAPI schema `definitions` (v2) or `component/schemas` (v3) から取得
- `openapiPath` : `openapi` のパス

openapi

`OpenAPIPath` は `OpenAPIRef` が参照する `openapi` のパスを指定する。
`openapi` のパスは `openapiPath` で指定する。

```
<OpenAPIPath  
  path="/plugins/v1alpha1/template/codeQuality/task/{task-id}/summary"  
  openapiPath="shared/openapis/katanomi.json"  
>
```

🔒🔒🔒🔒🔒🔒

```
<K8sPermissionTable functions={['devops-testplans', 'devops-testmodules']} />
```

🔒🔒

props

🔒🔒

props

- `functions`: `string[]` - 🔒🔒🔒🔒🔒🔒 `FunctionResource` 🔒🔒🔒🔒🔒

🔒🔒

🔒🔒	🔒🔒	🔒🔒🔒 🔒🔒	🔒🔒🔒 🔒🔒🔒	🔒🔒🔒 🔒🔒	🔒🔒🔒🔒 🔒🔒🔒	🔒🔒 🔒🔒	🔒🔒🔒 🔒🔒
🔒🔒🔒🔒 devops- testplans	🔒🔒	✓	✓	✓	✓	✓	✗
	🔒🔒	✓	✗	✓	✓	✓	✗
	🔒🔒	✓	✗	✓	✓	✓	✗
	🔒🔒	✓	✗	✓	✓	✓	✗

☐ Markdown ☐☐☐☐

```
<!-- reference-end -->
```

```
{/* reference-end */}
```

```
□□□□□□ <root>/public/_remotes/<name> □□□□
```

```
□□□□□ <!-- reference-start#ref --> □□□□□
```

11

frontmatterMode

□ □ □ □ □ □

reference:

```

- repo: alauda-public/product-doc-guide # 
branch: # [string] 
publicBase: # [string] /images/xx.png do
sources:
  - name: anchor # 
    path: docs/index.mdx# # doom.conf
    ignoreHeading: # [boolean] true
    processors: # 
      - type: ejTemplate
        data: # ejs `<%= data.xx %>` 
    frontmatterMode: merge # frontmatter ignore ign

```

frontmatterMode

- **ignore** frontmatter frontmatter
- **merge** frontmatter key
- **replace** frontmatter frontmatter
- **remove** frontmatter

-
-
-
-

```
doom build # 
doom serve # 
```

```
doom build dist -v 
```

```
# ===== release-4.0 == 4.0 ==
doom build -v 4.0 # == 4.0 ===== dist/4.0===== {base}/4.0
doom build -v master # == master ===== dist/master===== {base}/master
doom build -v {other} # ===== dist/{other}===== {base}/{other}

# unversioned = unversioned-x.y =====
doom build -v unversioned # ===== dist/unversioned===== {base}
doom build -v unversioned-4.0 # ===== 4.0 ===== dist/unversio
```

□□□□□□

```
|— console-platform
|   |— 4.0
|   |— 4.1
|   |— index.html
|   |— overrides.yaml
|   └— versions.yaml
|— console-devops-docs
|   |— 4.0
|   |— 4.1
|   |— index.html
|   |— overrides.yaml
|   └— versions.yaml
|— console-tekton-docs
|   |— 1.0
|   |— 1.1
|   |— index.html
|   |— overrides.yaml
|   └— versions.yaml
```

index.html

```
overrides.yaml
```

```
# □□□□□□□□□□□□□□□□□□  
title:  
  en: Doom - Alauda  
  zh: Doom - □□□  
logoText:  
  en: Doom - Alauda  
  zh: Doom - □□□
```

```
versions.yaml
```

- '4.1'
- '4.0'