

Doom [rspress](#) Alauda

11



0000000000 MDX 000 ↗ 0

0000

0000000000 Doom 00

00

00

0000

000000

00

MDX

📄 MDX 📄📄📄📄📄📄📄📄📄📄

rspress 📄

doom 📄

📄📄📄📄📄

📄📄📄

📄📄📄📄📄📄📄📄📄📄

i18n.json

.ts/.tsx

.mdx

API 📄

📄 API

CRD

📄📄📄

📄 openapi 📄

📄📄📄📄📄

props

📄

📄📄📄

📄📄📄📄

00

00000000000000000000 ACP 00

00000

00000

000000

00000000

📄📄

📄📄

📄📄📄📄

📄📄📄📄

📄📄📄📄

📄📄📄📄

📄📄📄

📄📄📄📄📄

📄📄📄

📄📄 PDF

📄📄📄

📄📄📄📄

📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄

`mkdir my-docs && cd my-docs`

📄 `npm init -y` 📄📄📄📄📄📄📄📄📄📄📄📄 `npm`📄`yarn` 📄 `pnpm` 📄📄 `doom:`

 `npm`

 `yarn`

 `pnpm`

 `bun`

 `deno`

```
npm install -D @alauda/doom typescript
```

创建文档目录:

```
# 创建 docs 目录
mkdir docs/en && echo '# Hello World' > docs/en/index.md
mkdir docs/zh && echo '# 文档' > docs/zh/index.md
```

在 `package.json` 中添加:

```
{
  "scripts": {
    "dev": "doom dev",
    "build": "doom build",
    "new": "doom new",
    "serve": "doom serve",
    "translate": "doom translate",
    "export": "doom export"
  }
}
```

创建配置文件 `doom.config.yml`:

```
title: My Docs
```

创建 `tsconfig.json` 文件

```
{
  "compilerOptions": {
    "jsx": "react-jsx",
    "module": "NodeNext",
    "moduleResolution": "NodeNext",
    "noUnusedLocals": true,
    "noUnusedParameters": true,
    "resolveJsonModule": true,
    "skipLibCheck": true,
    "strict": true,
    "target": "ESNext",
  },
  "mdx": {
    "checkMdx": true,
  },
}
```

📄📄📄 `global.d.ts` 📄📄📄📄📄📄

```
/// <reference types="@alauda/doom/runtime" />
```

📄📄📄📄📄 `.mdx` 📄📄📄📄📄📄📄 `doom` 📄📄📄📄📄📄📄

📄📄📄📄📄



```
doom -h
```

```
# output
```

```
Usage: doom [options] [command]
```

```
Doctor Doom making docs.
```

```
Options:
```

```
  -V, --version                output the version number
  -c, --config <config>       Specify the path to the config file
  -v <version>                 Specify the version of the document
                                ation, can also be `unversioned` or `unversioned-x.y`
  -b, --base <base>           Override the base of the documentat
                                ion
  -p, --prefix <prefix>       Specify the prefix of the documenta
                                tion base
  -f, --force [boolean]        Force to
                                1. fetch latest reference remotes o
                                r scaffolding templates, otherwise use local cache
                                2. translate ignore hash equality c
                                heck and original text (default: false)
  -i, --ignore [boolean]       Ignore internal routes (default: fa
                                lse)
  -d, --download [boolean]     Display download pdf link on nav ba
                                r (default: false)
  -e, --export [boolean]       Run or build in exporting PDF mode,
                                `apis/**` and `*/apis/**` routes will be ignored automatically (default:
                                false)
  -I, --include <language...> Include **only** the specific langu
                                age(s), `en ru` for example
  -E, --exclude <language...> Include all languages except the sp
                                ecific language(s), `ru` for example
  -o, --out-dir <path>         Override the `outDir` defined in th
                                e config file or the default `dist/{base}/{version}`, the resulting path
                                will be `dist/{outDir}/{version}`
  -r, --redirect <enum>        Whether to redirect to the locale c
                                losest to `navigator.language` when the user visits the site, could be `a
                                uto`, `never` or `only-default-lang` (default: "only-default-lang")
  -R, --edit-repo [boolean|url|lang] Whether to enable or override the `
                                editRepoBaseUrl` config feature, `https://github.com/` prefix could be om
                                itted; if a language code is provided, all other languages will use the s
                                ame repo but with the language code as sub-path (default: false)
  -a, --algolia [boolean|alauda] Whether to enable or use the alauda
```

```
(docs.alauda.io) preset for Algolia search (default: false)
  -S, --site-url           Whether to enable the siteUrl for s
itemap generation (default: false)
  -n, --no-open           Do not open the browser after start
ing the server
  --lang <language>      Specify the language of the documen
tation
  -h, --help              display help for command
```

Commands:

```
dev [options] [root]      Start the development server
build [root]              Build the documentation
preview|serve [options] [root] Preview the built documentation
new [template]            Generate scaffolding from templates
translate [options] [root] Translate the documentation
export [options] [root]   Export the documentation as PDF, `a
pis/**` and `*/apis/**` routes will be ignored automatically
lint [options] [root]     Lint the documentation
help [command]            display help for command
```

yarn dev

```
doom dev -h
```

```
# output
```

```
Usage: doom dev [options] [root]
```

```
Start the development server
```

```
Arguments:
```

```
  root                                Root directory of the documentation
```

```
Options:
```

```
  -H, --host [host]                  Dev server host name
```

```
  -P, --port [port]                  Dev server port number
```

```
  -l, --lazy [boolean]               Whether to enable `lazyCompilation` which could improve the compilation performance (default: true)
```

```
  --no-lazy                          Do not enable `lazyCompilation`
```

```
  -h, --help                          display help for command
```

📄📄📄📄📄📄

📄 `yarn build` 📄📄📄📄📄📄📄📄📄📄📄📄📄 `dist` 📄📄📄📄📄📄

📄📄📄📄

📄 `yarn serve` 📄📄📄📄📄📄📄📄📄📄📄📄📄 `-b`, `-p` 📄📄📄📄📄📄📄📄📄 `-b`, `-p`

📄📄

📄📄📄📄📄📄📄

📄 `yarn new` 📄📄📄📄📄📄📄📄📄📄📄📄📄

📄📄📄📄

```
doom translate -h
```

```
# output
```

```
Usage: doom translate [options] [root]
```

```
Translate the documentation
```

```
Arguments:
```

```
  root                                Root directory of the documentation
```

```
Options:
```

```
  -s, --source <language>  Document source language, one of en, zh, ru (default: "en")
```

```
  -t, --target <language>  Document target language, one of en, zh, ru (default: "zh")
```

```
  -g, --glob <path...>    Glob patterns of source dirs/files to translate
```

```
  -C, --copy [boolean]     Whether to copy relative assets to the target directory instead of following links (default: false)
```

```
  -h, --help               display help for command
```

- `-g, --glob` 指定要翻译的源目录/文件的glob模式 `glob` 模式支持通配符 `*` 和 `?`。
 1. `yarn translate -g abc xyz` 将 `<root>/<source>/abc` 和 `<root>/<source>/xyz` 目录下的所有文件复制到 `<root>/<target>/abc` 和 `<root>/<target>/xyz` 目录下。
 2. `yarn translate -g '*'` 将 `<root>/<source>` 目录下的所有文件复制到 `<root>/<target>` 目录下。
- `-C, --copy` 指定是否将源目录/文件中的相对资产复制到目标目录，而不是通过链接（默认：false）。
 1. `/<source>/abc.jpg` 文件将被复制到 `<root>/public/<source>/abc.jpg` 和 `<root>/public/<target>/abc.jpg` 文件中。
 2. `<root>/<source>/abc.mdx` 文件将被复制到 `./assets/xyz.jpg` 文件中，而不是 `<root>/<source>/assets/xyz.jpg` 文件中。

WARNING

```

$ yarn build

```

```
doom export -h
```

```
# output
```

Usage: doom export [options] [root]

Export the documentation as PDF, ``apis/**`` and ``*/apis/**`` routes will be ignored automatically

Arguments:

```
root          Root directory of the documentation
```

Options:

-H, --host [host] Serve host name

`-P, --port [port]` Serve port number (default: "4173")

```
-h, --help    display help for command
```

□□ yarn export □□□□□ PDF □□□□□□□□□□ -b , -p □□□□□□□□□□□□□□ -b , -p □□

playwright ↗ build-harbor.alauda.cn/frontend/playwright-runner:doom

`.env.yarn`

```
PLAYWRIGHT_DOWNLOAD_HOST="https://cdn.npmmirror.com/binaries/playwright"
```

□□□□□□□□ pdf □□□□ doom □□□□□□□□□□ pdf □□□□□□□□□□ □□□□□□

--	--	--	--

```
doom lint -h
```

```
# output
```

```
Usage: doom lint [options] [root]
```

```
Lint the documentation
```

```
Arguments:
```

```
  root                Root directory of the documentation
```

```
Options:
```

```
  -g, --glob <path...>  Glob patterns of source dirs/files to lint (default: "**/*.{js,jsx,ts,tsx,md,mdx}")
  --no-cspell            Disable cspell linting
  -h, --help            display help for command
```

```
doom lint ESLint cspell
```

[ESLint](#) / [CSpell](#):

- `eslint.config.mjs`:

```
import doom from '@alauda/doom/eslint'

export default doom(new URL('docs', import.meta.url))
```

- `cspell.config.mjs`:

```
export { default } from '@alauda/doom/cspell'
```

`CWD` `.cspell` `CSpell`

```
.cspell/k8s.txt
```

```
k8s
kubernetes
```


📄📄

📄📄

📄📄 `doom` 📄📄📄

📄📄📄📄

📄📄📄📄

API 📄📄📄📄

📄📄📄📄📄📄📄

📄📄📄📄📄

📄📄📄📄📄

📄📄📄📄📄

📄📄📄📄📄📄📄

📄📄📄📄📄📄📄

📄📄📄📄📄📄

`sites.yaml` 📄📄

📄📄📄📄

📄📄📄📄📄📄📄📄

📄📄📄📄📄

📄📄📄📄📄

Algolia 📄📄📄📄

Sitemap 📄📄

11

Mermaid

□ □ □ □ □ □ □

.mdx

□□ openapi □□

000000

props

00

0000

000000

00

000000000000000000000000 ACP 00

00000

00000

000000

00000000

🐙🐙

🐙🐙

🐙🐙🐙🐙

🐙🐙🐙🐙

API 🐙🐙🐙🐙

🐙🐙🐙🐙🐙🐙🐙🐙

🐙🐙🐙🐙🐙🐙

frontmatterMode

🐙🐙🐙🐙🐙🐙

🐙🐙🐙🐙🐙

🐙🐙🐙🐙🐙🐙🐙🐙

🐙🐙🐙🐙🐙🐙🐙🐙

🐙🐙🐙🐙🐙🐙🐙

sites.yaml 🐙🐙

🐙🐙🐙🐙

🐙🐙🐙🐙🐙🐙🐙🐙

🐙🐙🐙🐙🐙🐙

🐙🐙🐙🐙🐙🐙

Algolia 🐙🐙🐙🐙

Sitemap 🐙🐙

--	--	--	--

```

    doom.config.yaml
    doom.config.yaml
    rspress
    js/ts
    .js/.ts/.mjs/.mts/.cjs/.cts

```

```

❏ js/ts ❏ @alauda/doom/config ❏ defineConfig
❏

```

```
import { defineConfig } from '@alauda/doom/config'

export default defineConfig({})
```

--	--	--	--

- `lang` `en` `null` `undefined`
- `title`
- `logo` `public` `doom` `alauda logo`
- `logoText` `logo`
- `icon` `favicon` `logo`
- `base` `product-docs` `/`
- `outDir` `dist/{base}/{version}` `dist/{outDir}/{version}` `version`

API ☐ ☐ ☐ ☐

api:

```
# CRD 配置 doom.config.* 文件 glob 模式 json/yaml 文件
```

crds:

```
- docs/shared/crds/*.yaml
```

```
# OpenAPI 配置 doom.config.* 文件 glob 模式 json/yaml 文件
```

openapis:

```
- docs/shared/openapis/*.json
```

```
# 配置 openapi 文件
```

```
# 配置 https://doom.alauda.cn/apis/references/CodeQuality.html#v1alpha1.C
```

```
odeQualitySpec
```

references:

```
  v1alpha1.CodeQualityBranch: /apis/references/CodeQualityBranch#v1alpha1.CodeQualityBranch
```

```
# 配置 API 网关 gateway 文件
```

```
pathPrefix: /apis
```

配置 API 文件

配置 API 文件

```
# 配置 doom.config.* 文件 glob 模式 json/yaml 文件
```

permission:**functionresources:**

```
# `kubectl get functionresources`
```

```
- docs/shared/functionresources/*.yaml
```

roletemplates:

```
# `kubectl get roletemplates -l auth.cpaas.io/roletemplate.official=true`
```

```
- docs/shared/roletemplates/*.yaml
```

配置 API 文件

配置 API 文件

reference:

```
- repo: alauda-public/product-doc-guide # 

```

frontmatterMode

- `ignore` 忽略 frontmatter 内容
- `merge` 合并 frontmatter 内容
- `replace` 替换 frontmatter 内容
- `remove` 移除 frontmatter 内容

📄📄📄📄📄

📄📄📄📄📄

releaseNotes:

queryTemplates:

```
fixed: # 使用 ejs 模板
unfixed:
```

release-notes.md



translate:

```
# =====ejs ===== `sourceLang`, `targetLang`, `userPrompt`, `additionalPrompts`, `terms`, `titleTranslationPrompt`
#  `sourceLang`  `targetLang`  ``  ``
#    `userPrompt` =====
#    `additionalPrompts`  `frontmatter.i18n`  `additionalPrompts`
=====
#    `terms`  `titleTranslationPrompt` ===== AI
=====
# =====
```

systemPrompt: |

You are a professional technical documentation engineer, skilled in writing high-quality technical documentation in `<%= targetLang %>`. Please accurately translate the following text from `<%= sourceLang %>` to `<%= targetLang %>`, maintaining the style consistent with technical documentation in `<%= sourceLang %>`.

Baseline Requirements

- Sentences should be fluent and conform to the expression habits of the `<%= targetLang %>` language.
- Input format is MDX; output format must also retain the original MDX format. Do not translate the names of jsx components such as `<Overview />`, and do not wrap output in unnecessary code blocks.
- ****CRITICAL****: Do not translate or modify ANY link content in the document. This includes:
 - **URLs in markdown links**: `[text](URL)` - keep URL exactly as is
 - **Reference-style links**: `[text][ref]` and `[ref]: URL` - keep both ref and URL unchanged
 - **Inline URLs**: `https://example.com` - keep completely unchanged
 - **Image links**: `![alt](src)` - keep src unchanged, but alt text can be translated
 - **Anchor links**: `[text](#anchor)` - keep `#anchor` unchanged
 - Any href attributes in HTML tags - keep unchanged
- **Do not translate professional technical terms and proper nouns, including but not limited to**: Kubernetes, Docker, CLI, API, REST, GraphQL, JSON, YAML, Git, GitHub, GitLab, AWS, Azure, GCP, Linux, Windows, macOS, Node.js, React, Vue, Angular, TypeScript, JavaScript, Python, Java, Go, Rust, etc. Keep these terms in their original form.
- The title field and description field in frontmatter should be translated, other frontmatter fields should retain and do not translate.
- Content within MDX components needs to be translated, whereas MDX component names and parameter keys do not.
- Do not modify or translate any placeholders in the format of `__ANCHOR_N`

__ (where N is a number). These placeholders must be kept exactly as they appear in the source text.

- Keep original escape characters like backslash, angle brackets, etc. unchanged during translation.

- Do not add any escape characters to special characters like [], (), {}, etc. unless they were explicitly present in the source text. For example:

- If source has "Architecture [Optional]", keep it as "Architecture [Optional]" (not "Architecture \[Optional]")

- If source has "Function (param)", keep it as "Function (param)" (not "Function \ (param)")

- Only add escape characters if they were present in the original text

- Preserve and do not translate the following comments, nor modify their content:

- { /* release-notes-for-bugs */ }

- <!-- release-notes-for-bugs -->

- Remove and do not retain the following comments:

- { /* reference-start */ }

- { /* reference-end */ }

- <!-- reference-start -->

- <!-- reference-end -->

- Ensure the original Markdown format remains intact during translation, such as frontmatter, code blocks, lists, tables, etc.

- Do not translate the content of the code block.

```
<% if (titleTranslationPrompt) { %>
```

```
<%- titleTranslationPrompt %>
```

```
<% } %>
```

```
<% if (terms) { %>
```

```
<%- terms %>
```

```
<% } %>
```

```
<% if (userPrompt || additionalPrompts) { %>
```

```
## Additional Requirements
```

These are additional requirements for the translation. They should be met along with the baseline requirements, and in case of any conflict, the baseline requirements should take precedence.

The text for translation is provided below, within triple quotes:

```
"""
```

```
<% if (userPrompt) { %>
```

```
<%- userPrompt %>
```

```
<% } %>
```

```
<% if (additionalPrompts) { %>
```

```
<%- additionalPrompts %>
```

```
<% } %>
""
<% } %>
```

📄📄📄📄📄📄📄📄

```
editRepoBaseUrl: alauda/doom/tree/main/docs # https://github.com/ 📄📄📄📄
📄📄📄 -R, --edit-repo` 📄📄📄📄📄📄
```

📄📄📄📄📄📄

```
export:
  - name: Concepts # 📄📄📄📄 pdf 📄📄📄📄📄📄
    scope: '*/concepts' # 📄📄📄📄📄📄📄📄📄📄 glob 📄📄📄📄 docs 📄
```

📄📄📄📄📄📄

```
lint:
  cspellOptions: # 📄📄📄cspell 📄📄📄📄 https://github.com/streetsidesoftware/cspell/tree/main/packages/cspell-eslint-plugin#options
```

Algolia 📄📄📄📄

```
algolia: # 📄📄📄Algolia 📄📄📄📄📄📄 -a, --algolia` 📄📄📄📄📄
appId: # Algolia 📄 ID
apiKey: # Algolia API Key
indexName: # Algolia 📄📄📄
```

📄📄📄 `public/robots.txt` 📄📄 Algolia 📄📄📄📄

📄 `rspress` 📄📄📄📄📄📄 **Algolia** 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄
📄@alauda/doom/theme 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄

theme/index.ts

```
export * from '@alauda/doom/theme'
```

Sitemap 📄📄

```
siteUrl: https://docs.alauda.cn # 📄📄📄📄📄📄 URL📄📄📄📄📄📄 sitemap📄📄📄📄📄📄 ` -S, --site  
-url` 📄📄📄📄📄📄📄📄📄📄
```


#

<Overview />

Markdown

[gfm](#) Doom Markdown

Callouts

Mermaid

Callouts

Note

- ; , % , # , // , /** */ , -- <!-- -->
- [\\!code callout]
- :::callouts <div class="doom-callouts"> <Callouts>

```

```sh
Memory overhead per virtual machine ≈ (1.002 × requested memory) \
 + 218 MiB \ # [!code callout]
 + 8 MiB × (number of vCPUs) \ # [!code callout]
 + 16 MiB × (number of graphics devices) \ # [!code callou
t]
 + (additional memory overhead) # [!code callout]
...

```

:::callouts

1. Required for the processes that run in the `virt-launcher` pod.
2. Number of virtual CPUs requested by the virtual machine.
3. Number of virtual graphics cards requested by the virtual machine.
4. Additional memory overhead:
  - If your environment includes a Single Root I/O Virtualization (SR-IOV) network device or a Graphics Processing Unit (GPU), allocate 1 GiB additional memory overhead for each device.
  - If Secure Encrypted Virtualization (SEV) is enabled, add 256 MiB.
  - If Trusted Platform Module (TPM) is enabled, add 53 MiB.

:::

```

Memory overhead per virtual machine ≈ (1.002 × requested memory) \
 + 218 MiB \ ①
 + 8 MiB × (number of vCPUs) \ ②
 + 16 MiB × (number of graphics devices) \ ③
 + (additional memory overhead) ④

```


1. Required for the processes that run in the `virt-launcher` pod.
2. Number of virtual CPUs requested by the virtual machine.
3. Number of virtual graphics cards requested by the virtual machine.
4. Additional memory overhead:
  - If your environment includes a Single Root I/O Virtualization (SR-IOV) network device or a Graphics Processing Unit (GPU), allocate 1 GiB additional memory overhead for each device.
  - If Secure Encrypted Virtualization (SEV) is enabled, add 256 MiB.

- If Trusted Platform Module (TPM) is enabled, add 53 MiB.

Shiki Transformers ↗

## Mermaid ↗

```
mermaid
graph TD;
 A-->B;
 A-->C;
 B-->D;
 C-->D;
```



Markdown Preview Mermaid ↗ VSCode

# MDX

[MDX](#) [Markdown](#) [Markdown](#) [JSX](#) [rspress MDX](#)

[rspress](#)

doom

Overview

Directive

ExternalSite

ExternalSiteLink

AcpApisOverview ExternalApisOverview

Term

props

TermsTable

props

JsonViewer

## rspress

[rspress](#) [.mdx](#)

- [Badge](#)
- [Card](#)
- [LinkCard](#)
- [PackageManagerTabs](#)
- [Steps](#)
- [Tab/Tabs](#)
- [Toc](#)

[rspress/theme](#)

preview.mdx

```
import { SourceCode } from '@rspress/core/theme'

<SourceCode href="/" />
```

# doom

[doom](#)

## Overview

## Directive

[Directive](#)

[illegible]

- ( doc/en )□□□□□□ □ doc/zh □□□□□□□□□□□□□□□□□□□□□□□□  
□□□□

11

doc/zh

## ExternalSite

--	--	--	--	--	--	--	--

```
<ExternalSite name="connectors" />
```

### Note

[DevOps](#) [DevOps](#)

## ExternalSiteLink



```
<ExternalSiteLink name="connectors" href="link.mdx#hash" children="Content" />
```

[Content](#) ↗

**TIP**



```
mdx <ExternalSiteLink name="connectors" href="link" children="Content" />
```

```
<ExternalSiteLink name="connectors" href="link">
 Content {/* `p` */}
</ExternalSiteLink>
```

```
 p children
```

## AcpApisOverview

## ExternalApisOverview

API

```
<AcpApisOverview />
{/* same as following */}
<ExternalApisOverview name="acp" />

<ExternalApisOverview name="connectors" />
```

Note

ACP APIs [ACP APIs](#)

Note

DevOps APIs [DevOps APIs](#)

## Term

```
<Term name="company" textCase="capitalize" />
<Term name="product" textCase="lower" />
<Term name="productShort" textCase="upper" />
<Term name="alaudaCloudLink" />
```

ACP [Alauda Cloud](#)

props

- `name` :
- `textCase` : `lower` , `upper` , `capitalize`

## TermsTable

```
<TermsTable />
```

company		-	Alauda	-	
product		-	Alauda Container Platform	-	
productShort	ACP	-	ACP	-	
alaudaCloudLink	<a href="#">Alauda Cloud ↗</a>	-	<a href="#">Alauda Cloud ↗</a>	-	-

## props

- `terms` : `NormalizedTermItem[]`

## JsonViewer

```
<JsonViewer value={{ key: 'value' }} />
```

yaml json

```
key: value
```

□□□□□□□□

□□□□□□□□□□□□□□□□ **shared** □□□□□□□□□□□□□□□□□□□□

```
import CommonContent from './shared/CommonContent.mdx'
```

```
<CommonContent />
```

□□□□□□□□ **runtime** ↑ □□□ API□□□□□□ **.jsx/.tsx** □□□□□□□□ **.mdx** □□□□□□□□

```
// shared/CommonContent.tsx
```

```
export const CommonContent = () => {
 const { page } = usePageData()
 return <div>{page.title}</div>
}
```

```
// showcase/content.mdx
```

```
import { CommonContent } from './shared/CommonContent'
<CommonContent />
```

## WARNING

□□□□□□ **.mdx** □□□□□□□□□□ **props** □□□□□□ issue ↑□□□□□□□□□□ **props** □□□□□□□□  
**.jsx/.tsx** □□□□□□□□

Docs

`alauda` 文档 `en / zh` `public` `en / zh`

Docs

- `i18n.json`
- `.ts/.tsx`
- `.mdx`

## i18n.json

文档 `docs` `i18n.json` `useI18n`

docs/i18n.json

```
{
 "title": {
 "zh": "标题",
 "en": "Title"
 },
 "description": {
 "zh": "描述",
 "en": "description"
 }
}
```

## .ts/.tsx

```
import { useI18n } from '@rspress/core/runtime'

export const CommonContent = () => {
 const t = useI18n()
 return <h1>{t('title')}</h1>
}
```

## .mdx

```
import { useI18n } from '@rspress/core/runtime'

{useI18n()('title')}

{useI18n()('description')}
```

# API 文档

API 文档 API 文档 CRD (Custom Resource Definition) 文档

```
├─ apis
│ ├── advanced-apis # API
│ ├── crds # CRDs
│ └─ references # 文档
```

文档

- API
- props
- CRD
- props
- 文档
- props
- openapi 文档

## API

advanced-apis/codeQualityTaskSummary.mdx

```
CodeQualityTaskSummary

<OpenAPIPath path="/plugins/v1alpha1/template/codeQuality/task/{task-id}/summ
```

CodeQualityTaskSummary

props

- path: OpenAPI schema paths
- pathPrefix: api.pathPrefix
- openapiPath: openapi

CRD

crds/ArtifactCleanupRun.mdx

```
ArtifactCleanupRun

<K8sCrd name="artifactcleanupruns.artifacts.katanomi.dev" />
```

ArtifactCleanupRun

props

- name: CRD metadata.name
- crdPath: openapi CRD

references/CodeQuality.mdx

```
CodeQuality
```

```
<OpenAPIRef schema="v1alpha1.CodeQuality" />
```

関数 `CodeQuality`

## props

- `schema`: OpenAPI schema `definitions` (v2) or `component/schemas` (v3) を参照
- `openapiPath`: 参照する `openapi` のパス

## 関数 `openapi`

関数 `OpenAPIPath` は関数 `OpenAPIRef` を参照する `openapi` のパスを返します。

関数 `openapi` は関数 `openapiPath` を参照します。

```
<OpenAPIPath
 path="/plugins/v1alpha1/template/codeQuality/task/{task-id}/summary"
 openapiPath="shared/openapis/katanomi.json"
>
```



权限管理

```
<K8sPermissionTable functions={['devops-testplans', 'devops-testmodule
s']} />
```

权限

props

权限

props

- functions: string[] - 权限列表 FunctionResource 权限列表

权限

权限	权限	权限 名称	权限 名称	权限 名称	权限 名称	权限 名称	权限 名称
权限 devops- testplans	权限	✓	✓	✓	✓	✓	×
	权限	✓	×	✓	✓	✓	×
	权限	✓	×	✓	✓	✓	×

测试点	测试用例	测试用例	测试用例	测试用例	测试用例	测试用例	测试用例
	测试用例	✓	✗	✓	✓	✓	✗
	测试用例	✓	✓	✓	✓	✓	✗
测试用例	测试用例	✓	✗	✓	✓	✓	✗
devops- testmodules	测试用例	✓	✗	✓	✓	✓	✗
	测试用例	✓	✗	✓	✓	✓	✗

--	--	--	--

```
<!-- reference-end -->
```

```
{/* reference-end */}
```

```

□□□□□ <!-- reference-start#ref --> □□□□□

```

frontmatterMode



**reference:**

```

- repo: alauda-public/product-doc-guide #
 branch: # [string]
 publicBase: # [string] /images/xx.png
 docs/public
 sources:
 - name: anchor #
 path: docs/index.mdx# # doom.c
onfig.*
 ignoreHeading: # [boolean] true
 processors: #
 - type: ejsTemplate
 data: # ejs `<%= data.xx %>`
 frontmatterMode: merge # frontmatter ignore
ignore/merge/replace/remove

```

**frontmatterMode**

- **ignore** frontmatter frontmatter
- **merge** frontmatter key
- **replace** frontmatter frontmatter
- **remove** frontmatter

□ □ □ □ □ □ □ □

[illegible]

```
doom build # ████████
doom serve # ████████████████
```



```
doom build dist -v
```

```
===== release-4.0 == 4.0 ==
doom build -v 4.0 # == 4.0 ===== dist/4.0===== {base}/4.0
doom build -v master # == master ===== dist/master===== {base}/master
doom build -v {other} # ===== dist/{other}===== {base}/{other}

unversioned = unversioned-x.y =====
doom build -v unversioned # ===== dist/unversioned===== {base}
doom build -v unversioned-4.0 # ===== 4.0 ===== dist/unversioned===== {base}
```

□□□□□□

```
|— console-platform
| |— 4.0
| |— 4.1
| |— index.html
| |— overrides.yaml
| |— versions.yaml
|— console-devops-docs
| |— 4.0
| |— 4.1
| |— index.html
| |— overrides.yaml
| |— versions.yaml
|— console-tekton-docs
| |— 1.0
| |— 1.1
| |— index.html
| |— overrides.yaml
| |— versions.yaml
```

index.html

```
<!DOCTYPE html>
<html>
 <head>
 <title>Redirecting...</title>
 <meta http-equiv="refresh" content="0; url=/console-docs/4.1" />
 </head>
 <body>
 <p>Redirecting to /console-docs/4.1</p>
 </body>
</html>
```

🌑🌑🌑🌑🌑🌑🌑

#### overrides.yaml

```
🌑🌑🌑🌑🌑🌑🌑🌑🌑
title:
 en: Doom - Alauda
 zh: Doom - 🌑🌑🌑
logoText:
 en: Doom - Alauda
 zh: Doom - 🌑🌑🌑
```

#### versions.yaml

```
- '4.1'
- '4.0'
```