

□□□□ >

Doom  [rspress](#)  Alauda                                                                                                                                  

□ □ □ □

- □□□□□□□□□□□□□□□□□□
- □□□□□□□□
- □□□□□

MDX ██████████ Markdown ████████ Markdown █████  
 React ███



0000000000 MDX 00 ↗

0000

0000000000 Doom 00

00

00

0000

000000

00



## Markdown

Callouts

Mermaid

📄📄📄

## MDX

📄 MDX 📄📄📄📄📄📄📄📄📄📄

rspress 📄

doom 📄

📄📄📄📄📄

📄📄

📄📄📄📄📄📄📄📄📄

i18n.json

.ts/.tsx

.mdx

## API 📄

📄 API

CRD

📄📄📄

📄 openapi 📄

📄📄📄📄📄

props

📄



📄📄

📄📄

📄📄📄

📄📄📄📄

📄📄📄📄📄

📄📄📄📄📄

📄📄📄

📄📄📄📄📄📄

📄📄📄

📄📄 PDF


📄📄📄

📄📄📄📄

📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄

```
mkdir my-docs && cd my-docs
```

📄 `npm init -y` 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄 `npm`📄`yarn` 📄 `pnpm` 📄📄 `doom:`



```
npm install -D @alauda/doom typescript
```

📄📄📄📄📄📄📄📄:

```
# 创建 docs 目录并初始化
mkdir docs/en && echo '# Hello World' > docs/en/index.md
mkdir docs/zh && echo '# 文档' > docs/zh/index.md
```

在 `package.json` 中添加脚本:

```
{
  "scripts": {
    "dev": "doom dev",
    "build": "doom build",
    "new": "doom new",
    "serve": "doom serve",
    "translate": "doom translate",
    "export": "doom export"
  }
}
```

在 `doom.config.yml` 中添加:

```
title: My Docs
```

在 `tsconfig.json` 中添加:

```
{
  "compilerOptions": {
    "jsx": "react-jsx",
    "module": "NodeNext",
    "moduleResolution": "NodeNext",
    "noUnusedLocals": true,
    "noUnusedParameters": true,
    "resolveJsonModule": true,
    "skipLibCheck": true,
    "strict": true,
    "target": "ESNext",
  },
  "mdx": {
    "checkMdx": true,
  },
}
```

global.d.ts

```
/// <reference types="@alauda/doom/runtime" />
```

.mdx doom

```
doom -h
```

```
# output
```

```
Usage: doom [options] [command]
```

```
Doctor Doom making docs.
```

```
Options:
```

```
  -V, --version                output the version number
  -c, --config <config>       Specify the path to the config file
  -v <version>                 Specify the version of the
documentation, can also be `unversioned` or `unversioned-x.y`
  -b, --base <base>            Override the base of the
documentation
  -p, --prefix <prefix>        Specify the prefix of the
documentation base
  -f, --force [boolean]         Force to
                                1. fetch latest reference remotes or
                                scaffolding templates, otherwise use local cache
                                2. translate ignore hash equality
                                check and original text (default: false)
  -i, --ignore [boolean]        Ignore internal routes (default:
false)
  -d, --download [boolean]       Display download pdf link on nav bar
(default: false)
  -e, --export [boolean]         Run or build in exporting PDF mode,
`apis/**` and `*/apis/**` routes will be ignored automatically (default:
false)
  -I, --include <language...>   Include only the specific
language(s), `en ru` for example
  -E, --exclude <language...>   Include all languages except the
specific language(s), `ru` for example
  -o, --out-dir <path>           Override the `outDir` defined in the
config file or the default `dist/{base}/{version}`, the resulting path
will be `dist/{outDir}/{version}`
  -r, --redirect <enum>          Whether to redirect to the locale
closest to `navigator.language` when the user visits the site, could be
`auto`, `never` or `only-default-lang` (default: "only-default-lang")
  -R, --edit-repo [boolean|url|lang] Whether to enable or override the
`editRepoBaseUrl` config feature, `https://github.com/` prefix could be
omitted; if a language code is provided, all other languages will use the
same repo but with the language code as sub-path (default: false)
  -a, --algolia [boolean|alauda] Whether to enable or use the alauda
```

```
(docs.alauda.io) preset for Algolia search (default: false)
  -S, --site-url                Whether to enable the siteUrl for
sitemap generation (default: false)
  -n, --no-open                Do not open the browser after
starting the server
  -h, --help                    display help for command

Commands:
  dev [options] [root]        Start the development server
  build [root]                Build the documentation
  preview|serve [options] [root] Preview the built documentation
  new [template]              Generate scaffolding from templates
  translate [options] [root]  Translate the documentation
  export [options] [root]     Export the documentation as PDF,
`apis/**` and `*/apis/**` routes will be ignored automatically
  lint [options] [root]       Lint the documentation
  help [command]              display help for command
```

|  |  |  |  |  |  |
|--|--|--|--|--|--|
|  |  |  |  |  |  |
|--|--|--|--|--|--|

```

  yarn dev

```

```
doom dev -h

# output
Usage: doom dev [options] [root]

Start the development server

Arguments:
  root                Root directory of the documentation

Options:
  -H, --host [host]   Dev server host name
  -P, --port [port]   Dev server port number
  -l, --lazy [boolean] Whether to enable `lazyCompilation` which
could improve the compilation performance (default: true)
  --no-lazy            Do not enable `lazyCompilation`
  -h, --help          display help for command
```

安装依赖

使用 `yarn build` 命令来构建项目，使用 `dist` 命令来打包。

安装依赖

使用 `yarn serve` 命令来启动服务，使用 `-b` 和 `-p` 选项来指定端口和地址。

安装依赖

使用 `yarn new` 命令来创建新项目。

安装依赖

```
doom translate -h
```

```
# output
```

```
Usage: doom translate [options] [root]
```

```
Translate the documentation
```

```
Arguments:
```

```
  root
```

```
      Root directory of the documentation
```

```
Options:
```

```
  -s, --source <language> Document source language, one of en, zh, ru  
(default: "en")
```

```
  -t, --target <language> Document target language, one of en, zh, ru  
(default: "zh")
```

```
  -g, --glob <path...>   Glob patterns of source dirs/files to translate
```

```
  -C, --copy [boolean]    Wether to copy relative assets to the target  
directory instead of following links (default: false)
```

```
  -h, --help              display help for command
```

- `-g, --glob` 指定要翻译的源目录/文件的glob模式，使用 `glob` 命令来安装。

1. `yarn translate -g abc xyz` `<root>/<source>/abc` ,  
`<root>/<source>/xyz` `<root>/<target>/abc` ,  
`<root>/<target>/xyz`

2. `yarn translate -g '*'` `<root>/<source>`

- `-C, --copy` `false`

- 

1. `<root>/public/<source>/abc.jpg` `<root>/public/<target>/abc.jpg`

2. `<root>/<source>/abc.mdx` `./assets/xyz.jpg` `<root>/<source>/assets/xyz.jpg` `<root>/<target>/assets/xyz.jpg`

3. `<root>/<source>/abc.mdx` `./assets/<source>/xyz.jpg` `<root>/<source>/assets/<source>/xyz.jpg` `<root>/<target>/assets/<target>/xyz.jpg` `./assets/<target>/xyz.jpg`

- 

1. `<root>/public/<target>/abc.jpg` `<root>/public/<target>/abc.jpg`

2. `<root>/<source>/abc.mdx` `./assets/<source>/xyz.jpg` `<root>/<target>/assets/<target>/xyz.jpg` `./assets/<target>/xyz.jpg` `../<source>/assets/<target>/xyz.jpg`

## WARNING

`-g '*'` `source` `target` `internalRoutes` `target`

## TIP

`AZURE_OPENAI_API_KEY` Leader

🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑

```
il8n:
  title:
    en: DevOps Connectors
  additionalPrompts: '🌑🌑🌑 Connectors 🌑🌑🌑🌑🌑🌑🌑'
  disableAutoTranslation: false
title: DevOps 🌑🌑
```

🌑🌑🌑🌑🌑🌑🌑🌑🌑

🌑🌑 PDF

**WARNING**  
🌑🌑🌑🌑🌑🌑🌑🌑🌑 `yarn build` 🌑🌑🌑

```
doom export -h

# output
Usage: doom export [options] [root]

Export the documentation as PDF, `apis/**` and `*/apis/**` routes will be
ignored automatically

Arguments:
  root                Root directory of the documentation

Options:
  -H, --host [host]   Serve host name
  -P, --port [port]   Serve port number (default: "4173")
  -h, --help          display help for command
```

🌑🌑 `yarn export` 🌑🌑🌑🌑 PDF 🌑🌑🌑🌑🌑🌑🌑🌑 `-b` , `-p` 🌑🌑🌑🌑🌑🌑🌑🌑🌑 `-b` , `-p`  
🌑🌑

🌑🌑🌑🌑🌑 `playwright` ➔🌑🌑🌑🌑🌑🌑 `build-harbor.alauda.cn/frontend/playwright-`  
`runner:doom` 🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑🌑

```
.env.yarn
```

```
PLAYWRIGHT_DOWNLOAD_HOST="https://cdn.npmmirror.com/binaries/playwright"
```

pdf doom pdf

```
doom lint -h
```

```
# output
```

```
Usage: doom lint [options] [root]
```

```
Lint the documentation
```

```
Arguments:
```

```
  root                Root directory of the documentation
```

```
Options:
```

```
  -g, --glob <path...>  Glob patterns of source dirs/files to lint
                          (default: "**/*.{js,jsx,ts,tsx,md,mdx}")
  --no-cspell             Disable cspell linting
  -h, --help             display help for command
```

```
doom lint ESLint cspell
```

ESLint / CSpell:

- eslint.config.mjs:

```
import doom from '@alauda/doom/eslint'

export default doom(new URL('docs', import.meta.url))
```

- cspell.config.mjs:

```
export { default } from '@alauda/doom/cspell'
```

000000000000 CWD 00 .cspell 0000000 CSpell 00000000000000  
.cspell/k8s.txt 0

k8s  
kubernetes

0000000000000000



📄

📄 `doom` 📄📄

📄📄

📄📄

API 📄📄

📄📄📄📄

📄📄📄

📄📄📄

📄📄📄

📄📄📄📄

📄📄📄📄📄

📄📄📄📄

`sites.yaml` 📄

📄📄

📄📄📄📄📄

📄📄📄

📄📄📄

Algolia 📄📄

Sitemap 📄

11

□ □ □ □

□ □ □ □ □ □ □

`.mdx`

API 00

00 API

CRD

0000

00 openapi 00

000000

props

00

0000

000000

00

000000000000000000000000 ACP 00

00000

00000

000000

00000000

📄📄

📄📄

📄📄📄📄

📄📄📄📄

API 📄📄📄📄

📄📄📄📄📄📄📄📄

📄📄📄📄📄📄

frontmatterMode

📄📄📄📄📄📄

📄📄📄📄📄

📄📄📄📄📄📄📄📄

📄📄📄📄📄📄📄📄

📄📄📄📄📄📄📄📄

sites.yaml 📄📄

📄📄📄📄

📄📄📄📄📄📄📄📄

📄📄📄📄📄📄

📄📄📄📄📄📄

Algolia 📄📄📄📄

Sitemap 📄📄

📄📄📄📄📄📄

```

##### yaml ##### doom.config.yaml []

doom.config.yaml ##### rspress ##### js/ts #####

##### .js/.ts/.mjs/.mts/.cjs/.cts #####

[] js/ts ##### @alauda/doom/config ##### defineConfig []
#####

```

```
import { defineConfig } from '@alauda/doom/config'

export default defineConfig({})
```

|  |  |  |  |
|--|--|--|--|
|  |  |  |  |
|--|--|--|--|

- [illegible]

API ☐ ☐ ☐ ☐

**api:**

```
# CRD 配置文件 doom.config.* 文件 glob 模式 json/yaml 文件
```

**crds:**

```
- docs/shared/crds/*.yaml
```

```
# OpenAPI 配置文件 doom.config.* 文件 glob 模式 json/yaml 文件
```

**openapis:**

```
- docs/shared/openapis/*.json
```

```
# 为 openapi 文件生成 OpenAPI 规范文档
```

```
# 为
```

<https://doom.alauda.cn/apis/references/CodeQuality.html#v1alpha1.CodeQualityS>

**references:**

```
  v1alpha1.CodeQualityBranch:
```

</apis/references/CodeQualityBranch#v1alpha1.CodeQualityBranch>

```
# 为 API 文件生成 OpenAPI 规范文档 gateway 文件
```

```
pathPrefix: /apis
```

为 API 文件

为 API 文件

```
# 为 API 文件生成 OpenAPI 规范文档 gateway 文件
```

**permission:****functionresources:**

```
# `kubectl get functionresources`
```

```
- docs/shared/functionresources/*.yaml
```

**roletemplates:**

```
# `kubectl get roletemplates -l
```

```
auth.cpaas.io/roletemplate.official=true`
```

```
- docs/shared/roletemplates/*.yaml
```

为 API 文件

为 API 文件

**reference:**

```

- repo: alauda-public/product-doc-guide #
branch: # [string]
publicBase: # [string] /images/xx.png
docs/public
sources:
- name: anchor #
path: docs/index.mdx# #
doom.config.*
ignoreHeading: # [boolean] true
processors: #
- type: ejsTemplate
data: # ejs `<%= data.xx %>`
frontmatterMode: merge # frontmatter ignore
ignore/merge/replace/remove

```

**frontmatterMode**

- **ignore** frontmatter frontmatter
- **merge** frontmatter key
- **replace** frontmatter frontmatter
- **remove** frontmatter

**releaseNotes:****queryTemplates:**

```

fixed: # ejs jql
unfixed:

```

release-notes.md



```
onlyIncludeRoutes: # 只包含 glob 匹配的 docs 页面 cli 中 -i, --ignore 选项
                    匹配的路径/文件夹名称 `internalRoutes` 中指定的路径
    - '*/internal/**'
internalRoutes:
    - '*/internal/overview.mdx'
```



```
shiki:
  theme: # optional, https://shiki.style/themes
  langs: # optional, https://shiki.style/languages
  transformers: # optional, only available in js/ts config,
https://shiki.style/guide/transformers
```

## WARNING

plaintext

`sites.yaml` ☐ ☐

```
sites.yaml
```

```
#####
```

```
###
```

```
- name: connectors # 连接器
base: /devops-connectors # 连接器
version: v1.1 # 连接器 ExternalSite/ExternalSiteLink 连接器

displayName: # 连接器 name
  en: DevOps Connectors
  zh: DevOps 连接器

# 连接器
# 连接器
repo: https://github.com/AlaudaDevops/connectors-operator # 连接器
gitlab slug: `alauda/product-docs`
image: devops/connectors-docs # 连接器
```

🔒🔒🔒🔒

## translate:

```
# 将源语言 `sourceLang` 翻译成目标语言 `targetLang`，`userPrompt`，
`additionalPrompts`，`terms`，`titleTranslationPrompt`
# 将 `sourceLang` 翻译成 `targetLang` 的 `terms` 和 `title` 的翻译
# `userPrompt` 的翻译
# `additionalPrompts` 的翻译 `frontmatter.il18n` 的 `additionalPrompts`
的翻译
# `terms` 和 `titleTranslationPrompt` 的翻译 AI
的翻译
# 的翻译
```

### systemPrompt: |

You are a professional technical documentation engineer, skilled in writing high-quality technical documentation in <%= targetLang %>. Please accurately translate the following text from <%= sourceLang %> to <%= targetLang %>, maintaining the style consistent with technical documentation in <%= sourceLang %>.

### ## Baseline Requirements

- Sentences should be fluent and conform to the expression habits of the <%= targetLang %> language.
- Input format is MDX; output format must also retain the original MDX format. Do not translate the names of jsx components such as <Overview />, and do not wrap output in unnecessary code blocks.
- **\*\*CRITICAL\*\***: Do not translate or modify ANY link content in the document. This includes:
  - **URLs in markdown links**: [text](URL) - keep URL exactly as is
  - **Reference-style links**: [text][ref] and [ref]: URL - keep both ref and URL unchanged
  - **Inline URLs**: https://example.com - keep completely unchanged
  - **Image links**: ![alt](src) - keep src unchanged, but alt text can be translated
  - **Anchor links**: [text](#anchor) - keep #anchor unchanged
  - Any href attributes in HTML tags - keep unchanged
- Do not translate professional technical terms and proper nouns, including but not limited to: Kubernetes, Docker, CLI, API, REST, GraphQL, JSON, YAML, Git, GitHub, GitLab, AWS, Azure, GCP, Linux, Windows, macOS, Node.js, React, Vue, Angular, TypeScript, JavaScript, Python, Java, Go, Rust, etc. Keep these terms in their original form.
- The title field and description field in frontmatter should be translated, other frontmatter fields should retain and do not translate.
- Content within MDX components needs to be translated, whereas MDX component names and parameter keys do not.
- Do not modify or translate any placeholders in the format of

`__ANCHOR_N__` (where N is a number). These placeholders must be kept exactly as they appear in the source text.

- Keep original escape characters like backslash, angle brackets, etc. unchanged during translation.
- Do not add any escape characters to special characters like `[]`, `()`, `{}`, etc. unless they were explicitly present in the source text. For example:
  - If source has "Architecture [Optional]", keep it as "Architecture [Optional]" (not "Architecture \[Optional]")
  - If source has "Function (param)", keep it as "Function (param)" (not "Function \((param)")
  - Only add escape characters if they were present in the original text
- Preserve and do not translate the following comments, nor modify their content:
  - `{/* release-notes-for-bugs */}`
  - `<!-- release-notes-for-bugs -->`
- Remove and do not retain the following comments:
  - `{/* reference-start */}`
  - `{/* reference-end */}`
  - `<!-- reference-start -->`
  - `<!-- reference-end -->`
- Ensure the original Markdown format remains intact during translation, such as frontmatter, code blocks, lists, tables, etc.
- Do not translate the content of the code block.

```
<% if (titleTranslationPrompt) { %>
<%- titleTranslationPrompt %>
<% } %>
<% if (terms) { %>
<%- terms %>
<% } %>
```

```
<% if (userPrompt || additionalPrompts) { %>
```

```
## Additional Requirements
```

These are additional requirements for the translation. They should be met along with the baseline requirements, and in case of any conflict, the baseline requirements should take precedence.

The text for translation is provided below, within triple quotes:

```
"""
```

```
<% if (userPrompt) { %>
<%- userPrompt %>
<% } %>
```

```
<% if (additionalPrompts) { %>
<%- additionalPrompts %>
```

```
<% } %>
""
<% } %>
```

```
editRepoBaseUrl: alauda/doom/tree/main/docs # https://github.com/
`-R, --edit-repo`
```

```
export:
- name: Concepts # pdf
scope: '*/concepts' # glob docs
```

```
lint:
  cspellOptions: #
https://github.com/streetsidesoftware/cspell/tree/main/packages/cspell-
eslint-plugin#options
```

Algolia

```
algolia: # Algolia 配置参数 -a, --algolia` 配置参数
appId: # Algolia ID
apiKey: # Algolia API Key
indexName: # Algolia 索引名
```

public/robots.txt Algolia

**INFO**

`rspress` Algolia [\[REDACTED\]](#) [@alauda/doom/theme](#)

theme/index.ts

```
export * from '@alauda/doom/theme'
```

## Sitemap ☐ ☐

```
siteUrl: https://docs.alauda.cn # 指定 URL 生成 sitemap 文件 -S, --site-  
url` 指定生成 sitemap 文件的 URL
```

□ □ □ □

333

11

11

|  |  |  |  |
|--|--|--|--|
|  |  |  |  |
|--|--|--|--|

index

index.md index.mdx

```
├─ index.md
├─ start.mdx
└─ usage
    ├── index.mdx
    └─ convention.md
```

|  |  |  |  |  |  |
|--|--|--|--|--|--|
|  |  |  |  |  |  |
|--|--|--|--|--|--|

1. `public` □□□□□□□□□□□□□□□□
2. `public/_remotes` □□□□□□□□□□□□□□□□□□□□□□□□□□□□  
`*/public/_remotes` □□ `.gitignore` □□□□□□□□□□
3. `shared` □□□□□□□□□□□□□□□□□□□□□□□□□□□□

🐱🐱

🐱🐱🐱🐱🐱🐱 `frontmatter` 🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱

```
---
title: 🐱
description: 🐱
author: 🐱
category: 🐱
---
```

🐱🐱🐱🐱🐱🐱 `MDX` 🐱 `.mdx` 🐱🐱🐱🐱🐱 `frontmatter` 🐱🐱🐱🐱🐱🐱

🐱🐱

🐱 `index.md` 🐱 `index.mdx` 🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱 `frontmatter` 🐱  
`weight` 🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱 `weight` 🐱🐱🐱🐱🐱🐱

```
---
weight: 1
---
```

### WARNING

🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱🐱

🐱🐱

index.mdx Overview

```
#  
  
<Overview />
```

# Markdown

[gfm](#) [Doom](#) [Markdown](#)



## Callouts

Mermaid

□ □ □ □

## Callouts

□ □ □ □ □ □

## NOTE

1. `;;,%,#,//,/***/,--` `<!-- -->`
2. `[!\code callout]`
3. `:::callouts` `<div class="doom-callouts">`  
`<Callouts>`

```
```sh
```

```
Memory overhead per virtual machine ≈ (1.002 × requested memory) \
+ 218 MiB \ # [!code callout]
+ 8 MiB × (number of vCPUs) \ # [!code callout]
+ 16 MiB × (number of graphics devices) \ # [!code callout]
+ (additional memory overhead) # [!code callout]
```

```
```
```

```
:::callouts
```

1. Required for the processes that run in the `virt-launcher` pod.
2. Number of virtual CPUs requested by the virtual machine.
3. Number of virtual graphics cards requested by the virtual machine.
4. Additional memory overhead:
  - If your environment includes a Single Root I/O Virtualization (SR-IOV) network device or a Graphics Processing Unit (GPU), allocate 1 GiB additional memory overhead for each device.
  - If Secure Encrypted Virtualization (SEV) is enabled, add 256 MiB.
  - If Trusted Platform Module (TPM) is enabled, add 53 MiB.

```
:::
```


```
Memory overhead per virtual machine ≈ (1.002 × requested memory) \
+ 218 MiB \ ①
+ 8 MiB × (number of vCPUs) \ ②
+ 16 MiB × (number of graphics devices) \ ③
+ (additional memory overhead) ④
```

- ① Required for the processes that run in the `virt-launcher` pod.
- ② Number of virtual CPUs requested by the virtual machine.
- ③ Number of virtual graphics cards requested by the virtual machine.
- ④ Additional memory overhead:
  - If your environment includes a Single Root I/O Virtualization (SR-IOV) network device or a Graphics Processing Unit (GPU), allocate 1 GiB additional memory overhead for each device.
  - If Secure Encrypted Virtualization (SEV) is enabled, add 256 MiB.
  - If Trusted Platform Module (TPM) is enabled, add 53 MiB.

Shiki Transformers ↗

# Mermaid ↗

```
mermaid
graph TD;
  A-->B;
  A-->C;
  B-->D;
  C-->D;
```



Markdown Preview Mermaid ↗ VSCode

**WARNING**  
 `.md` [issue ↗](#)

```
{width="100" height="100"}
```



# MDX

[MDX](#) [Markdown](#) [Markdown](#) [JSX](#) [rspress MDX](#)

rspress

doom

Overview

Directive

ExternalSite

ExternalSiteLink

AcpApis0verview ExternalApis0verview

Term

props

TermsTable

props

JsonViewer

## rspress

rspress [rspress](#) [.mdx](#)

- Badge
- Card

- [LinkCard](#)
- [PackageManagerTabs](#)
- [Steps](#)
- [Tab/Tabs](#)
- [Toc](#)

在 `rspress/theme` 中配置

preview.mdx

```
import { SourceCode } from '@rspress/core/theme'

<SourceCode href="/" />
```

## doom 文档

`doom` 是一个用于生成文档的工具。

### Overview

文档生成工具

### Directive

在文档中使用 `Directive` 来指定文档的元数据。

- 在 ``doc/en`` 中指定文档的元数据，在 ``doc/zh`` 中指定文档的元数据。

```
<Directive type="danger" title="危险">
  这是一个危险的文档。
  `doc/zh` 中指定文档的元数据
</Directive>
```

- 在 `doc/en` 中，`doc/zh` 是默认语言，`doc/en` 是可选语言。

在 `doc/zh` 中，`doc/zh` 是默认语言，`doc/en` 是可选语言。

## ExternalSite

在 `doc/zh` 中

```
<ExternalSite name="connectors" />
```

### Note

在 `DevOps` 中，`DevOps` 是默认语言，`DevOps` 是可选语言。  
[DevOps 文档](#)

## ExternalSiteLink

在 `doc/zh` 中

```
<ExternalSiteLink name="connectors" href="link.mdx#hash" children="Content" />
```

[Content](#)

### TIP

在 `mdx` 中，`<ExternalSiteLink name="connectors" href="link" children="Content" />` 是默认语言，`doc/zh` 是可选语言。

```
<ExternalSiteLink name="connectors" href="link">
  Content {/* `p` */}
</ExternalSiteLink>
```

p children

## AcpApisOverview ExternalApisOverview

API

```
<AcpApisOverview />
{/* same as following */}
<ExternalApisOverview name="acp" />

<ExternalApisOverview name="connectors" />
```

### Note

ACP APIs [ACP APIs](#)

### Note

DevOps APIs [DevOps APIs](#)

## Term

```
<Term name="company" textCase="capitalize" />
<Term name="product" textCase="lower" />
<Term name="productShort" textCase="upper" />
```

ACP

props

- `name` : □□□□□□□□□□□□□□□□
- `textCase` : □□□□□□□□□□□□ `lower` , `upper` , `capitalize`

## TermsTable



```
<TermsTable />
```

| 公司           | 名称       | 类型 | 名称                           | 类型 | 名称       |
|--------------|----------|----|------------------------------|----|----------|
| company      | 名称       | -  | Alauda                       | -  | 名称       |
| product      | 名称<br>名称 | -  | Alauda Container<br>Platform | -  | 名称       |
| productShort | ACP      | -  | ACP                          | -  | 名称<br>名称 |

## props

- terms : NormalizedTermItem[] □□□□□□□□□□□□□□□□□□□□□□□□

## JsonViewer

```
<JsonViewer value={{ key: 'value' }} />
```

```
yaml      json
         
key: value
```

□□□□□□□□

□□□□□□□□□□□□□□□□ `shared` □□□□□□□□□□□□□□□□□□

```
import CommonContent from './shared/CommonContent.mdx'

<CommonContent />
```

□□□□□□□□ [runtime](#) ↗ □□□ API□□□□□□ `.jsx/.tsx` □□□□□□□□ `.mdx` □□□□□□□□

```
// shared/CommonContent.tsx
export const CommonContent = () => {
  const { page } = usePageData()
  return <div>{page.title}</div>
}

// showcase/content.mdx
import { CommonContent } from './shared/CommonContent'
;<CommonContent />
```

## WARNING

□□□□□ `.mdx` □□□□□□□□□ `props` □□□□□□ [issue](#) ↗ □□□□□□□□ `props` □□□□□□□□  
`.jsx/.tsx` □□□□□□□□

📄📄📄

`alauda` 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄 `en / zh` 📄📄📄📄📄📄📄📄📄📄📄📄  
📄 `public` 📄📄📄 `en / zh` 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄

📄📄

- `i18n.json`
- `.ts/.tsx`
- `.mdx`

## `i18n.json`

📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄 `docs` 📄📄📄 `i18n.json` 📄📄  
📄📄📄📄📄 `useI18n` 📄📄📄📄📄📄📄📄

docs/i18n.json

```
{
  "title": {
    "zh": "标题",
    "en": "Title"
  },
  "description": {
    "zh": "描述",
    "en": "description"
  }
}
```

## .ts/.tsx

```
import { useI18n } from '@rspress/core/runtime'

export const CommonContent = () => {
  const t = useI18n()
  return <h1>{t('title')}</h1>
}
```

## .mdx

```
import { useI18n } from '@rspress/core/runtime'

# {useI18n()}('title')}

{useI18n()}('description')}
```

# API 文档

API 文档 API 文档 CRD (Custom Resource Definition) 文档

```
├─ apis
│   ├── advanced-apis # API
│   ├── crds # CRDs
│   └── references # 文档
```

文档

API

props

CRD

props

文档

props

openapi 文档

## API

advanced-apis/codeQualityTaskSummary.mdx

```
# CodeQualityTaskSummary

<OpenAPIPath path="/plugins/v1alpha1/template/codeQuality/task/{task-id}/summary" />
```

文档 CodeQualityTaskSummary

props

- path : OpenAPI schema paths
- pathPrefix : api.pathPrefix
- openapiPath : openapi

CRD

crds/ArtifactCleanupRun.mdx

```
# ArtifactCleanupRun

<K8sCrd name="artifactcleanupruns.artifacts.katanomi.dev" />
```

文档 ArtifactCleanupRun

props

- name : CRD metadata.name
- crdPath : openapi CRD

references/CodeQuality.mdx

# CodeQuality

```
<OpenAPIRef schema="v1alpha1.CodeQuality" />
```

関数 `CodeQuality`

## props

- `schema` : OpenAPI schema `definitions` (v2) or `component/schemas` (v3) の参照
- `openapiPath` : 参照する `openapi` のパス

## 関数 `openapi`

関数 `OpenAPIPath` は `OpenAPIRef` の参照する `openapi` のパスを返します。  
関数 `openapi` は `openapiPath` の参照する

```
<OpenAPIPath  
  path="/plugins/v1alpha1/template/codeQuality/task/{task-id}/summary"  
  openapiPath="shared/openapis/katanomi.json"  
>
```

测试计划

```

<K8sPermissionTable functions={['devops-testplans', 'devops-testmodules']}
/>

```

测试计划

props

测试计划

props

- functions : string[] - 测试计划 FunctionResource 测试计划

测试计划

| 测试计划                     | 测试计划 | 测试计划<br>测试计划 | 测试计划<br>测试计划 | 测试计划<br>测试计划 | 测试计划<br>测试计划 | 测试计划<br>测试计划 | 测试计划<br>测试计划 |
|--------------------------|------|--------------|--------------|--------------|--------------|--------------|--------------|
| 测试计划<br>devops-testplans | 测试计划 | ✓            | ✓            | ✓            | ✓            | ✓            | ✗            |
|                          | 测试计划 | ✓            | ✗            | ✓            | ✓            | ✓            | ✗            |
|                          | 测试计划 | ✓            | ✗            | ✓            | ✓            | ✓            | ✗            |
|                          | 测试计划 | ✓            | ✗            | ✓            | ✓            | ✓            | ✗            |

| 测试用例                           | 测试用例 | 测试用例         | 测试用例         | 测试用例         | 测试用例         | 测试用例         | 测试用例         |
|--------------------------------|------|--------------|--------------|--------------|--------------|--------------|--------------|
| 测试用例<br>devops-<br>testmodules | 测试用例 | 测试用例<br>测试用例 | 测试用例<br>测试用例 | 测试用例<br>测试用例 | 测试用例<br>测试用例 | 测试用例<br>测试用例 | 测试用例<br>测试用例 |
|                                | 测试用例 | ✓            | ✓            | ✓            | ✓            | ✓            | ✗            |
|                                | 测试用例 | ✓            | ✗            | ✓            | ✓            | ✓            | ✗            |
|                                | 测试用例 | ✓            | ✗            | ✓            | ✓            | ✓            | ✗            |
|                                | 测试用例 | ✓            | ✗            | ✓            | ✓            | ✓            | ✗            |

☐ Markdown ☐☐☐☐

```
<!-- reference-end -->
```

```
{/* reference-end */}
```

```
□□□□□□ <root>/public/_remotes/<name> □□□□
```

```

□□□□□ <!-- reference-start#ref --> □□□□□

```

|  |  |  |  |  |  |
|--|--|--|--|--|--|
|  |  |  |  |  |  |
|--|--|--|--|--|--|

frontmatterMode

|  |  |  |  |  |  |
|--|--|--|--|--|--|
|  |  |  |  |  |  |
|--|--|--|--|--|--|

**reference:**

```

- repo: alauda-public/product-doc-guide # 文档仓库地址
branch: # [string] 分支名称
publicBase: # [string] 文档仓库地址 /images/xx.png 文档仓库地址
docs/public
sources:
- name: anchor # 文档仓库名称
path: docs/index.mdx# # 文档仓库地址
doom.config.*
ignoreHeading: # [boolean] 是否忽略 heading true 忽略
processors: # 处理器
- type: ejsTemplate
data: # ejs 模板数据 `<%= data.xx %>` 模板
frontmatterMode: merge # 文档仓库 frontmatter 模式 ignore 忽略
ignore/merge/replace/remove

```

**frontmatterMode**

- **ignore** 忽略 frontmatter
- **merge** 合并 frontmatter key 冲突时合并
- **replace** 替换 frontmatter
- **remove** 移除 frontmatter

文档仓库地址

```
doom build # 
doom serve # 
```

doom build dist -v

```
# 4.0 4.0
doom build -v 4.0 # 4.0 dist/4.0 {base}/4.0
doom build -v master # master dist/master {base}/master
doom build -v {other} # dist/{other} {base}/{other}

# unversioned unversioned-x.y
doom build -v unversioned # dist/unversioned {base}
doom build -v unversioned-4.0 # 4.0 dist/unversioned {base}
```

```
├─ console-platform
│   ├── 4.0
│   ├── 4.1
│   ├── index.html
│   ├── overrides.yaml
│   └── versions.yaml
├─ console-devops-docs
│   ├── 4.0
│   ├── 4.1
│   ├── index.html
│   ├── overrides.yaml
│   └── versions.yaml
├─ console-tekton-docs
│   ├── 1.0
│   ├── 1.1
│   ├── index.html
│   ├── overrides.yaml
│   └── versions.yaml
```

index.html

```
<!DOCTYPE html>
<html>
  <head>
    <title>Redirecting...</title>
    <meta http-equiv="refresh" content="0; url=/console-docs/4.1" />
  </head>
  <body>
    <p>Redirecting to <a href="/console-docs/4.1">/console-docs/4.1</a>
  </p>
  </body>
</html>
```

□□□□□□□□

#### overrides.yaml

```
# 配置本地化内容
title:
  en: Doom - Alauda
  zh: Doom - 道门
logoText:
  en: Doom - Alauda
  zh: Doom - 道门
```

#### versions.yaml

```
- '4.1'
- '4.0'
```