IP Whitelisting

🛡️ IP Whitelisting Reference

To ensure seamless connectivity and secure communication between your devices and the GCXONE platform, it is essential to permit traffic to the following IP addresses on your network's firewall.

☁️ Core Platform Gateways

These IP addresses are mandatory for the core platform functionality.

Service IP Address Description **Primary Gateway** `18.185.17.113` Main platform handshake **Backup Gateway** `3.124.50.242` Global failover node **Messaging Gateway** `3.127.50.212` Secure event delivery

📹 Streaming Gateways (WebRTC)

Whitelist these IPs to enable high-performance, low-latency video streaming in your browser.

Node IP Address Region **Primary Stream** `3.126.237.150` Europe (Central) **Secondary Stream** `3.75.73.51` Europe (Central) **Overflow Stream** `18.156.39.63` Europe (Central)

📱 Manufacturer Alarm Receivers

Permit traffic to these receivers based on the hardware you are deploying:

Manufacturer IP Address Role **Camect** `3.122.169.231` Smart Hub Bridge **Dahua** `52.59.60.20` Native Alarm Receiver **Hikvision** `35.156.60.98` Native Alarm Receiver **Hanwha** `18.184.110.24` Native Alarm Receiver **Milestone** `3.66.98.181` VMS Alarm Bridge **Uniview** `18.158.140.99` Native Alarm Receiver **Heitel (Live)** `3.123.206.197` Video Gateway **Heitel (Events)** `3.124.38.48` Event Gateway

🔗 Talos Integration

For organizations integrating with **Evalink Talos**, the following specific routes are required:

- `195.8.103.10` - `195.8.103.11` - `195.8.103.12` - `193.151.94.10` - `193.151.94.11` - `193.151.94.12` - `91.240.18.20` - `91.240.19.20` Whitelist these wildcards for application services: - `*.evalink.io` - `*.talos-app.io` - `*.eu.auth0.com`

Related Articles

Still have questions? Contact support for assistance.