CENTRO FP SUPERIOR
CAMPUS CÁMARA COMERCIO SEVILLA

Fase Práctica: *Hardening* y Vigilancia en la Trinchera

Nombre y Apellidos: Alba Duran Bernal
Modulo: Sistemas informaticos
Fecha de entrega: 17/04/2026
Docente: Willman Acosta Lugo

Reto A: Auditoría de Accesos e Intrusiones (Log Analysis y Scripting)

Ejecutamos el comando *ip addr show* para mostrar la ip

```
alba@serverubuntu:~$ ip addr show
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
       valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
       valid_lft forever preferred_lft forever
2: enp0s3: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 10
0
    link/ether 08:00:27:34:36:1e brd ff:ff:ff:ff:ff:ff
    inet6 fe80::a00:27ff:fe34:361e/64 scope link
       valid_lft forever preferred_lft forever
```

Tras crear el primero, nos inventamos una contraseña para este mismo y repetimos el proceso 4 veces más

```
alba@serverubuntu:~$ ssh administrador_falso@127.0.0.1
The authenticity of host '127.0.0.1 (127.0.0.1)' can't be established.
ED25519 key fingerprint is SHA256:dw4XQbhy4rQCJbaIlLddU+UdtSryCH4K8lu/bodng8k.
This key is not known by any other names
Are you sure you want to continue connecting (yes/no/[fingerprint])? y
Please type 'yes', 'no' or the fingerprint: yes
Warning: Permanently added '127.0.0.1' (ED25519) to the list of known hosts.
administrador_falso@127.0.0.1's password:
```