

rucrdtw: Fast time series subsequence search in R

Philipp H Boersch-Supan¹

DOI: [10.21105/joss.00100](https://doi.org/10.21105/joss.00100)

¹ Department of Geography and Emerging Pathogens Institute, University of Florida

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Licence

Authors of JOSS papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC-BY](#)).

Summary

Dynamic Time Warping (DTW) methods provide algorithms to optimally map a given time series onto all or part of another time series (Berndt and Clifford 1994). The remaining cumulative distance between the series after the alignment is a useful distance metric in time series data mining applications for tasks such as classification, clustering, and anomaly detection.

Calculating a DTW alignment is computationally relatively expensive, and as a consequence DTW is often a bottleneck in time series data mining applications. The UCR Suite (Rakthanmanon et al. 2012) provides a highly optimized algorithm for best-match subsequence searches that avoids unnecessary distance computations and thereby enables fast DTW and Euclidean Distance queries even in data sets containing trillions of observations.

A broad suite of DTW algorithms is implemented in R in the `dtw` package (Giorgino 2009). The `rucrdtw` R package provides complementary functionality for fast similarity searches by providing R bindings for the UCR Suite via `Rcpp` (Eddelbuettel and Francois 2011). In addition to queries and data stored in text files, `rucrdtw` also implements methods for queries and/or data that are held in memory as R objects, as well as a method to do fast similarity searches against reference libraries of time series.

References

- Berndt, Donald J, and James Clifford. 1994. "Using Dynamic Time Warping to Find Patterns in Time Series." In *KDD Workshop*, 10:359–70. 16. AAAI. <http://www.aaai.org/Library/Workshops/1994/ws94-03-031.php>.
- Eddelbuettel, Dirk, and Romain Francois. 2011. "Rcpp: Seamless R and C++ Integration." *Journal of Statistical Software* 40 (1): 1–18. doi:10.18637/jss.v040.i08.
- Giorgino, Toni. 2009. "Computing and Visualizing Dynamic Time Warping Alignments in R: The Dtw Package." *Journal of Statistical Software* 31 (7): 1–24. doi:10.18637/jss.v031.i07.
- Rakthanmanon, Thanawin, Bilson Campana, Abdullah Mueen, Gustavo Batista, Brandon Westover, Qiang Zhu, Jesin Zakaria, and Eamonn Keogh. 2012. "Searching and Mining Trillions of Time Series Subsequences Under Dynamic Time Warping." In *Proceedings of the 18th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 262–70. ACM. doi:10.1145/2339530.2339576.




Figure 1: Figure 1: UCR DTW is approximately 3 orders of magnitude faster than a naive sliding-window search using DTW distance.