

nse: Computation of Numerical Standard Errors in R

David Ardia¹ and Keven Bluteau¹

DOI: [10.21105/joss.00172](https://doi.org/10.21105/joss.00172)

¹ Institute of Financial Analysis - University of Neuchâtel

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Licence

Authors of JOSS papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC-BY](#)).

Summary

`nse` is an R package (R Core Team (2016)) for computing the numerical standard error (NSE), an estimate of the standard deviation of a simulation result, if the simulation experiment were to be repeated many times. The package provides a set of wrappers around several R packages, which give access to more than thirty estimators, including batch means estimators (Geyer (1992 Section 3.2)), initial sequence estimators (Geyer (1992 Equation 3.3)), spectrum at zero estimators (Heidelberger and Welch (1981), Flegal and Jones (2010)), heteroskedasticity and autocorrelation consistent (HAC) kernel estimators (Newey and West (1987), Andrews (1991), Andrews and Monahan (1992), Newey and West (1994), Hirukawa (2010)), and bootstrap estimators Politis and Romano (1992), Politis and Romano (1994), Politis and White (2004)). The full set of methods available is presented in Ardia, Bluteau, and Hoogerheide (2016) together with several examples of applications of NSE in econometrics and finance. The latest version of the package is available at '<https://github.com/keblu/nse>'.

References

- Andrews, D. W. K. 1991. "Heteroskedasticity and Autocorrelation Consistent Covariance Matrix Estimation." *Econometrica* 59 (3): 817–58. doi:10.2307/2938229.
- Andrews, D. W. K., and J Christopher Monahan. 1992. "An Improved Heteroskedasticity and Autocorrelation Consistent Covariance Matrix Estimator." *Econometrica* 60 (4): 953–66. doi:10.2307/2951574.
- Ardia, D., K. Bluteau, and Lennart F. Hoogerheide. 2016. "Comparison of Multiple Methods for Computing Numerical Standard Errors: An Extensive Monte Carlo Study." https://papers.ssrn.com/sol3/papers.cfm?abstract_id=2741587.
- Flegal, J. M., and G. L. Jones. 2010. "Batch Means and Spectral Variance Estimators in Markov Chain Monte Carlo." *Annals of Statistics* 38 (2): 1034–70. doi:10.1214/09-aos735.
- Geyer, C. J. 1992. "Practical Markov Chain Monte Carlo." *Statistical Science* 7 (4): 473–83. doi:10.1214/ss/1177011137.
- Heidelberger, Philip, and Peter D. Welch. 1981. "A Spectral Method for Confidence Interval Generation and Run Length Control in Simulations." *Communications of the ACM* 24 (4): 233–45. doi:10.1145/358598.358630.
- Hirukawa, Masayuki. 2010. "A Two-Stage Plug-in Bandwidth Selection and Its Implementation for Covariance Estimation." *Econometric Theory* 26 (3): 710–43. doi:10.1017/s0266466609990089.
- Newey, Whitney K, and Kenneth D West. 1987. "A Simple, Positive Semi-Definite, Heteroskedasticity and Autocorrelation Consistent Covariance Matrix." *Econometrica* 55

(3): 703–8. doi:10.2307/1913610.

———. 1994. “Automatic Lag Selection in Covariance Matrix Estimation.” *Review of Economic Studies* 61 (4): 631–53. doi:10.3386/t0144.

Politis, Dimitris N, and Joseph P Romano. 1992. “A Circular Block-Resampling Procedure for Stationary Data.” In *Exploring the Limits of Bootstrap*, 263–70. John Wiley & Sons.

———. 1994. “The Stationary Bootstrap.” *Journal of the American Statistical Association* 89 (428): 1303–13. doi:10.2307/2290993.

Politis, Dimitris N, and Halbert White. 2004. “Automatic Block-Length Selection for the Dependent Bootstrap.” *Econometric Reviews* 23 (1): 53–70. doi:10.1081/etc-120028836.

R Core Team. 2016. *R: A Language and Environment for Statistical Computing*. Vienna, Austria: R Foundation for Statistical Computing. <http://www.R-project.org/>.