

# 92586 Computational Linguistics

## Lesson 4. More Math

Alberto Barrón-Cedeño

Alma Mater Studiorum-Università di Bologna

a.barron@unibo.it

@albarron\_

10/03/2020



# Previously

- Pre-processing
- BoW representation

# Previously

- Pre-processing
- BoW representation
- One rule-based sentiment model
- One statistical model (Naïve Bayes)

# Table of Contents

① From BoW to *tf*

② Zipf's Law

③ Inverse Document Frequency

These slides cover roughly chapter 3 of Lane et al. (2019)

## From BoW to tf

# Intuition

- ① The frequency of a token in a document is an important factor of its **relevance**

# Intuition

- ① The frequency of a token in a document is an important factor of its **relevance**
- ② The relative frequency of a word in a document wrt **all other documents** in the collection provide better information

# Binary Bag of Words

We departed from a binary representation.

We are simply interested in the existence (or not) of a word in a document.



# Binary Bag of Words

We departed from a binary representation.

We are simply interested in the existence (or not) of a word in a document.

$$\begin{array}{lcl} d_1 & = & \begin{bmatrix} 0 & 1 & 0 & 0 & 1 & 0 & 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix} \\ d_2 & = & \begin{bmatrix} 1 & 1 & 1 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 1 & 1 & 1 \end{bmatrix} \end{array}$$

# “Counting” Bag of Words

The more times a word occurs, the more meaning it contributes to the document

# “Counting” Bag of Words

The more times a word occurs, the more meaning it contributes to the document

A document with many occurrences of “good”, “awesome”, “best” is more **positive** than one in which they occur only once.

# “Counting” Bag of Words

The more times a word occurs, the more meaning it contributes to the document

A document with many occurrences of “good”, “awesome”, “best” is more **positive** than one in which they occur only once.


$$\begin{array}{lcl} d_1 & = & \begin{bmatrix} 0 & 1 & 0 & 0 & 2 & 0 & 1 & 3 & 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix} \\ d_2 & = & \begin{bmatrix} 2 & 3 & 5 & 0 & 0 & 0 & 0 & 4 & 0 & 0 & 0 & 4 & 2 \end{bmatrix} \end{array}$$

# “Counting” Bag of Words

The more times a word occurs, the more meaning it contributes to the document

A document with many occurrences of “good”, “awesome”, “best” is more **positive** than one in which they occur only once.

$$\begin{array}{lcl} d_1 & = & \begin{bmatrix} 0 & 1 & 0 & 0 & 2 & 0 & 1 & 3 & 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix} \\ d_2 & = & \begin{bmatrix} 2 & 3 & 5 & 0 & 0 & 0 & 0 & 4 & 0 & 0 & 0 & 4 & 2 \end{bmatrix} \end{array}$$


 Let us see the difference...

# “Counting” Bag of Words

The more times a word occurs, the more meaning it contributes to the document

A document with many occurrences of “good”, “awesome”, “best” is more **positive** than one in which they occur only once.

$$\begin{array}{lcl} d_1 & = & \begin{bmatrix} 0 & 1 & 0 & 0 & 2 & 0 & 1 & 3 & 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix} \\ d_2 & = & \begin{bmatrix} 2 & 3 & 5 & 0 & 0 & 0 & 0 & 4 & 0 & 0 & 0 & 4 & 2 \end{bmatrix} \end{array}$$

 Let us see the difference. . .

Already a useful representation to diverse tasks, such as detecting **spam** and computing “**sentiment**”

# *tf*: Term Frequency

The number of times a word occurs in a document

# *tf*: Term Frequency

The number of times a word occurs in a document

(In general!) the times a word occurs depends on the length of the document.

- Shorter document → lower frequencies
- Longer document → higher frequencies



# *tf*: Term Frequency

The number of times a word occurs in a document

(In general!) the times a word occurs depends on the length of the document.

- Shorter document  $\rightarrow$  lower frequencies
- Longer document  $\rightarrow$  higher frequencies

Ideally, our counting should be document-length independent.

# *tf*: Term Frequency

The number of times a word occurs in a document

(In general!) the times a word occurs depends on the length of the document.

- Shorter document  $\rightarrow$  lower frequencies
- Longer document  $\rightarrow$  higher frequencies

Ideally, our counting should be document-length independent.

## **Normalisation!**

# *tf*: Term Frequency (Normalised)

Why should we normalise?

$d_1$  contains word dog 3 times

$d_2$  contains word dog 100 times

dog is way more important for  $d_2$  than for  $d_1$ , right?

# *tf*: Term Frequency (Normalised)

Why should we normalise?

$d_1$  contains word dog 3 times

$d_2$  contains word dog 100 times

dog is way more important for  $d_2$  than for  $d_1$ , right?

$d_1$  is an email by a veterinarian (30 words)

$d_2$  is *War & Peace* (580,000 words!)

# *tf*: Term Frequency (Normalised)

Why should we normalise?

$d_1$  contains word dog 3 times

$d_2$  contains word dog 100 times

dog is way more important for  $d_2$  than for  $d_1$ , right?

$d_1$  is an email by a veterinarian (30 words)

$d_2$  is *War & Peace* (580,000 words!)

$$tf(\text{dog}, d_1) = 3/30 = 0.1$$

$$tf(\text{dog}, d_2) = 100/580000 = 0.00017$$

# *tf*: Term Frequency (Normalised)

Why should we normalise?

$d_1$  contains word dog 3 times

$d_2$  contains word dog 100 times

dog is way more important for  $d_2$  than for  $d_1$ , right?

$d_1$  is an email by a veterinarian (30 words)

$d_2$  is *War & Peace* (580,000 words!)

$$tf(\text{dog}, d_1) = 3/30 = 0.1$$

$$tf(\text{dog}, d_2) = 100/580000 = 0.00017$$

**Remember:** normalised frequencies are indeed probabilities

# *tf*: Term Frequency (Normalised)

Playing with a longer text

[https://en.wikipedia.org/wiki/Coronavirus\\_disease\\_2019](https://en.wikipedia.org/wiki/Coronavirus_disease_2019)

Coronavirus disease 2019 (COVID-19) is an infectious disease caused by severe acute respiratory syndrome coronavirus 2 (SARS coronavirus 2, or SARS-CoV-2), a virus closely related to the SARS virus. The disease was discovered and named during the 2019{20 coronavirus outbreak. Those affected may develop a fever, dry cough, fatigue, and shortness of breath. A sore throat, runny nose or sneezing is less common. While the majority of cases result in mild symptoms, some can progress to pneumonia and multi-organ failure.  
[...]

**Note.** The examples use NLTK. Nowadays, there are better tools. For instance, parsing with **spaCy** is faster and more accurate

# *tf*: Term Frequency (Normalised)

Playing with a longer text

- Loading frequencies into a dictionary
- Vectorising frequencies
- Normalising frequencies



# *tf*: Term Frequency

From a single to multiple documents

- The vectors have to be comparable across documents → **normalisation**

See [https://en.wikipedia.org/wiki/Sparse\\_matrix](https://en.wikipedia.org/wiki/Sparse_matrix)

# *tf*: Term Frequency

From a single to multiple documents

- The vectors have to be comparable across documents → **normalisation**
- Each value in the vectors must represent **the same word**

See [https://en.wikipedia.org/wiki/Sparse\\_matrix](https://en.wikipedia.org/wiki/Sparse_matrix)

# *tf*: Term Frequency

From a single to multiple documents

- The vectors have to be comparable across documents → **normalisation**
- Each value in the vectors must represent **the same word**

This is when representations become sparse: many values become 0

Sparse vector most of the elements are **zero**

Dense vector most of the elements are **nonzero**

See [https://en.wikipedia.org/wiki/Sparse\\_matrix](https://en.wikipedia.org/wiki/Sparse_matrix)

# *tf*: Term Frequency


From a single to multiple documents

- The vectors have to be comparable across documents → **normalisation**
- Each value in the vectors must represent **the same word**

This is when representations become sparse: many values become 0

Sparse vector most of the elements are **zero**

Dense vector most of the elements are **nonzero**

 Let us see

See [https://en.wikipedia.org/wiki/Sparse\\_matrix](https://en.wikipedia.org/wiki/Sparse_matrix)

# Vectors of Term Frequency

## Vectors

- Primary building blocks of linear algebra
- Ordered list of numbers, or coordinates, in a vector space

# Vectors of Term Frequency

## Vectors

- Primary building blocks of linear algebra
- Ordered list of numbers, or coordinates, in a vector space
- They describe a location or position in that space. . .
- or identify a particular direction/magnitude/distance in that space

# Vectors of Term Frequency

## Vectors

- Primary building blocks of linear algebra
- Ordered list of numbers, or coordinates, in a vector space
- They describe a location or position in that space. . .
- or identify a particular direction/magnitude/distance in that space

**A space** is the collection of all possible vectors that could appear in that space

$[1, 4] \rightarrow$  2D vector space

$[1, 4, 9] \rightarrow$  3D vector space

# Vectors of Term Frequency

## Vectors

- Primary building blocks of linear algebra
- Ordered list of numbers, or coordinates, in a vector space
- They describe a location or position in that space. . .
- or identify a particular direction/magnitude/distance in that space

**A space** is the collection of all possible vectors that could appear in that space

$[1, 4] \rightarrow$  2D vector space

$[1, 4, 9] \rightarrow$  3D vector space

We have a 18D vectors space (we have seen 1kD and bigger ones!)



# Comparing Vectors


Cosine similarity

The cosine of the angle between two vectors ( $\theta$  theta)

# Comparing Vectors

Cosine similarity


The cosine of the angle between two vectors ( $\theta$  theta)



# Comparing Vectors

Cosine similarity

The cosine of the angle between two vectors ( $\theta$  theta)




$$\cos \theta = \frac{A \cdot B}{|A||B|} \quad (1)$$

# Comparing Vectors

Cosine similarity

The cosine of the angle between two vectors ( $\theta$  theta)



$$\cos \theta = \frac{A \cdot B}{|A||B|} \quad (1)$$


where

$A \cdot B$  is the **dot product** (we know it!)

# Comparing Vectors

Cosine similarity

The cosine of the angle between two vectors ( $\theta$  theta)




$$\cos \theta = \frac{A \cdot B}{|A||B|} \quad (1)$$

where

$A \cdot B$  is the **dot product** (we know it!)

$|A|$  is the **magnitude** of vector  $A$

 Let us see an implementation (but there are efficient libraries to do it)

# Comparing Vectors

## Cosine similarity

### Properties of the cosine similarity

- It is ranged in  $[-1, 1]$
- This is a very convenient range for ML

# Comparing Vectors

## Cosine similarity

### Properties of the cosine similarity

- It is ranged in  $[-1, 1]$
- This is a very convenient range for ML
- $\cos = 1$  represents identical normalized vectors that point in exactly the same direction

# Comparing Vectors

## Cosine similarity

### Properties of the cosine similarity

- It is ranged in  $[-1, 1]$
- This is a very convenient range for ML
- $\cos = 1$  represents identical normalized vectors that point in exactly the same direction
- $\cos = 0$  represents two vectors that share no components (they are perpendicular in all dimensions) the closer the two vectors are in angle



# Comparing Vectors

## Cosine similarity

### Properties of the cosine similarity

- It is ranged in  $[-1, 1]$
- This is a very convenient range for ML
- $\cos = 1$  represents identical normalized vectors that point in exactly the same direction
- $\cos = 0$  represents two vectors that share no components (they are perpendicular in all dimensions) the closer the two vectors are in angle
- In NLP, at least for *tf*-like representation, it is ranged in  $[0, 1]$  (frequencies are not negative)

# Comparing Vectors

## Cosine similarity

### Properties of the cosine similarity

- It is ranged in  $[-1, 1]$
- This is a very convenient range for ML
- $\cos = 1$  represents identical normalized vectors that point in exactly the same direction
- $\cos = 0$  represents two vectors that share no components (they are perpendicular in all dimensions) the closer the two vectors are in angle
- In NLP, at least for *tf*-like representation, it is ranged in  $[0, 1]$  (frequencies are not negative)

# Zipf's Law

# Zipf's Law

Given some corpus of natural language utterances, the frequency of any word is inversely proportional to its rank in the frequency table.<sup>1</sup>

---

<sup>1</sup>George K. Zipf; 1930s

# Zipf's Law

Given some corpus of natural language utterances, the frequency of any word is inversely proportional to its rank in the frequency table.<sup>1</sup>

$$\frac{pos(w)}{freq(w)}$$

---

<sup>1</sup>George K. Zipf; 1930s

# Zipf's Law

Given some corpus of natural language utterances, the frequency of any word is inversely proportional to its rank in the frequency table.<sup>1</sup>

$$\frac{\textit{pos}(w)}{1\text{st}} \propto \frac{\textit{freq}(w)}{k}$$

---

<sup>1</sup>George K. Zipf; 1930s

# Zipf's Law

Given some corpus of natural language utterances, the frequency of any word is inversely proportional to its rank in the frequency table.<sup>1</sup>

$pos(w)$	$freq(w)$
1st	$k$
2nd	$k/2$

---

<sup>1</sup>George K. Zipf; 1930s

# Zipf's Law

Given some corpus of natural language utterances, the frequency of any word is inversely proportional to its rank in the frequency table.<sup>1</sup>

$pos(w)$	$freq(w)$
1st	$k$
2nd	$k/2$
3rd	$k/3$
...	...

---

<sup>1</sup>George K. Zipf; 1930s



# Zipf's Law

Given some corpus of natural language utterances, the frequency of any word is inversely proportional to its rank in the frequency table.<sup>1</sup>

$pos(w)$	$freq(w)$
1st	$k$
2nd	$k/2$
3rd	$k/3$
...	...

The system behaves **“roughly” exponentially**

---

<sup>1</sup>George K. Zipf; 1930s

# Zipf's Law

Given some corpus of natural language utterances, the frequency of any word is inversely proportional to its rank in the frequency table.<sup>1</sup>

$pos(w)$	$freq(w)$
1st	$k$
2nd	$k/2$
3rd	$k/3$
...	...

The system behaves **“roughly” exponentially**

**Examples** population dynamics, economic output

---

<sup>1</sup>George K. Zipf; 1930s

# Zipf's Law

Given some corpus of natural language utterances, the frequency of any word is inversely proportional to its rank in the frequency table.<sup>1</sup>

$pos(w)$	$freq(w)$
1st	$k$
2nd	$k/2$
3rd	$k/3$
...	...

The system behaves **“roughly” exponentially**

**Examples** population dynamics, economic output and **COVID-19**

---

<sup>1</sup>George K. Zipf; 1930s


# Zipf's Law

Given some corpus of natural language utterances, the frequency of any word is inversely proportional to its rank in the frequency table.<sup>1</sup>

$pos(w)$	$freq(w)$
1st	$k$
2nd	$k/2$
3rd	$k/3$
...	...

The system behaves **“roughly” exponentially**

**Examples** population dynamics, economic output and **COVID-19**

 Let's see this in words

---

<sup>1</sup>George K. Zipf; 1930s

# Zipf's Law

Frequencies of the Brown corpus

$w$	$f_{exp}(w)$	$f_{act}(w)$
the	–	69,971
of	34,985	36,412
and	23,323	28,853
to	17,492	26,158
a	13,994	23,195
in	11,661	21,337
that	9,995	10,594
is	8,746	10,109
was	7,774	9,815
he	6,997	9,548
for	6,361	9,489
it	5,830	8,760
with	5,382	7,289
as	4,997	7,253
his	4,664	6,996



# Zipf's Law

## Stats

- This distribution only holds with large volumes of data (not in a sentence, not in a couple of texts)

# Zipf's Law

## Stats

- This distribution only holds with large volumes of data (not in a sentence, not in a couple of texts)
- By computing this distribution, we can obtain an a priori likelihood that a word  $w$  will appear in a document of the corpus

# Inverse Document Frequency



# *idf*–Inverse Document Frequency

There are two ways to count tokens

- Per document (*tf*)

# *idf*–Inverse Document Frequency


There are two ways to count tokens

- Per document (*tf*)
- Across the entire corpus: *idf*

# *idf*–Inverse Document Frequency

There are two ways to count tokens


- Per document (*tf*)
- Across the entire corpus: *idf*

 Let's see. . .

# *idf*–Inverse Document Frequency

There are two ways to count tokens

- Per document (*tf*)
- Across the entire corpus: *idf*


 Let's see...

**IDF** How strange is it that this token is in this document?

# *idf*–Inverse Document Frequency

There are two ways to count tokens

- Per document (*tf*)
- Across the entire corpus: *idf*

 Let's see...


**IDF** How strange is it that this token is in this document?

If  $w$  appears in  $d$  a lot of, but rarely un any  $d' \in D \mid d' \neq d$   
 $w$  is quite important for  $d$ !

# *idf*–Inverse Document Frequency


There are two ways to count tokens

- Per document (*tf*)
- Across the entire corpus: *idf*

 Let's see...

**IDF** How strange is it that this token is in this document?

If  $w$  appears in  $d$  a lot of, but rarely un any  $d' \in D \mid d' \neq d$   
 $w$  is quite important for  $d$ !

 Let's see

# IDF and Zipf

Let us assume a corpus  $D$ , such that  $|D| = 1M$

- 1 document  $d \in D$  contains “cat”  
 $\text{idf}(\text{cat}) = 1,000,000 / 1 = 1,000,000$

# IDF and Zipf

Let us assume a corpus  $D$ , such that  $|D| = 1M$

- 1 document  $d \in D$  contains “cat”  
 $\text{idf}(\text{cat}) = 1,000,000 / 1 = 1,000,000$
- 10 document  $\{d_1, d_2, \dots, d_{10}\} \in D$  contain “dog”  
 $\text{idf}(\text{dog}) = 1,000,000 / 10 = 100,000$



# IDF and Zipf

Let us assume a corpus  $D$ , such that  $|D| = 1M$

- 1 document  $d \in D$  contains “cat”  
 $\text{idf}(\text{cat}) = 1,000,000 / 1 = 1,000,000$
- 10 document  $\{d_1, d_2, \dots, d_{10}\} \in D$  contain “dog”  
 $\text{idf}(\text{dog}) = 1,000,000 / 10 = 100,000$

According to Zipf’s Law, when comparing  $w_1$  and  $w_2$ , even if  $f(w_1) \sim f(w_2)$ , one will be **exponentially higher** than the other one!

# IDF and Zipf

Let us assume a corpus  $D$ , such that  $|D| = 1M$

- 1 document  $d \in D$  contains “cat”  
 $\text{idf}(\text{cat}) = 1,000,000 / 1 = 1,000,000$
- 10 document  $\{d_1, d_2, \dots, d_{10}\} \in D$  contain “dog”  
 $\text{idf}(\text{dog}) = 1,000,000 / 10 = 100,000$

According to Zipf’s Law, when comparing  $w_1$  and  $w_2$ , even if  $f(w_1) \sim f(w_2)$ , one will be **exponentially higher** than the other one!

We need the inverse of  $\exp()$  to mild the effect:  $\log()$

# IDF and Zipf

Let us assume a corpus  $D$ , such that  $|D| = 1M$

- 1 document  $d \in D$  contains “cat”  
 $\text{idf}(\text{cat}) = 1,000,000 / 1 = 1,000,000$
- 10 document  $\{d_1, d_2, \dots, d_{10}\} \in D$  contain “dog”  
 $\text{idf}(\text{dog}) = 1,000,000 / 10 = 100,000$

According to Zipf’s Law, when comparing  $w_1$  and  $w_2$ , even if  $f(w_1) \sim f(w_2)$ , one will be **exponentially higher** than the other one!

We need the inverse of  $\exp()$  to mild the effect:  $\log()$

$$\text{idf} = \log(1,000,000/1) = 6$$

$$\text{idf} = \log(1,000,000/10) = 5$$

*tf-idf*

$$tf(t, d) = \frac{count(t)}{count(d)} \quad (2)$$

## *tf-idf*

$$tf(t, d) = \frac{count(t)}{count(d)} \quad (2)$$

$$idf(t, D) = \log \frac{\text{number of documents}}{\text{number of documents containing } t} \quad (3)$$

## *tf-idf*

$$tf(t, d) = \frac{count(t)}{count(d)} \quad (2)$$

$$idf(t, D) = \log \frac{\text{number of documents}}{\text{number of documents containing } t} \quad (3)$$

$$tfidf(t, d, D) = tf(t, d) * idf(t, D) \quad (4)$$

## *tf-idf*

$$tf(t, d) = \frac{count(t)}{count(d)} \quad (2)$$

$$idf(t, D) = \log \frac{\text{number of documents}}{\text{number of documents containing } t} \quad (3)$$

$$tfidf(t, d, D) = tf(t, d) * idf(t, D) \quad (4)$$

- The more often  $t$  appears in  $d$ , the higher the TF (and hence the TF-IDF)

$$tf(t, d) = \frac{count(t)}{count(d)} \quad (2)$$

$$idf(t, D) = \log \frac{\text{number of documents}}{\text{number of documents containing } t} \quad (3)$$

$$tfidf(t, d, D) = tf(t, d) * idf(t, D) \quad (4)$$

- The more often  $t$  appears in  $d$ , the higher the TF (and hence the TF-IDF)
- The higher the number of documents containing  $t$ , the lower the IDF (and hence the TF-IDF)



**Outcome** The importance of a token in a specific document given its usage across the entire corpus.

*tf-idf*

**Outcome** The importance of a token in a specific document given its usage across the entire corpus.

"TF-IDF, is the humble foundation of a simple search engine" (Lane et al., 2019, p. 90)



Let's see

# Coming Next

- Towards “semantics”

# References

Lane, H., C. Howard, and H. Hapkem

2019. *Natural Language Processing in Action*. Shelter Island, NY:  
Manning Publication Co.