



ALMA MATER STUDIORUM
UNIVERSITÀ DI BOLOGNA
CAMPUS DI FORLÌ

91258 / B0385

Natural Language Processing

Lesson 11. “More than One” Neuron

Alberto Barrón-Cedeño
a.barron@unibo.it

13/11/2024

Previously

- The perceptron
- Intro to neural networks

Table of Contents

1. Backpropagation (brief)

2. Keras


3. Some Guidelines

Chapter 5 of Lane et al. (2019)

Backpropagation (brief)

Weight Updating

Learning in a “simple” perceptron¹ vs a fully-connected network





(Lane et al., 2019, p. 158, 168)

¹Remember: aka linear regression

Weight Updating


Learning in a “simple” perceptron¹ vs a fully-connected network



(Lane et al., 2019, p. 158, 168)


¹Remember: aka linear regression

Backpropagation (of the errors)



²Notice that the first W_{1j} should be W_{1i}


Backpropagation (of the errors)



- The error is computed on the output vector
- How much error did W_{1i} "contribute"?²

²Notice that the first W_{1j} should be W_{1i}

Backpropagation (of the errors)



- The error is computed on the output vector
- How much error did W_{1i} "contribute"?²
- "Path": $W_{1i} \rightarrow [W_{1j}, W_{2j}] \rightarrow output$

²Notice that the first W_{1j} should be W_{1i}

Backpropagation (of the errors)

A better activation function

Step function: $f(\vec{x}) = \begin{cases} 1 & \text{if } \sum_{i=0}^n x_i w_i > \text{threshold} \\ 0 & \text{otherwise} \end{cases}$

³The change of the output is not proportional to the change of the input. ▶

Backpropagation (of the errors)

A better activation function

Step function: $f(\vec{x}) = \begin{cases} 1 & \text{if } \sum_{i=0}^n x_i w_i > \text{threshold} \\ 0 & \text{otherwise} \end{cases}$

Sigmoid function: non-linear³ and continuously differentiable

$$S(x) = \frac{1}{1 + e^{-x}} \quad (1)$$

³The change of the output is not proportional to the change of the input. ▶

Backpropagation (of the errors)

A better activation function

Step function: $f(\vec{x}) = \begin{cases} 1 & \text{if } \sum_{i=0}^n x_i w_i > \text{threshold} \\ 0 & \text{otherwise} \end{cases}$

Sigmoid function: non-linear³ and continuously differentiable

$$S(x) = \frac{1}{1 + e^{-x}} \quad (1)$$

 Let us see

³The change of the output is not proportional to the change of the input. ▶

Backpropagation (of the errors)


A better activation function

Step function: $f(\vec{x}) = \begin{cases} 1 & \text{if } \sum_{i=0}^n x_i w_i > \text{threshold} \\ 0 & \text{otherwise} \end{cases}$

Sigmoid function: non-linear³ and continuously differentiable

$$S(x) = \frac{1}{1 + e^{-x}} \quad (1)$$

 Let us see



Non-linear → model non-linear relationships

Continuously differentiable → partial derivatives wrt various variables to
_____ update the weights

³The change of the output is not proportional to the change of the input. ▶

Backpropagation

Differentiating to adjust

Squared error⁴

$$SE = (y - f(x))^2 \quad (2)$$

⁴In (Lane et al., 2019, p. 171) they say this is MSE; but there is no mean

Backpropagation

Differentiating to adjust

Squared error⁴

$$SE = (y - f(x))^2 \quad (2)$$

Mean squared error

$$MSE = \frac{1}{n} \sum_{i=1}^n (y - f(x))^2 \quad (3)$$

⁴In (Lane et al., 2019, p. 171) they say this is MSE; but there is no mean

Backpropagation

Differentiating to adjust

Squared error⁴

$$SE = (y - f(x))^2 \quad (2)$$

Mean squared error

$$MSE = \frac{1}{n} \sum_{i=1}^n (y - f(x))^2 \quad (3)$$

Calculus chain rule

$$f(g(x))' = F'(x) = f'(g(x)) g'(x) \quad (4)$$

⁴In (Lane et al., 2019, p. 171) they say this is MSE; but there is no mean

Backpropagation

Differentiating to adjust

Squared error⁴

$$SE = (y - f(x))^2 \quad (2)$$

Mean squared error

$$MSE = \frac{1}{n} \sum_{i=1}^n (y - f(x))^2 \quad (3)$$

Calculus chain rule

$$f(g(x))' = F'(x) = f'(g(x)) g'(x) \quad (4)$$

With (4) we can find the derivative of the actfunct \forall unit wrt its input.

⁴In (Lane et al., 2019, p. 171) they say this is MSE; but there is no mean

Backpropagation

Differentiating to adjust

Squared error⁴

$$SE = (y - f(x))^2 \quad (2)$$

Mean squared error

$$MSE = \frac{1}{n} \sum_{i=1}^n (y - f(x))^2 \quad (3)$$

Calculus chain rule

$$f(g(x))' = F'(x) = f'(g(x)) g'(x) \quad (4)$$

With (4) we can find the derivative of the actfunct \forall unit wrt its input.


Plain words: find the contribution of a weight to the error and adjust it!

(no further math)

⁴In (Lane et al., 2019, p. 171) they say this is MSE; but there is no mean

Backpropagation (of the errors)

~Gradient descent: minimising the error




Convex error curve


(Lane et al., 2019, p. 173–174)

Backpropagation (of the errors)

~Gradient descent: minimising the error



Convex error curve



Non-convex error curve

(Lane et al., 2019, p. 173–174)

Addressing Local minima

Batch learning

- Aggregate the error for the batch
- Update the weight at the end

Addressing Local minima

Batch learning

- Aggregate the error for the batch
- Update the weight at the end
- → hard to find global minimum

Addressing Local minima

Batch learning

- Aggregate the error for the batch
- Update the weight at the end
- \rightarrow hard to find global minimum

Stochastic gradient descent

- Look at the error for each single instance
- Update the weights right away

Addressing Local minima

Batch learning

- Aggregate the error for the batch
- Update the weight at the end
- → hard to find global minimum

Stochastic gradient descent

- Look at the error for each single instance
- Update the weights right away
- → more likely to make it to the global minimum

Addressing Local minima

Batch learning

- Aggregate the error for the batch
- Update the weight at the end
- → hard to find global minimum

Stochastic gradient descent

- Look at the error for each single instance
- Update the weights right away
- → more likely to make it to the global minimum

Mini-batch

- Much smaller batch, combining the best of the two worlds
- → Fast as batch, resilient as stochastic gradient descent

Addressing Local minima

Batch learning

- Aggregate the error for the batch
- Update the weight at the end
- → hard to find global minimum

Stochastic gradient descent

- Look at the error for each single instance
- Update the weights right away
- → more likely to make it to the global minimum

Mini-batch

- Much smaller batch, combining the best of the two worlds
- → Fast as batch, resilient as stochastic gradient descent

Important parameter: learning rate α

A parameter to define at what extent should we “correct” the error

Keras

Some Popular Libraries

There are many high- and low-level libraries in multiple languages

- **PyTorch**

Community-driven; <https://pytorch.org/>

- **TensorFlow**

Google Brain; <https://www.tensorflow.org/>

- **Others**

Some Popular Libraries

There are many high- and low-level libraries in multiple languages

- **PyTorch**

Community-driven; <https://pytorch.org/>

- **TensorFlow**

Google Brain; <https://www.tensorflow.org/>

- **Others**

We will use **Keras**; <https://keras.io/>

What is Keras

- A high-level wrapper with an accessible API for Python

What is Keras

- A high-level wrapper with an accessible API for Python
- It gives access to three alternative backends
 - TensorFlow
 - CNTK (MS)

Keras

Logical exclusive OR (XOR) in Keras

input		output
0	0	0
0	1	1
1	0	1
1	1	0

1	●	●
0	●	●
	0	1

Keras

Logical exclusive OR (XOR) in Keras

input		output
0	0	0
0	1	1
1	0	1
1	1	0

1	●	●
0	●	●
	0	1

 Let us see

Keras

Logical exclusive OR (XOR) in Keras

input		output
0	0	0
0	1	1
1	0	1
1	1	0

1	●	●
0	●	●
	0	1

 Let us see

First dense layer

- 2 inputs, 10 units
- 30 parameters

Keras

Logical exclusive OR (XOR) in Keras

input		output
0	0	0
0	1	1
1	0	1
1	1	0

1	●	●
0	●	●
	0	1

 Let us see

First dense layer

- 2 inputs, 10 units
- 30 parameters
- $2 \times 10 \rightarrow 20$

Keras

Logical exclusive OR (XOR) in Keras

input		output
0	0	0
0	1	1
1	0	1
1	1	0

1	●	●
0	●	●
	0	1

 Let us see

First dense layer

- 2 inputs, 10 units
- 30 parameters
- $2 \times 10 \rightarrow 20$
- But we also have the bias! (10 more weights)

Keras

Logical exclusive OR (XOR) in Keras

input		output
0	0	0
0	1	1
1	0	1
1	1	0

1	●	●
0	●	●
	0	1

 Let us see

First dense layer

- 2 inputs, 10 units
- 30 parameters
- $2 \times 10 \rightarrow 20$
- But we also have the bias! (10 more weights)

Second dense layer

- 10 inputs, 1 unit
- 11 parameters

Keras

Logical exclusive OR (XOR) in Keras

input		output
0	0	0
0	1	1
1	0	1
1	1	0

1	●	●
0	●	●
	0	1

 Let us see

First dense layer

- 2 inputs, 10 units
- 30 parameters
- $2 \times 10 \rightarrow 20$
- But we also have the bias! (10 more weights)

Now we can compile the model

 Let us see

Second dense layer

- 10 inputs, 1 unit
- 11 parameters

Some Guidelines

Design Decisions

Activation functions

Sigmoid

ReLU Rectified linear unit (and variations)

tanh Hyperbolic tangent

Design Decisions

Activation functions

Sigmoid

ReLU Rectified linear unit (and variations)

tanh Hyperbolic tangent




Figure source: (Kandel and Castelli, 2020)

Design Decisions

Activation functions

- Sigmoid
- ReLU (rectified linear unit)
- tanh (hyperbolic tangent)

Learning rate

- Choosing one in advance
- Use **momentum** to perform dynamic adjustments

Design Decisions

Activation functions

- Sigmoid
- ReLU (rectified linear unit)
- tanh (hyperbolic tangent)

Learning rate

- Choosing one in advance
- Use **momentum** to perform dynamic adjustments

Dropout

- Ignore randomly-chosen weights in a training pass to prevent overfitting

Design Decisions

Activation functions

- Sigmoid
- ReLU (rectified linear unit)
- tanh (hyperbolic tangent)

Learning rate

- Choosing one in advance
- Use **momentum** to perform dynamic adjustments

Dropout

- Ignore randomly-chosen weights in a training pass to prevent overfitting

Regularisation

- Dampen a weight from growing/shrinking too far from the rest to prevent overfitting

Normalisation

Example House classification.

Input number of bedrooms, last selling price

Output Likelihood of selling

Vector `input_vec = [4, 12000]`

Normalisation

Example House classification.

Input number of bedrooms, last selling price

Output Likelihood of selling

Vector `input_vec = [4, 12000]`

All input dimensions should have comparable values

Ideally, all features should be in the range $[-1, 1]$ or $[0, 1]$

Normalisation

Example House classification.

Input number of bedrooms, last selling price

Output Likelihood of selling

Vector `input_vec = [4, 12000]`

All input dimensions should have comparable values

Ideally, all features should be in the range $[-1, 1]$ or $[0, 1]$

Typical normalisation: mean normalisation, feature scaling, coefficient of variation

Normalisation

Example House classification.

Input number of bedrooms, last selling price

Output Likelihood of selling

Vector `input_vec = [4, 12000]`

All input dimensions should have comparable values

Ideally, all features should be in the range $[-1, 1]$ or $[0, 1]$

Typical normalisation: mean normalisation, feature scaling, coefficient of variation

NLP typically uses TF-IDF, one-hot encoding, word2vec (already normalised)

References

Kandel, I. and M. Castelli

2020. Transfer learning with convolutional neural networks for diabetic retinopathy image classification. a review. *Applied Sciences*, 10(6).

Lane, H., C. Howard, and H. Hapkem

2019. *Natural Language Processing in Action*. Shelter Island, NY: Manning Publication Co.