

Page Layout for a₁bCorp Documents

Author

Andrew Lincoln Burrow
albcorp@internode.on.net

Abstract

The `AlbCorpLayout` package provides a single `alb-corp` L^AT_EX document class. The class implements a book design for a₁bCorp documents that is designed for the documentation of L^AT_EX packages. It sets up the page layout and section formatting. It also provides a command to capture the document title, commands and environments to typeset the title material, commands to typeset L^AT_EX commands, a collection of logo commands, and markup in the a₁b name space. All commands and environments are available through the AUCT_EX interface.

Copyright

Copyright © 2002–2006 Andrew Lincoln Burrow.

This program may be distributed and/or modified under the conditions of the L^AT_EX Project Public License, either version 1.3 of this license or (at your option) any later version.

The latest version of this license is in

<http://www.latex-project.org/lppl.txt>

and version 1.3 or later is part of all distributions of L^AT_EX version 2005/12/01 or later.

This work has the LPPL maintenance status ‘author-maintained’.

This work consists of the files

`alb-corp.cls` and `alb-corp-layout-documentation.tex`.

Version Information

Revision: 1.17

Date: 2006-06-23 06:33:00

1 Introduction

The `AlbCorpLayout` package is designed to assist in the documentation of \LaTeX packages. It consists of the document class `alb-corp`. This class is designed to achieve consistency and to provide guidance when writing documentation for *a₁b* packages. The fictional *a₁b* corporation is mnemonic for the naming conventions that prefix each identifier by `alb`. The `alb-corp` class extends this fiction to the presentation of documentation for packages written by the author.

The page layout provides a wide gutter margin for binding, and a narrow column close to the outer edge. Large floats access the inner gutter via the `albInflate` environment of the `AlbFloatTools` package.

Page numbers are placed in the running headers with the title and section information. In twoside mode, the left header contains the page number and the document title, while the right header contains the current section title and page number.

In addition to setting the document appearance, the class provides a single environment for creating a title page, an associated command for designating the title, another associated command for adding sections to the titlepage, simple commands for typesetting \LaTeX commands, and a collection of logo commands. The class is supported by an emacs lisp file customising \LaTeX to automate the insertion of these commands and environments.

2 Suggested Document Structure

The `alb-corp` document class places few restrictions on the document structure. It is primarily intended for articles. Documents must insert title information at the head of the document, since this information is used in the header.

2.1 Page Layout Options

The `alb-corp` document class attempts to respect page layout options. In particular, you can use `oneside`, `twoside`, `titlepage`, and `notitlepage` as global options. However, the page layout will not accomodate `twocolumn` or `reversemp`. The page layout accomodates `a4paper` and `letterpaper` page sizes.

Page layout options must be placed in the `documentclass` declaration, and each relevant option should be explicitly declared since the `AlbLaTeXDocumentTemplate` makefile parses document class options. The following content is a typical example of the document class declaration.

```
\documentclass[10pt,a4paper,twoside]{alb-journal}
```

3 Using the Commands and Environments

The commands and environments of the `alb-corp` class are divided into three groups. The first concerns the title page and title information. These commands should occur early in the document. The second group concerns the commands to typeset \LaTeX commands and environments. The third group provides additional logos that are likely to be referred to whilst documenting \LaTeX packages.

3.1 Title Material

Documents of the `alb-corp` class should begin with an `albTitle` command. This command accepts a single argument, which is the title of the article. The value is shared by the page headers as well as the title page.

Documents should follow the `albTitle` command with an `albTitlePage` environment. The contents of this environment should be sectioned by instances of the `albTitlePageSection` command, where each instance takes the name of the section as its argument, and is followed by the text of the section.

For example, a document might begin with the following \LaTeX code.

```
\albTitle{Example Title}

\begin{albTitlePage}
  \albTitlePageSection{Author}

  Andrew Lincoln Burrow\\
  \texttt{albcorp@internode.on.net}\\
  \albLogo{} Corp

  \albTitlePageSection{Abstract}

  This document is completely fictitious.
  If you are reading this, then you should stop now.
\end{albTitlePage}
```

3.2 Command Typesetting Commands

The next group of commands provided by the `alb-corp` class typeset \LaTeX commands. In particular, they provide a simple markup scheme for the parts of a \LaTeX command or environment invocation so that it can be documented.

`\albLtxCmd{cmd}` Typeset the \LaTeX command *cmd* with the preceding backslash. For example,

```
\albLtxCmd{albLogo}
```

produces `\albLogo`.

`\albLtxEnv{env}` Typeset the \LaTeX environment *env* with the `begin` command that would open the environment. For example,

```
\albLtxEnv{albTitlePage}
```

produces `\begin{albTitlePage}`

`\albLtxOpt{opt}` and `\albLtxArg{arg}` Typeset an optional argument *opt* or a mandatory argument *arg* supplied to a \LaTeX command or environment, and use the correct brackets. For example,

```
\albLtxCmd{rule}%
\albLtxOpt{lift}\albLtxArg{width}\albLtxArg{height}
```

produces `\rule[lift]{width}{height}`.

`\albLtxPrm{arg}` Typeset the formal parameter of an optional or mandatory argument without the brackets so that it can be used in the explanatory text. For example,

`\albLtxPrm{arg}`

produces *arg*.

3.3 Logo Commands

The remainder of the commands provided by the `alb-corp` class typeset logos.

`\PDFLaTeX` produces PDF_LA_TE_X.

`\AUCTeX` produces AUCT_EX.

`\RefTeX` produces Ref_TE_X.

`\albLogo` produces *a₁b*.

4 AUCT_EX Customisations

Under AUCT_EX the file `alb-corp.el` is automatically loaded whenever the `alb-corp` class is used. The customisation adds the symbols and environments to AUCT_EX. This provides the following simple prompting.

- Tab completion and argument prompting for the commands:
`albTitle`, `albTitlePageSection`, `albLtxCmd`, `albLtxEnv`, `albLtxOpt`,
`albLtxArg`, `albLtxPrm`, `PDFLaTeX`, `AUCTeX`, `RefTeX`, and `albLogo`.
- Tab completion for the environments:
`albTitlePage`.

The customisation is not context sensitive, and will not ensure that these commands and environments are used correctly.