

Typesetting Graph Theory Under L^AT_EX

Author

Andrew Lincoln Burrow
albcorp@gmail.com

Abstract

The `AlbGraphTheory` package provides a single `alb-graph-theory` L^AT_EX package provide markup for graph theory. It is designed to make the L^AT_EX input more readable, to allow the actual symbols to be adjusted from a single file, to enable the typesetting of graph theoretic constructions to be designed in the context of the entire suite of required markup commands, and to place the extended markup in the `alb` namespace. The package is supported by an emacs lisp file customising AUC_TE_X, which provides command name completion and argument prompting.

Copyright

Copyright © 2004–2006, 2013 Andrew Lincoln Burrow.

This program may be distributed and/or modified under the conditions of the L^AT_EX Project Public License, either version 1.3 of this license or (at your option) any later version.

The latest version of this license is in

<http://www.latex-project.org/lppl.txt>

and version 1.3 or later is part of all distributions of LaTeX version 2005/12/01 or later.

This work has the LPPL maintenance status ‘author-maintained’.

This work consists of the files

`alb-algorithms.sty`, `alb-avm.sty`, `alb-latex.cls`,
`alb-float-tools.sty`, `alb-graph-theory.sty`,
`alb-journal.cls`, `alb-order-theory.sty`,
`alb-proofs.sty`, `alb-theorems.sty`, `alb-thesis.cls`,
`alb-algorithms.tex`, `alb-avm.tex`, `alb-latex.tex`,
`alb-float-tools.tex`, `alb-graph-theory.tex`,
`alb-journal.tex`, `alb-order-theory.tex`,
`alb-proofs.tex`, `alb-theorems.tex`, `alb-thesis.tex`.
`alb-journal-glossary.ist`, `alb-journal-index.ist`,
`alb-thesis-glossary.ist`, and `alb-thesis-index.ist`.

Version Information

Revision

Date

1 Introduction

The `alb-graph-theory` \LaTeX package is designed to typeset graph theory. In practice, this means that it supplies a large collection of simple math commands. The main benefit is consistency, and the ability to easily change a decision about typesetting for all documents.

2 Using the Commands and Environments

The commands and environments of the `alb-order-theory` \LaTeX package are all used within math mode. They accept arguments and generate graph theory mathematical constructions.

<code>\albHead{e}</code>	$\text{head}(e)$
<code>\albTail{e}</code>	$\text{tail}(e)$
<code>\albDistance{u}{v}</code>	$\text{distance}(u, v)$
<code>\albDistanceIn{G}{u}{v}</code>	$\text{distance}_G(u, v)$

3 $\text{AUCT}_{\text{E}}\text{X}$ Customisations

Under $\text{AUCT}_{\text{E}}\text{X}$ the file `alb-graph-theory.el` is automatically loaded whenever the `alb-graph-theory` package is used. The customisation adds the math commands to $\text{AUCT}_{\text{E}}\text{X}$. This provides the simple prompting for all the supplied math commands.

It may be worthwhile also loading the `alb-order-theory` package because `alb-order-theory.el` causes a special equation number counter to be stored as a local variable. `alb-LaTeX-equation-counter` counts numbers assigned to labels for equations. This ensures dirty numbers are not reissued, as reissuing a number could make stale references hard to detect.