

The Alberta Buck - Printable Receipt (v1.0)

A Plain-Text, Independently Re-Verifiable Record of an Identity-Bound BUCK Payment

Perry Kundert

2026-05-29



The cryptography of the Alberta Buck identity layer names an *identity point* $M \in \mathbb{G}_1$ and binds a transaction; the artifact a human actually holds is a *receipt*. This document specifies that receipt: a plain-text slip, sized for an 80mm thermal printer, that prints the plain-text Identity of both parties and the transaction details, and embeds – as a wrapped text payload – everything required to re-verify the payment by re-scanning the slip and re-running the wallet’s verifiers. The receipt closes two gaps the on-chain proofs leave open: it carries each party’s **canonical_identity_data** so a point M resolves to a human name (verified by recomputing $M = \text{keccak}(\text{data}) \cdot G$), and it states which on-chain facts (registry records, the **Transfer** / **SpentCoupled*** event) anchor the proof. Verification is two-tier: *offline*, re-running the proof algebra and the point→human bridge from the embedded payload alone; and *chain-anchored*, confirming the embedded records against a node. Five receipt kinds are specified – an EOA transfer from a public or a private counterparty, and the B1, A1, and A2 Note flavors. The Note kinds are producible by *either* party – the depositor’s copy or the issuer’s "I paid X" copy – because the Identity-M note payload (the **idHash** preimage material: the addressed ciphertexts and issuer-signature words) is held by both, and the receipt’s disclosed identity preimages let any verifier derive the identity scalars and re-check it deterministically. The remaining proofs are the primitives already shipped (the approve handshake + **verifiable_decrypt** for EOA, the batch Schnorr for public issuers, and for the private-issuer A2 case the recipient-blinded **verifyIssuerReenc** binding the mint verified on chain). (Decryptability, Identity)

Contents

1	What a Receipt Is (and Is Not)	3
2	Two Gaps the Proofs Leave to the Receipt	3
2.1	The point -> human bridge	3
2.2	The trust anchor	3
3	The Two-Tier Verification Model	3
4	The AB-RCPT/1 Envelope	4
5	Per-Scenario Payloads	5
5.1	coa-pub – EOA transfer from a public counterparty	5
5.2	coa-priv – EOA transfer from a private counterparty	5
5.3	note-b1 / note-a1 – Note from a public issuer	5
5.4	note-a2 – Note from a private issuer	6
5.5	Why there is no "B2" (private-issuer bearer) receipt	6
6	The Physical Artifact (ESC/POS, 80mm, 203dpi, 576px)	6
7	Verification Procedure	7
8	Wallet UX and Storage	8
9	The Whole Flow, Executed: Live EVM, Real Proofs, Both Receipts	8
9.1	Boot: a chain whose id the proofs demand	9
9.2	The A2 world: a private issuer pays an addressed recipient	9
9.3	Deploy the real stack; bind the Identities (Merkle updates on the EVM)	10
9.4	Fund, and the identity-bound approve (the real CP handshake)	10
9.5	Mint (the issuer's act)	10
9.6	Transmission verification (the recipient's act, offline)	11
9.7	Deposit (the recipient's act, on chain)	11
9.8	The two receipts, side by side	11
9.9	Tier-2: anchoring both slips to the live chain	12
9.10	All three flavors: the cost of each step	13
9.11	Shutdown	13
10	Security Considerations	13
11	Phasing	14
12	Open Questions	15

1 What a Receipt Is (and Is Not)

A BUCK receipt is a **record of a completed payment**, generated by a party to that payment and printable on a commodity thermal printer. For an EOA transfer the generator is the *recipient*; for a Note it is **either** party – the depositor prints their copy, the issuer prints the payer-side "I paid X" copy – since the Identity-M note payload travels to both at mint/spend. The receipt's **role** field records which side produced it, and the renderer marks that party "- you". It is the bilateral-disclosure half of the system's privacy promise made tangible: bulk chain-analytics cannot reconstruct who paid whom, but either party to a payment can produce a slip that names the counterparty in the clear and proves it.

- **It IS:** human-readable; names both parties' plain-text Identity (a display subset on paper, the full KYC datum in the payload); states amount, kind, time, and on-chain references; self-verifying from its own text payload; and extensible with optional informational line items.
- **It is NOT:** a bearer instrument (it redeems nothing – the value already moved, and any Note nullifier it references is already spent); a chain explorer; or a re-derivation of the KYC binding of M to a legal person (that rests on the issuer's Pointcheval-Sanders credential, assumed here). The optional line items are **not** covered by verification.

2 Two Gaps the Proofs Leave to the Receipt

2.1 The point -> human bridge

Every shipped proof names an identity *point* M . A receipt must name a *person*. The link is the preimage:

Definition 1. A party's Identity datum is the canonical JSON *canonical_identity_data* (the KYC fields, sorted-key, no-whitespace – Identity Example). Its identity scalar is $m = \text{keccak}(\text{canonical}) \bmod \text{ORDER}$ and its identity point is $M = m \cdot G$.

The receipt therefore carries each party's *canonical_identity_data*, and a verifier recomputes $\text{keccak}(\text{data}) \cdot G$ and checks it equals the named M . That single check turns a curve point into "Alice Johnson, Alberta Identity Card, Alberta, Canada."

Requirement (data availability). The generating wallet must *hold* the counterparty's *canonical_identity_data*. For a **public** identity it is published (off-chain attestation). For a **private** identity it is disclosed bilaterally when the parties approve one another (or when a Note is delivered) – the same exchange that lets each verify $M = \text{keccak}(\cdot) \cdot G$ against the credential they can decrypt. A wallet that never received the preimage can still print the *point* and the issuer reference, but not the human name (see *Open Questions*).

2.2 The trust anchor

Offline math proves the receipt is *internally* sound; it cannot prove the embedded keys and events are the *real* on-chain ones. That is a chain read. Hence two tiers, both specified below.

3 The Two-Tier Verification Model

Tier	Needs	Confirms
1 – offline	the slip's text payload only	the proof algebra verifies; both M recompute from their <i>canonical_identity_data</i> ; for Notes the
2 – anchored	tier 1 + an RPC node	the embedded <code>pk / E_addr / isPublicIdentity</code> equal the registry's for each named address; the T

Tier 1 says *"these proofs are valid and name these humans"*; tier 2 says *"and those identities and that payment are the genuine on-chain ones."* Together they are the non-deniable receipt of *Decryptability*. Per the design decision, the payload is **offline-complete**: every value tier 1 needs is embedded, and tier 2's references ride alongside so anchoring is optional, not required, to read a receipt.

Property 2. (Receipt soundness.) *If tier 1 passes, the slip's proofs are valid for the embedded public inputs and each named M is the hash of the printed Identity datum. If tier 2 also passes, those inputs are the on-chain registry records and the payment is a mined event. No party can forge a passing slip naming a counterparty who did not transact (proof unforgeability + event immutability); a generator may decline to print a receipt, but cannot print a false one.*

4 The AB-RCPT/1 Envelope

The verified **core** is a deterministic map, serialized canonically (CBOR), and printed as **AB-RCPT/1**. followed by base64url of the bytes, wrapped to the print width. (Text-only by decision – no QR; the payload is literally plain-text, re-typable and OCR-able, and survives a scanner-less verifier.) The receipt id is `base32(sha256(core))` truncated to a short handle. The optional line items live *outside* the core (they are unverified) and are printed in their own section, never in the payload.

Shown as JSON for readability (the wire form is CBOR):

```
{
  "v": 1,
  "type": "eoa-pub" | "eoa-priv" | "note-b1" | "note-a1" | "note-a2",
  "role": "recipient" | "issuer",    // who generated it ("issuer": Note kinds only)
  "chainid": 1,
  "contracts": { "registry": "0x..", "buck": "0x..", "notes": "0x.." },
  "payer": Party,                    // funds FROM (for a Note: the issuer)
  "payee": Party,                    // funds TO (the recipient / depositor)
  "txn": Txn,
  "note": NotePayload,               // Note kinds: the Identity-M idHash preimage
  "proof": Proof,                    // type-specific (below)
  // role-dependent self-naming / counterparty-naming vd records:
  "payee_vd": Vd,                     // role=recipient: payee's own E_addr -> payee.M
  "payer_vd": Vd,                     // role=issuer, private payer (A2): own E_addr -> payer.M
  "vd_payee": Vd                      // role=issuer, B1: eDepForIss -> payee.M
}

Party {
  "addr": "0x..",
  "kind": "public" | "private",
  "identity": "<canonical_identity_data>", // preimage; keccak->m, M=m*G
  "M": ["0x..", "0x.."],                 // named identity point
  "pk": ["0x..", "0x.."],                 // registered_pk (tier-2 anchor)
  "E_addr": { "R":["..", ".."], "C":["..", ".."] } // registered ct (private; tier-2)
}

Txn {
  "kind": "eoa-transfer" | "note-spend",
  "value": 250000000,                     // BUCK base units (6 dp)
  "timestamp": 1779999011,                 // block time
  "event": "Transfer" | "SpentCoupledB1" | "SpentCoupledA1" | "SpentCoupledA2",
  "txhash": "0x..", "block": 1234567, "logindex": 3,
  // note-spend adds:
  "mint_txhash": "0x..", "mint_block": 1234500, "nullifier": "0x.."
}

NotePayload {
  // per flavor -- the idHash preimage material
  // B1: "sigma_R", "sigma_s"              (id_hash_b1(m_iss, sigma))
  //      + "eDepForIss"                  (the SpentCoupledB1 event ct)
```

```

// A1:  "eNote", "eRec", "sigma_R", "sigma_s"
//                                     (id_hash_a1(eNote, m_iss, sigma))
// A2:  "eNote", "eIss"                (id_hash_a2(eNote, eIss))
}

```

proof is the witness the matching verifier consumes (the approve handshake for eoa-priv; the note opening + minted **cms**[] + the public issuer's batch Schnorr + nullifier/face for the Note kinds; an A2 receipt additionally carries the mint's **issuer_reenc** binding). The vd records carry the generating side's self-naming – a **verifiable_decrypt** of one's *own* registered **E_addr** revealing one's **M** – and, for the issuer-side B1 receipt, the issuer's verifiable decryption of the event's **eDepForIss** naming the depositor. The Note legs themselves need **no** party proof: the disclosed identity preimages let any verifier derive **m_iss** / **m_rec**, recompute the **idHash**, and decrypt the addressed ciphertexts directly – which is exactly why both parties can generate the same receipt core.

5 Per-Scenario Payloads

For the EOA kinds the wallet owner is the **payee**; a Note receipt is generated from **either** side (the **role** field). Each row names the tier-1 re-check. All Note flavors use the unified spend nullifier Poseidon(ρ , **idHash**, 4242) (the shipped **spend.circom** tag) and anchor at the **Minted** and **SpentCoupled*** events.

type	payer	party-naming (tier-1 re-check)
eo-pub	EOA, public	none – payer.M recomputed from public identity ; pk anchors addr
eo-priv	EOA, private	approve handshake cp_proof + payee's vd of E_for_spender
note-b1	issuer, public	idHash = id_hash_b1 (m_iss , sigma) + batch Schnorr; issuer side: vd of eDepForIss names depositor
note-a1	issuer, public	idHash = id_hash_a1 (eNote , m_iss , sigma) + Schnorr; Dec (eNote , m_rec) = vG , Dec (eRec , m_rec) = M_rec
note-a2	issuer, private	idHash = id_hash_a2 (eNote , eIss); Dec (eNote , m_rec) = vG , Dec (eIss , m_rec) = M_iss ; issuer_reenc binding

5.1 eoa-pub – EOA transfer from a public counterparty

Lightest: the payer's **identity** is public, so **payer.M** is recomputed from it and no payer proof is needed; the payer **pk** ties the **Transfer.from** address to that public record (tier 2). Payload = payer Party (public) + payee Party + payee **vd_proof** + the **Transfer** anchor.

5.2 eoa-priv – EOA transfer from a private counterparty

The **ApproveReceipt** half: at approve time the payer re-encrypted their **M** for the payee (**E_for_spender**) and proved it (**cp_proof** = **verifyApprove**); the payee verifiably decrypts it to **payer.M** (**vd_proof**). Payload = both Parties (private) + **ApproveReceipt** proofs + payee self **vd_proof** + **Transfer** anchor + registry **pk** / **E_addr** for both (tier 2).

5.3 note-b1 / note-a1 – Note from a public issuer

The four-link chain, now Identity-M-bound: the opening recomputes **cm**, **cm** is in the mint **cms**[], the issuer is bound *into the leaf itself* (the verifier derives **m_iss** from the disclosed issuer preimage and requires **opening.idHash** to recompute as **id_hash_b1**(**m_iss**, **sigma**) / **id_hash_a1**(**eNote**, **m_iss**, **sigma**)) as well as over the batch (the Schnorr, whose Fiat-Shamir transcript folds in the issuer *account* + chainid – so the printed **acct** is provably the mint's **msg.sender**, the account whose BUCK funded the note), and the nullifier was burned in the **SpentCoupledB1** / **SpentCoupledA1** event paying the payee.

The payee leg differs by flavor. **A1** is addressed: **eNote** encrypts the face under the recipient identity point and **eRec** the recipient identity under itself, so $\text{Dec}(e\text{Note}, m_{\text{rec}}) = vG$ and $\text{Dec}(e\text{Rec}, m_{\text{rec}}) = M_{\text{rec}}$ bind the named recipient into the leaf – deterministically, from the disclosed preimage; only the addressed identity satisfies the **eNote** relation (the face-pinning principle). **B1** is bearer: the depositor is named at spend – the **SpentCoupledB1** event publishes **eDepForIss**, the depositor’s Identity re-encrypted under the public issuer’s registered key (proven well-formed on chain by **verifyDepositorBinding**) – so the *issuer-side* receipt names the depositor by verifiably decrypting it (**vd_payee**), while the *recipient-side* receipt self-names via **payee_vd** as usual.

5.4 note-a2 – Note from a private issuer

The hard case: both parties are encrypted-Identity. Identity-M targeting makes it symmetric and proof-free on the note legs: the issuer encrypted the face under the recipient identity point (**eNote**) and their *own* registered Identity under the same point (**eIss**), and **opening.idHash = id_hash_a2(eNote, eIss)** commits both. The verifier derives m_{rec} from the disclosed payee preimage and checks $\text{Dec}(e\text{Note}, m_{\text{rec}}) = vG$ and $\text{Dec}(e\text{Iss}, m_{\text{rec}}) = M_{\text{named}} = \text{payer.M}$ – the second equation *is* the coupling: it algebraically forces **eIss**’s key to be M_{rec} , so the note was addressed to the payee. Anti-framing – that **eIss** re-encrypts the issuer’s *registered* credential, so the recovered Identity is the true minter, never a victim – is the **issuer_reenc binding** the issuer shipped at mint, verified on chain by the A2 mint overload (**IdentityRegistry.verifyIssuerReenc** + the per-leaf **eIss** leaf-tie) and re-verified offline here; its transcript folds in the issuer account + chainid, anchoring the printed **acct** to the mint’s **msg.sender**.

Payload = both Parties (private) + the note payload (**eNote**, **eIss**) + the **issuer_reenc** binding + the generator’s self-naming (**payee_vd** or **payer_vd**) + mint and spend anchors. The chain saw only the *blinded* binding ($\hat{T}$ hides M_{iss} , Q hides M_{rec}); no un-blinding scalar is ever disclosed – the earlier account-keyed design needed a disclosed γ here, but identity-targeting lets the verifier decrypt directly, since the receipt already discloses the payee preimage. A receipt assembled *without* the binding still prints, with **M_iss** recovered but stamped **UNVERIFIED ISSUER** – a narrow case, since every chain-minted A2 leaf carries a verified binding (the mint reverts otherwise).

5.5 Why there is no "B2" (private-issuer bearer) receipt

A2 is the *only* private-issuer receipt kind because A2 is the only private-issuer note kind. A private-issuer *bearer* note ("B2") is impossible, not merely unimplemented: **eIss** is the issuer’s Identity re-encrypted under **the recipient’s** identity point, openable only with m_{rec} – and a bearer note has no recipient at mint for the issuer to address. Any binding the issuer could instead attach to "whoever bears the note" would be openable by every holder of the freely-circulating note (no privacy over a public B1 issuer) or by no one (no receipt). So a private issuer must address the note (A2) and a bearer note must have a public issuer (B1); the mint SNARK now *binds* this (**issuerMode**, *b14e0f0, 68e5b55*). See *Why B2 is impossible* in the Decryptability companion.

6 The Physical Artifact (ESC/POS, 80mm, 203dpi, 576px)

576 dots wide; Font A (12x24) gives **48 columns**, Font B (9x17) gives 64. The body prints at 48 cols; the base64url payload prints at Font B / 64 cols to cut its line count. Output is 7-bit ASCII only (names transliterated if needed – see *Open Questions*). ESC/POS control: **ESC @** init, **ESC a** n align, **ESC E** n emphasis, **GS V** cut; no graphics.

ALBERTA BUCK

PAYMENT RECEIPT

Receipt a2cg5sgjwfur

FROM (payer) (PRIVATE IDENTITY)

Alice Johnson

Alberta Identity Card - Alberta, Canada

acct 0x0a11ce000000000000000000000000000000a11ce

idpt 0x07a0b762be40..d418d7bf5e7c

TO (payee - you) (PRIVATE IDENTITY)

Bob Smith

Corporate Registration - Alberta, Canada

acct 0x0b0b00000000000000000000000000000000000000b0b

idpt 0x0cef52e77ea5..0ae1f916d96b

TRANSACTION

Type EOA xfer (Identity-bound, private payer)

Amount 500.000000 BUCK

When 2026-05-28 20:10 UTC

Chain 1

Block 1234567

Log 2

Tx 0xeccccccccccccc.....ccccccccccccc

VERIFICATION

status @ issue: VALID

receipt a2cg5sgjwfur

a record, not a bearer instrument

github.com/pjkundert/alberta-buck

albertabuck verify [-|FILE] [--rpc URL]:

- 7

(*Transfer / SpentCoupled**), *value / face*, *recipient / from / to*, and (for Notes) *nullifier match*, the *Minted* event at *mint_txhash* carries *cms[]* from the printed issuer *acct* (= the *transferFrom* source that funded the note), and (B1) the spend's *eDepForIss* equals the payload's; assert the block is mined and final.

4. **Report.** *VALID* (+ named identities, amount) / *INVALID* (reason) / *UNVERIFIED ISSUER* for an A2 slip carrying no binding.

8 Wallet UX and Storage

The receipt is generated from a selected payment:

1. **Select** a row in tx history where the owner is *to* (a *Transfer*) or *recipient* (a *SpentCoupled**); an issuer instead selects a spend of a note it minted (for B1, scanning *SpentCoupledB1* logs for its own *issuer* address and decrypting each *eDepForIss*).
2. **Gather** per the scenario table: a registry read (public payer), stored approve material (private EOA), or the stored note artifact – the *opening*, the Identity-M payload (*eNote / eRec / eIss*, *sigma*), and the mint reference; plus each party's *canonical_identity_data* from wallet storage.
3. **Self-name:** *verifiable_decrypt* the owner's own *E_addr* (and, B1 issuer side, the event's *eDepForIss*).
4. **Anchor:** read the *Transfer / SpentCoupled** event and registry records.
5. **Prove + assemble:** generate the *vd* record(s) with *sk_owner*, build the core, *verify it locally*, set the status banner.
6. **Render + print:** ESC/POS at the configured width; or emit plain text.

Storage the wallet must retain (beyond keys): the owner's (*sk*, *identity_data*); per approved counterparty (*addr*, *identity_data*, *E_for_me*, *cp_proof*); per received *or minted* Note the *opening* + the Identity-M payload and its mint reference (*mint_txhash*, *cms* or *cm index*, *issuer addr*, *issuer_sig | issuer_reenc binding*); and an event source (indexer or RPC) for the *Transfer / SpentCoupled** logs and registry reads. Note that this is exactly the material that already travels with a note off chain – the issuer keeps what it created at mint, the recipient what it was handed – so both-party generation needs no extra exchange.

CLI surface (proposed). `albertabuck receipt <txref> [--width 48|64] [--escpos|--text]` to produce a slip; `albertabuck verify [-|FILE] [--rpc]` to check a scanned payload. Both reuse the wallet library; *verify* has no wallet-secret dependency (a third party runs it).

9 The Whole Flow, Executed: Live EVM, Real Proofs, Both Receipts

Everything this document specifies **runs**. The blocks below are org-babel source blocks sharing one Python session: re-exporting this document (`make nix-venv-doc-receipt`) re-runs them top to bottom against a freshly spawned local EVM, and the printed **RESULTS** are regenerated. The worlds come from the committed end-to-end fixtures (`alberta_buck/test/vectors/e2e/{a1,a2,b1}.json`,

built by make `nix-snark-e2e-fixtures` and shipped as package data): one mutually-consistent world per Note flavor with a **real Groth16 proof at every gate** – batch mint, spend, bound G1-tie membership, and (A1/A2) the `note $\leftrightarrow$ eEnc` tie – and **real named identities**: the canonical Alice Johnson / Bob Smith KYC data of the wallet’s identity vectors. Proof generation happened when the fixtures were built (a wallet does it the same way; the measured prover wall-times ride along in each fixture, and the flow companion’s *Prover Bill of Materials* prices the artifacts and proving per flavor and role); everything below – registry Merkle updates, the identity-bound approve handshake, Groth16 verification, escrow and payout – is live EVM execution, exactly the path `test/NotesE2E.t.sol` drives under forge.

9.1 Boot: a chain whose id the proofs demand

Every Fiat-Shamir transcript and SNARK public input in the fixtures binds `chainid=1`, so the session runs anvil with chain-id 1; the pinned genesis timestamp (plus a fixed 12s block cadence below) makes the whole transcript – including the receipt bytes – reproducible run to run.

```
import random
from alberta_buck.sim.anvil import Anvil
from alberta_buck.sim.notes_stack import E2EFixture, NotesStack
from alberta_buck.wallet import backend
from alberta_buck.wallet.envelope import serialize_core, deserialize_core, receipt_id
from alberta_buck.wallet.verify_receipt import verify_receipt
from alberta_buck.wallet.render import render_receipt, TextDriver

assert backend() == "kernel", "receipts must verify on the production kernel"
print(f"wallet crypto backend: {backend()} (buck_core.buck_identity)")

_seed = random.Random(0xAB12C97)          # ONE deterministic transcript
rng = lambda: _seed.getrandbits(256)

anvil = Anvil(chain_id=1, auto_impersonate=True, timestamp=1780000000).start()
blk = anvil.w3.eth.get_block("latest")
print(f"anvil up: chain-id {anvil.w3.eth.chain_id}, genesis timestamp {blk['timestamp']}")

wallet crypto backend: kernel (buck_core.buck_identity)
anvil up: chain-id 1, genesis timestamp 1780000000
```

9.2 The A2 world: a private issuer pays an addressed recipient

The hardest flavor first. Bob Smith (a private Corporate Identity) minted a 250-BUCK note addressed to Alice Johnson’s identity **point** – not to any account she owns.

```
import json
fx = E2EFixture.load("a2")
iss, dep = json.loads(fx.issuer.identity), json.loads(fx.depositor.identity)
print(f"flavor      {fx.flavor} (addressed, PRIVATE issuer); face {fx.face/1e6:.6f} BUCK")
print(f"issuer      {iss['given_name']} {iss['family_name']} ({iss['id_type']})"
      f"  acct 0x{fx.issuer.addr:040x}")
print(f"depositor    {dep['given_name']} {dep['family_name']} ({dep['id_type']})"
      f"  acct 0x{fx.depositor.addr:040x}")
print(f"prover wall-times (offline, at mint/spend): {fx.timings}")

flavor      a2 (addressed, PRIVATE issuer); face 250.000000 BUCK
issuer      Bob Smith (Corporate Registration)  acct 0x0a11ce00000000000000000000000000000a11ce
depositor    Alice Johnson (Alberta Identity Card) acct 0xde905170000000000000000000000000000de90517
prover wall-times (offline, at mint/spend): {'mint_prove_s': 0.959, 'spend_prove_s': 0.76, 'membership_prove_s': 1.556, 'note_b
```

9.3 Deploy the real stack; bind the Identities (Merkle updates on the EVM)

The full contract stack – `IdentityRegistry` with the incremental Poseidon identity accumulator, the `Buck` stack, `Notes`, and the **real** generated Groth16 verifiers behind their adapters – then the two identity binds. Each bind appends the party’s identity leaf; the contract’s incrementally-maintained root must replay the wallet tree’s.

```
stack = NotesStack(anvil, fx, rng=rng, block_time=12)
binds = stack.bind_identities()
for s in binds:
    print(f"{s.name:26s} gas={s.gas:>9,}")
onchain = stack.reg.functions.identityRoot().call()
print(f"identityRoot (EVM-incremental Poseidon) = {hex(onchain)[:20]}...")
print(f" == the wallet's IdentityTree root:    {onchain == int(fx.raw['identityRoot'])}")
```

```
bind issuer          gas= 594,779
bind depositor       gas= 557,628
identityRoot (EVM-incremental Poseidon) = 0xab29ff540f4d0a25d9...
== the wallet's IdentityTree root:    True
```

9.4 Fund, and the identity-bound approve (the real CP handshake)

The issuer is granted `BuckCredit` and mints `BUCK`; then each private party identity-approves the `Notes` pool with the **real** Chaum-Pedersen re-encryption proof (`Buck.approve` / `IdentityRegistry.verifyApprove`) – the same mutual-decryptability handshake an EOA transfer uses, here providing the escrow allowance and the pool’s receipt fragments. No storage hacks: every step is the legitimate path.

```
for s in stack.fund_issuer():
    print(f"{s.name:26s} gas={s.gas:>9,}")
for party, amount, name in ((fx.issuer, 2 * fx.face, "approve issuer->pool"),
                             (fx.depositor, 0, "approve depositor->pool")):
    s = stack.approve_pool(party, amount, name)
    print(f"{s.name:26s} gas={s.gas:>9,}    (CP proof: verifyApprove)")
```

```
createCredit          gas= 202,935
activateCredit         gas= 42,349
buck.mint               gas= 97,850
approve issuer->pool    gas= 179,302    (CP proof: verifyApprove)
approve depositor->pool gas= 137,964    (CP proof: verifyApprove)
```

9.5 Mint (the issuer’s act)

The issuer submits the real `mint_batch_a2` Groth16 proof with the per-leaf re-encryption binding; the contract verifies both, escrows the face, and installs the SNARK-attested new note root.

```
mint = stack.mint()
print(f"Notes.mint tx {mint.txhash[:20]}.. block {mint.block} "
      f"gas {mint.gas:,} ({mint.seconds:.3f}s on anvil)")
print(f" proof was generated offline by the issuer in "
      f"{fx.timings['mint_prove_s']}s (Groth16, mint_batch_a2 N=1)")
pool = stack.buck.functions.balanceOf(stack.notes.address).call()
print(f" escrowed: pool balance = {pool/1e6:.6f} BUCK")
```

```
Notes.mint tx 0xc2fba76c99295fee9e.. block 32 gas 650,915 (0.108s on anvil)
proof was generated offline by the issuer in 0.959s (Groth16, mint_batch_a2 N=1)
escrowed: pool balance = 250.000000 BUCK
```

9.6 Transmission verification (the recipient's act, offline)

Alice receives the note off chain – the opening, the Identity-M payload (`eNote`, `eIss`), the binding, and the mint reference – and verifies it with **one secret she already owns**: her identity scalar m_{rec} . These are the same deterministic checks any receipt verifier later re-runs.

```
from alberta_buck.wallet.bn254 import G1, mul, eq
from alberta_buck.wallet.elgamal import elgamal_decrypt
from alberta_buck.wallet.notes import id_hash_a2, note_commitment
from alberta_buck.wallet.issuer_reenc import issuer_reenc_verify

nc = fx.note_ots()
m_rec = fx.depositor.m
print(f"idHash == Poseidon8(eNote, eIss):      "
      f"{id_hash_a2(nc['eNote'], nc['eIss']) == fx.opening.id_hash}")
print(f"Dec(eNote, m_rec) == v*G:             "
      f"{eq(elgamal_decrypt(nc['eNote'], m_rec), mul(G1, fx.opening.v))}")
print(f"Dec(eIss, m_rec) == issuer's M:       "
      f"{eq(elgamal_decrypt(nc['eIss'], m_rec), fx.issuer.M)}    (the coupling)")
print(f"mint binding (anti-framing) verifies: "
      f"{issuer_reenc_verify(fx.issuer.pk, fx.issuer.E, nc['eIss'], fx.binding, fx.issuer.addr, fx.chainid)}")
print(f"cm in the Minted batch:              "
      f"{note_commitment(fx.opening) in fx.cms}")

idHash == Poseidon8(eNote, eIss):      True
Dec(eNote, m_rec) == v*G:              True
Dec(eIss, m_rec) == issuer's M:        True    (the coupling)
mint binding (anti-framing) verifies: True
cm in the Minted batch:                True
```

9.7 Deposit (the recipient's act, on chain)

Alice spends from her registered account: the real spend Groth16 against the replayed note tree, the deposit-coupling sigma, the **bound** G1-tie membership proof over the same committed point, and the $\text{note} \leftrightarrow \text{eEnc} = \text{tie}$ – one atomic `spendCoupledA2`.

```
spend = stack.spend()
t = fx.timings
print(f"Notes.spendCoupledA2 tx {spend.txhash[:20]}.. block {spend.block} "
      f"gas {spend.gas:,} ({spend.seconds:.3f}s on anvil)")
print(f" proofs offline: spend {t['spend_prove_s']}s + membership "
      f"{t['membership_prove_s']}s + note-tie {t['note_binding_prove_s']}s")
print(f" nullifier burned: "
      f"{stack.notes.functions.nullifiers(fx.nullifier).call()}")
from web3 import Web3
bal = stack.buck.functions.balanceOf(
    Web3.to_checksum_address(f'0x{fx.payout:040x}')).call()
print(f" paid out: depositor balance = {bal/1e6:.6f} BUCK")
```

```
Notes.spendCoupledA2 tx 0xed88f3c35b57eefcb8.. block 33 gas 1,076,632 (0.106s on anvil)
 proofs offline: spend 0.76s + membership 1.556s + note-tie 11.7s
 nullifier burned: True
 paid out: depositor balance = 249.999999 BUCK
```

9.8 The two receipts, side by side

Both parties now print their slips from the material each already holds – Alice her copy, Bob his payer-side "I paid X" copy – anchored to the live chain's real transaction hashes, blocks, and timestamps. The deterministic note legs are byte-identical between the two; only the self-naming proof (and the "- you" marker) differs.

9.10 All three flavors: the cost of each step

The same lifecycle for B1 (bearer, public issuer) and A1 (addressed, public issuer), then the per-flavor cost table: on-chain gas for the two lifecycle transactions (full-call, as a node bills them) and the offline prover wall-times each party paid. Every flavor yields a VALID receipt for **both** parties.

```
runs = {"a2": (stack, mint, spend)}
for flavor in ("b1", "a1"):
    f2 = E2EFixture.load(flavor)
    st = NotesStack(anvil, f2, rng=rng, block_time=12)
    steps = st.run_lifecycle()
    runs[flavor] = (st, steps["mint"], steps["spend"])

hdr = (f"{'flavor':8s} {'mint gas':>10s} {'spend gas':>10s} "
      f"{'mint prove':>11s} {'spend proves':>13s} {'receipts (dep / iss)':>22s}")
print(hdr); print("-" * len(hdr))
for flavor in ("b1", "a1", "a2"):
    st, m, s = runs[flavor]
    f2, t = st.fx, st.fx.timings
    prove_spend = (t["spend_prove_s"] + t["membership_prove_s"]
                  + t.get("note_binding_prove_s", 0.0))
    a = st.anchors(m, s)
    rcpts = []
    for role in ("recipient", "issuer"):
        core = f2.build_receipt(role, st.contracts, rng=rng, **a)
        rcpts.append(verify_receipt(deserialize_core(serialize_core(core))).reason)
    print(f"{'flavor':8s} {'m.gas':>10,} {'s.gas':>10,} "
          f"{'t['mint_prove_s']':>10.2f}s {'prove_spend':>12.2f}s "
          f"{'rcpts[0]':>11s} / {'rcpts[1]'}")
```

flavor	mint gas	spend gas	mint prove	spend proves	receipts (dep / iss)
b1	520,944	751,313	0.94s	2.32s	VALID / VALID
a1	520,908	1,083,066	1.07s	16.39s	VALID / VALID
a2	650,915	1,076,632	0.96s	14.02s	VALID / VALID

The mint gas difference (A2 over B1/A1) is the on-chain verification of the per-leaf re-encryption binding – the price of an *anonymous* issuer; the spend difference (A1/A2 over B1) is the $\text{note} \leftrightarrow \text{eEnc}$ tie – the price of *addressed* ("only M_{rec} can spend"). The prover cost is dominated by the tie circuits (~2.4M-2.9M constraints); all on-chain verification is constant-gas.

9.11 Shutdown

```
anvil.stop()
print("anvil stopped. The receipts above remain verifiable offline --")
print("tier 1 needs no chain at all, only the slip's own text payload.")
```

```
anvil stopped. The receipts above remain verifiable offline --
tier 1 needs no chain at all, only the slip's own text payload.
```

10 Security Considerations

- **PII on paper.** The slip is a deliberate disclosure: anyone holding it can name both parties. The display subset (name / id_type / jurisdiction) keeps the *printed* face modest, but the payload carries each party's **full canonical_identity_data** in base64 – base64 is *encoding*, *not encryption*. A receipt must be handled like a signed KYC disclosure, not like cash.

- **No value, no replay.** The slip redeems nothing; a referenced Note nullifier is already burned, an EOA transfer already mined. Re-printing or copying a slip moves no funds.
- **Generator honesty bounds.** Tier-1/2 bind the parties, amount, and event; the free-text NOTES are unbound, so a generator may write anything there – hence they are labelled *informational, not verified*, and excluded from the receipt id.
- **A2 issuer privacy.** The A2 binding is *blinded*: the chain sees $\hat{T}$ and $Q = M_{rec} + \beta H$, revealing neither the issuer’s M_{iss} nor the recipient’s M_{rec} . An earlier draft published an unblinded T , which leaks $M_{iss} = C_i - T$ – and `msg.sender` at mint *is* the issuer – so the blind is load-bearing. The receipt discloses no un-blinding scalar at all: naming flows through decryption of `eIss` under m_{rec} , derivable from the payee preimage the receipt already disclosed – so the only new disclosure is the deliberate one. The mint-SNARK `issuerMode` signal is *bound*, the per-leaf `eIss` tie is on chain (the `mint_batch_a2` circuit exposes each committed leaf’s `eIss`, which `Notes.mint` matches to its binding), and the Identity-M spend gate (the deposit-coupling sigma + the *bound* membership proof over the same committed point + the `note $\leftrightarrow$ eEnc` tie) makes an un-nameable note un-spendable: `eIss` keyed to a throwaway key decrypts, under the depositor’s authenticated m_{rec} , to a non-member, and the spend reverts. UNVERIFIED ISSUER therefore narrows to a receipt assembled without its binding – never a spendable chain-minted leaf.
- **Account provenance.** The printed `acct` lines are not free text. The issuer account is folded into the Fiat-Shamir transcript of its binding (the batch Schnorr for B1/A1, `issuer_reenc` for A2), so tier 1 already pins it; tier 2 confirms it is the Minted event’s `issuer` – the `msg.sender` whose `transferFrom` funded the note. The payee account is the `SpentCoupled*` event’s payout `recipient`; the recipient-side receipt ties it to the named Identity by `payee_vd` (mirroring the on-chain deposit-coupling/depositor-binding sigma that authorized the spend from a registered account bound to the same identity scalar). Under Identity-M the spend account need not exist at mint – authorization keys on the *identity* – so the receipt names whichever registered account the recipient actually used, anchored by the event.
- **Trust roots.** Soundness rests on the proof algebra (tier 1), the on-chain registry + event (tier 2), and the KYC issuer’s $m \leftrightarrow \text{person}$ binding (out of scope; assumed via the PS credential).

11 Phasing

1. **Phase A (shipped).** Envelope + `verify` CLI + the plain-text renderer for all five kinds. `eoasub`, `eoasubpriv`, `note-b1`, `note-a1` are soundly bound; the receipt `core` (`envelope.py` / `build_receipt.py` / `verify_receipt.py` / `render.py`) is the shipped wallet surface.
2. **Phase B (shipped, off-chain + on-chain issuerMode + A2 leaf-tie).** `note-a2` is soundly bound: the `issuer_reenc` binding names the private issuer’s *registered* Identity; the slip reads `VALID`. The mint-SNARK `issuerMode` gate is bound on chain (`b14e0f0` / `584bb52` / `68e5b55`), so a bearer leaf cannot be private at all; and the per-leaf `eIss` tie (`mint_batch_a2` + `MintVerifierA2Adapter`) pins each binding to its committed leaf, so a `PRIVATE` batch cannot float or duplicate bindings.
3. **Phase C (shipped, Identity-M).** The note kinds re-built on the identity-targeted payloads: `idHash` preimages (`id_hash_b1/a1/a2`) are conveyed in the envelope and re-checked against the disclosed identity preimages; the addressed ciphertexts (`eNote` / `eRec` / `eIss`) decrypt

under the derivable m_{rec} , closing the recipient-key coupling at the receipt while the on-chain Identity-M spend gate (deposit-coupling + bound membership + $\text{note} \leftrightarrow \text{eEnc} = \text{tie}$) closes it at spend – a spendable note is always nameable, so no γ disclosure remains and **UNVERIFIED ISSUER** survives only for a receipt missing its binding. Receipts are generated by **both Note parties** (**role**): recipient-side and issuer-side ("I paid X") for B1/A1/A2, the B1 issuer naming its depositor from the **SpentCoupledB1** event's **eDepForIss**. Anchors moved to the unified 4242 nullifier and the **SpentCoupled*** events.

4. **Later.** The ESC/POS byte driver (Phase A shipped the plain-text driver; a port-9100 thermal driver is a new **Driver** subclass); optional QR rendering; payer-side *EOA* receipts; on-chain **RcptVerify** if a contract ever needs to gate on a receipt.

12 Open Questions

1. **Encoding for OCR.** base64url is compact but OCR-hostile (l/1/I, O/0); RFC 4648 base32 is ~20% larger but robust to hand entry and OCR. Default base64url, or base32 for paper? (The crypto payload is high-entropy, so compression buys little.)
2. **Unicode names.** Thermal output is ASCII; non-Latin **given_name** / **family_name** need transliteration for the *printed* face, while the payload keeps the exact UTF-8 **canonical_identity_data** (the hash preimage). How to transliterate without implying the printed name is the canonical one?
3. **Point-only fallback.** When the wallet lacks a private counterparty's **identity_data** preimage, should it print the *M* fingerprint + issuer reference (de-anonymizable by the issuer under subpoena), or refuse?
4. **Payload length.** Offline-complete + text-only makes Notes / private-EOA payloads ~2-2.7 KB of base64 (~30-50 Font-B lines). Acceptable for thermal, or offer a **--refs-only** compact mode that requires **--rpc** to verify?
5. **Time and locale.** Print block timestamp (consensus truth) or wall clock, and in UTC or the wallet's locale? The core stores unix block time; the printed string is a render choice.