

Alberta Buck - Identity and Cryptographic Receipts (DRAFT v0.3)

Perry Kundert

2026-04-08

Alberta Buck transactions carry provably authentic identity – without exposing it. Every participant holds an ElGamal ciphertext¹ of their identity, encrypted under their own public key, backed by a Pointcheval-Sanders rerandomizable signature² from the issuing authority. A citizen with multiple accounts derives an independent, unlinkable credential for each – rerandomizing the signature offline – yet every credential is independently verifiable as issued by the same authority. When a transaction requires identity exchange, the participant re-encrypts under the counterparty’s key and produces a Chaum-Pedersen proof³: a compact, unforgeable guarantee that the re-encrypted ciphertext contains the same identity as the registered credential. No one – not the contract, not the network, not the government – sees the plaintext.

Per-transaction identity verification costs $\sim 29,000$ gas via Ethereum’s `alt_bn128` scalar multiplication precompiles – no pairing operations at transaction time. Credential registration costs $\sim 235,000$ gas (a one-time pairing-based verification of the Pointcheval-Sanders signature). No trusted setup. Proof generation is instantaneous.

This document specifies identity requirements for every Alberta Buck operation, details the ElGamal + Pointcheval-Sanders + Chaum-Pedersen architecture, and demonstrates through adversarial scenarios that the scheme defeats forgery, substitution, and collusion while keeping on-chain costs minimal. (PDF, Text)

See Alberta Buck Identity - Cryptographic Examples for demonstrations of the cryptographic primitives used.

¹ElGamal Encryption. ElGamal, T. "A Public Key Cryptosystem and a Signature Scheme Based on Discrete Logarithms." IEEE Transactions on Information Theory, 1985. Semantic security (IND-CPA) under the Decisional Diffie-Hellman assumption. Alberta Buck uses ElGamal over the `alt_bn128` curve (BN254), which is supported by Ethereum’s EIP-196/197 precompiled contracts for efficient on-chain verification.

²Pointcheval-Sanders Signatures. Pointcheval, D. and Sanders, O. "Short Randomizable Signatures." CT-RSA 2016, LNCS 9610, pp. 111-126. Rerandomizable signatures: given a valid signature σ on message m , anyone can compute $\sigma' = (t * \sigma_1, t * \sigma_2)$ that is a valid, statistically unlinkable signature on the same m . Verification uses a bilinear pairing equation, compatible with Ethereum’s `alt_bn128` (BN254) `ecPairing` precompile.

³Chaum-Pedersen Protocol. Chaum, D. and Pedersen, T.P. "Wallet Databases with Observers." CRYPTO 1992, LNCS 740, pp. 89-105. The Chaum-Pedersen protocol proves equality of discrete logarithms (equivalently, that two ElGamal ciphertexts encrypt the same message) in zero knowledge. Made non-interactive via the Fiat-Shamir heuristic.

Contents

1	Identity with Anonymity	4
1.1	Revealing Identity while Preserving Privacy	4
1.2	Accounts Belong to Someone	8
1.3	Counterparties Exchange Identities	8
1.4	ElGamal and Pointcheval-Sanders Over a Mandated Curve Group	10
1.5	Chaum-Pedersen Proof of Re-Encryption Correctness	11
2	Attacks and Defenses	14
2.1	Attack 1: Alice Substitutes a False Identity for Bob	14
2.2	Attack 2: Alice Forges an Issuer Credential	15
2.3	Attack 3: Alice and Complicit Bob Launder With False Identities	16
2.4	Attack 4: Alice Repudiates a Transaction She Made	17
2.5	Attack 5: Criminal Bob Denies Receiving Alice’s Identity	18
2.6	Attack 6: Eve Links Alice’s Identities Across Counterparties	19
2.7	Attack 7: Alice Uses a Revoked or Expired Credential	20
2.8	Attack 8: Unwitting Bob Receives a Transaction From Criminal Alice	21
2.9	Attack 9: Systematic Forgery – Alice Attacks the Trust Chain	22
2.10	Summary: Why the Scheme Defeats All Attacks	24
3	Identity Visibility Modes	25
4	Operations Table	25
4.1	Core BUCK (ERC-20) Operations	25
4.2	BuckCredit (ERC-721) Operations	25
4.3	BuckKController (PID Stabilization)	26
4.4	Oracle Operations	26
4.5	DeFi Integration (Uniswap, Lending, etc.)	26
4.6	Identity Management	26
5	Contract Identity: How DeFi Pools Become BUCK Counterparties	27
6	On-Chain Integration: Receipts and Transfer Flow	27
6.1	The Receipt Constraint	28
6.2	The <code>approve</code> Function as Identity Handshake	28
6.3	Receipt Construction: What the Contract Emits	30
6.4	The Complete <code>transfer</code> / <code>transferFrom</code> Flow	31
6.5	Holochain: Off-Chain Computation and Storage	32
6.6	Summary: What Each Layer Sees	34
7	Cryptographic Receipts: 3-Party ECDH	35
7.1	The Three Keys	35
7.2	Encryption Scheme	35
7.3	Who Can Decrypt	36

8	Play-by-Play: BUCK/USDT Swap on Uniswap	37
8.1	Prerequisites (One-Time Setup)	37
8.2	The Swap Transaction	38
9	Edge Cases and Design Considerations	42
9.1	Flash Loans and Atomic Transactions	42
9.2	Multi-Hop Swaps	42
9.3	Contract-to-Contract Transfers	42
9.4	Wrapping and Bridging	43
9.5	Gas Costs	43
9.6	Privacy of Pool Deployer Identity	43
9.7	alt_bn128 Security Horizon	44
10	Alternative Approaches Considered	44
10.1	Pedersen Commitments + Groth16 ZK Proofs	45
10.2	Proxy Re-Encryption (NuCypher Umbral)	45
10.3	BBS+ Signatures with Selective Disclosure	46
10.4	Camenisch-Shoup Verifiable Encryption	47
10.5	Pedersen Equality Proofs (Homomorphic Comparison)	47
10.6	Comparison Summary	48
11	Summary: Identity Requirement by Risk Level	48

1 Identity with Anonymity

The expectation to be able to transact Alberta BUCKs in complete freedom (no one else can prevent it) and anonymity (no one else can identify the parties) is paramount. This is consistent with the expectation that one is innocent until proven guilty. Asking permission from anyone before we can buy, sell or trade is unacceptable to any free people. Anything less turns a free citizen into a serf. If the government or some regulator can lock your account and freeze you on a park bench at will, how free are you?

The expectation that I can be certain of my counterparty's identity, and that it is *at least* as reliable as the group(s) issuing it is also critical. Millions of financial fraud phone calls flood Albertans' phones daily, pillaging our neighbours and grand-parents, each carrying the government issued identity of the Canadian phone number it "originates" from – under the cover of regulators. *Everyone* involved knows where the call is coming from (the termination contract with the VoIP carrier), who is carrying it into our phone system (the VoIP carrier's contract with phone system providers), and who they are calling - except for *you*. Allowing arbitrary hostile groups to ravage a community under the cover of darkness has been used throughout history to subjugate free people. If the government can issue identity documents to whomever they wish, and you are forced to trust them, how free are you?

The Alberta Buck enforces these principles: the freedom to *transact in privacy and peace*, and the confidence that your counterparty *is who they say they are*.

1.1 Revealing Identity while Preserving Privacy

If I am suspected of a crime, an Alberta court can compel me to decrypt the participants in BUCK transactions they suspect are related to that crime, and reveal the identity of counterparties I've transacted with. I may resist, and face the consequences. But the organizations that Alberta tasks with overseeing the authenticity of my Alberta issued identity must not be able to simply authorize decryption of my counterparties' identities! They can only vouch for and reveal the identities they've directly issued, just as I can vouch for my daughter's – they can't decrypt arbitrary participants in each transaction.

This is how the cryptography enforces it: each re-encrypted identity is an ElGamal ciphertext under the specific counterparty's public key. Only that counterparty's private key can recover the plaintext. The identity issuer cannot decrypt it – they signed the identity, not the ciphertext; the encryption is mine alone. The government cannot decrypt it. No registry operator, no Holochain node, no subpoena served on anyone other than a direct participant can break this. A court must compel a *specific participant* to decrypt a *specific transaction's counterparties'* identity data. Every individual's credential must be attacked separately. The cost to surveil is $O(N)$, not $O(1)$.

1.1.1 The Identity Fountain

A citizen with income, savings, inheritance, and walking-around-money accounts should not have those accounts linkable to each other by any outside observer. Ethereum balances

are public; if all of Alice's accounts trace back to the same identity credential, her entire financial life is exposed to anyone who notices the link.

The identity fountain solves this. It gives every citizen the ability to derive unlimited, unlinkable identity credentials – each independently verifiable as issued by the same authority – from a single KYC ceremony. The construction uses Pointcheval-Sanders (PS) rerandomizable signatures² over the `alt_bn128` curve.

1. Issuance: The Issuer Signs Once

During the KYC ceremony, the issuer:

- (a) Verifies Alice's identity (documents, biometrics, whatever the jurisdiction requires).
- (b) Computes the identity scalar $m = H(\text{identity_data})$.
- (c) Picks a random point h in G_1 and computes the PS signature:
 $\text{sigma} = (h, (x + m * y) * h)$
where (x, y) is the issuer's secret key.
- (d) Gives Alice the identity scalar m and signature $(\text{sigma}_1, \text{sigma}_2)$.
- (e) Publishes the issuance event to the issuer's Holochain source chain.

The issuer's public key $(X, Y) = (x * g_2, y * g_2)$ in G_2 is registered in the TrustedIssuersRegistry on Ethereum. The issuer is now done – permanently, if desired.

2. What `identity_data` Contains

`identity_data` is a canonical (deterministically serialized) structure containing Alice's verified identity claims:

```
identity_data = canonical_encode({
  given_name:    "Alice",
  family_name:   "Johnson",
  jurisdiction:  "Alberta, Canada",
  id_type:       "Alberta Identity Card",
  id_number:     "AIC-2026-4839201",
  date_of_birth: "1992-03-15",
  issuer_id:     "atb-financial-ca",
  issued_at:     "2026-01-20T14:30:00Z",
  epoch:        42
})
```

The identity scalar is $m = H(\text{identity_data})$ where H is keccak256 over the canonical encoding. The canonical encoding is deterministic: field order, encoding format, and whitespace are fixed by the hApp DNA, so any party who holds the same `identity_data` computes the same m .

The issuer verifies these claims during the KYC ceremony and computes m . Alice receives both m (the scalar) and `identity_data` (the plaintext). The plaintext never touches Ethereum – it is the *content* that the on-chain proof chain guarantees. Alice stores `identity_data` as a Private entry on her Holochain source chain, encrypted with her agent key and never published to the DHT.

Different issuers may define different schemas (a province vs. a bank), but all schemas produce a single scalar m via the same hash function. The `epoch` field binds the credential to a renewal period (see Epoch-Based Credential Renewal below).

3. Derivation: Alice Generates Credentials Offline

For each new Ethereum account, Alice’s Holochain wallet:

- (a) Picks a random scalar t and rerandomizes the PS signature:

`sigma' = (t * sigma_1, t * sigma_2)`

This `sigma'` is a valid PS signature on the same m under the same issuer public key – but is *statistically unlinkable* to `sigma` or to any other rerandomization. No algorithm can correlate `sigma'` back to `sigma`.

- (b) Generates a fresh identity key pair (`sk_new`, `pk_new`) on `alt_bn128`.

- (c) Encrypts the identity under the new key using ElGamal:

`E_new = (r * G, m * G + r * pk_new)`

- (d) Computes a non-interactive zero-knowledge proof `pi` that `E_new` encrypts the same m that `sigma'` signs:

"I know (m , t , r) such that:

- a) $e(\text{sigma}'_1, X + m * Y) = e(\text{sigma}'_2, g_2)$ -- valid PS signature
- b) $C = m * G + r * \text{pk_new}$ -- ElGamal encryption of m
- c) $R = r * G$ -- consistent randomness"

- (e) Packages (`pk_new`, `E_new`, `sigma'`, `pi`) for registration.

This derivation runs entirely on Alice’s device. She can pre-generate a hundred credentials in a batch and store them in her Holochain wallet, pulling one out whenever she creates a new account.

Each credential derivation corresponds to a **separate Holochain agent**. Alice’s wallet spawns a new Holochain agent – a fresh Ed25519 key pair and an independent source chain – for each Ethereum account. From the perspective of both Ethereum and Holochain, these agents are entirely distinct identities: separate addresses, separate agent IDs, separate source chains. The one artifact shared across agents is Alice’s `identity_data` (and therefore $m = H(\text{identity_data})$), which is copied into each new agent’s Private entry store. Since m is committed only inside ElGamal ciphertexts (IND-CPA secure) and PS signatures (statistically rerandomized), no observer on either network can detect that two agents share the same m .

4. Registration: One-Time On-Chain Verification

Alice registers the derived credential in the IdentityRegistry:

```
identityRegistry.registerCredential(  
    alice_new_address,  
    pk_new,           // identity public key  
    E_new,            // ElGamal ciphertext (4 uint256)  
    sigma_prime,      // rerandomized PS signature (2 G_1 points)  
    pi                // NIZK proof linking sigma' to E_new  
)
```

The contract verifies the PS signature and NIZK proof using the `ecPairing` pre-compile (address `0x08`), `ecMul`, and `ecAdd`. Gas cost: $\sim 235,000$ gas, paid once per account.

After registration, `isVerified(alice_new_address) == true`. The credential is stored on-chain as an ElGamal ciphertext and an identity public key. No subsequent operation consults the PS signature again; per-transaction verification is pure Chaum-Pedersen ($\sim 29,000$ gas).

5. What the World Sees

Alice creates five accounts over two years. Each registers a credential (`pk_i`, `E_i`, `sigma'_i`, `pi_i`). An observer can verify:

- Each `sigma'_i` was produced by the known issuer – the pairing check passes.
- Each `E_i` encrypts the identity that `sigma'_i` signs – the proof `pi_i` confirms it.
- Whether any two credentials belong to the same person – **no**.

PS rerandomization is *statistically* unlinkable – not merely computationally hard to correlate, but information-theoretically impossible. The credentials contain zero bits of mutual information. Alice's inheritance account, her walking-around-money account, her savings account – each carries the issuer's stamp of authenticity, each is cryptographically invisible to the others.

6. Epoch-Based Credential Renewal

If the issuer revokes Alice's identity (fraud, death, court order), all her derived credentials must be invalidated – without linking them.

Credentials carry an expiry epoch (e.g., one year). The issuer publishes epoch keys; credential derivation requires the current epoch key. Revocation means the issuer refuses to provide Alice's next epoch key. Expired credentials are rejected at `isVerified` time. Alice must periodically re-derive from a fresh issuance – giving the issuer a natural checkpoint for continued eligibility.

This fits Alberta Buck's model: the issuer remains the trust anchor for "is this person still in good standing," which is the real-world question regardless of the cryptography.

1.2 Accounts Belong to Someone

I may be a citizen of Alberta and have a minor child. My child's identity is vouched by me, and my identity is vouched by Alberta. I have several accounts associated with encrypted copies of my identity (income, savings, etc) and several unencrypted accounts (walking-around money). I can transfer money from my savings to my walking-around account (anonymously, via my BUCK account at ATB).

My encrypted savings account identity has been authorized by ATB to send funds. My walking-around money account has a plaintext identity, so Starbucks' BUCK account doesn't need to pre-authorize incoming transactions – it accepts BUCK transfers from any BUCK account with a public identity.

This just cuts out the middleman, and gives every citizen what government and institutions already have: knowledge of the participants in transactions with public accounts. If I prefer, I can set up a Starbucks account, and ask them to authorize me to send money to them. Again, allowing with BUCKs what is already allowed with a pre-loaded Starbucks card – private transactions with a public account. Starbucks and Visa both know who paid to fund the Visa card, and who funded their Starbucks account with that card. Now, citizens can set up similar arrangements and retain that knowledge amongst themselves.

If a court compels one of the participants (for example, as the result of an arrest in a sting operation against some members of a group performing some illicit activity), then that person's transactions with other members of the group can be discovered. Otherwise: *financial activity remains confidential, at the sole choice of the participants.*

The expectation that any government or bank functionary – or any random attacker exploiting government or bank incompetence – can know the details of a citizen's financial activities is unacceptable. The attack cost must be $O(N)$, not $O(1)$: every individual's credential must be attacked separately, not extracted from one compromised custodian.

1.3 Counterparties Exchange Identities

Each transaction is between parties identified to each other by provably untampered copies of their identity, encrypted by each party specifically for that counterparty.

The identity credential lifecycle:

1. **Issuance:** A trusted issuer (the Alberta government, ATB Financial, etc.) verifies Alice's identity through a KYC ceremony and produces a Pointcheval-Sanders signature on her identity scalar $m = H(\text{identity_data})$. Alice receives (m, sigma) and stores it in her Holochain wallet. (See The Identity Fountain for the full PS construction.)
2. **Derivation:** For each Ethereum account, Alice's wallet rerandomizes the PS signature, generates a fresh identity key pair, encrypts her identity under the new key

using ElGamal, and produces a NIZK proof linking the rerandomized signature to the ciphertext. This runs entirely offline.

3. **Registration:** Alice registers the derived credential (`pk`, `E_alice`, `sigma'`, `pi`) in the on-chain IdentityRegistry. The contract verifies the PS signature and NIZK proof via the `ecPairing` precompile (235,000 gas, one-time). After registration, `~isVerified(alice) == true`.

4. **Re-encryption:** When Alice must identify herself to counterparty Bob (e.g., during an `approve` call on the BUCK contract), she decrypts her credential locally (she knows `sk_alice`) and re-encrypts the identity under Bob's public key with fresh randomness:

$$E_{\text{bob}} = (r' * G, r' * pk_{\text{bob}} + M)$$

where $M = m * G$ is the identity message point. She produces a Chaum-Pedersen proof³ `pi` that `E_bob` encrypts the same point `M` as her registered `E_alice` – without revealing `m`.

5. **Verification:** The BUCK smart contract verifies:

- `E_alice` is read from the IdentityRegistry (not from Alice's calldata)
- `pi` proves `E_bob` encrypts the same plaintext as `E_alice`

Verification requires only 3-4 elliptic curve scalar multiplications (~29,000 gas via the `alt_bn128` precompiles). No pairing operations at transaction time. The PS signature was verified once, at registration, and is never consulted again.

6. **Decryption:** Only Bob can decrypt `E_bob` (he has `sk_bob`). Only Alice can decrypt `E_alice` (she has `sk_alice`). The issuer cannot decrypt either – they signed Alice's identity scalar, they never encrypted under any key. No third party can decrypt any re-encrypted copy.

This is a **two-channel design**. The on-chain ElGamal ciphertexts and Chaum-Pedersen proofs form the *proof chain*: they bind Alice's registered identity to the re-encrypted ciphertext Bob receives, without revealing content. The actual `identity_data` (name, jurisdiction, ID number) travels via the *data channel*: Alice's Holochain hApp sends it to Bob's hApp, encrypted end-to-end. Bob verifies the binding:

```
M = C_b - sk_bob * R_b           // decrypt ElGamal ciphertext
assert H(identity_data) * G == M  // bind off-chain data to proof chain
```

EC-ElGamal decryption yields a curve point `M`, not the scalar `m`. Recovering `m` from $M = m * G$ is the discrete logarithm problem. The proof chain never carries plaintext – it proves *which* identity was sent. The data channel delivers *what* that identity contains. The hash commitment $H(\text{identity_data}) * G == M$ binds them cryptographically: Bob can verify the `identity_data` he received via Holochain is exactly the identity the issuer certified and Alice registered on-chain.

There is no need for Proxy Re-Encryption (PRE), because Alice is online when she calls `approve` and can perform the re-encryption directly. The Chaum-Pedersen proof is the trust anchor at transaction time: it is a mathematical guarantee – unforgeable under the discrete logarithm assumption – that Alice re-encrypted her genuine, registered identity and not a substitute. The PS signature is the trust anchor at registration time: it guarantees the credential was issued by an authorized issuer.

1.4 ElGamal and Pointcheval-Sanders Over a Mandated Curve Group

Alberta Buck mandates that all identity credentials, all participant key pairs, all re-encryption operations, and all issuer signatures use the `alt_bn128` elliptic curve (BN254)¹ – the curve supported by Ethereum’s precompiled contracts:

- `ecAdd` (address `0x06`): point addition, 150 gas
- `ecMul` (address `0x07`): scalar multiplication, 6,000 gas
- `ecPairing` (address `0x08`): bilinear pairing check, 34,000 gas per pair + 45,000 base

This mandate is a design strength, not a limitation:

- **Uniform proof verification:** every Chaum-Pedersen proof and every Pointcheval-Sanders signature verification uses the same curve group, so a single on-chain verifier handles all identity operations.
- **Precompile efficiency:** per-transaction Chaum-Pedersen verification uses `ecMul` / `ecAdd` (29,000 gas). One-time credential registration uses `~ecPairing` for PS signature verification (`~235,000` gas).
- **No cross-group compatibility issues:** since all participants, issuers, and credentials use the same curve, re-encryption between any two participants is always algebraically compatible.

Participant key pairs for identity purposes are distinct from their Ethereum signing keys (which use `secp256k1`). The identity key pair is generated during credential derivation (not during the KYC ceremony – the KYC ceremony produces only the PS signature). The public key is registered in the IdentityRegistry alongside the participant’s Ethereum address.

When Alice re-encrypts for N different counterparties, each re-encryption uses independent randomness. The resulting ciphertexts are IND-CPA secure: computationally indistinguishable from random curve points. An observer who collects all N ciphertexts cannot determine that they encrypt the same plaintext (without access to a counterparty’s private key).

1.5 Chaum-Pedersen Proof of Re-Encryption Correctness

The Chaum-Pedersen protocol³ is a sigma protocol (Schnorr family) that proves two ElGamal ciphertexts encrypt the same message point, without revealing the message. Made non-interactive via the Fiat-Shamir heuristic, the proof is compact (~128 bytes: two scalars and two curve points) and verification requires only 3-4 multi-scalar multiplications.

1.5.1 Setup

Registered credential (verified at registration via PS signature + NIZK):

$E_{\text{alice}} = (R_a, C_a) = (r_a * G, r_a * pk_{\text{alice}} + M)$

where $M = m * G$ (identity encoded as a curve point, $m = H(\text{identity_data})$)

Rerandomized PS signature σ verified at registration (not consulted again)

Alice's re-encryption for Bob:

$E_{\text{bob}} = (R_b, C_b) = (r_b * G, r_b * pk_{\text{bob}} + M)$

using the SAME message point M

1.5.2 What Alice Proves (Non-Interactively)

"I know (sk_{alice}, r_b) such that:

1. $pk_{\text{alice}} = sk_{\text{alice}} * G$ -- I own this public key
2. $R_b = r_b * G$ -- I know E_{bob} 's randomness
3. $C_a - sk_{\text{alice}} * R_a = C_b - r_b * pk_{\text{bob}}$ -- same message point M "

Statement 3 is the core. The left side decrypts E_{alice} (only Alice can compute this, since she knows sk_{alice}), yielding the message point M . The right side extracts M from E_{bob} (only Bob could alternatively compute this with sk_{bob}). If Alice encrypted different data I_{fake} , then $I * G \neq I_{\text{fake}} * G$ and no valid proof exists – it is not merely hard to compute, it is mathematically impossible under the discrete logarithm assumption.

1.5.3 Verification (What the Contract Computes)

Given public inputs:

$E_{\text{alice}} = (R_a, C_a)$ -- from IdentityRegistry (PS-verified at registration, read from storage -- NOT supplied by Alice)
 $E_{\text{bob}} = (R_b, C_b)$ -- from Alice's approve() calldata
 pk_{alice} -- from IdentityRegistry
 pk_{bob} -- from IdentityRegistry
 $\text{proof} = (e, s1, s2)$ -- Fiat-Shamir challenge and responses

Verify:

Recompute challenge e from commitments

Check consistency of `s1`, `s2` against `e`, the public keys, and ciphertexts
 3-4 `ecMul` + 3-4 `ecAdd` operations

Critical implementation requirement: `E_alice` is **read from on-chain storage** (the IdentityRegistry), not supplied by Alice as calldata. This anchors the proof to the registered credential. If Alice could supply her own `E_alice`, she could substitute a fake credential and produce a valid proof against it.

The Fiat-Shamir challenge must bind all public inputs and context to prevent replay and malleability:

`e = H(G, pk_alice, pk_bob, R_a, C_a, R_b, C_b, T1, T2, msg.sender, spender, block.chainid)`

Including `msg.sender` and `spender` (Ethereum addresses) binds the proof to the specific transaction context. Including `block.chainid` prevents cross-chain replay. On-chain, `msg.sender` is authenticated by ECDSA and `spender` is a calldata argument to `approve()`, but including them in the hash explicitly prevents a proof generated for one (`sender`, `spender`) pair from being replayed in another context. This is standard Fiat-Shamir domain separation, not an additional cryptographic assumption.

1.5.4 Gas Cost

1. Per-Transaction (Chaum-Pedersen Verification at `approve`)

Operation	Count	Gas each	Total
<code>ecMul</code> (precompile)	4	6,000	24,000
<code>ecAdd</code> (precompile)	4	150	600
<code>keccak256</code> (Fiat-Shamir)	1	36	36
Calldata (128 bytes)			2,048
Storage read (<code>E_alice</code>)	1	2,100	2,100
Total			~29,000 gas

The `approve` call costs 29,000 gas for the identity proof plus the standard ERC-20 `approve` cost (~46,000 gas), totaling ~75,000 gas. This is paid once per counterparty pair. Subsequent `~transfer` and `transferFrom` calls emit only minimal receipt events (addresses + opaque hashes, ~2,000 gas) with no additional proof work.

2. One-Time (PS Signature + NIZK Verification at Registration)

Operation	Count	Gas each	Total
<code>ecPairing</code> (precompile)	3-4	34,000	147,000
<code>ecPairing</code> base cost	1	45,000	45,000
<code>ecMul</code> (NIZK verification)	3-4	6,000	24,000
<code>ecAdd</code> (NIZK verification)	3-4	150	600
Calldata + SSTORE overhead			~10,000
Total			~235,000 gas

The NIZK proof linking the PS signature to the ElGamal ciphertext is a standard Schnorr-family sigma protocol – *not* a Groth-Sahai proof. The PS verification relation $e(\text{sigma}'_1, X + m * Y) = e(\text{sigma}'_2, g_2)$ is *linear* in m : the public inputs $\text{sigma}'_1, \text{sigma}'_2, X, Y, g_2$ are fixed curve points, and the secret m enters linearly via $m * Y$. A single challenge-response pair binds m to both the pairing equation and the ElGamal ciphertext. The pairing is computed by the *verifier* on public inputs; the prover demonstrates knowledge of m via scalar responses. No bilinear-map proof system is needed.

The concrete verification protocol:

Public inputs:

```
sigma' = (sigma'_1, sigma'_2)  -- rerandomized PS signature (G_1)
E_new  = (R, C)               -- ElGamal ciphertext (G_1)
pk_new                                -- identity public key (G_1)
(X, Y)                               -- issuer public key (G_2)
g_2                                    -- generator (G_2)
```

Proof: $\text{pi} = (e, s_m, s_r)$

Verifier computes:

```
// (a) PS signature check via ecPairing precompile:
//   Reconstruct the commitment A = s_m * sigma'_1 - e * sigma'_2
//   in G_1, then verify the pairing product equation:
A_ps = ecMul(sigma'_1, s_m) + ecMul(sigma'_2, -e)  // 2 ecMul + 1 ecAdd
ecPairing([A_ps, Y], [ecMul(sigma'_1, e), X],
          [ecMul(sigma'_2, -e), g_2]) == 1          // 3 pairings

// (b) ElGamal consistency check (pure G_1 arithmetic):
//   s_m * G + s_r * pk_new == e * C + T_b
//   s_r * G == e * R + T_r
//   where T_b, T_r are the prover's commitments (included in proof)

// (c) Fiat-Shamir challenge reconstruction:
e' = H(sigma', E_new, pk_new, A_ps, T_b, T_r, registrant_address)
require(e' == e)
```

Part (a) uses the `ecPairing` precompile (3 pairs: 147K gas). Parts (b) and (c) use `~ecMul / ecAdd` (~30K gas). Total: ~235K gas. This is a standard Schnorr-family sigma protocol applied to a linear pairing relation – the same class of proof used in BLS signature verification and PS credential presentation protocols.

This one-time registration cost is comparable to deploying a small contract. For an account that will hold meaningful value and transact many times, it is negligible. Compare: Groth16 SNARK verification requires similar pairing opera-

tions (~200,000-300,000 gas) but must be performed *per transaction* if used for re-encryption proofs.

2 Attacks and Defenses

The following scenarios demonstrate that the ElGamal Chaum-Pedersen proof scheme defeats identity fraud, even when participants are actively criminal. In each scenario we show what the attacker attempts, why it fails mathematically, and what the on-chain verifier sees.

The trust chain in every scenario is:

Issuer PS-signs identity m	--> identity is genuine
Alice derives $(E_{\text{alice}}, \sigma', \pi)$	--> credential is unlinkable
PS + NIZK verified at registration	--> credential is issuer-authorized
E_{alice} stored in registry	--> contract reads the genuine credential
Chaum-Pedersen proof verified	--> E_{bob} encrypts same identity as E_{alice}
Only Bob can decrypt E_{bob}	--> identity revealed only to counterparty

Breaking any link requires breaking either the q-SDH assumption (PS signature unforgeability), the discrete logarithm assumption on alt_bn128 (Chaum-Pedersen soundness, ElGamal security), or ECDSA (Ethereum transaction authenticity) – all standard hardness assumptions underpinning Ethereum’s own security.

2.1 Attack 1: Alice Substitutes a False Identity for Bob

2.1.1 Scenario

Alice is a sanctioned individual. She completed KYC under her real identity and received a legitimate PS-verified credential E_{alice} containing her true identity I . She now wants to transact with Bob but wants Bob (and any future court) to believe she is someone else – say, her clean associate Carol.

Alice constructs a fake re-encryption using Carol’s identity I_{fake} :

$$E_{\text{bob_fake}} = (r' * G, \quad r' * \text{pk_bob} + I_{\text{fake}} * G)$$

She submits $E_{\text{bob_fake}}$ to `approve()` and attempts to produce a Chaum-Pedersen proof tying it to her registry credential.

2.1.2 Why It Fails

The Chaum-Pedersen verification checks:

$$C_a - \text{sk_alice} * R_a == C_b - r' * \text{pk_bob}$$

Expanding the left side (from the registered E_{alice} in the registry):

$$\begin{aligned}
& (r_a * pk_alice + I * G) - sk_alice * (r_a * G) \\
&= r_a * sk_alice * G + I * G - sk_alice * r_a * G \\
&= I * G
\end{aligned}$$

Expanding the right side (from Alice's fake E_bob):

$$\begin{aligned}
& (r' * pk_bob + I_fake * G) - r' * pk_bob \\
&= I_fake * G
\end{aligned}$$

The proof requires $I * G == I_fake * G$, which requires $I == I_fake$. Since $I != I_fake$ (Alice is not Carol), these are distinct curve points. Under the discrete logarithm assumption, Alice **cannot produce valid proof scalars ($s1, s2$)** that satisfy the verification equations. The proof does not exist – not "hard to find," but mathematically non-existent.

2.1.3 What the Contract Sees

`approve()` reverts: "Re-encryption proof invalid." The transaction fails on-chain. Alice cannot complete the identity handshake with false data. The revert is indistinguishable from a malformed transaction – no information about Alice's intent leaks.

2.1.4 Cost to Alice

She wasted gas on a failed transaction. Her address is still associated with her real registered credential in the registry. Nothing has changed.

2.2 Attack 2: Alice Forges an Issuer Credential

2.2.1 Scenario

Alice never completed KYC, or completed KYC but wants a credential with different identity data. She picks a fabricated identity scalar $m_fake = H(fake_data)$, generates a random PS-like signature, creates an ElGamal ciphertext, and fabricates a NIZK proof:

```

m_fake      = H("Carol Smith, Alberta, ...")
sigma_fake  = (random_h, random_s)           -- not a valid PS signature
E_alice_fake = (r * G, m_fake * G + r * pk_alice)
pi_fake     = ...                           -- fabricated NIZK

```

She attempts to register this credential in the IdentityRegistry.

2.2.2 Why It Fails

The IdentityRegistry verifies the Pointcheval-Sanders signature against trusted issuer public keys registered in the TrustedIssuersRegistry (part of the ERC-3643 framework⁴). Registration checks the pairing equation:

⁴ERC-3643 (T-REX): Token for Regulated EXchanges. The on-chain identity framework (IdentityRegistry, TrustedIssuersRegistry, ClaimTopicsRegistry) used by Alberta Buck for credential management. <https://eips.ethereum.org/EIPS/eip-3643>

$e(\text{sigma}'_1, X + m * Y) == e(\text{sigma}'_2, g_2)$

where (X, Y) is the trusted issuer's public key in G_2 . Alice does not know the issuer's secret key (x, y) , so she cannot produce a sigma' that satisfies this equation for any m – let alone for m_{fake} . The PS signature is unforgeable under the q-SDH assumption.

Even if Alice could somehow produce a valid-looking PS signature (she cannot), the NIZK proof pi must prove that the ElGamal ciphertext E_{alice} encrypts the same m that the PS signature covers. Forging the proof requires breaking the discrete logarithm assumption.

Two independent barriers must both be broken. Neither has been broken in the history of elliptic curve cryptography.

2.2.3 What the Contract Sees

`registerCredential()` reverts: "Invalid issuer signature." Alice is not registered; `isVerified(alice) == false`. She cannot participate in any BUCK operation requiring identity.

2.3 Attack 3: Alice and Complicit Bob Launder With False Identities

2.3.1 Scenario

Alice and Bob are both criminals. Both have legitimate PS-verified credentials (they passed KYC under their real identities). They want to transact with each other, but want the encrypted identity records to show *different* people – so that if a court later compels Bob to decrypt Alice's identity blob, it points to an innocent third party.

They agree: Alice will encrypt a false identity I_{fake} for Bob and submit it. Bob will claim (if asked) that the decrypted identity is genuine.

2.3.2 Why It Fails

Alice's `approve()` call must pass Chaum-Pedersen verification. The contract reads E_{alice} from the IdentityRegistry – not from Alice's calldata.

```
// Inside approve():
E_alice = identityRegistry.getCredential(msg.sender);
require(chaumPedersenVerify(E_alice, E_bob_submitted, proof));
```

Alice cannot substitute a different E_{alice} because the contract reads it from storage. She cannot produce a valid Chaum-Pedersen proof linking her fake E_{bob} to the real E_{alice} because the message points differ (same math as Attack 1).

Bob's willingness to accept false data is irrelevant. The proof was verified against the registered credential *before* E_{bob} was stored. If `approve()` succeeded, E_{bob} necessarily contains Alice's real identity. When a court later compels Bob to decrypt, he produces Alice's true identity – regardless of any prior agreement between them.

Bob cannot produce a *different* plaintext from the same E_{bob} (ElGamal decryption is deterministic given the private key). Bob cannot claim the E_{bob} is unrelated to Alice

(the on-chain `IdentityExchange` event records that Alice submitted it during `approve`, and the proof verification succeeded).

2.3.3 What the Contract Sees

If Alice submits false data: `approve()` reverts ("Re-encryption proof invalid") – same as Attack 1.

If Alice submits real data (because she has no choice): `approve()` succeeds, and `E_bob` provably contains her real identity. The laundering scheme fails silently – Alice and Bob transacted, but the identity trail is genuine and court-recoverable.

2.4 Attack 4: Alice Repudiates a Transaction She Made

2.4.1 Scenario

Alice transacted legitimately with Bob (a law-abiding merchant). Later, Alice is investigated. She claims she never transacted with Bob, or that the identity Bob received was fabricated by Bob. Alice hopes that because the re-encrypted blob is opaque to everyone except Bob, a court cannot verify its authenticity without trusting Bob's word.

2.4.2 Why It Fails

The on-chain record contains everything needed to verify, without trusting Bob:

1. The `IdentityExchange(alice, bob, E_bob)` event is on-chain, emitted during Alice's `approve()` call. It was sent from Alice's address (verified by `msg.sender`).
2. The `approve()` transaction succeeded on-chain, which means the Chaum-Pedersen proof verified against Alice's registered `E_alice` from the registry. This is an immutable execution fact.
3. Therefore `E_bob` provably encrypts the same identity as `E_alice`. This follows from the soundness of the Chaum-Pedersen protocol – it is a mathematical fact, not testimony.
4. When the court compels Bob to decrypt `E_bob`, the resulting plaintext `I` is provably Alice's issuer-certified identity. The chain of trust:

Issuer PS-signed Alice's identity <code>m</code>	(verified at registration)
<code>E_alice</code> stored in <code>IdentityRegistry</code>	(on-chain, immutable)
Alice called <code>approve()</code> with <code>E_bob</code> + proof	(on-chain tx, <code>msg.sender = alice</code>)
Chaum-Pedersen proof verified on-chain	(execution succeeded)
$\Rightarrow$ <code>E_bob</code> encrypts Alice's real identity	(mathematical fact)
Bob decrypts <code>E_bob</code> $\rightarrow$ <code>I</code>	(compelled, deterministic)
<code>I</code> is Alice's issuer-certified identity	(proven)

2.4.3 What the Court Sees

An unbroken, cryptographically verified chain from issuer to decrypted identity. Alice's repudiation is contradicted by on-chain proof verification records that she cannot alter or dispute.

2.5 Attack 5: Criminal Bob Denies Receiving Alice's Identity

2.5.1 Scenario

Bob is a criminal merchant. Alice (law-abiding) transacted with Bob. Authorities investigate Bob. Bob claims he never received Alice's identity and cannot produce it – hoping to deny knowledge of his counterparties, or to shield Alice from being identified as his customer.

2.5.2 Why It Fails

The `IdentityExchange(alice, bob, E_bob)` event is on-chain and immutable. The court retrieves `E_bob` directly from the blockchain – Bob's cooperation is not needed to find the ciphertext.

Bob is compelled to decrypt:

$$M = C_b - sk_{bob} * R_b$$

If Bob claims he "lost" his identity private key (the `alt_bn128` key, which is distinct from his Ethereum signing key):

- The court holds Bob in contempt, as it would for any refusal to produce subpoenaed records. "I lost the key" is no more credible for a cryptographic key than for a filing cabinet – particularly when the key was generated during a KYC ceremony and Bob accepted transactions requiring its use.
- Even without Bob's cooperation, the court can establish from the on-chain proof verification that `E_bob` *does* contain a genuine identity. Bob's refusal to decrypt is itself evidence of obstruction.

Bob cannot claim `E_bob` is meaningless or fabricated: the successful Chaum-Pedersen proof verification is an on-chain fact.

2.5.3 What the Court Sees

`E_bob` is on-chain. The proof that it contains Alice's real identity is on-chain. Bob decrypts or faces contempt. The cryptographic record is self-authenticating.

2.6 Attack 6: Eve Links Alice’s Identities Across Counterparties

2.6.1 Scenario

Eve is a surveillance actor (competitor, stalker, rogue state). She observes that Alice’s address called `approve` for multiple counterparties: Bob, Carol, and Dave. Eve collects the `IdentityExchange` events:

```
IdentityExchange(alice_addr, bob_addr, E_bob)
IdentityExchange(alice_addr, carol_addr, E_carol)
IdentityExchange(alice_addr, dave_addr, E_dave)
```

Eve wants to learn Alice’s real identity, or to determine whether these transactions reveal a pattern (e.g., Alice’s spending habits).

2.6.2 Why It Fails (Content Privacy Holds)

Each re-encryption uses independent randomness:

```
E_bob    = (r_1 * G, r_1 * pk_bob  + I * G)
E_carol  = (r_2 * G, r_2 * pk_carol + I * G)
E_dave   = (r_3 * G, r_3 * pk_dave  + I * G)
```

The ciphertexts are IND-CPA secure (semantic security of ElGamal): each is computationally indistinguishable from a random pair of curve points. Eve cannot decrypt any of them without the counterparty’s private key. She cannot determine from the ciphertexts alone what identity they encode, nor can she compare them to determine if they encode the same identity.

What Eve does know: all three events originate from `alice_addr`. But this is exactly the information already visible in standard ERC-20 `Approval` events. The encrypted identity blobs add **zero additional linkability** beyond Ethereum’s inherent pseudonymous address model.

What Eve does not know: Alice’s name, jurisdiction, ID number, or any attribute of her identity. She sees an address; she does not see a person.

2.6.3 What Eve Sees

Pseudonymous Ethereum addresses and opaque ciphertexts that are computationally indistinguishable from random. The same view she has of any ERC-20 token, plus meaningless (to her) encrypted blobs.

2.6.4 Cross-Account Unlinkability

A stronger version of this attack: Eve suspects that addresses `addr_1`, `addr_2`, and `addr_3` all belong to Alice. She examines each address’s registered credential in the `IdentityRegistry`.

Each credential was derived independently through the Identity Fountain: different rerandomized PS signatures, different identity key pairs, different ElGamal ciphertexts with independent randomness. PS rerandomization is *statistically* unlinkable – not merely computationally hard to correlate, but information-theoretically impossible. The credentials contain zero bits of mutual information.

Eve’s only path to linking accounts is off-chain analysis: timing, amounts, behavioral patterns. The cryptographic identity layer gives her nothing.

2.6.5 Scope of Unlinkability

Alberta Buck provides *identity privacy* (no observer can determine who owns an address from the credential) and *credential unlinkability* (no observer can cryptographically link two credentials to the same person). It does *not* provide *transaction graph privacy*: Ethereum balances and transfer events are public, and standard chain-analysis techniques – timing correlation, amount matching, funding-source tracing – apply to BUCK as they do to any ERC-20 token.

Transaction graph privacy is a distinct problem solved by different primitives (confidential transactions, mixing protocols, or fully shielded transfers as in Zcash). These are orthogonal to the identity layer and could complement it in the future. The identity system’s guarantee is narrower but sufficient: even if Eve links Alice’s addresses through behavioral analysis, she cannot learn Alice’s *name* or *identity data* from any on-chain artifact. The cryptographic identity layer ensures that linking addresses reveals spending patterns, not people.

2.7 Attack 7: Alice Uses a Revoked or Expired Credential

2.7.1 Scenario

Alice’s identity credential was revoked by the issuer (e.g., her Alberta residency expired, fraud was detected in her original KYC documents, or she is subject to new sanctions). Alice still holds her old `E_alice` and `sigma` and attempts to continue transacting.

2.7.2 Why It Fails

The IdentityRegistry tracks credential validity. When the issuer revokes Alice’s credential:

```
identityRegistry.revokeIdentity(alice_address)
```

Subsequent calls to `isVerified(alice)` return false. Alice’s `approve` call – and any `transfer` or `transferFrom` – reverts at the identity check, before the Chaum-Pedersen proof is even evaluated.

Alice’s old credential and proofs remain mathematically valid (the cryptography is eternal), but the contract refuses to accept them because her registration is no longer active. The revocation is a separate on-chain state, controlled by the trusted issuer.

2.7.3 What the Contract Sees

`isVerified(alice) == false`. Transaction reverts immediately. The still-valid-but-revoked credential is never consulted.

2.8 Attack 8: Unwitting Bob Receives a Transaction From Criminal Alice

2.8.1 Scenario

Bob is a law-abiding merchant running a BUCK-accepting storefront. Alice is a criminal who passed KYC (perhaps before she was sanctioned, or under a jurisdiction that has not yet flagged her). Alice sends BUCK to Bob through a normal transaction. Bob has no way to know Alice is a criminal at the time of the transaction.

Later, authorities investigate Alice. Bob is concerned: did he unknowingly participate in money laundering? Can Alice's identity in the receipt exonerate him?

2.8.2 Why the Scheme Protects Bob

Bob received Alice's re-encrypted identity `E_bob` during the `approve` handshake (or Bob pre-approved Alice via `approve(alice, 0, ...)` to receive from her). The Chaum-Pedersen proof verified on-chain, so `E_bob` provably contains Alice's real, issuer-certified identity.

When authorities investigate:

1. Bob decrypts `E_bob` and produces Alice's identity `I`.
2. The on-chain proof record establishes that `I` is genuine (not something Bob fabricated to frame Alice, and not something Alice fabricated to deceive Bob).
3. Bob can demonstrate he had no way to know Alice was a criminal: the identity he received was a valid, PS-verified credential at the time of the transaction. The revocation (if any) came later.
4. Bob's good faith is supported by the cryptographic record: he accepted a transaction from a verified participant and holds a court-presentable receipt.

The system protects honest participants by creating a tamper-proof record of who they transacted with. Bob is not liable for Alice's criminality; he is protected by the same cryptographic chain that convicts Alice.

2.8.3 What the Court Sees

Bob holds a provably genuine receipt. Alice's identity was valid at transaction time. Bob acted in good faith. The receipt is evidence of Bob's compliance, not his complicity.

2.9 Attack 9: Systematic Forgery – Alice Attacks the Trust Chain

The previous attacks target individual operations. This attack assumes Alice is willing to lie about *every* artifact she produces – hashes, proofs, signatures, ciphertexts – and asks whether she can deceive anyone about the validity or content of her identity.

The trust chain has three links. We attack each one.

2.9.1 Link 1: PS Signature (Issuer Authority)

Alice has $(m, \text{sigma}_1, \text{sigma}_2)$ from the issuer. She produces $\text{sigma}' = (t * \text{sigma}_1, t * \text{sigma}_2)$.

Can she produce a sigma' that signs a different m_{fake} ?

PS verification checks:

$$e(\text{sigma}'_1, X + m * Y) = e(\text{sigma}'_2, g_2)$$

Rearranging:

$$e(\text{sigma}'_1, Y)^m = e(\text{sigma}'_2, g_2) * e(\text{sigma}'_1, X)^{-1}$$

The right side is fixed by sigma' (which Alice chose). The left side is determined by m . For sigma' derived from the issuer's signature on m , this equation holds only for the real m . Alice cannot produce a valid PS signature on any m_{fake} without the issuer's secret key (x, y) . **Blocked by q-SDH unforgeability.**

2.9.2 Link 2: NIZK Proof (Binding PS Signature to ElGamal Ciphertext)

Alice provides $(\text{sigma}', E_{\text{new}}, \text{pk}_{\text{new}}, \text{pi})$. The NIZK proof proves knowledge of (m, r) satisfying:

- a) $e(\text{sigma}'_1, X + m * Y) = e(\text{sigma}'_2, g_2)$ -- sigma' signs m
- b) $C = m * G + r * \text{pk}_{\text{new}}$ -- E_{new} encrypts m
- c) $R = r * G$ -- consistent randomness

Can she use a valid sigma' (signing m) but create E_{new} encrypting m_{fake} ?

The sigma protocol uses a single response scalar s_m that must simultaneously satisfy conditions (a) and (b):

- For condition (a): s_m encodes the real m (the value sigma' signs)
- For condition (b): s_m encodes whatever is in E_{new}

If E_{new} encrypts $m_{\text{fake}} \neq m$, no single s_m satisfies both checks. **Blocked by sigma protocol soundness.**

Can she forge the Fiat-Shamir challenge? The challenge $e = H(\text{sigma}', E_{\text{new}}, \text{pk}_{\text{new}}, \text{commitments})$ depends on all public inputs. Finding inputs that yield a favorable challenge requires a keccak256 preimage attack. **Blocked by random oracle assumption.**

2.9.3 Link 3: Chaum-Pedersen Proof (Binding Re-encryption to Registered Credential)

At `approve()` time, Alice provides `E_bob` and a Chaum-Pedersen proof. The contract reads `E_alice` from storage.

Can she re-encrypt a different identity? The proof requires:

$$C_a - sk_alice * R_a = C_b - r_b * pk_bob$$

Both sides must equal the same message point $M = m * G$. If Alice encrypts `M_fake` $\neq M$, the equation is unsatisfiable. **Blocked by DLog hardness.** (Same mathematics as Attack 1.)

Can she supply a different `E_alice`? No – read from storage, not from calldata.

2.9.4 Critical Edge Case: The Trivial Signature

If Alice sets `sigma' = (0, 0)` where 0 is the point at infinity:

$$\begin{aligned} e(0, X + m * Y) &= 1 && \text{(pairing with identity is trivial)} \\ e(0, g_2) &= 1 && \text{(same)} \end{aligned}$$

The pairing equation $1 = 1$ holds **for any** `m`. Alice could register a credential encrypting any `m_fake` she wants, produce a valid-looking NIZK proof (because condition (a) is trivially satisfied), and the verification would pass.

She achieves this by picking `t = 0` in the rerandomization: `sigma' = (0 * sigma_1, 0 * sigma_2) = (0, 0)`.

The fix is standard: the PS signature specification requires `sigma'_1 != 0`. The registration contract must check this before evaluating the pairing:

```
require(sigma_prime[0] != 0 || sigma_prime[1] != 0, "Degenerate signature");
```

On BN254, `G_1` has prime order (cofactor 1), so there are no small-order points. The identity check `sigma'_1 != 0` is the *only* degenerate case.

Without this check, the entire fountain is broken. With it, the system is sound.

2.9.5 Additional Attack Surfaces

Off-curve points: post-Istanbul, the `ecPairing` precompile validates that inputs lie on `alt_bn128` and reverts otherwise. Alice cannot use off-curve points to confuse the pairing computation.

Subgroup attacks on `G_2`: the `ecPairing` precompile validates `G_2` subgroup membership (EIP-197). Alice cannot exploit small subgroups in the twist curve.

Eve copies Alice's registered credential: Eve can read `(pk, E, sigma', pi)` from the chain and re-register it for her own address. But Eve cannot *use* it – the Chaum-Pedersen proof requires knowledge of `sk_alice` (condition 1: `pk_alice = sk_alice * G`). A stolen credential is useless without the corresponding secret key.

Alice shares raw credential material: Alice can give (m, σ) to an accomplice, who can then derive valid credentials containing Alice's identity. But the decrypted identity is always Alice's – the consequences fall on her. This is inherent in any bearer credential system; it is no different from handing someone your driver's license.

2.9.6 Verdict

The system is sound against an untrustworthy Alice who is willing to lie about every artifact she produces. She cannot forge any artifact that would cause a verifier to accept a false identity. The three layers – PS unforgeability, NIZK soundness, Chaum-Pedersen soundness – chain together so that breaking any link requires breaking a standard hardness assumption.

One critical implementation requirement: $\sigma'_1 \neq 0$ must be checked at credential registration. This is a standard requirement of the Pointcheval-Sanders scheme and costs negligible gas.

2.10 Summary: Why the Scheme Defeats All Attacks

Every attack that involves substituting false identity data fails for the same fundamental reason: the Chaum-Pedersen proof is **sound**. A valid proof for a false statement does not exist.

The proof asserts:	E_bob encrypts the same M as E_alice
The contract reads:	E_alice from the registry (PS-verified, immutable)
Therefore:	E_bob must encrypt Alice's real identity
Alice cannot:	supply a different E_alice (contract reads from storage)
Alice cannot:	produce a valid proof for different M (soundness)
Alice cannot:	forge the issuer's PS signature (q-SDH unforgeability)
Alice cannot:	link her accounts to each other (PS rerandomization)
Bob cannot:	produce a different plaintext (ElGamal decryption is deterministic)
Eve cannot:	decrypt E_bob (she lacks sk_bob)
Eve cannot:	link Alice's accounts (statistical unlinkability)

Three independent hardness assumptions protect the system:

1. **PS signature unforgeability** (q-SDH assumption): prevents forged credentials
2. **Discrete logarithm hardness** (alt_bn128): prevents false Chaum-Pedersen proofs and unauthorized ElGamal decryption
3. **ECDSA unforgeability** (secp256k1): authenticates Ethereum transactions

All three assumptions also underpin Ethereum itself. If any breaks, Ethereum's own security fails first – the Alberta Buck identity system does not introduce any novel cryptographic assumptions.

3 Identity Visibility Modes

Mode	What on-chain reveals	What off-chain reveals
Anonymous-valid (private)	Address is verified (bit) isVerified(addr) == true	Encrypted receipt: identities of both parties, decryptable only by participants + optional regulatory escrow key. Requires bilateral approve for transfer.
Public	Address is verified + public identity claim (plaintext) isPublic(addr) == true	Full name, jurisdiction, credentials, track record – world-readable. No approve needed – counterparties already have this account’s identity.
Contract	Contract address is verified; linked to deployer’s identity	Deployer’s identity is the contract’s identity; receipts encrypted to deployer
Permissionless	No identity check	N/A

4 Operations Table

4.1 Core BUCK (ERC-20) Operations

Operation	Caller identity	Counterparty identity	Receipt	Notes
mint	Anonymous-valid KYC (topic 1)	N/A (self-mint)	Event log	Caller must hold BuckCredits; identity verified but not disclosed on-chain
burn	Anonymous-valid KYC (topic 1)	N/A (self-burn)	Event log	Reduces outstanding balance
transfer	Anonymous-valid KYC (topic 1)	Anonymous-valid KYC (topic 1)	Encrypted 3-party	Both parties verified; receipt encrypted 3-party ECDH (no unilateral decryption)
transferFrom	Anonymous-valid KYC (topic 1)	Anonymous-valid KYC (topic 1)	Encrypted 3-party	Spender verified; owner and recipient identities in encrypted receipt
approve	Anonymous-valid KYC (topic 1)	Anonymous-valid KYC (topic 1)	Event log	Approving a spender for transferFrom

4.2 BuckCredit (ERC-721) Operations

Operation	Caller identity	Counterparty identity	Receipt	Notes
createCredit	Public KYC + insurer (42)	Anonymous-valid KYC (topic 1)	Encrypted to parties	Insurer MUST be publicly identified (their reputation backs the credit) Client may be anonymous-valid
activate	Anonymous-valid KYC (topic 1)	N/A (self)	Event log	Credit owner activates portfolio
updateCredit	Public KYC + insurer (42)	N/A	Event log	Insurer updates params; mutual reappraisal is a public commitment
transfer (NFT)	Anonymous-valid KYC (topic 1)	Anonymous-valid KYC (topic 1)	Encrypted 3-party	Transferring insurance NFT inherits the credit

4.3 BuckKController (PID Stabilization)

Operation	Caller identity	Receipt	Notes
<code>compute</code>	Permissionless	Event log	Anyone can trigger PID update; minter pays gas. No identity needed.
<code>setGains</code>	Governance	Event log	Governance multisig or vote result. Governance members publicly identified.
<code>addBasketComponent</code>	Governance	Event log	Adding a new commodity to the basket.
<code>setDT</code>	Governance	Event log	Changing the PID update interval.

4.4 Oracle Operations

Operation	Caller identity	Receipt	Notes
Submit claim	Public KYC + reporter (43)	Public log	"I, Perry Kundert, claim Gold was \$2905 at block 19400000." Public identity is the entire point: reputation accrues.
Commit value (L1)	Public KYC + reporter (43)	Event log	Authorized reporters sign the commitment. Signatures are publicly verifiable.
Challenge/dispute	Anonymous-valid KYC (topic 1)	Evidence on-chain	Challenger need not be public; the evidence speaks for itself.
Governance vote (oracle selection)	Anonymous-valid KYC (topic 1)	Vote record	Stake-weighted vote on oracle selection. Vote weight from Buck holdings is public; voter identity may be private.

4.5 DeFi Integration (Uniswap, Lending, etc.)

Operation	Caller identity	Contract identity	Receipt	Notes
Create pool (BUCK/USDT)	Public KYC (topic 1)	Contract registered to deployer's identity	Event log	Pool deployer is publicly identified. Contract address linked to deployer's ElGamal credential in Identity.
Swap BUCK -> USDT	Anonymous-valid KYC (topic 1)	Contract (deployer)	Encrypted 3-party	User sends BUCK to pool. Receipt: user + deployer
Swap USDT -> BUCK	Anonymous-valid KYC (topic 1)	Contract (deployer)	Encrypted 3-party	Pool sends BUCK to user.
Add liquidity	Anonymous-valid KYC (topic 1)	Contract (deployer)	Encrypted 3-party	User transfers BUCK to pool.
Remove liquidity	Anonymous-valid KYC (topic 1)	Contract (deployer)	Encrypted 3-party	Pool transfers BUCK to user.

4.6 Identity Management

Operation	Caller identity	Issuer identity	Receipt	Notes
KYC ceremony	Self	Trusted issuer	Off-chain	Participant submits docs to issuer
	(no claims yet)	(publicly identified)	PS sig	issuer PS-signs identity scalar.
Register in registry	Self	N/A	Event log	Derives credential offline; registers with PS signature + NIZK proof
Add public identity claim	Self	Trusted issuer	On-chain	Opts in to public identification.
	KYC (topic 1)	(publicly identified)	claim	Exempts counterparties from approval
Revoke claim	Issuer or self	N/A	Event log	Removes a claim (e.g., expired license)
N/M recovery	N-of-M parties	N/A	On-chain	Transfers identity to new address
	(all identified)		+ off-chain	N of M designated parties agree

5 Contract Identity: How DeFi Pools Become BUCK Counterparties

A Uniswap pool contract is just an address. For BUCK transfers to/from that address to pass `isVerified`, the contract must have an identity in the IdentityRegistry. But a contract can't do KYC. The solution:

The pool deployer's identity becomes the contract's identity.

When someone creates a BUCK/USDT Uniswap pool:

1. Deployer (a verified BUCK participant) calls the Uniswap factory to create the pool. The factory deploys a new contract at a deterministic address.
2. Deployer derives a separate credential for the pool contract (from the same PS-signed identity, via the Identity Fountain) and registers it: `identityRegistry.registerCredential(poolAddress, pk_deployer, E_deployer, sigma', pi)`
This links the pool contract's address to the deployer's credential. The pool inherits the deployer's verified identity.
3. Now `isVerified(poolAddress)` returns true. BUCK transfers to/from the pool pass the identity check.
4. When a user calls `approve` for the pool, the Chaum-Pedersen proof is verified against the pool's credential (which is the deployer's credential). The deployer's identity becomes the counterparty identity in all encrypted receipts.

This means: if you deploy a BUCK DeFi pool, you are the identified legal operator. Your identity is on the line for every transaction through that pool. If a court subpoenas you, you can be compelled to decrypt the ElGamal ciphertexts (because your identity private key was used for the pool's identity exchange handshakes).

6 On-Chain Integration: Receipts and Transfer Flow

The cryptography is sound. The question is where it meets the EVM – a machine that hides nothing.

6.1 The Receipt Constraint

Events are public. Every `emit` on Ethereum is readable by every node. A naive design that emits identity addresses or public keys in receipt events creates a permanent, public, linkable identity graph of every BUCK transfer – defeating the entire privacy model.

The constraints that drive the on-chain design:

1. **The EVM is transparent:** every contract execution, every storage slot, every emitted event is publicly reconstructible. The BUCK contract cannot hold decrypted identity data, even transiently.
2. **The contract must verify, not learn:** the BUCK contract enforces `isVerified` and verifies Chaum-Pedersen proofs. It confirms that a re-encrypted identity ciphertext is genuine. It never learns the identity itself.
3. **DeFi timing:** in a `transferFrom` call, the Uniswap router cannot pass receipt data. Identity exchange must happen earlier, at `approve` time.

The ElGamal Chaum-Pedersen approach resolves all three. The contract reads `E_alice` from the `IdentityRegistry` (not from `calldata`), verifies a compact Chaum-Pedersen proof (~29,000 gas), stores a hash of the re-encrypted ciphertext, and emits only opaque curve point coordinates. No identity content touches the EVM in any form.

6.2 The approve Function as Identity Handshake

The ERC-20 `approve` function is the natural point for identity exchange. Alice is directly calling the BUCK contract – she can provide the re-encrypted ElGamal ciphertext and the Chaum-Pedersen proof:

```
function approve(
    address spender,
    uint256 amount,
    uint256[4] calldata E_spender,          // ElGamal ciphertext (R.x, R.y, C.x, C.y)
    uint256[3] calldata chaumPedersen       // Fiat-Shamir proof (e, s1, s2)
) public returns (bool) {
    _approve(msg.sender, spender, amount);

    // Read the caller's registered credential from the registry
    // CRITICAL: read from storage, never from calldata
    uint256[4] memory E_caller = identityRegistry.getCredential(msg.sender);
    uint256[2] memory pk_caller = identityRegistry.getIdentityKey(msg.sender);
    uint256[2] memory pk_spender = identityRegistry.getIdentityKey(spender);

    // Verify Chaum-Pedersen proof: E_spender encrypts same M as E_caller
    require(
        _verifyChaumPedersen(
```

```

        E_caller, E_spender, pk_caller, pk_spender, chaumPedersen
    ),
    "Re-encryption proof invalid"
);

// Store hash of the verified re-encrypted ciphertext for this pair
_receiptFragments[msg.sender][spender] = keccak256(
    abi.encodePacked(E_spender)
);

// Emit ONLY the opaque ElGamal ciphertext (4 uint256 curve coordinates)
emit IdentityExchange(msg.sender, spender, E_spender);
return true;
}

```

What the public sees in the `IdentityExchange` event:

- Alice's address approved a spender (same as standard ERC-20 Approval)
- Four `uint256` values encoding an ElGamal ciphertext – opaque curve point coordinates that only the spender can decrypt
- **No** identity address, **no** public key, **no** linkable identifier

What the contract verified (in ~29,000 gas):

- The ciphertext contains Alice's real identity (Chaum-Pedersen proof passed against the registered credential read from the registry)

What the spender (Bob / pool operator) can do:

- Decrypt `E_bob` using `sk_bob`: $M = C_b - sk_bob * R_b$
- Receive `identity_data` from Alice via Holochain (encrypted for Bob)
- Verify authenticity: $H(identity_data) * G == M$ (binds off-chain data to the on-chain proof chain)
- Store verified identity for receipt construction on Holochain

6.2.1 Bilateral Identity Exchange

The `transfer` and `transferFrom` functions require that *both* parties' identities are available to each other. For private accounts, this means both must call `approve`:

```

// Alice (private) wants to transact with Bob (private):
// Step 1: Alice approves Bob -- re-encrypts her identity for Bob
buck.approve(bob, amount, E_alice_for_bob, chaumPedersenProof)

```

```
// Step 2: Bob approves Alice -- re-encrypts his identity for Alice
buck.approve(alice, 0, E_bob_for_alice, chaumPedersenProof)
// Amount = 0: no spending authorization, just identity exchange
```

Both identity fragments must exist before BUCK can move. If Bob is a **public** account (e.g., a Uniswap pool operator), step 2 is unnecessary: `isPublic(bob) == true` satisfies the bilateral check, and Alice can look up Bob's `identity_data` directly from the IdentityRegistry.

This means a public pool operator receives BUCK from any verified private account that has done a single **approve** – no per-counterparty setup on the pool's side. Two public accounts can **transfer** with no **approve** at all – a standard ERC-20 transfer with identity verification.

6.3 Receipt Construction: What the Contract Emits

The BUCK contract emits a **minimal** event that reveals only pseudonymous addresses (which the ERC-20 **Transfer** event already reveals) plus a reference to the pre-stored identity fragments:

```
event BuckTransferReceipt(
    address indexed from,
    address indexed to,
    uint256 amount,
    bytes32 fromIdentityHash, // keccak256 of from's ElGamal ciphertext for to
    bytes32 toIdentityHash    // keccak256 of to's ElGamal ciphertext for from
);
```

The `fromIdentityHash` and `toIdentityHash` are keccak256 hashes of the opaque ElGamal ciphertexts stored during **approve**. They add **no linkability** beyond what the **Transfer** event already provides (the addresses are the same in both events).

The actual re-encrypted identity ciphertexts are retrievable:

- From the **IdentityExchange** events (emitted during **approve**)
- From Holochain (stored on the participants' source chains)

Only the counterparty (who has the identity private key to decrypt the ElGamal ciphertext) can recover the plaintext identity.

6.3.1 Canonical Receipts and Public Accounts

Both parties in a transfer hold each other's plaintext `identity_data` (either from **approve** + Holochain, or from the public IdentityRegistry). Both hold the transfer data (from the on-chain event). If the receipt format is canonical (deterministic field order, encoding), either party can independently construct the identical receipt and compute `H(receipt)`. The receipts match without coordination.

The receipt model varies by visibility mode:

Sender	Receiver	Receipt construction
Public	Public	Fully on-chain. Reconstructable by anyone from Transfer event + public IdentityRegistry entries. No off-chain component.
Public	Private	Private identity delivered via Holochain. Both parties construct canonical receipt off-chain.
Private	Private	Both identities delivered via Holochain. Both parties construct canonical receipt off-chain.

For transfers involving private accounts, the contract cannot compute $H(\text{receipt})$ because it never sees plaintext identities. The on-chain `BuckTransferReceipt` event provides anchoring data (the ElGamal ciphertext hashes from `approve`) that binds the off-chain receipt to the on-chain transfer.

For two public accounts, no receipt hash is needed: every input to the receipt is already public on-chain. The transfer is a standard ERC-20 `transfer` with identity verification – no Holochain wallet, no off-chain coordination required.

6.4 The Complete transfer / transferFrom Flow

```
function transfer(address to, uint256 amount) public override returns (bool) {
    require(identityRegistry.isVerified(msg.sender), "Sender not verified");
    require(identityRegistry.isVerified(to), "Receiver not verified");
    require(compliance.canTransfer(msg.sender, to, amount), "Compliance");

    // Bilateral identity exchange: each party's identity must be
    // available to the other -- via approve() or public registration.
    require(
        identityRegistry.isPublic(msg.sender)
        || _receiptFragments[msg.sender][to] != 0,
        "Sender identity not available to receiver"
    );
    require(
        identityRegistry.isPublic(to)
        || _receiptFragments[to][msg.sender] != 0,
        "Receiver identity not available to sender"
    );

    _transfer(msg.sender, to, amount);
    compliance.transferred(msg.sender, to, amount);

    // Emit minimal receipt -- no identity data, just hashes of
    // pre-stored re-encrypted ElGamal ciphertexts
```

```

emit BuckTransferReceipt(
    msg.sender, to, amount,
    _receiptFragments[msg.sender][to],
    _receiptFragments[to][msg.sender]
);

return true;
}

```

The bilateral identity check enforces that both parties' identities are available to their counterpart before any BUCK can move. A **public** account (pool operator, insurer) is exempt from the **approve** requirement because its **identity_data** is already world-readable in the IdentityRegistry. This gives four transfer modes:

Sender	Receiver	Approvals needed
Private	Private	Both approve each other
Private	Public	Only sender approves receiver
Public	Private	Only receiver approves sender
Public	Public	None – standard ERC-20 transfer

For two public accounts, the transfer is a plain ERC-20 **transfer** with identity verification – no Holochain wallet, no Chaum-Pedersen proofs, no off-chain coordination. All identity data is already on-chain.

The **transferFrom** path applies the same bilateral check. The receipt fragment hashes were stored during **approve**, so no additional identity data passes through the DeFi router. The Chaum-Pedersen proof was verified once (at **approve** time); subsequent transfers emit only the minimal receipt event (~2,000 gas).

6.5 Holochain: Off-Chain Computation and Storage

Alice's wallet (a Holochain hApp) performs all credential derivation and transaction preparation:

- **Credential derivation:** Alice's PS-signed identity (**m**, **sigma**) lives on her Holochain source chain. For each new account, the hApp rerandomizes the PS signature, generates a fresh key pair, creates an ElGamal encryption, and computes the NIZK proof. This runs entirely offline and can be batched – Alice can pre-generate credentials for future accounts.
- **Identity data storage:** Alice's plaintext **identity_data** is stored as a **Private entry** on her Holochain source chain, encrypted with her agent key and never published to the DHT. Only Alice's own agent can read it. This is the master copy from which **m** = **H(identity_data)** can always be recomputed.
- **Credential storage:** Each derived credential (**pk**, **E_alice**, **sigma'**, **pi**, **sk**) is also stored as a Private entry on the agent's source chain. The identity private key

`sk` (an `alt_bn128` scalar) is stored alongside the credential. The ElGamal ciphertext binds `m` to the credential; the plaintext `identity_data` that gives `m` meaning lives only in the Private entry, never on Ethereum.

- **Identity data delivery** (the data channel): When Alice re-encrypts her identity for Bob, her hApp also sends `identity_data` to Bob's hApp via Holochain, encrypted under Bob's Holochain agent public key. Bob's hApp decrypts it, computes $H(\text{identity_data}) * G$, and checks equality with `M` recovered from the on-chain ElGamal ciphertext. This verification binds the off-chain plaintext to the on-chain proof chain. The Holochain data channel carries the content; the Ethereum proof chain guarantees its authenticity.
- **Re-encryption**: The hApp decrypts `E_alice` locally (Alice has `sk_alice`), extracts the message point `M`, and re-encrypts for Bob: $E_{\text{bob}} = (r' * G, r' * pk_{\text{bob}} + M)$. This is 2 scalar multiplications and 1 point addition – milliseconds on any device.
- **Proof generation**: The Chaum-Pedersen proof is a Schnorr-family sigma protocol. Generation requires 2 scalar multiplications and 1 hash – instantaneous on any modern device. Unlike Groth16 SNARK proofs (which require minutes of circuit evaluation and a trusted setup ceremony), Chaum-Pedersen proof generation is negligible.
- **Receipt storage**: Full encrypted receipts (with decrypted identity details, transaction metadata, purpose) are stored on both parties' Holochain source chains. The on-chain `BuckTransferReceipt` event provides only an anchor hash.

6.5.1 Agent Isolation Model

Alice does not reuse a single Holochain agent across multiple BUCK accounts. For each Ethereum address she creates, her wallet application spawns a new Holochain agent:

- A fresh Holochain key pair (Ed25519) is generated.
- A new source chain is initialized.
- The hApp DNA is the same (same code, same hash), but the agent identity is distinct.
- Alice copies her `identity_data` into the new agent's Private store and derives a credential from it (rerandomizing her PS signature, generating a fresh `alt_bn128` key pair, encrypting via ElGamal, computing the NIZK proof).

Why agent isolation matters: Holochain's DHT uses agent public keys as identifiers. If Alice used a single Holochain agent for all her BUCK accounts, a DHT observer could correlate them: "agent X stored credentials for addresses `addr_1`, `addr_2`, `addr_3`." With separate agents, each agent's DHT presence is independent. No Holochain observer can link `Alice_1` to `Alice_2`, just as no Ethereum observer can link `addr_1` to `addr_2`.

Practical operation: Alice’s wallet application (a Holochain Launcher or custom conductor) manages multiple agent instances internally. From Alice’s perspective, she sees a unified wallet with multiple accounts. Under the hood, each account is a separate Holochain agent with its own source chain. The wallet stores a master seed (protected by Alice’s passphrase or biometrics) from which all agent keys are deterministically derived, allowing backup and recovery without storing raw keys.

What is NOT shared across agents: Holochain key pairs, source chain entries, Ethereum addresses, alt_bn128 identity key pairs, ElGamal ciphertexts, PS signature rerandomizations, NIZK proofs. **What IS shared** (locally, within Alice’s wallet, never on any network): Alice’s plaintext `identity_data` and the master PS signature (`m`, `sigma`) from the issuer.

Holochain provides agent-centric, cryptographically auditable storage: the hApp DNA is identified by hash, so anyone can verify the exact code that runs on each participant’s node. However, Holochain is **not** the trust anchor: Alice runs her own node and could run modified code. The on-chain verifications are the trust anchors – PS signature verification at registration and Chaum-Pedersen proof verification at transaction time are mathematically verifiable on-chain regardless of what software generated them. Holochain provides the execution environment; the proofs provide the guarantees.

6.6 Summary: What Each Layer Sees

Layer	What it sees
Ethereum (everyone)	<code>Transfer(from, to, amount)</code> – pseudonymous addresses <code>BuckTransferReceipt</code> – same addresses + opaque hashes <code>IdentityExchange</code> – address + opaque ElGamal ctxt Chaum-Pedersen proof verified (pass/fail) – no content
BUCK contract	<code>isVerified(from) == true, isVerified(to) == true</code> Chaum-Pedersen proof of re-encryption correctness keccak256 of re-encrypted ElGamal ciphertext (stored) Never sees plaintext identity
Counterparty (Bob)	Decrypts ElGamal ciphertext -> learns Alice’s identity Constructs full receipt on Holochain
Sender (Alice)	Knows her own identity, knows Bob’s (from his approve) Constructs full receipt on Holochain
Holochain hApp	Derives credentials (PS rerandomization + NIZK) Re-encrypts credential + generates proof locally Stores encrypted receipts on source chains Code identified by DNA hash (auditable)
Court (with subpoena)	Compels Bob to decrypt his ElGamal ciphertext On-chain proof record authenticates the decrypted result

7 Cryptographic Receipts: 3-Party ECDH

The BUCK contract emits minimal on-chain receipt events (previous section). The wallet layer (Holochain hApp) constructs full receipts with decrypted identity details, then encrypts them via 3-party ECDH so that only the participants can decrypt.

7.1 The Three Keys

For a transfer from Alice to a DeFi pool operated by Bob:

Key	Held by	Purpose
<code>k_s</code> (sender)	Alice	Sender's identity private key (alt_bn128)
<code>k_e</code> (ephemeral)	Deterministic	Derived from hash of on-chain receipt event; reproducible by anyone who knows the event
<code>K_r</code> (receiver)	Bob (deployer)	Receiver's identity public key (from registry)

The ephemeral key `k_e` is derived deterministically from the on-chain receipt event data (which is immutable and publicly verifiable):

```
// All fields are from the on-chain BuckTransferReceipt event:
receipt_anchor = abi.encode(
    from, to, amount,
    fromIdentityHash, toIdentityHash,
    block.number
)
k_e = keccak256(receipt_anchor) // deterministic "private key"
```

Note: `receipt_anchor` contains only pseudonymous addresses and opaque hashes – no identity content. The identity public keys `K_s` and `K_r` are looked up from the IdentityRegistry (on-chain, public), not emitted in events.

7.2 Encryption Scheme

The wallet (Holochain hApp) computes the encryption key via ECDH:

```
// Alice's hApp computes (knows k_s, k_e; looks up K_r from registry):
K_r = identityRegistry.getIdentityKey(to) // Bob's identity public key
shared_1 = ECDH(k_s, K_r) // sender-receiver shared secret
shared_2 = ECDH(k_e, K_r) // ephemeral-receiver shared secret
encryption_key = keccak256(shared_1 || shared_2)

// Construct the full receipt with decrypted identity data:
full_receipt = {
    from, to, amount, block.number, tx_hash, // from on-chain event
    sender_identity: decrypt(E_alice), // from Alice's source chain
    receiver_identity: decrypt(E_bob_for_alice), // from Bob's approve
```

```

    purpose: "Uniswap V3 BUCK->USDT swap"
}

```

```

// Encrypt:
ciphertext = AES-GCM(encryption_key, encode(full_receipt))

```

The encrypted receipt is stored on Holochain (both parties' source chains). A commitment hash can optionally be emitted on-chain to anchor the receipt:

```

event ReceiptCommitment(
    bytes32 indexed transferHash,    // hash of the BuckTransferReceipt event
    bytes32 receiptHash             // hash of the encrypted full receipt
);

```

7.3 Who Can Decrypt

7.3.1 Sender (Alice)

Alice has k_s (her identity private key) and can recompute k_e from the on-chain receipt event:

```

k_e = keccak256(receipt_anchor)    // deterministic from on-chain data
K_r = identityRegistry.getIdentityKey(to) // look up receiver's key
shared_1 = ECDH(k_s, K_r)          // she has k_s
shared_2 = ECDH(k_e, K_r)          // she has k_e
encryption_key = keccak256(shared_1 || shared_2)

```

7.3.2 Receiver / Pool Operator (Bob)

Bob has k_r (his identity private key) and looks up Alice's identity public key from the registry:

```

K_e = G * k_e                      // computable: k_e from receipt anchor
K_s = identityRegistry.getIdentityKey(from) // Alice's identity public key
shared_1 = ECDH(k_r, K_s)          // he has k_r
shared_2 = ECDH(k_r, K_e)          // he has k_r
encryption_key = keccak256(shared_1 || shared_2)

```

7.3.3 Court-Compelled Decryption (Subpoena of Pool Operator)

A court subpoenas Bob to decrypt a specific transaction receipt:

```

// Court provides: the transaction hash
// Bob looks up: the BuckTransferReceipt event from that transaction
// Bob computes (using his identity private key k_r):
K_s = identityRegistry.getIdentityKey(from)

```

```

K_e = G * keccak256(receipt_anchor)
shared_1 = ECDH(k_r, K_s)
shared_2 = ECDH(k_r, K_e)
encryption_key = keccak256(shared_1 || shared_2)
receipt = AES-GCM-decrypt(encryption_key, ciphertext_from_holochain)

```

Bob reveals only the decrypted receipt. He never reveals k_r . He cannot decrypt receipts where he is not a party.

7.3.4 Regulatory Escrow (Optional)

A regulatory authority's public key K_{reg} adds a third shared secret:

```

shared_3 = ECDH(k_e, K_reg)
encryption_key = keccak256(shared_1 || shared_2 || shared_3)

```

The regulator can compute $shared_3$ (they have k_{reg} , and K_e is deterministic from the on-chain event). They can also compute $shared_2 = ECDH(k_e, K_r)$ since the ephemeral key k_e is deterministic from public on-chain data. But they cannot compute $shared_1 = ECDH(sk_{sender}, K_{receiver})$ – this requires the sender's or receiver's private key. Without a participant's cooperation, the regulator holds two of three ECDH components and cannot reconstruct the encryption key. No unilateral surveillance.

This is the deliberate design: a court compels a *participant* to decrypt; the escrow key merely lets the regulator *verify* the decryption (by independently recomputing the same key once a participant cooperates). Contrast with custodial key escrow, where the authority holds a master decryption key and can surveil at $O(1)$ cost. Here the cost is $O(N)$ – one subpoena per participant, per transaction.

8 Play-by-Play: BUCK/USDT Swap on Uniswap

Alice holds 1000 BUCK and wants to swap 500 BUCK for USDT. Bob has deployed a BUCK/USDT Uniswap V3 pool.

8.1 Prerequisites (One-Time Setup)

Alice:

1. Completed KYC with trusted issuer (off-chain ceremony)
2. Issuer PS-signs Alice's identity: $\sigma = PS.Sign(sk_{issuer}, m)$
where $m = H(identity_data)$
3. Alice receives (m, σ) and stores in Holochain wallet
4. Alice's wallet derives a credential for this account (offline):
 - Rerandomizes PS signature: $\sigma' = (t * \sigma_1, t * \sigma_2)$
 - Generates fresh identity key pair (sk_{alice}, pk_{alice})
 - Encrypts: $E_{alice} = (r * G, m * G + r * pk_{alice})$
 - Computes NIZK proof π linking σ' to E_{alice}

5. Registers on-chain (~235K gas):
`identityRegistry.registerCredential(
 alice_wallet, pk_alice, E_alice, sigma', pi)`
6. `identityRegistry.isVerified(alice_wallet) == true`

Bob (pool deployer):

1. Completed KYC (same ceremony as Alice)
2. Derived credential for his account (same offline process)
3. Credential registered in IdentityRegistry (~235K gas)
4. Created BUCK/USDT pool via Uniswap factory
 -> pool deployed at address 0xP00L
5. Derived and registered a separate credential for the pool
 (from same PS-signed identity, via the Identity Fountain):
`identityRegistry.registerCredential(
 0xP00L, pk_bob_pool, E_bob_pool, sigma'_pool, pi_pool)`
6. `identityRegistry.isVerified(0xP00L) == true`

8.2 The Swap Transaction

8.2.1 Step 1: Alice Approves the Router (Identity Handshake)

Alice's wallet (Holochain hApp) prepares the identity exchange locally, then Alice calls approve on the BUCK contract:

```
// 1. Off-chain (Holochain hApp on Alice's node -- milliseconds):
//   - Read E_alice from her source chain
//   - Decrypt:  $M = C_a - sk_{alice} * R_a$  (extract message point)
//   - Look up the pool operator's identity public key pk_bob
//   - Re-encrypt:  $E_{bob} = (r' * G, r' * pk_{bob} + M)$ 
//   - Generate Chaum-Pedersen proof:
//       "E_bob encrypts the same M as E_alice"
//       (2 scalar muls + 1 hash -- instantaneous)

// 2. On-chain:
buck.approve(
    uniswapRouter,           // spender
    500e18,                  // amount
    [R_b.x, R_b.y, C_b.x, C_b.y], // E_bob (ElGamal ciphertext)
    [e, s1, s2]              // Chaum-Pedersen proof
)
```

The BUCK contract:

1. Sets `allowance[alice][uniswapRouter] = 500e18`
2. Reads `E_alice` from IdentityRegistry (PS-verified, immutable)
3. Verifies Chaum-Pedersen proof: `E_bob` encrypts same `M` as `E_alice`

```

(4 ecMul + 4 ecAdd + 1 keccak256 = ~29,000 gas)
4. Stores keccak256(E_bob) in _receiptFragments[alice][0xP00L]
5. Emits IdentityExchange(alice, 0xP00L, E_bob)
   -- the event contains ONLY the opaque ElGamal ciphertext
   -- no identity address, no public key, no linkable identifier

```

This is the critical moment. Alice is directly calling the BUCK contract, so she can provide the re-encrypted ciphertext and proof. By the time `transferFrom` is called later (by the router), the verified identity fragment is already stored.

Note: the pool (0xP00L) is a **public** account – its `identity_data` is registered publicly in the IdentityRegistry. Alice’s wallet can look it up directly, so the pool does not need to call `approve` for Alice. The bilateral identity check in `transferFrom` passes because `isPublic(0xP00L) == true` satisfies the pool-side requirement.

8.2.2 Step 2: Alice Calls the Router

```

// Alice initiates the swap (standard Uniswap call -- no BUCK-specific data)
uniswapRouter.exactInputSingle(
    tokenIn:  BUCK,
    tokenOut: USDT,
    fee:      3000,           // 0.3% fee tier
    recipient: alice,
    amountIn: 500e18,
    amountOutMinimum: 490e6, // slippage protection
    sqrtPriceLimitX96: 0
)

```

No identity data passes through this call. The router is a standard Uniswap contract that knows nothing about BUCK identity.

8.2.3 Step 3: Router Calls BUCK.transferFrom (Minimal Receipt Emission)

Inside the router, the swap triggers:

```
buck.transferFrom(alice, 0xP00L, 500e18)
```

The BUCK contract executes (no identity data passes through the router):

```

function transferFrom(address from, address to, uint256 amount) ...
{
    _spendAllowance(from, msg.sender, amount);
    require(identityRegistry.isVerified(from), "Sender not verified");
    require(identityRegistry.isVerified(to),   "Receiver not verified");
    require(compliance.canTransfer(from, to, amount), "Compliance");

    _transfer(from, to, amount);
}

```

```

    compliance.transferred(from, to, amount);

    // Emit minimal receipt -- ONLY hashes of pre-stored ElGamal ciphertexts
    emit BuckTransferReceipt(
        from, to, amount,
        _receiptFragments[from][to],    // keccak256 of Alice's E_bob
        _receiptFragments[to][from]     // keccak256 of Bob's E_alice
    );

    return true;
}

```

What the public sees: the same from/to/amount as the standard ERC-20 Transfer event, plus two opaque hashes. No identity addresses. No public keys. No linkable identity information beyond the pseudonymous Ethereum addresses.

What the contract verified (during approve, earlier): the Chaum-Pedersen proof that Alice's re-encrypted ElGamal ciphertext encrypts the same identity as her registered credential.

8.2.4 Step 4: Wallet Constructs the Full Receipt (Off-Chain)

Alice's wallet (Holochain hApp) observes the `BuckTransferReceipt` event and the `IdentityExchange` events to construct the full receipt:

```

// 1. From on-chain events (trusted, immutable):
transfer_data = {from, to, amount, block.number, tx_hash}
receipt_hashes = {fromIdentityHash, toIdentityHash}

// 2. From IdentityExchange event (emitted during approve):
E_bob = Alice's re-encrypted identity for Bob (ElGamal ciphertext)

// 3. Alice already knows her own identity (she submitted it at KYC):
alice_identity = alice_identity_data    // local, never on-chain

// 4. From Bob's IdentityExchange (if Bob also did approve for Alice):
E_alice_from_bob = Bob's re-encrypted identity for Alice
M_bob = C_b' - sk_alice * R_b'    // Alice decrypts with her key
bob_identity_data = receive_via_holochain(bob) // off-chain data channel
assert H(bob_identity_data) * G == M_bob    // bind to on-chain proof

// 5. Construct full receipt with decrypted identities
full_receipt = {
    transfer:      transfer_data,
    sender_name:   alice_identity.name,    // "Alice Johnson"
    receiver_name: bob_identity.name,      // "Bob Smith, DeFi Ops Inc."
}

```



```

    operation:      "Uniswap V3 swap BUCK -> USDT",
    pool:           "0xPOOL",
    timestamp:      block.timestamp
}

// 6. Encrypt the full receipt with 3-party ECDH
//     (see Cryptographic Receipts section)
receipt_anchor = abi.encode(from, to, amount, receipt_hashes, block.number)
k_e = keccak256(receipt_anchor)
K_bob = identityRegistry.getIdentityKey(to) // look up from registry
shared_1 = ECDH(sk_alice, K_bob)
shared_2 = ECDH(k_e, K_bob)
encryption_key = keccak256(shared_1 || shared_2)
ciphertext = AES-GCM(encryption_key, encode(full_receipt))

// 7. Store on Holochain (both parties' source chains)
holochain.store(alice_chain, ciphertext)
holochain.store(bob_chain, ciphertext)

```

8.2.5 Step 5: Pool Executes the Swap

The Uniswap pool sends USDT to Alice. Since USDT is not an Alberta Buck token, the USDT transfer has no BUCK identity requirements (it follows whatever rules USDT imposes, which is typically none).

8.2.6 Step 6: Completed State

On-chain (public):

- ERC-20 Transfer event: `alice_addr -> 0xPOOL, 500 BUCK`
- `BuckTransferReceipt`: same addresses + two opaque bytes32 hashes
- `IdentityExchange` (from approve): `alice_addr + opaque ElGamal ciphertext`
- Swap event: `BUCK/USDT pool, 500 BUCK in, ~495 USDT out`
- Chaum-Pedersen proof verified (29K gas, no identity content leaked)

Off-chain (Holochain, encrypted):

- Full encrypted receipt on Alice's and Bob's source chains
- Alice's re-encrypted identity (ElGamal ciphertext, only Bob can decrypt)
- Bob's re-encrypted identity (ElGamal ciphertext, only Alice can decrypt)
- PS-signed identity on issuer's source chain (audit trail)

What anyone can see:

- Two pseudonymous addresses transacted 500 BUCK
- Both addresses pass `isVerified` (they are KYC'd participants)
- Opaque ElGamal ciphertexts and hashes (indistinguishable from random)
- A Chaum-Pedersen proof was verified (the ciphertexts are genuine)

What Alice can see:

- Her own identity (trivially)
- Bob's identity (decrypt his ElGamal ciphertext with her key)
- Full receipt with names, amounts, purpose

What Bob can see:

- His own identity (trivially)
- Alice's identity (decrypt her ElGamal ciphertext with his key)
- Full receipt with names, amounts, purpose

What a court can compel (via subpoena of Bob):

- Bob decrypts Alice's ElGamal ciphertext for the specific transaction
- On-chain Chaum-Pedersen proof record authenticates the result
- Reveals Alice's identity for that one receipt
- Bob never reveals his private key

What the public CANNOT see:

- Alice's real name or identity details
- Bob's real name (as pool operator)
- Any linkable identity across transactions
- The purpose or terms of the transaction

9 Edge Cases and Design Considerations

9.1 Flash Loans and Atomic Transactions

A flash loan borrows and repays in a single transaction. The borrower's address must be verified, and the lending contract must be registered. The receipt covers the full borrow-repay cycle as a single atomic event.

9.2 Multi-Hop Swaps

A swap routed through BUCK -> WETH -> USDT involves two BUCK transfers (BUCK -> pool1, pool1 -> pool2 if intermediate). Each BUCK transfer generates its own encrypted receipt. The router contract must also be registered if it holds BUCK transiently.

9.3 Contract-to-Contract Transfers

When one DeFi contract sends BUCK to another (e.g., a yield aggregator moving BUCK between pools), both contracts must be registered. The receipt identifies both contracts' deployers as the parties. This creates a clear chain of custody: every BUCK movement has an identified legal operator at each end.

9.4 Wrapping and Bridging

If BUCK is wrapped (WBUCK) for use on another chain, the wrapping contract must be registered. The wrap/unwrap generates receipts. On the destination chain, the bridged BUCK may operate under different identity rules (or no identity rules if the destination chain doesn't enforce ERC-3643). This is a known limitation – the Alberta Buck's identity guarantees only hold on chains where the IdentityRegistry is deployed.

9.5 Gas Costs

The design has three gas-consuming identity operations:

Operation	Cost (~gas)	When
registerCredential with PS verify (PS pairing: ~181K + NIZK: ~44K)	~235,000 gas	Once per account
approve with Chaum-Pedersen verify (proof verify: ~29K + std approve: ~46K)	~75,000 gas	Once per pair
BuckTransferReceipt event (2 indexed addresses + 3 uint256)	~2,000 gas	Per transfer

Credential registration uses the **ecPairing** precompile to verify the Pointcheval-Sanders signature and NIZK proof (235,000 gas, once per account). The Chaum-Pedersen proof verification uses **~ecMul / ecAdd** (~29,000 gas per counterparty pair). Subsequent transfers emit only the minimal receipt event (~2,000 gas) with no additional proof work.

All encrypted identity data and full receipts are stored on Holochain, not on Ethereum. The only identity-related data emitted on-chain is the compact ElGamal ciphertext (4 curve coordinates = 128 bytes of calldata) during **approve**, and two **bytes32** hashes during each transfer.

9.6 Privacy of Pool Deployer Identity

The pool deployer's ElGamal credential is stored in the IdentityRegistry alongside the pool contract's address. The credential **E_deployer** is an opaque ciphertext – anyone can see it on-chain, but no one can decrypt it without the deployer's identity private key.

What is publicly visible: "0xPOOL is operated by a verified entity" (because **isVerified(0xPOOL) == true**). What is **not** visible: who that entity is. The deployer's real identity is revealed only in the ElGamal ciphertexts re-encrypted for specific counterparties during **approve** handshakes.

If a deployer wants public identification (e.g., "DeFi Ops Inc., Alberta"), they can register a separate plaintext identity claim alongside their encrypted credential. This is the expected case for commercial DeFi operators – public identity builds trust and attracts liquidity.

9.7 alt_bn128 Security Horizon

The alt_bn128 curve (BN254) offers ~ 128 -bit security for discrete logarithm in G_1 but only ~ 100 -bit security against pairing-based attacks, due to Kim-Barbulescu tower-NFS improvements (2016) to the Number Field Sieve in extension fields. This affects the PS signature verification (which uses pairings at registration) but *not* the Chaum-Pedersen proof (which uses only G_1 scalar multiplications at transaction time and remains at full ~ 128 -bit security).

This is not specific to Alberta Buck. *Every* Ethereum application using the `ecPairing` precompile – Groth16 SNARK verifiers (zkSync, Polygon zkEVM), BLS signature schemes, any pairing-based construction – faces the same constraint. The alt_bn128 precompiles are the only pairing-capable curve available on-chain until EIP-2537 (BLS12-381 precompiles) is deployed.

Three mitigations apply:

1. **Epoch-based credential expiry:** PS signatures are verified once at registration and carry an expiry epoch. An attacker who invests computational resources to break a pairing equation recovers a single credential that has likely already expired. The Identity Fountain’s renewal model limits the value of any single break.
2. **DLog security is unaffected:** Per-transaction Chaum-Pedersen proofs rely on discrete logarithm hardness in G_1 , which remains at ~ 128 -bit security. An attacker who breaks pairings cannot forge re-encryption proofs or decrypt ElGamal ciphertexts.
3. **BLS12-381 migration path:** EIP-2537 introduces precompiles for BLS12-381 (128-bit pairing security). When deployed, credential registration migrates to BLS12-381 for PS verification while the Chaum-Pedersen layer continues on alt_bn128 (or also migrates). The architecture’s separation of registration-time pairings from transaction-time scalar multiplications makes this migration straightforward -- only the `registerCredential` function changes.

The ~ 100 -bit pairing security is adequate for the current threat model. The practical cost of a tower-NFS attack on BN254 pairings remains far beyond the value of any single Alberta Buck credential, particularly given epoch-based expiry. The system shares this constraint with the entire Ethereum L2 scaling ecosystem.

10 Alternative Approaches Considered

The ElGamal Chaum-Pedersen scheme was chosen after evaluating several cryptographic alternatives. Each has merits for other use cases, but none matches the combination of low gas cost, zero setup, instant proof generation, and strong security guarantees needed for an ERC-20 identity layer.

10.1 Pedersen Commitments + Groth16 ZK Proofs

In this approach, the issuer stores a Pedersen commitment $C = v \cdot G + r \cdot H$ on-chain. Alice proves in zero knowledge (via a Groth16 SNARK) that her re-encrypted ciphertext E_{bob} encrypts the same value v committed in C .

Advantages:

- Extremely flexible: the ZK circuit can prove arbitrary predicates alongside re-encryption correctness (age > 18, jurisdiction membership, credit score in range, etc.)
- Information-theoretically hiding (Pedersen commitments hide v perfectly, vs. ElGamal's computational hiding)
- Well-supported toolchain (circom, snarkjs, Hardhat plugins)

Why Chaum-Pedersen is superior for Alberta Buck:

- **Gas cost:** Groth16 verification requires the `ecPairing` precompile (~113,000 gas base + per-pair costs), totaling ~200,000-300,000 gas. Chaum-Pedersen costs ~29,000 gas – **7-10x cheaper**.
- **Trusted setup:** Groth16 requires a multi-party computation ceremony to generate proving/verification keys. A compromised ceremony allows forged proofs – the one thing the system cannot tolerate. Chaum-Pedersen has no setup of any kind.
- **Proof generation time:** Groth16 proof generation takes seconds to minutes (circuit evaluation, witness computation, FFTs over large fields). Chaum-Pedersen proof generation is 2 scalar multiplications and 1 hash – milliseconds on a phone.
- **Complexity:** Groth16 requires circuit definition (R1CS/circom), a prover library, and careful constraint engineering. A bug in the circuit silently compromises soundness. Chaum-Pedersen is ~50 lines of elliptic curve arithmetic with a well-understood security proof.
- **Unnecessary generality:** Alberta Buck needs exactly one thing: proof that two ElGamal ciphertexts encrypt the same message point. Groth16 can prove anything in NP; that generality is wasted here and only adds attack surface.

10.2 Proxy Re-Encryption (NuCypher Umbral)⁵

In PRE, Alice generates a re-encryption key $rk_{\{A \rightarrow B\}}$ that allows an untrusted proxy to transform E_{alice} into E_{bob} without decrypting. Umbral includes NIZK proofs of correct re-encryption.

Advantages:

⁵Umbral: A Threshold Proxy Re-Encryption Scheme. NuCypher. Reference implementation: <https://github.com/nucypher/pyUmbral> Whitepaper: <https://raw.githubusercontent.com/nucypher/umbral-doc/master/umbral-doc.pdf>

- Alice does not need to be online at re-encryption time (the proxy acts on her behalf)
- Threshold PRE distributes trust across multiple proxies (no single point of compromise)
- Algebraic NIZK proofs are efficient (comparable gas cost to Chaum-Pedersen)

Why Chaum-Pedersen is superior for Alberta Buck:

- **Alice is always online:** in the Alberta Buck model, Alice calls `approve` directly – she is necessarily online. The proxy delegation feature of PRE is unnecessary complexity.
- **No proxy metadata leakage:** even with threshold PRE, the proxies learn metadata (who is re-encrypting for whom, how often). Direct re-encryption eliminates this metadata channel entirely.
- **Simpler key management:** PRE requires generating and distributing re-encryption keys per counterparty pair. Direct ElGamal re-encryption uses only the existing identity key pairs already registered on-chain.
- **Protocol complexity:** Umbral manages capsules, key fragments, and proxy coordination. Direct re-encryption with Chaum-Pedersen is two scalar multiplications and a sigma protocol – no capsules, no fragments, no proxies.
- PRE remains valuable in other contexts (e.g., encrypted email where the sender may be offline), but Alberta Buck’s on-chain interaction model makes it unnecessary.

10.3 BBS+ Signatures with Selective Disclosure

BBS+ (pairing-based multi-message signatures) allows an issuer to sign a vector of attributes. Alice can selectively disclose specific attributes while hiding others, with ZK proofs of signature validity. The W3C Verifiable Credentials standard is converging on BBS+ for exactly this use case.

Advantages:

- Attribute-level granularity: prove "jurisdiction = Alberta" without revealing name or ID number
- Unlinkable presentations (different proofs from the same credential cannot be correlated)
- Ecosystem alignment with W3C VC / DID standards

Why Chaum-Pedersen is superior for Alberta Buck:

- **Gas cost:** BBS+ verification requires pairing operations ($\sim 113,000+$ gas). Chaum-Pedersen uses only scalar multiplications ($\sim 29,000$ gas).

- **Selective disclosure is the wrong primitive:** Alberta Buck transfers require the *full* identity to be re-encrypted for the counterparty (for court-recoverable receipts). Selective attribute hiding would defeat the purpose: the counterparty needs the whole identity, and a court needs the whole identity.
- **Different trust model:** BBS+ proves "I hold a valid credential with these properties." Alberta Buck needs "this ciphertext contains my specific issuer-certified identity." The latter is a re-encryption correctness proof, not a selective disclosure proof.
- **Cross-account unlinkability is already solved:** Pointcheval-Sanders rerandomizable signatures provide unlinkable credential derivation for different accounts. Within a single account, re-encryptions share a common Ethereum address regardless of the credential scheme, so BBS+ presentation unlinkability adds nothing.
- BBS+ could complement Chaum-Pedersen in the future – e.g., for compliance checks that verify jurisdiction eligibility without full identity disclosure. But it does not replace the core re-encryption mechanism.

10.4 Camenisch-Shoup Verifiable Encryption

A purpose-built primitive: encrypt a value and simultaneously prove that the plaintext satisfies a public relation, without revealing it.

Advantages:

- Theoretically clean: directly solves "encrypt for Bob, prove to everyone it's the right value"
- Can prove arbitrary relations on the encrypted plaintext

Why Chaum-Pedersen is superior for Alberta Buck:

- Camenisch-Shoup is the general framework; Chaum-Pedersen is its optimal specialization for the "same plaintext" relation. When the relation is "same plaintext as another ElGamal ciphertext in the same group," the Chaum-Pedersen protocol is the canonical, minimal-cost instantiation.
- General Camenisch-Shoup constructions are more complex and less efficient.

10.5 Pedersen Equality Proofs (Homomorphic Comparison)⁶

Pedersen commitments support homomorphic equality checking: given $C_1 = v \cdot G + r_1 \cdot H$ and $C_2 = v \cdot G + r_2 \cdot H$, revealing $\text{delta}_r = r_1 - r_2$ lets the verifier check $C_1 - C_2 == \text{delta}_r \cdot H$ without learning v .

⁶Pedersen Commitments and Bulletproofs. Bulletproofs: Short Proofs for Confidential Transactions and More. Bunz, Bootle, Boneh, Poelstra, Wuille, Maxwell. Overview: <https://tlu.tarilabs.com/cryptography/the-bulletproof-protocols> Pedersen commitments in confidential transactions: <https://www.nccgroup.com/research/on-the-use-of-pedersen-commitments-for-confidential-payments/>

Advantages:

- Extremely cheap (1 point addition, 1 scalar multiplication)
- Information-theoretically hiding

Why this is insufficient for Alberta Buck:

- Pedersen commitments are *commitments*, not *encryptions*. They hide the value but do not allow a specific party to decrypt. Alberta Buck needs Bob to recover Alice's identity, not just to verify that two opaque commitments match. ElGamal provides both hiding and targeted decryption.
- Revealing `delta_r` to prove equality leaks the randomness difference, which is acceptable for on-chain verification but means the commitment scheme cannot support multiple independent equality proofs without additional blinding (each proof leaks one linear relation on the randomness).

10.6 Comparison Summary

Approach	On-chain gas	Proof gen	Setup	Targeted decryption	Sufficient alone?
ElGamal Chaum-Pedersen	~29K	ms	none	yes	yes
Groth16 SNARK	~200-300K	sec-min	trusted	yes	yes
Umbral PRE	~30-50K	ms	none	yes	yes
BBS+	~150-200K	ms	pairing params	no (proves properties)	no (complement)
Camenisch-Shoup	~50-100K	ms	none	yes	yes
Pedersen equality	~7K	ms	none	no	no

ElGamal Chaum-Pedersen wins on per-transaction gas cost, has zero setup requirements, generates proofs instantly, supports targeted decryption, and requires minimal implementation. Combined with Pointcheval-Sanders rerandomizable signatures for credential derivation (one-time ~235K gas at registration), the system achieves both cross-account unlinkability and per-transaction re-encryption correctness – without the gas burden or trusted setup of SNARK-based alternatives.

11 Summary: Identity Requirement by Risk Level

Risk level	Operations	Identity mode	Receipt
Highest	BuckCredit creation/update, oracle claims, governance	Public	On-chain event + public record
High	Pool deployment, compliance changes	Public	On-chain event
Medium	BUCK transfer, DeFi swap, add/remove liquidity	Anonymous-valid	Encrypted 3-party ECDH receipt
Low	BUCK burn, credit activation	Anonymous-valid	On-chain event
None	BuckK compute, read oracle, view balances	Permissionless	On-chain event

DRAFT