

The Alberta Buck - Printable Receipt (DRAFT v0.2)

A Plain-Text, Independently Re-Verifiable Record of an Identity-Bound BUCK Payment

Perry Kundert

2026-05-29



The cryptography of the Alberta Buck identity layer names an *identity point* $M \in \mathbb{G}_1$ and binds a transaction; the artifact a human actually holds is a *receipt*. This document specifies that receipt: a plain-text slip, sized for an 80mm thermal printer, that prints the plain-text Identity of both parties and the transaction details, and embeds – as a wrapped text payload – everything required to re-verify the payment by re-scanning the slip and re-running the wallet’s verifiers. The receipt closes two gaps the on-chain proofs leave open: it carries each party’s **canonical_identity_data** so a point M resolves to a human name (verified by recomputing $M = \text{keccak}(\text{data}) \cdot G$), and it states which on-chain facts (registry records, the **Transfer** / **Spent*** event) anchor the proof. Verification is two-tier: *offline*, re-running the proof algebra and the point→human bridge from the embedded payload alone; and *chain-anchored*, confirming the embedded records against a node. Five receipt kinds are specified – an EOA transfer from a public or a private counterparty, and the B1, A1, and A2 Note flavors. The Note kinds are producible by *either* party – the depositor’s copy or the issuer’s "I paid X" copy – because the Identity-M note payload (the **idHash** preimage material: the addressed ciphertexts and issuer-signature words) is held by both, and the receipt’s disclosed identity preimages let any verifier derive the identity scalars and re-check it deterministically. The remaining proofs are the primitives already shipped (the approve handshake + **verifiable_decrypt** for EOA, the batch Schnorr for public issuers, and for the private-issuer A2 case the recipient-blinded **verifyIssuerReenc** binding the mint verified on chain). (Decryptability, Identity)

Contents

1	What a Receipt Is (and Is Not)	3
2	Two Gaps the Proofs Leave to the Receipt	3
2.1	The point -> human bridge	3
2.2	The trust anchor	3
3	The Two-Tier Verification Model	3
4	The AB-RCPT/1 Envelope	4
5	Per-Scenario Payloads	5
5.1	coa-pub – EOA transfer from a public counterparty	5
5.2	coa-priv – EOA transfer from a private counterparty	5
5.3	note-b1 / note-a1 – Note from a public issuer	5
5.4	note-a2 – Note from a private issuer	6
5.5	Why there is no "B2" (private-issuer bearer) receipt	6
6	The Physical Artifact (ESC/POS, 80mm, 203dpi, 576px)	6
7	Verification Procedure	7
8	Wallet UX and Storage	8
9	Security Considerations	9
10	Phasing	9
11	Open Questions	10

1 What a Receipt Is (and Is Not)

A BUCK receipt is a **record of a completed payment**, generated by a party to that payment and printable on a commodity thermal printer. For an EOA transfer the generator is the *recipient*; for a Note it is **either** party – the depositor prints their copy, the issuer prints the payer-side "I paid X" copy – since the Identity-M note payload travels to both at mint/spend. The receipt's **role** field records which side produced it, and the renderer marks that party "- you". It is the bilateral-disclosure half of the system's privacy promise made tangible: bulk chain-analytics cannot reconstruct who paid whom, but either party to a payment can produce a slip that names the counterparty in the clear and proves it.

- **It IS:** human-readable; names both parties' plain-text Identity (a display subset on paper, the full KYC datum in the payload); states amount, kind, time, and on-chain references; self-verifying from its own text payload; and extensible with optional informational line items.
- **It is NOT:** a bearer instrument (it redeems nothing – the value already moved, and any Note nullifier it references is already spent); a chain explorer; or a re-derivation of the KYC binding of M to a legal person (that rests on the issuer's Pointcheval-Sanders credential, assumed here). The optional line items are **not** covered by verification.

2 Two Gaps the Proofs Leave to the Receipt

2.1 The point -> human bridge

Every shipped proof names an identity *point* M . A receipt must name a *person*. The link is the preimage:

Definition 1. A party's Identity datum is the canonical JSON *canonical_identity_data* (the KYC fields, sorted-key, no-whitespace – Identity Example). Its identity scalar is $m = \text{keccak}(\text{canonical}) \bmod \text{ORDER}$ and its identity point is $M = m \cdot G$.

The receipt therefore carries each party's *canonical_identity_data*, and a verifier recomputes $\text{keccak}(\text{data}) \cdot G$ and checks it equals the named M . That single check turns a curve point into "Alice Johnson, Alberta Identity Card, Alberta, Canada."

Requirement (data availability). The generating wallet must *hold* the counterparty's *canonical_identity_data*. For a **public** identity it is published (off-chain attestation). For a **private** identity it is disclosed bilaterally when the parties approve one another (or when a Note is delivered) – the same exchange that lets each verify $M = \text{keccak}(\cdot) \cdot G$ against the credential they can decrypt. A wallet that never received the preimage can still print the *point* and the issuer reference, but not the human name (see *Open Questions*).

2.2 The trust anchor

Offline math proves the receipt is *internally* sound; it cannot prove the embedded keys and events are the *real* on-chain ones. That is a chain read. Hence two tiers, both specified below.

3 The Two-Tier Verification Model

Tier	Needs	Confirms
1 – offline	the slip's text payload only	the proof algebra verifies; both M recompute from their <i>canonical_identity_data</i> ; for Notes the
2 – anchored	tier 1 + an RPC node	the embedded <code>pk</code> / <code>E_addr</code> / <code>isPublicIdentity</code> equal the registry's for each named address; the T

Tier 1 says *"these proofs are valid and name these humans"*; tier 2 says *"and those identities and that payment are the genuine on-chain ones."* Together they are the non-deniable receipt of *Decryptability*. Per the design decision, the payload is **offline-complete**: every value tier 1 needs is embedded, and tier 2's references ride alongside so anchoring is optional, not required, to read a receipt.

Property 2. (Receipt soundness.) *If tier 1 passes, the slip's proofs are valid for the embedded public inputs and each named M is the hash of the printed Identity datum. If tier 2 also passes, those inputs are the on-chain registry records and the payment is a mined event. No party can forge a passing slip naming a counterparty who did not transact (proof unforgeability + event immutability); a generator may decline to print a receipt, but cannot print a false one.*

4 The AB-RCPT/1 Envelope

The verified **core** is a deterministic map, serialized canonically (CBOR), and printed as AB-RCPT/1. followed by base64url of the bytes, wrapped to the print width. (Text-only by decision – no QR; the payload is literally plain-text, re-typable and OCR-able, and survives a scanner-less verifier.) The receipt id is `base32(sha256(core))` truncated to a short handle. The optional line items live *outside* the core (they are unverified) and are printed in their own section, never in the payload.

Shown as JSON for readability (the wire form is CBOR):

```
{
  "v": 1,
  "type": "eoa-pub" | "eoa-priv" | "note-b1" | "note-a1" | "note-a2",
  "role": "recipient" | "issuer",    // who generated it ("issuer": Note kinds only)
  "chainid": 1,
  "contracts": { "registry": "0x..", "buck": "0x..", "notes": "0x.." },
  "payer": Party,                    // funds FROM (for a Note: the issuer)
  "payee": Party,                    // funds TO (the recipient / depositor)
  "txn": Txn,
  "note": NotePayload,               // Note kinds: the Identity-M idHash preimage
  "proof": Proof,                    // type-specific (below)
  // role-dependent self-naming / counterparty-naming vd records:
  "payee_vd": Vd,                    // role=recipient: payee's own E_addr -> payee.M
  "payer_vd": Vd,                    // role=issuer, private payer (A2): own E_addr -> payer.M
  "vd_payee": Vd                     // role=issuer, B1: eDepForIss -> payee.M
}

Party {
  "addr": "0x..",
  "kind": "public" | "private",
  "identity": "<canonical_identity_data>", // preimage; keccak->m, M=m*G
  "M": ["0x..", "0x.."],                 // named identity point
  "pk": ["0x..", "0x.."],                 // registered_pk (tier-2 anchor)
  "E_addr": { "R":["..", ".."], "C":["..", ".."] } // registered ct (private; tier-2)
}

Txn {
  "kind": "eoa-transfer" | "note-spend",
  "value": 250000000,                     // BUCK base units (6 dp)
  "timestamp": 1779999011,                 // block time
  "event": "Transfer" | "SpentCoupledB1" | "SpentCoupledA1" | "SpentCoupledA2",
  "txhash": "0x..", "block": 1234567, "logindex": 3,
  // note-spend adds:
  "mint_txhash": "0x..", "mint_block": 1234500, "nullifier": "0x.."
}

NotePayload {
  // per flavor -- the idHash preimage material
  // B1: "sigma_R", "sigma_s"              (id_hash_b1(m_iss, sigma))
  //      + "eDepForIss"                   (the SpentCoupledB1 event ct)
```

```

// A1:  "eNote", "eRec", "sigma_R", "sigma_s"
//                                     (id_hash_a1(eNote, m_iss, sigma))
// A2:  "eNote", "eIss"                (id_hash_a2(eNote, eIss))
}

```

proof is the witness the matching verifier consumes (the approve handshake for eoa-priv; the note opening + minted `cms[]` + the public issuer's batch Schnorr + nullifier/face for the Note kinds; an A2 receipt additionally carries the mint's `issuer_reenc` binding). The vd records carry the generating side's self-naming – a **verifiable_decrypt** of one's *own* registered `E_addr` revealing one's `M` – and, for the issuer-side B1 receipt, the issuer's verifiable decryption of the event's `eDepForIss` naming the depositor. The Note legs themselves need **no** party proof: the disclosed identity preimages let any verifier derive `m_iss` $\neq$ `m_rec`, recompute the `idHash`, and decrypt the addressed ciphertexts directly – which is exactly why both parties can generate the same receipt core.

5 Per-Scenario Payloads

For the EOA kinds the wallet owner is the **payee**; a Note receipt is generated from **either** side (the `role` field). Each row names the tier-1 re-check. All Note flavors use the unified spend nullifier `Poseidon( $\rho$ , idHash, 4242)` (the shipped `spend.circum` tag) and anchor at the `Minted` and `SpentCoupled*` events.

type	payer	party-naming (tier-1 re-check)
eo-pub	EOA, public	none – <code>payer.M</code> recomputed from public identity; pk anchors addr
eo-priv	EOA, private	approve handshake <code>cp_proof</code> + payee's vd of <code>E_for_spender</code>
note-b1	issuer, public	<code>idHash = id_hash_b1(m_iss, sigma)</code> + batch Schnorr; issuer side: vd of <code>eDepForIss</code> names depositor
note-a1	issuer, public	<code>idHash = id_hash_a1(eNote, m_iss, sigma)</code> + Schnorr; <code>Dec(eNote, m_rec) = vG</code> , <code>Dec(eRec, m_rec) = M_rec</code>
note-a2	issuer, private	<code>idHash = id_hash_a2(eNote, eIss)</code> ; <code>Dec(eNote, m_rec) = vG</code> , <code>Dec(eIss, m_rec) = M_iss</code> ; <code>issuer_reenc</code> binding

5.1 eoa-pub – EOA transfer from a public counterparty

Lightest: the payer's identity is public, so `payer.M` is recomputed from it and no payer proof is needed; the payer `pk` ties the `Transfer.from` address to that public record (tier 2). Payload = payer Party (public) + payee Party + payee `vd_proof` + the `Transfer` anchor.

5.2 eoa-priv – EOA transfer from a private counterparty

The `ApproveReceipt` half: at approve time the payer re-encrypted their `M` for the payee (`E_for_spender`) and proved it (`cp_proof = verifyApprove`); the payee verifiably decrypts it to `payer.M` (`vd_proof`). Payload = both Parties (private) + `ApproveReceipt` proofs + payee self `vd_proof` + `Transfer` anchor + registry `pk` $\neq$ `E_addr` for both (tier 2).

5.3 note-b1 / note-a1 – Note from a public issuer

The four-link chain, now Identity-M-bound: the opening recomputes `cm`, `cm` is in the mint `cms[]`, the issuer is bound *into the leaf itself* (the verifier derives `m_iss` from the disclosed issuer preimage and requires `opening.idHash` to recompute as `id_hash_b1(m_iss, sigma)` / `id_hash_a1(eNote, m_iss, sigma)`) as well as over the batch (the Schnorr, whose Fiat-Shamir transcript folds in the issuer *account* + chainid – so the printed `acct` is provably the mint's `msg.sender`, the account whose BUCK funded the note), and the nullifier was burned in the `SpentCoupledB1` $\neq$ `SpentCoupledA1` event paying the payee.

The payee leg differs by flavor. **A1** is addressed: **eNote** encrypts the face under the recipient identity point and **eRec** the recipient identity under itself, so $\text{Dec}(e\text{Note}, m_{\text{rec}}) = vG$ and $\text{Dec}(e\text{Rec}, m_{\text{rec}}) = M_{\text{rec}}$ bind the named recipient into the leaf – deterministically, from the disclosed preimage; only the addressed identity satisfies the **eNote** relation (the face-pinning principle). **B1** is bearer: the depositor is named at spend – the **SpentCoupledB1** event publishes **eDepForIss**, the depositor’s Identity re-encrypted under the public issuer’s registered key (proven well-formed on chain by **verifyDepositorBinding**) – so the *issuer-side* receipt names the depositor by verifiably decrypting it (**vd_payee**), while the *recipient-side* receipt self-names via **payee_vd** as usual.

5.4 note-a2 – Note from a private issuer

The hard case: both parties are encrypted-Identity. Identity-M targeting makes it symmetric and proof-free on the note legs: the issuer encrypted the face under the recipient identity point (**eNote**) and their *own* registered Identity under the same point (**eIss**), and **opening.idHash = id_hash_a2(eNote, eIss)** commits both. The verifier derives m_{rec} from the disclosed payee preimage and checks $\text{Dec}(e\text{Note}, m_{\text{rec}}) = vG$ and $\text{Dec}(e\text{Iss}, m_{\text{rec}}) = M_{\text{named}} = \text{payer.M}$ – the second equation *is* the coupling: it algebraically forces **eIss**’s key to be M_{rec} , so the note was addressed to the payee. Anti-framing – that **eIss** re-encrypts the issuer’s *registered* credential, so the recovered Identity is the true minter, never a victim – is the **issuer_reenc binding** the issuer shipped at mint, verified on chain by the A2 mint overload (**IdentityRegistry.verifyIssuerReenc** + the per-leaf **eIss** leaf-tie) and re-verified offline here; its transcript folds in the issuer account + chainid, anchoring the printed **acct** to the mint’s **msg.sender**.

Payload = both Parties (private) + the note payload (**eNote, eIss**) + the **issuer_reenc** binding + the generator’s self-naming (**payee_vd** or **payer_vd**) + mint and spend anchors. The chain saw only the *blinded* binding ($\hat{T}$ hides M_{iss} , Q hides M_{rec}); no un-blinding scalar is ever disclosed – the earlier account-keyed design needed a disclosed γ here, but identity-targeting lets the verifier decrypt directly, since the receipt already discloses the payee preimage. A receipt assembled *without* the binding still prints, with **M_iss** recovered but stamped **UNVERIFIED ISSUER** – a narrow case, since every chain-minted A2 leaf carries a verified binding (the mint reverts otherwise).

5.5 Why there is no "B2" (private-issuer bearer) receipt

A2 is the *only* private-issuer receipt kind because A2 is the only private-issuer note kind. A private-issuer *bearer* note ("B2") is impossible, not merely unimplemented: **eIss** is the issuer’s Identity re-encrypted under **the recipient’s** identity point, openable only with m_{rec} – and a bearer note has no recipient at mint for the issuer to address. Any binding the issuer could instead attach to "whoever bears the note" would be openable by every holder of the freely-circulating note (no privacy over a public B1 issuer) or by no one (no receipt). So a private issuer must address the note (A2) and a bearer note must have a public issuer (B1); the mint SNARK now *binds* this (**issuerMode, b14e0f0, 68e5b55**). See *Why B2 is impossible* in the Decryptability companion.

6 The Physical Artifact (ESC/POS, 80mm, 203dpi, 576px)

576 dots wide; Font A (12x24) gives **48 columns**, Font B (9x17) gives 64. The body prints at 48 cols; the base64url payload prints at Font B / 64 cols to cut its line count. Output is 7-bit ASCII only (names transliterated if needed – see *Open Questions*). ESC/POS control: **ESC @** init, **ESC a** n align, **ESC E** n emphasis, **GS V** cut; no graphics.

The human-readable parties and amount are *derived from the verified core* – a single source of truth – so what a person reads cannot drift from what a verifier checks. Only the NOTES section is free text.

```
=====
                ALBERTA BUCK
                P A Y M E N T   R E C E I P T
=====
Receipt  ab1q7x...4f9          (sha256 handle)
Issued    2026-05-29 14:32 MST    AB-RCPT/1
-----
FROM (payer)                [PRIVATE IDENTITY]
  Alice Johnson
  Alberta Identity Card - Alberta, Canada
  acct  0xa11ce...a11ce
  id pt 8f3a..1c    (point->name VERIFIED)
-----
TO (payee - you)            [PRIVATE IDENTITY]
  Bob Smith
  Corporate Registration - Alberta, Canada
  acct  0x0b0b...0b0b
  id pt 2d77..9a    (point->name VERIFIED)
-----
TRANSACTION
  Type    EOA transfer (Identity-bound)
  Amount  $   250.00 BUCK
  When    2026-05-29 14:30 MST
  Chain 1  Block 1234567    Log #3
  Tx      0x9c2f...e1
-----
NOTES (informational - NOT verified)
  Invoice INV-2026-0042
  Consulting services, May 2026
-----
VERIFICATION                status @ issue: VALID
  Re-verify: scan the payload below into
    albertabuck verify -
  (offline checks proofs + names; add --rpc
    to anchor to chain)

AB-RCPT/1.
o7VkdHlwZWVvYS1wcm12ZGNoYWluAWhjb250cmFjdH0j
aHJlZ2lzdHJ5VAr..Q3R4ZWVidWNrV... (wrapped,
Font B, ~30-50 lines depending on kind)
.END
=====
  a record, not a bearer instrument
  github.com/pjkundert/alberta-buck
=====
```

7 Verification Procedure

`albertabuck verify [-|FILE] [--rpc URL]:`

1. **Parse.** Strip to AB-RCPT/1.END, base64url-decode, decode the canonical bytes to the core map; reject unknown `v / type / role`.
2. **Tier 1 (always).** For payer and payee: recompute $M' = \text{keccak}(\text{identity}) \cdot G$ and require $M' = M$. Check the generating side's self-naming per `role` (recipient: `payee_vd`; issuer: `payer_vd` for a private payer). Dispatch on `type`: `ea-pub` needs no payer proof; `ea-priv` re-runs the approve handshake + the payee's `vd` of `E_for_spender`. For the Note kinds derive m_{iss}, m_{rec} from the disclosed preimages and require: the opening's `cm` $\in$ `cms[]`;

`opening.idHash` recomputes from the `note` payload (`id_hash_b1/a1/a2`); the addressed ciphertexts decrypt correctly under m_{rec} (A1: `eNote`, `eRec`; A2: `eNote`, `eIss` – the latter to `payer.M`, the coupling); the public issuer’s batch Schnorr (B1/A1) or the `issuer_reenc` binding (A2) verifies against the embedded registry record and the printed issuer `acct`; the nullifier equals $\text{Poseidon}(\rho, \text{idHash}, 4242)$; and `face = opening.v = txn.value`. For an issuer-side B1 receipt also verify `vd_payee` over the event’s `eDepForIss`. Require the named M , `value`, and addresses to match the human-readable fields the renderer derived.

3. **Tier 2 (--rpc).** For each named address read `_pk`, `_E_addr`, `isPublicIdentity` and assert equality with the payload; read the log at (`txhash`, `logIndex`) and assert the `event` (`Transfer` / `SpentCoupled*`), `value` $\neq$ `face`, `recipient` $\neq$ `from` $\neq$ `to`, and (for Notes) nullifier match, the Minted event at `mint_txhash` carries `cms[]` from the printed issuer `acct` (= the `transferFrom` source that funded the note), and (B1) the spend’s `eDepForIss` equals the payload’s; assert the block is mined and final.
4. **Report.** `VALID` (+ named identities, amount) / `INVALID` (reason) / `UNVERIFIED ISSUER` for an A2 slip carrying no binding.

8 Wallet UX and Storage

The receipt is generated from a selected payment:

1. **Select** a row in tx history where the owner is `to` (a `Transfer`) or `recipient` (a `SpentCoupled*`); an issuer instead selects a spend of a note it minted (for B1, scanning `SpentCoupledB1` logs for its own `issuer` address and decrypting each `eDepForIss`).
2. **Gather** per the scenario table: a registry read (public payer), stored approve material (private EOA), or the stored note artifact – the `opening`, the Identity-M payload (`eNote` $\neq$ `eRec` $\neq$ `eIss`, `sigma`), and the mint reference; plus each party’s `canonical_identity_data` from wallet storage.
3. **Self-name:** `verifiable_decrypt` the owner’s own `E_addr` (and, B1 issuer side, the event’s `eDepForIss`).
4. **Anchor:** read the `Transfer` / `SpentCoupled*` event and registry records.
5. **Prove + assemble:** generate the `vd` record(s) with `sk_owner`, build the core, *verify it locally*, set the status banner.
6. **Render + print:** ESC/POS at the configured width; or emit plain text.

Storage the wallet must retain (beyond keys): the owner’s (`sk`, `identity_data`); per approved counterparty (`addr`, `identity_data`, `E_for_me`, `cp_proof`); per received *or minted* Note the `opening` + the Identity-M payload and its mint reference (`mint_txhash`, `cms` or `cm index`, `issuer addr`, `issuer_sig` | `issuer_reenc` binding); and an event source (indexer or RPC) for the `Transfer` / `SpentCoupled*` logs and registry reads. Note that this is exactly the material that already travels with a note off chain – the issuer keeps what it created at mint, the recipient what it was handed – so both-party generation needs no extra exchange.

CLI surface (proposed). `albertabuck receipt <txref> [--width 48|64] [--escpos|--text]` to produce a slip; `albertabuck verify [-|FILE] [--rpc]` to check a scanned payload. Both reuse the wallet library; `verify` has no wallet-secret dependency (a third party runs it).

9 Security Considerations

- **PII on paper.** The slip is a deliberate disclosure: anyone holding it can name both parties. The display subset (name / id_type / jurisdiction) keeps the *printed* face modest, but the payload carries each party’s **full canonical_identity_data** in base64 – base64 is *encoding*, not *encryption*. A receipt must be handled like a signed KYC disclosure, not like cash.
- **No value, no replay.** The slip redeems nothing; a referenced Note nullifier is already burned, an EOA transfer already mined. Re-printing or copying a slip moves no funds.
- **Generator honesty bounds.** Tier-1/2 bind the parties, amount, and event; the free-text NOTES are unbound, so a generator may write anything there – hence they are labelled *informational*, *not verified*, and excluded from the receipt id.
- **A2 issuer privacy.** The A2 binding is *blinded*: the chain sees $\hat{T}$ and $Q = M_{rec} + \beta H$, revealing neither the issuer’s M_{iss} nor the recipient’s M_{rec} . An earlier draft published an unblinded T , which leaks $M_{iss} = C_i - T$ – and `msg.sender` at mint *is* the issuer – so the blind is load-bearing. The receipt discloses no un-blinding scalar at all: naming flows through decryption of `eIss` under m_{rec} , derivable from the payee preimage the receipt already disclosed – so the only new disclosure is the deliberate one. The mint-SNARK `issuerMode` signal is *bound*, the per-leaf `eIss` tie is on chain (the `mint_batch_a2` circuit exposes each committed leaf’s `eIss`, which `Notes.mint` matches to its binding), and the Identity-M spend gate (the deposit-coupling sigma + the *bound* membership proof over the same committed point + the `note $\leftrightarrow$ eEnc=` tie) makes an un-nameable note un-spendable: `eIss` keyed to a throwaway key decrypts, under the depositor’s authenticated m_{rec} , to a non-member, and the spend reverts. UNVERIFIED ISSUER therefore narrows to a receipt assembled without its binding – never a spendable chain-minted leaf.
- **Account provenance.** The printed `acct` lines are not free text. The issuer account is folded into the Fiat-Shamir transcript of its binding (the batch Schnorr for B1/A1, `issuer_reenc` for A2), so tier 1 already pins it; tier 2 confirms it is the Minted event’s `issuer` – the `msg.sender` whose `transferFrom` funded the note. The payee account is the `SpentCoupled*` event’s payout `recipient`; the recipient-side receipt ties it to the named Identity by `payee_vd` (mirroring the on-chain deposit-coupling/depositor-binding sigma that authorized the spend from a registered account bound to the same identity scalar). Under Identity-M the spend account need not exist at mint – authorization keys on the *identity* – so the receipt names whichever registered account the recipient actually used, anchored by the event.
- **Trust roots.** Soundness rests on the proof algebra (tier 1), the on-chain registry + event (tier 2), and the KYC issuer’s $m \leftrightarrow \text{person}$ binding (out of scope; assumed via the PS credential).

10 Phasing

1. **Phase A (shipped).** Envelope + `verify` CLI + the plain-text renderer for all five kinds. `eoapub`, `eoapriv`, `note-b1`, `note-a1` are soundly bound; the receipt `core` (`envelope.py` / `build_receipt.py` / `verify_receipt.py` / `render.py`) is the shipped wallet surface.
2. **Phase B (shipped, off-chain + on-chain issuerMode + A2 leaf-tie).** `note-a2` is soundly bound: the `issuer_reenc` binding names the private issuer’s *registered* Identity; the slip reads `VALID`. The mint-SNARK `issuerMode` gate is bound on chain (`b14e0f0` / `584bb52` /

68e5b55), so a bearer leaf cannot be private at all; and the per-leaf `eIss` tie (`mint_batch_a2 + MintVerifierA2Adapter`) pins each binding to its committed leaf, so a PRIVATE batch cannot float or duplicate bindings.

3. **Phase C (shipped, Identity-M).** The note kinds re-built on the identity-targeted payloads: `idHash` preimages (`id_hash_b1/a1/a2`) are conveyed in the envelope and re-checked against the disclosed identity preimages; the addressed ciphertexts (`eNote/=eRec/=eIss`) decrypt under the derivable m_{rec} , closing the recipient-key coupling at the receipt while the on-chain Identity-M spend gate (deposit-coupling + bound membership + `note $\leftrightarrow$ =eEnc=` tie) closes it at spend – a spendable note is always nameable, so no γ disclosure remains and UNVERIFIED ISSUER survives only for a receipt missing its binding. Receipts are generated by **both Note parties** (`role`): recipient-side and issuer-side ("I paid X") for B1/A1/A2, the B1 issuer naming its depositor from the `SpentCoupledB1` event's `eDepForIss`. Anchors moved to the unified 4242 nullifier and the `SpentCoupled*` events.
4. **Later.** The ESC/POS byte driver (Phase A shipped the plain-text driver; a port-9100 thermal driver is a new `Driver` subclass); optional QR rendering; payer-side *EOA* receipts; on-chain `RcptVerify` if a contract ever needs to gate on a receipt.

11 Open Questions

1. **Encoding for OCR.** `base64url` is compact but OCR-hostile (l/1/I, O/0); RFC 4648 `base32` is ~20% larger but robust to hand entry and OCR. Default `base64url`, or `base32` for paper? (The crypto payload is high-entropy, so compression buys little.)
2. **Unicode names.** Thermal output is ASCII; non-Latin `given_name / family_name` need transliteration for the *printed* face, while the payload keeps the exact UTF-8 `canonical_identity_data` (the hash preimage). How to transliterate without implying the printed name is the canonical one?
3. **Point-only fallback.** When the wallet lacks a private counterparty's `identity_data` preimage, should it print the M fingerprint + issuer reference (de-anonymizable by the issuer under subpoena), or refuse?
4. **Payload length.** Offline-complete + text-only makes Notes / private-EOA payloads ~2-2.7 KB of `base64` (~30-50 Font-B lines). Acceptable for thermal, or offer a `--refs-only` compact mode that requires `--rpc` to verify?
5. **Time and locale.** Print block timestamp (consensus truth) or wall clock, and in UTC or the wallet's locale? The core stores unix block time; the printed string is a render choice.