

Computational approach to jigsaw puzzles

Friday sparks

Albertas Dvirnas

2026/03/20



- Cartographer John Spilsbury believed to have produced the first jigsaw puzzle around 1760 using a marquetry saw;



- Made from paperboard;
- World's largest puzzle had 551,232 pieces and was assembled by 1,600 students in Vietnam;
- Wikipedia's logo is a puzzle;
- From 2019, there's an annual World Jigsaw Puzzle Championship;











Types of puzzles





- Flip all pieces right side up;
- Sort out edge pieces;
- Separate into distinguishable colours;
- Use sorting boxes/plates;
- Sort by shape (brute force);
- Start by making the sky (if you're me)



How fast are the speed puzzlers?


- Puzzle from the individual final:




How fast are the speed puzzlers?




Is there a more mathematical approach to solving puzzles?




- Markaki S, Panagiotakis C. Jigsaw puzzle solving techniques and applications: a survey. The Visual Computer. 2023 Oct;39(10):4405-21.








Shuffled & Rotated



Solved

Why would a computer science puzzle algorithm matter to an ecologist or an interdisciplinary?


From Jigsaw Puzzles to Puzzles of Science





Algorithms for jigsaw puzzles inspire methods across the sciences

Can some research problems be "popularized" by interpreting them as puzzles?

Each row is one variable — e.g. species abundance, temperature, nutrient levels







5x100 Puzzle — library (cols 0–49) visible, second half masked

Left: grid heatmap - Right: per-component time series

Puzzle grid (5 × 100)



- 1 **Observation vector.** Each time step t yields a p -dimensional observation:

$$\mathbf{x}(t) = [x_1(t), x_2(t), \dots, x_p(t)]^\top \in \mathbb{R}^p$$

- 2 **Delay embedding (Takens, 1981).** Reconstruct the state space by stacking E lagged copies separated by delay τ :

$$\mathbf{v}(t) = [\mathbf{x}(t), \mathbf{x}(t - \tau), \dots, \mathbf{x}(t - (E - 1)\tau)]^\top \in \mathbb{R}^{pE}$$

Parameters E (embedding dimension) and τ (delay) are chosen to best unfold the attractor.

- 3 **Library construction.** The first half of the time series forms the *library* $\mathcal{L}$ of n embedded state vectors, each paired with its τ -ahead target:

$$\mathcal{L} = \{ (\mathbf{v}(t_i), \mathbf{x}(t_i + \tau)) \}_{i=1}^n$$

- 1 **Query vector.** Given the last observed columns, build the current state:

$$\mathbf{v}^* = [\mathbf{x}(T), \mathbf{x}(T - \tau), \dots, \mathbf{x}(T - (E - 1)\tau)]^\top$$

- 2 **Nearest-neighbour search.** Find the $E + 1$ library vectors closest to $\mathbf{v}^*$ in Euclidean distance:

$$d_j = \|\mathbf{v}^* - \mathbf{v}(t_j)\|_2, \quad j \in \mathcal{N}_{E+1}(\mathbf{v}^*)$$

- 3 **Exponential weights (Simplex Projection).** Weight each neighbour by proximity, normalised to sum to one:


$$w_j = \frac{\exp(-d_j / d_{\min})}{\sum_k \exp(-d_k / d_{\min})}, \quad d_{\min} = \min_j d_j$$

- ① **Prediction.** The forecast τ steps ahead is the weighted average of the neighbours' future values:

$$\hat{\mathbf{x}}(T + \tau) = \sum_{j \in \mathcal{N}_{E+1}} w_j \cdot \mathbf{x}(t_j + \tau)$$

- ② **Iterative completion.** Append $\hat{\mathbf{x}}(T + \tau)$ to the library and repeat steps 4–7 to reconstruct the full second half of the puzzle, column by column.

Empirical dynamical modelling approach



What other scientific problems at IceLab could be reframed as a jigsaw puzzle?