


GRAPHSAGE

INDUCTIVE REPRESENTATION LEARNING ON LARGE GRAPHS

Thomas Gantz
Alberto Finardi
Tommaso Crippa
Jan Marxen


December 4, 2025



Introduction

Primary focus: Node-level prediction — predict properties of individual nodes (classification, regression).

- **Node-level (focus):** Predict node attributes or labels using features and neighbor information.
- **Edge-level:** Predict relationships between node pairs (link prediction, edge classification).
- **Graph-level:** Predict properties of whole graphs (e.g., molecule properties).




What is a Graph Neural Network?

Introduction

A **learnable transformation** on graph attributes that:

- Updates node/edge/graph features using **neural networks**
- **Respects graph structure** by aggregating information from neighbors
- Is **permutation invariant** (order of nodes doesn't matter)




Message Passing: The Core Idea

Introduction

Three steps repeated at each layer:

1. **Gather:** Collect embeddings from neighboring nodes
2. **Aggregate:** Combine neighbors' info (sum / mean / max)
3. **Update:** Apply learned transform using the aggregated vector



Message Passing: Notation

Introduction

Message Passing Equation

$$h_v^{(k)} = \sigma \left(W \cdot \left[h_v^{(k-1)}, \text{AGG}(\{h_u : u \in N(v)\}) \right] \right)$$

- $h_v^{(k)}$ — Node v repr. at layer k
- h_u — Neighbor node u repr.
- $N(v)$ — Neighbors of v
- k — Layer index (hops)
- $\text{AGG}(\cdot)$ — Aggregator (mean, sum, max)
- W — Learnable weight matrix
- σ — Activation (ReLU, tanh)

Before GraphSAGE: The Problem

Introduction

Let's audit the limitations of existing approaches...

- **DeepWalk / node2vec:** Transductive: embed every node; new nodes need full retraining.
 - ▷ Not GNNs — random-walk based embeddings, no message passing
- **GCNs:** Often require access to the full graph during training/inference; can be costly to scale.
 - ▷ GNNs — but transductive: fixed node set at training
- **Result:** No compact parametric function to generate embeddings for unseen nodes.

This motivates GraphSAGE's key insight...

The Key Insight

The Key Insight

The Key Insight

Don't learn embeddings for each node...

Learn a **FUNCTION** that generates embeddings

By sampling & aggregating neighborhood features




GraphSAGE Framework

GraphSAGE: Inductive Framework

GraphSAGE Framework

Core Principle: Sample + Aggregate

- Learn **aggregator functions** (not node embeddings)
- For any node v : **sample neighbors, aggregate their features**
- Pass through learned neural networks
- **Inference:** Apply same function to unseen nodes



Implementation

Implementation

Implementation

Implementation details coming soon...

Hyperparameters

Hyperparameters

Hyperparameters

Hyperparameter tuning details coming soon...

Results

Experimental results coming soon...

Any Question?

- [1] Dominique Brodbeck et al. “Domesticating Bead: Adapting an Information Visualization System to a Financial Institution”. In: *Proceedings of the IEEE Symposium on Information Visualization (InfoVis '97)*. Los Alamitos, CA: IEEE Computer Society, 1997, pp. 73–80.
- [2] Aditya Grover and Jure Leskovec. “node2vec: Scalable Feature Learning for Networks”. In: *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. 2016, pp. 855–864.
- [3] William L. Hamilton, Rex Ying, and Jure Leskovec. “Inductive Representation Learning on Large Graphs”. In: *Advances in Neural Information Processing Systems (NeurIPS)*. Vol. 30. 2017, pp. 1024–1034. URL: <https://arxiv.org/abs/1706.02216>.
- [4] Susan Havre et al. “ThemeRiver: Visualizing Thematic Changes in Large Document Collections”. In: *IEEE Transactions on Visualization and Computer Graphics* 8.1 (2002), pp. 9–20. DOI: 10.1109/2945.981848.
- [5] Thomas N. Kipf and Max Welling. “Semi-Supervised Classification with Graph Convolutional Networks”. In: *arXiv preprint arXiv:1609.02907* (2016).
- [6] Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. “DeepWalk: Online Learning of Social Representations”. In: *Proceedings of the 20th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. 2014, pp. 701–710.
- [7] James A. Wise et al. “Visualizing the Non-Visual: Spatial Analysis and Interaction with Information from Text Documents”. In: *Readings in Information Visualization: Using Vision to Think*. Ed. by Stuart K. Card, Jock D. Mackinlay, and Ben Shneiderman. San Francisco: Morgan Kaufmann, 1999, pp. 442–445.