PrestaShop Cheat Sheet

PrestaShop 9.2.0 (2026-09-30) · 8.2.8 extended support · Symfony 6.4 · PHP 8.1-8.5
Checked on 2026-10-27 · Irurueta Docs, E-commerce > PrestaShop

VERSIONS AND SUPPORT

Branch	Latest	Status 2026-10-27
9.2.x	9.2.0 2026-09-30	maintained until 9.3.0
9.1.x / 9.0.x	9.1.5 08-18 / 9.0.3 02-03	ended
8.2.x	8.2.8 2026-08-18	extended: critical and security fixes until 10.0.0

PrestaShop	PHP (recommended)	Symfony
9.2 / 9.1	8.1 to 8.5 (8.5)	6.4 LTS
9.0	8.1 to 8.4 (8.4)	
8.x	7.2 to 8.1 (8.1)	4.4

PHP security ends: 8.1 2025-12-31, 8.2 2026-12-31, 8.3 2027-12-31, 8.4 2028-12-31, 8.5 2029-12-31: use 8.4 or 8.5 on new shops. The 9.2 PHP range is inferred.
9.2.0 ships: Symfony 6.4.46, Smarty 4.5.7, Twig 3.27.1, Doctrine ORM 2.20, API Platform 3.4.17, Hummingbird 2.1.2 (default theme), Classic 3.1.2 (deprecated). Needs MySQL 5.7+ or MariaDB 10.2+, Apache 2.4, memory_limit 512M; Node 24+ builds Hummingbird.
8 to 9: `FrameworkBundleAdminController` deprecated 9.0, removed 10.0 (use `PrestaShopAdminController`); legacy product page (18 hooks) and 7 login hooks removed; Guzzle, SwiftMailer gone.

INSTALL AND DOCKER

```
docker compose up -d  #
prestashop/prestashop:9.2.0 = latest
# PHP 8.5.12; tags 9.2.0-8.1 .. -8.5, -fpm,
nightly
php install/index_cli.php --db_server=.. --
db_name=.. --domain=..
```

PS_INSTALL_AUTO=1	run index_cli.php on first start; needs DB_SERVER, DB_PORT, DB_NAME, DB_USER, DB_PASSWD
PS_DOMAIN	host:port seen by the browser (else container IP is stored)
ADMIN_MAIL, ADMIN_PASSWD	first employee
PS_ENABLE_SSL	HTTPS
PS_DEV_MODE	default 0; any string but 0/empty (even "false") = dev ON
PS_FOLDER_ADMIN	leave default: the installer fails

9.2 deletes `install/` after install; the installer renames `admin` randomly.

MODULE SKELETON

```
modules/pcfcbasics/ pcfcbasics.php config.xml
composer.json
  src/Install/Installer.php upgrade/upgrade-
1.1.0.php
  config/{services,routes}.yml
views/{templates/hook,css}
```

```
if (!defined('_PS_VERSION_')) { exit; }
class Pcfcbasics extends Module {          // =
folder name
 __construct(): name, tab, version, author,
need_instance=0,
  ps_versions_compliancy=
['min'=>'9.0.0','max'=>'9.99.99'],
  bootstrap=true; parent::__construct();
displayName,
  description, confirmUninstall via $this->trans()
 isUsingNewTranslationSystem(): true
 install(): parent::install() && tables &&
Configuration
   && $this->registerHook('displayHeader')
 uninstall(): drop config + tables &&
parent::uninstall()
 hookDisplayHeader(array $params) {}   // 'hook' +
Name
```

Composer: `"type": "prestashop-module"`, PSR-4 `src/`, require `vendor/autoload.php`. Tables: `CREATE TABLE IF NOT EXISTS` in install, drop in uninstall.
Upgrade script: file `upgrade/upgrade-1.1.0.php` (exactly one dash: `upgrade-1.2.0-rc1.php` never runs), function `upgrade_module_1_1_0($module)`, run in order when the file version is newer; `install()` is not re-run, so add schema, keys and hooks there; anything but `true` stops the chain.

CQRS: COMMAND AND QUERY

`CommandBusInterface::handle($message)`; ids `prestashop.core.command_bus`, `prestashop.core.query_bus`; both wrap Symfony Messenger (synchronous, one handler per message, domain exceptions arrive unwrapped).

```
#[AsCommandHandler]        // or #[AsQueryHandler]
final class SetRoastDateHandler { public function
__invoke(
  SetRoastDateCommand $c): void {} }
$commandBus->handle(new SetRoastDateCommand($id,
$date));
$info = $queryBus->handle(new GetRoastDate($id));
```

`prestashop:list:commands-and-queries [--domain=Tax]`; `debug:messenger`.

COMMON HOOKS

Display hooks return HTML; action hooks ignore the return.

Front	displayHeader, displayHome, displayFooter, displayFooterBefore, displayProductAdditionalInfo, displayProductButtons, displayOrderDetail, displaySearch
Assets	actionFrontControllerSetMedia, actionFrontControllerSetVariables, actionAdminControllerSetMedia
Orders	actionValidateOrder, actionOrderHasBeenShipped, actionOrderHasBeenDelivered, actionCheckoutBuildProcess
Modules	actionModuleEnable, actionModuleDisable, actionModuleUpgradeAfter (9.1)
Dispatch	actionDispatcherBefore, actionDispatcher, actionDispatcherAfter

```
Hook::exec($hook_name, $hook_args = [], $id_module
= null,
 $array_return = false, $check_exceptions = true,
 $use_push = false, $id_shop = null, $chain =
false)
// own hook: $h = new Hook(); name, title,
description,
//  position = true; $h->add();  delete it in
uninstall()
// chain=true: each subscriber gets the previous
result
```

Smarty: `{hook h='displayX' product=$product}`.

SERVICES, ROUTES, ADMIN CONTROLLER

config/	Symfony: back office + Admin API (not front)
config/admin/	Symfony + admin legacy container
config/front/	light front container, explicit arguments

File priority, first wins (9.2+): `services.php`, `services-9.2.yml`, `services-9.yml`, `services.yml`.

```
services:
  _defaults: { public: false, autowire: true,
autoconfigure: true }
  PrestaShop\Module\Pcfdadmin\: { resource:
'../src/*',
    exclude:
['../src/index.php','../src/*/index.php'] }
# config/routes.yml
pcfdadmin_roasts:
  path: /pcfdadmin/roasts
  methods: [GET]
  defaults:
    _controller:
'PrestaShop\Module\Pcfdadmin\Controller\RoastContr
oller::indexAction'
    _legacy_controller: AdminPcfdadminRoasts   #
Tab class_name
    _legacy_link: AdminPcfdadminRoasts
class RoastController extends
PrestaShopAdminController {
 #[AdminSecurity("is_granted('read',
request.get('_legacy_controller'))")]
 public function indexAction(Request $r): Response
{
   return $this-
>render('@Modules/pcfdadmin/views/templates/admin/
x.html.twig', []); }
 #[DemoRestricted(redirectRoute:
'pcfdadmin_roasts')]  // writes
 // $this->isCsrfTokenValid('id', $t); $this-
>addFlash(..)
```

Declare the page in main class `$tabs` (class_name, parent_class_name): it creates the menu entry and 4 roles `ROLE_MOD_TAB_*_CREATE|READ|UPDATE|DELETE`. After services or routes change: `cache:clear` (and `--app-id=admin-api`).

OBJECTMODEL AND Db SAFETY RULES

- Table = `_DB_PREFIX_` + module + name; `Db::execute()/executeS()` add no prefix, `insert/update/delete` and `DbQuery::from()` do. Engine `_MYSQL_ENGINE_`, `utf8mb4`.
- **Cast and escape: `(int)/(float)`, `pSQL($s)` strings, `bqSQL($c)` identifiers; `pSQL($s, true)` keeps HTML (purify first).**
- Never alter core tables or add foreign keys to them: own table, ObjectModel or Extra Properties (9.2). Never show SQL errors.

```
public static $definition =
['table'=>'pcfe47_roast_batch',

'primary'=>'id_pcfe47_roast_batch','multilang'=>tr
ue,'fields'=>[
 'sku'=>
['type'=>self::TYPE_STRING,'validate'=>'isReferenc
e',
   'required'=>true,'size'=>32],
 'kg'=>
['type'=>self::TYPE_FLOAT,'validate'=>'isFloat'],
 'note'=>
['type'=>self::TYPE_STRING,'lang'=>true,'validate'
=>'isCleanHtml']]];
```

Keys: type, validate, required, size, values, range, default, lang, shop, allow_null. Types: INT, BOOL, FLOAT, STRING, HTML, DATE, SQL, NOTHING (unsafe). Overrides are exclusive and forbidden in partner modules: prefer hooks or `#[AsDecorator]`.

THEME FILES AND theme.yml

```
themes/NAME/ config/theme.yml preview.png
assets/css/
  templates/{catalog,layouts}/*.tpl
modules/MOD/views/..
```

```
parent: hummingbird    name: pcfgcoffee   (=
folder)
display_name: Pocket Coffee   version: 1.0.0
author: {name,url}
meta: {compatibility: {from: 9.2.0, to: ~9.2.0,
  framework: bootstrap-v5.3.3}, available_layouts:
{..}}
assets: {use_parent_assets: true, css: {all: [{id:
x,
  path: assets/css/x.css, priority: 210}]}}
global_settings: {image_types: {cart_default:
{width: 125,
  height: 125, scope: [products]}, ..}, hooks:
{custom_hooks: []}}
theme_settings: {default_layout: layout-full-
width}
```

All parent `image_types` are required or `prestashop:theme:enable` fails. Override: `{extends file='parent:catalog/product.tpl'}` + `{block name='x' append}`.

WEBSERVICE (/api): key as Basic user

```
Configuration::updateValue('PS_WEBSERVICE', 1);
// Apache CGIPassAuth On
$k = new WebserviceKey(); $k->key =
bin2hex(random_bytes(16)); $k->save();
WebserviceKey::setPermissionForAccount($k->id,
['products'=>['GET'=>1]]); $k->associateTo([1]);
curl -s -g -u "${PS_WS_KEY}:" "$B/customers?
display=[id,email]
 &filter[email]=%[example.test]&sort=
[id_DESC]&limit=0,10&output_format=JSON"
# filters [a] ![a] >[n] [a,b] %[x]; ?
schema=blank|synopsis
# POST (XML) 201, PUT, PATCH, DELETE; Local-
Content-Sha1 -> 304
```

ADMIN API (/admin-api)

```
bin/console prestashop:api-client create erp --
name="ERP" \
  --scopes=product_read,customer_group_write --
timeout=900
curl -X POST https://shop.example.test/admin-
api/access_token \
 -d grant_type=client_credentials -d
client_id="${PS_CLIENT_ID}" \
 -d client_secret="${PS_CLIENT_SECRET}" -d
scope="product_read"
#
{"token_type":"Bearer","expires_in":900,"access_to
ken":".."}
curl -H "Authorization: Bearer ${PS_TOKEN}" \
 "https://shop.example.test/admin-api/products?
limit=2&orderBy=productId&sortOrder=desc"
# POST 201 | PUT | PATCH partial | DELETE 204
```

OAuth2 client credentials + JWT. Scopes `RESOURCE_read|_write` (71 in 9.2.0); write does not imply read (403). HTTPS only; switch `PS_ENABLE_ADMIN_API`.

bin/console AND CACHE

`prestashop:config get|set|remove KEY [--value=]`, `prestashop:module install|uninstall|enable|disable|reset|upgrade|delete`, `prestashop:module:list`, `prestashop:feature-flag list|enable|disable`, `prestashop:api-client create|delete`, `prestashop:employee:create-admin`, `prestashop:theme:enable|export`, `prestashop:search:index [--full]`, `prestashop:thumbnails:regenerate`, `prestashop:htaccess:generate`, `debug:router|container|messenger`.

```
bin/console cache:clear --env=prod [--app-
id=admin-api]
bin/console cache:warmup --env=prod     # -e
default is dev!
# --no-debug --app-id=admin|admin-api -n -vvv;
debug:router
# failing module action still exits 0: check
module:list
```

SECURITY HARDENING CHECKLIST

- Patch core and modules separately (`ps_facetedsearch` < 4.0.4: CVE-2026-54159, CVSS 10).
- Production: `_PS_MODE_DEV_`, `_PS_DEBUG_PROFILING_` false; PHP 8.4/8.5; HTTPS via `PS_SSL_ENABLED_EVERYWHERE`.
- Core sends no CSP, X-Frame-Options or HSTS: add them at the web server (CSP Report-Only first).
- DB account limited to the shop schema; web user writes only var/, img/, upload/, download/.
- Back office: strong passwords, minimum profiles, admin folder limited by IP/VPN; `PS_SHOP_ENABLE` + `PS_MAINTENANCE_IP` for maintenance.
- Module code: Smarty `|escape:'html':'UTF-8'` (avoid `nofilter`); CSRF tokens + `hash_equals()`; `#[AdminSecurity]` on admin actions.