

FICHA TÉCNICA

Tira de LED flexible COB de 5m CRI90
17W/m 85W 24V

29017()71



CARACTERÍSTICAS

Tipo	PVC, flexible, 528chip/m, chip EPISTAR
CRI y protección	CRI90, IP20 Y IP65
Voltaje:	24V
Potencia:	17W/m - 85W/5m
Temperatura	Ta: -20° a 40° // Tc: 60°
Ángulos	120°
Vida útil	30000 Horas
Garantía	3 Años

ESPECIFICACIONES TÉCNICAS

IP20

-  **29017(2022)71:** Tira Led 2200k, 7600Lm
-  **29017(2032)71:** Tira Led 2600-3200k, 7900Lm
-  **29017(2040)71:** Tira Led 4000-4200k, 8200Lm
-  **29017(2060)71:** Tira Led 6000-6500k, 8500Lm



IP65

-  **29017(6522)71:** Tira Led 2200k, 7600Lm
-  **29017(6532)71:** Tira Led 2600-3200k, 7900Lm
-  **29017(6540)71:** Tira Led 4000-4200k, 8200Lm
-  **29017(6560)71:** Tira Led 6000-6500k, 8500Lm


DIMENSIONES

Rollo: 5 metros

IP20



IP67



APLICACIONES

Aplicación	Descripción
Iluminación directa e indirecta	Equilibrio entre funcionalidad y estética
Señalización	Iluminación precisa y uniforme para alta visibilidad
Publicidad	Resalta marcas y mensajes con máxima eficiencia visual

