

INRAE



université
PARIS-SACLAY


➤ Making sense of CNNs: Visualization techniques

Alberto TONDA, Ph.D. (Senior permanent researcher, DR)

*UMR 518 MIA-PS, INRAE, AgroParisTech, Université Paris-Saclay
UAR 3611, Institut des Systèmes Complexes de Paris Île-de-France*

➤ Outline

- xAI: eXplainable AI
- Visualization of feature patterns
- Saliency maps
- Grad-CAM



➤ Black-box effect

- Black-box effect is common to all ML algorithms
 - We know that the prediction is, but not why the model did it
 - Too many parameters to analyze, even for RF or big Decision Trees
- For CNNs, it's even *worse*
 - Feature construction/extraction step
 - What are the features used? What do they look like?
 - What parts of the images is the CNN analyzing to give a decision?

➤ xAI: eXplainable AI

- Relatively new research field
 - “Open the black box”, answer “Why is it behaving like that?”
 - **Local explanation**: why behavior for **this sample**?
 - **Global explanation**: why behavior in general, or for a class?
- Ongoing discussion
 - What is the definition of **explanation**?
 - Difference between *explanation* and *interpretation*
 - Is it possible to build white-box ML algorithms? Yes, but...*

*...this is a long discussion. The short version is that there seems to be a **trade-off** between **interpretability** and **performance**




➤ xAI: eXplainable AI

- Model-agnostic methods
 - Local Interpretable Model-agnostic Explanations (LIME)
 - SHapley Additive exPlanations (SHAP/SHAPLY)
 - Relative feature importance (e.g. permutation importance)
- For CNNs, we have some model-specific methods
 - Since the models are performing **feature construction/extraction**
 - We are not even sure of *what the features are!*





➤ Visualization of feature patterns



Feature visualization of convolutional net trained on ImageNet from [Zeiler & Fergus 2013]

➤ Visualization of feature patterns

- Optimize an *image*
 - Treat pixel values as variables in the optimization problem
 - Generate image that *maximizes* output of a target filter
 - Backpropagating gradients to the *pixels*



➤ Hooks?

- The implementation uses **pytorch hooks**
 - Not very well documented
 - Essentially, connect a function to a module or tensor
 - Every time computes outputs (**forward**)...
 - Every time computes gradient (**backward**)...
 - ...the function is invoked!
- Useful for debugging or visualization
 - Without having to tweak with model
 - E.g. without writing extra methods



➤ Saliency maps

- What are the **most important pixels** for the decision?
 - Forward pass of an image through the network
 - Take relevant output (classification: tensor value for target class)
 - Compute derivative of that output w.r.t. to *pixels* (backward pass)
- Pixels with **high values of gradient** are more important
 - Changing their value might greatly impact decision
 - Visualize which pixels impact decision the most

➤ Grad-CAM

- Looking at *one single pixel* at the time not very informative
 - Later CNN filters (high-level features) map to *image areas*
 - Can't we do the same as saliency maps, but image areas?
- Gradient-weighted Class Activation Maps
 - Focus is on a **target class** for a classification problem
 - Outputs of **target modules(s)** more important for final decision?
- Obstacle: last part of CNN is a very complex set of non-linearities, hard to interpret
- Solution: replace it with a linear classifier, retrain it



INRAE



université
PARIS-SACLAY

➤ Questions?

Bibliography

- Lundberg, S. M., & Lee, S. I. (2017). *A unified approach to interpreting model predictions*. Advances in neural information processing systems, 30. [**SHAP**]
- Ribeiro, M. T., Singh, S., & Guestrin, C. (2016). "Why should I trust you?" *Explaining the predictions of any classifier*. In Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining (pp. 1135-1144). [**LIME**]
- Selvaraju, R. R., Cogswell, M., Das, A., Vedantam, R., Parikh, D., & Batra, D. (2017). *Grad-cam: Visual explanations from deep networks via gradient-based localization*. In Proceedings of the IEEE international conference on computer vision (pp. 618-626).
- Simonyan, K., Vedaldi, A., & Zisserman, A. (2013). Deep inside convolutional networks: Visualising image classification models and saliency maps. arXiv preprint arXiv:1312.6034.
- Springenberg, J. T., Dosovitskiy, A., Brox, T., & Riedmiller, M. (2014). *Striving for simplicity: The all convolutional net*. arXiv preprint arXiv:1412.6806. [**Visualizing Feature Patterns**]

Images and videos: unless otherwise stated, I stole them from the Internet. I hope they are not copyrighted, or that their use falls under the Fair Use clause, and if not, I am sorry. Please don't sue me.