

arXiv forecasts

Executive summary

Roberto Albesiano, Maneesha Ampagouni, Bobby Zhang

Project Mentor: Alec Traaseth

GitHub: [arXiv forecasts](#)

The [arXiv](#) is a major open-access repository for preprints in fields such as Physics, Mathematics, and Computer Science. Given the high and varying volume of daily submissions, the visibility of a preprint may change significantly depending on when it is posted.

Goal. Develop a short-term forecasting algorithm to predict the number of preprints to be posted daily per category in the upcoming week: the fewer competing papers, the higher chance of being noticed.

We assume that preprint visibility is inversely related to the number of submissions on a given day. This is supported by the fact that arXiv usage seems fairly stable throughout the week and does not increase proportionally with the number of submissions.

Data sources

- For preprints metadata, we use the official arXiv [Kaggle](#) dataset.
- We collect usage data directly from the [arXiv API](#).

Usage data

Aiming for the day with fewest posts is not necessarily the best strategy if the audience size depends on the day of the week or on the number of posts. Analysis of usage data shows that:

- the day of the week does not have a statistically significant effect on arXiv traffic,
- there is no statistically significant correlation between number of posts and arXiv traffic.

Best strategy: assume audience is constant and aim for the day with fewest predicted posts.

Baseline models

We compare four simple baseline models, trained on a 150-day rolling window:

- **Dummy model:** predict the mean.
- **Time regression** (`t_reg`): linear regress in time.
- **Weekday regression** (`day_reg`): predict the mean for each business day.
- **Time/weekday regression** (`tday_reg`): combine `t_reg` and `day_reg`.

The best performing model in training is `day_reg`, having the lowest mean squared error for 53.5% of the categories. It turns out that this model is probably overfitting (see the following section).

Models comparison

We study the performance of three models — Holt–Winters (both additive and multiplicative), SARIMA, and [Facebook Prophet](#) — in comparison with the dummy model and `day_reg`:

- **SARIMA** is the strongest and most stable forecasting model overall, recommended as the primary choice for most categories.
- **Holt–Winters** performs nearly as well, offering faster training and a good alternative to SARIMA.
- The **dummy model** serves as a reliable baseline, particularly effective for stationary data.
- **Facebook Prophet** shows high variance and poor performance on sparse or noisy data, and is generally not recommended.
- The **regression on weekdays** baseline model (`day_reg`) actually performs very poorly in testing, likely indicating overfitting during training.

Future directions

- **Improve performance for challenging categories:** Some categories exhibit poor forecasting performance across all models. Future work can focus on developing category-specific models to improve accuracy in these harder cases.
- **Long-term forecasting:** Extend the framework to support long-term visibility forecasting. This could help researchers explore adjacent fields by identifying categories projected to receive more attention over time.
- **Interactive web application:** Build a user-friendly web app that leverages these forecasting models to assist researchers in selecting optimal submission dates and viewing category-level predictions, enhancing accessibility and practical impact.