

arXiv forecasts

Executive summary

Roberto Albesiano, Maneesha Ampagouni, Bobby Zhang

Project Mentor: Alec Traaseth

GitHub: [arXiv forecasts](#)

Abstract

The [arXiv](#) is a major open-access repository for preprints in fields like Physics, Mathematics, and Computer Science. Given the high and varying volume of daily submissions, the visibility of a preprint can depend heavily on when it is posted.

The goal of this project is to develop a short-term forecasting algorithm that predicts the number of preprints to be posted per category in the upcoming week. By identifying days with the lowest expected submission counts, the model would help researchers to strategically select submission dates to maximize visibility and audience reach.

The strategy is based on the assumption that preprint visibility is inversely related to the number of submissions on a given day — i.e. the fewer competing papers, the higher chance of being noticed. This is supported by the analysis of the arXiv usage data, which shows that usage remains fairly stable throughout the week and does not increase proportionally with the number of submissions.

Data collection, cleaning, and pre-processing

The arXiv maintains an official dataset on [Kaggle](#), containing metadata for more than 2.2 million preprints submitted since the late 1980s. Each entry includes fields such as `id`, `authors`, `title`, `categories`, `abstract`, `versions`, and more. We perform the following cleaning/pre-processing steps:

1. Remove unessential columns, retaining only `id`, `versions`, and `categories`.
2. Extract the date of the first version from the `v1` field of `versions`.
3. Split space-separated category strings from `categories` into lists of individual categories.
4. Identify and map outdated or deprecated category labels to current ones.
5. Construct a date-indexed dataset recording the number of preprints submitted per category on each day. This dataset is the primary input for forecasting models.

Additionally, we collect daily arXiv usage data — specifically, the number of connections to the arXiv website per day from 2024/01/01 to 2025/04/10 — directly from the [arXiv API](#):

1. For every date in the totals dataset, connect to the API and request usage.
2. Sum the daily connections (given as hourly usage).
3. Create a new dataset of daily connections.

Usage data

Aiming for the day with fewest posts is not necessarily the best strategy if the audience size depends on the day of the week or on the number of posts. We analyze the number of server connections, which serves as a proxy for audience size, to see if it depends on the day of the week or the number of posts.

- **Dependence on day of the week:** An F-test comparing the null hypothesis of no dependence on day of the week to the alternative hypothesis of dependence on day of the week gives a p-value of 0.706, indicating that the **day of the week does not have a statistically significant effect** on arXiv traffic.
- **Correlation with submissions:** A Pearson correlation analysis between the number of connections and the total number of article appearances per day shows a correlation coefficient of approximately 0.0095 with a p-value of 0.863, indicating again **no statistically significant correlation between number of posts and arXiv traffic**.

Thus, the best strategy is to assume that audience is constant, and to aim for the day with fewest predicted posts.

Baseline models

To evaluate short-term forecasting performance, we implement and compare four simple baseline models, trained on 150-day rolling windows and evaluated using 5-fold cross-validation with a 15-business-day test horizon:

- **Dummy model:** Predicts the mean of the previous 150 days.
- **Time regression (`t_reg`):** Linear regression on time only (captures trend).
- **Weekday regression (`day_reg`):** Linear regression on one-hot encoded weekdays features (captures weekly seasonality).
- **Time/weekday regression (`tday_reg`):** Combines both trend and weekday information in a single linear model.

The best performing model in training is `day_reg`, having the lowest mean squared error for 53.5% of the categories. It turns out that this model is probably overfitting (see the following section).

Model comparison

We study the performance of three models — Holt–Winters (both additive and multiplicative), SARIMA, and [Facebook Prophet](#) — compared to the baseline model (`day_reg`):

- **SARIMA** is the strongest and most stable forecasting model overall, recommended as the primary choice for most categories.
- **Holt–Winters** performs nearly as well, offering faster training and a good alternative to SARIMA.
- The **dummy model** serves as a reliable baseline, particularly effective for stationary data.
- **Facebook Prophet** shows high variance and poor performance on sparse or noisy data, and is generally not recommended.
- The **regression on weekdays** baseline model (`day_reg`) actually performs the worst in testing, likely indicating overfitting during training.

Future directions

- **Improve performance for challenging categories:** Some categories exhibit poor forecasting performance across all models. Future work can focus on developing category-specific models to improve accuracy in these harder cases.
- **Long-term forecasting:** Extend the framework to support long-term visibility forecasting. This could help researchers explore adjacent fields by identifying categories projected to receive more attention over time.
- **Interactive web application:** Build a user-friendly web app that leverages these forecasting models to assist researchers in selecting optimal submission dates and viewing category-level predictions, enhancing accessibility and practical impact.