

# What is Decidable about String Constraints with the ReplaceAll Function

Taolue Chen (Birkbeck)

Yan Chen (Chinese Academy of Sciences)

Matthew Hague (Royal Holloway)

Anthony W. Lin (Oxford)


Zhilin Wu (Chinese Academy of Sciences)

# String Data Type

Prevalent in today's software


# String Data Type

Prevalent in today's software



# String Data Type


Prevalent in today's software



← `<a onclick="viewPerson('Ben')">Ben</a>`

# String Data Type

Prevalent in today's software




← `<a onclick="viewPerson('Ben')">Ben</a>`

Dynamically generated by

```
var x = htmlEscape(name);
var y = escapeString(x);
nameElem.innerHTML = '<a onclick=' +
    '"viewPerson(\' ' + y + '\')"' + x + '</a>';
```

# String Data Type

Prevalent in today's software



← `<a onclick="viewPerson('Ben')">Ben</a>`


Dynamically generated by

```
var x = htmlEscape(name);  
var y = escapeString(x);  
nameElem.innerHTML = '<a onclick=' +  
    '"viewPerson(\"' + y + '\")">' + x + '</a>';
```

Many string-related bugs — hard to find by random testing

# String Data Type

Prevalent in today's software



← `<a onclick="viewPerson('Ben')">Ben</a>`

Dynamically generated by

```
var x = htmlEscape(name);
var y = escapeString(x);
nameElem.innerHTML = '<a onclick=' +
    '"viewPerson(\' + y + \' )"' + x + '</a>';
```


Many string-related bugs — hard to find by random testing

`<a onclick="viewPerson(''); attackScript();....."> ..... </a>`

XSS

# String Data Type

Prevalent in today's software



← `<a onclick="viewPerson('Ben')">Ben</a>`

Dynamically generated by

```
var x = htmlEscape(name);  
var y = escapeString(x);  
nameElem.innerHTML = '<a onclick=' +  
    '"viewPerson(\' ' + y + '\')"' + x + '</a>';
```

Many string-related bugs — hard to find by random testing


`<a onclick="viewPerson(''); attackScript();....."> ..... </a>`

XSS



# String Data Type

Prevalent in today's software



← `<a onclick="viewPerson('Ben')">Ben</a>`

Dynamically generated by

```
var x = htmlEscape(name);  
var y = escapeString(x);  
nameElem.innerHTML = '<a onclick=' +  
    '"viewPerson(\' + y + \' )"' + x + '</a>';
```

Many string-related bugs — hard to find by random testing

`<a onclick="viewPerson(''); attackScript();....."> ..... </a>`

XSS

**Q:** Does the sanitisation work?

# String theory (a la SMT)

**Constants/Variables:** over the string domain (over a finite alphabet)

**String operations:**

- equality (=)
- concatenation (+)
- regex matching
- length function (len)
- replaceAll
- ...

**Formulas:** quantifier-free, first-order

**Problem:** satisfiability (existence of a solution)

# String theory (a la SMT)

**Constants/Variables:** over the string domain (over a finite alphabet)

**String operations:**

- equality (=)
- concatenation (+)
- regex matching
- length function (len)
- replaceAll
- ...

**Formulas:** quantifier-free, first-order

**Problem:** satisfiability (existence of a solution)

$$(y + \text{'ba'} + x) = (x + \text{'ab'} + y)$$

# String theory (a la SMT)

**Constants/Variables:** over the string domain (over a finite alphabet)

**String operations:**

- equality (=)
- concatenation (+)
- regex matching
- length function (len)
- replaceAll
- ...

**Formulas:** quantifier-free, first-order

**Problem:** satisfiability (existence of a solution)

$$(y + \text{'ba'} + x) = (x + \text{'ab'} + y)$$

**satisfiable:**  $x \rightarrow \text{'b'}$ ,  $y \rightarrow \text{''}$

# String Solvers Everywhere

Kaluza

Z3

Z3-str

Kudzu

PISA

IBM AppScan

HAMPI

Saner

Sloth

S3

Stranger

STP

Norn

StrSolve

...

CVC4

SUSHI

# String Solvers Everywhere

Kaluza

Z3

Z3-str

Kudzu

PISA

IBM AppScan

HAMPI

Saner

Sloth

S3

Stranger

STP

Norn

StrSolve

...

CVC4

SUSHI

**Focus on “heuristics”**

# Decidable String Theories

# Decidable String Theories

## Word Equations

$$(y + \text{'ba'} + x = x + \text{'ab'} + y)$$

Decidable [Makanin'77]



# Decidable String Theories

## Word Equations

$$(y + \text{'ba'} + x = x + \text{'ab'} + y)$$

Decidable [Makanin'77]

## Word Equations with Regular Constraints

$$(y + \text{'ba'} + x = x + \text{'ab'} + y) \wedge x \text{ in } a^*$$

Decidable [Schulz'90]

# Decidable String Theories

## Word Equations

$$(y + \text{'ba'} + x = x + \text{'ab'} + y)$$

Decidable [Makanin'77]

## Word Equations with Regular Constraints

$$(y + \text{'ba'} + x = x + \text{'ab'} + y) \wedge x \text{ in } a^*$$

Decidable [Schulz'90]

## Theory of Concatenation with Regular Constraints

$$s_2 = s_1 + s_1 \wedge s_3 + s_2 \neq s_1 + s_7 + s_8 \\ \wedge s_1 \text{ in } a^* \wedge s_3 \text{ in } b^* a^*$$

Decidable [Buchi&Senger'90]

# Decidable String Theories

## Word Equations

$$(y + \text{'ba'} + x = x + \text{'ab'} + y)$$

Decidable [Makanin'77]

## Word Equations with Regular Constraints

$$(y + \text{'ba'} + x = x + \text{'ab'} + y) \wedge x \text{ in } a^*$$

Decidable [Schulz'90]

## Theory of Concatenation with Regular Constraints

$$s_2 = s_1 + s_1 \wedge s_3 + s_2 \neq s_1 + s_7 + s_8 \\ \wedge s_1 \text{ in } a^* \wedge s_3 \text{ in } b^* a^*$$

Decidable [Buchi&Senger'90]

## Word Equations with Length Constraints

$$(y + \text{'ba'} + x = x + \text{'ab'} + y) \wedge \\ (\text{len}(x) = \text{len}(y))$$

**Long-standing classical  
open problem**

# Decidable String Theories

## Word Equations

$$(y + 'ba' + x = x + 'ab' + y)$$

Decidable [Makanin'77]

## Word Equations with Regular Constraints

$$(y + 'ba' + x = x + 'ab' + y) \wedge x \text{ in } a^*$$

Decidable [Schulz'90]

## Theory of Concatenation with Regular Constraints

$$s_2 = s_1 + s_1 \wedge s_3 + s_2 \neq s_1 + s_7 + s_8 \\ \wedge s_1 \text{ in } a^* \wedge s_3 \text{ in } b^* a^*$$

Decidable [Buchi&Senger'90]

## Word Equations with Length Constraints

$$(y + 'ba' + x = x + 'ab' + y) \wedge \\ (\text{len}(x) = \text{len}(y))$$

**Long-standing classical  
open problem**

Many string operations are still missing

**Problem: replaceAll is  
by and large missing**

**Problem:** **replaceAll** is  
by and large missing

**Proposal:** add **replaceAll**  
to string theories in a  
decidable way

# The ReplaceAll Function

```
replaceAll(subject,pat,rep)
```

# The ReplaceAll Function

**replaceAll**(*subject*,*pat*,*rep*)

**Output:** *subject* with \*all\* occurrences of strings matching *pat* replaced by *rep*



# The ReplaceAll Function

**replaceAll**(*subject*,*pat*,*rep*)

**Output:** *subject* with \*all\* occurrences of strings matching *pat* replaced by *rep*

In VIM: %s/*pat*/*rep*/g

# The ReplaceAll Function

**replaceAll**(*subject*,*pat*,*rep*)

**Output:** *subject* with \*all\* occurrences of strings matching *pat* replaced by *rep*

In VIM: %s/*pat*/*rep*/g

## The Road Not Taken

BY ROBERT FROST

Two roads diverged in a yellow wood,  
And sorry I could not travel both  
And be one traveler, long I stood  
And looked down one as far as I could  
To where it bent in the undergrowth;

Then took the other, as just as fair,  
And having perhaps the better claim,  
Because it was grassy and wanted wear;  
Though as for that the passing there  
Had worn them really about the same,

And both that morning equally lay  
In leaves no step had trodden black.  
Oh, I kept the first for another day!  
Yet knowing how way leads on to way,  
I doubted if I should ever come back.

I shall be telling this with a sigh  
Somewhere ages and ages hence:  
Two roads diverged in a wood, and I—  
I took the one less traveled by,  
And that has made all the difference.

*subject*

# The ReplaceAll Function

**replaceAll**(*subject*,*pat*,*rep*)

**Output:** *subject* with \*all\* occurrences of strings matching *pat* replaced by *rep*

In VIM: %s/*pat*/*rep*/g

## The Road Not Taken

BY ROBERT FROST

Two roads diverged in a yellow wood,  
And sorry I could not travel both  
And be one traveler, long I stood  
And looked down one as far as I could  
To where it bent in the undergrowth;

Then took the other, as just as fair,  
And having perhaps the better claim,  
Because it was grassy and wanted wear;  
Though as for that the passing there  
Had worn them really about the same,

And both that morning equally lay  
In leaves no step had trodden black.  
Oh, I kept the first for another day!  
Yet knowing how way leads on to way,  
I doubted if I should ever come back.

I shall be telling this with a sigh  
Somewhere ages and ages hence:  
Two roads diverged in a wood, and I—  
I took the one less traveled by,  
And that has made all the difference.

*pat* = "Two"

*rep* = "Three"

*subject*

# The ReplaceAll Function

**replaceAll**(*subject*,*pat*,*rep*)

**Output:** *subject* with \*all\* occurrences of strings matching *pat* replaced by *rep*

In VIM: %s/*pat*/*rep*/g

## The Road Not Taken

BY ROBERT FROST

Two roads diverged in a yellow wood,  
And sorry I could not travel both  
And be one traveler, long I stood  
And looked down one as far as I could  
To where it bent in the undergrowth;

Then took the other, as just as fair,  
And having perhaps the better claim,  
Because it was grassy and wanted wear;  
Though as for that the passing there  
Had worn them really about the same,

And both that morning equally lay  
In leaves no step had trodden black.  
Oh, I kept the first for another day!  
Yet knowing how way leads on to way,  
I doubted if I should ever come back.

I shall be telling this with a sigh  
Somewhere ages and ages hence:  
Two roads diverged in a wood, and I—  
I took the one less traveled by,  
And that has made all the difference.

*pat* = "Two"

*rep* = "Three"

*subject*

# The ReplaceAll Function

**replaceAll**(*subject*,*pat*,*rep*)

**Output:** *subject* with \*all\* occurrences of strings matching *pat* replaced by *rep*

In VIM: %s/*pat*/*rep*/g

## The Road Not Taken

BY ROBERT FROST

Two roads diverged in a yellow wood,  
And sorry I could not travel both  
And be one traveler, long I stood  
And looked down one as far as I could  
To where it bent in the undergrowth;

Then took the other, as just as fair,  
And having perhaps the better claim,  
Because it was grassy and wanted wear;  
Though as for that the passing there  
Had worn them really about the same,

And both that morning equally lay  
In leaves no step had trodden black.  
Oh, I kept the first for another day!  
Yet knowing how way leads on to way,  
I doubted if I should ever come back.

I shall be telling this with a sigh  
Somewhere ages and ages hence:  
Two roads diverged in a wood, and I—  
I took the one less traveled by,  
And that has made all the difference.

*subject*

*pat* = "Two"

*rep* = "Three"

## The Road Not Taken

BY ROBERT FROST

Three roads diverged in a yellow wood,  
And sorry I could not travel both  
And be one traveler, long I stood  
And looked down one as far as I could  
To where it bent in the undergrowth;

Then took the other, as just as fair,  
And having perhaps the better claim,  
Because it was grassy and wanted wear;  
Though as for that the passing there  
Had worn them really about the same,

And both that morning equally lay  
In leaves no step had trodden black.  
Oh, I kept the first for another day!  
Yet knowing how way leads on to way,  
I doubted if I should ever come back.

I shall be telling this with a sigh  
Somewhere ages and ages hence:  
Three roads diverged in a wood, and I—  
I took the one less traveled by,  
And that has made all the difference.


%s/Two/Three/g

# Application I: Sanitisers

```
var x = htmlEscape(name);  
var y = escapeString(x);  
nameElem.innerHTML = '<a onclick=' +  
    '"viewPerson\' + y + '\'">' + x + '</a>';
```


# Application I: Sanitisers

```
var x = htmlEscape(name);  
var y = escapeString(x);  
nameElem.innerHTML = '<a onclick=' +  
    '"viewPerson(\"' + y + '\")">' + x + '</a>';
```



# Application I: Sanitisers

```
var x = htmlEscape(name);  
var y = escapeString(x);  
nameElem.innerHTML = '<a onclick=' +  
    '"viewPerson(\"' + y + '\")">' + x + '</a>';
```





# Application II: Web Templating

# Application II: Web Templating

## HTML template (with Mustache)

```
...  
<h1> User <span  
  onclick="popupText('{{bio}}')">  
  {{userName}}</span> </h1>  
...
```

# Application II: Web Templating

## HTML template (with Mustache)

```
...  
<h1> User <span  
  onclick="popupText('{{bio}}')">  
  {{userName}}</span> </h1>  
...
```

## JSON files

```
...  
bio = "John is 19";  
userName = "John";  
...
```

# Application II: Web Templating

## HTML template (with Mustache)



```
...  
<h1> User <span  
  onclick="popupText('{{bio}}')">  
  {{userName}}</span> </h1>  
...
```

## HTML

```
...  
<h1> User <span  
  onclick="popupText('John is 19')">  
  John</span> </h1>  
...
```

## JSON files

```
...  
bio = "John is 19";  
userName = "John";  
...
```



# Application II: Web Templating

## HTML template (with Mustache)



```
...  
<h1> User <span  
  onclick="popupText('{{bio}}')">  
  {{userName}}</span> </h1>  
...
```

## HTML

```
...  
<h1> User <span  
  onclick="popupText(''); attackScript('')">  
  Evil</span> </h1>  
...
```

## JSON files

```
...  
bio = "'); attackScript('';  
userName = "Evil";  
...
```



# replaceAll in String Theory

```
x = replaceAll(subject,pat,rep)
```

# replaceAll in String Theory


```
x = replaceAll(subject,pat,rep)
```

Can be a string constant/variable



# replaceAll in String Theory

$x = \mathbf{replaceAll}(subject, pat, rep)$



Can be a string constant/variable


*pat* can be a regular expression (over string constants)

(semantics: leftmost/longest match)



# replaceAll in String Theory

$x = \mathbf{replaceAll}(subject, pat, rep)$



Can be a string constant/variable

`pat` can be a regular expression (over string constants)


(semantics: leftmost/longest match)

**Most common usage: `pat/rep` are constants**

`escapeString(x,z) := y = replaceAll(x,"","\'") /\ z = replaceAll(y,'","\')`

# replaceAll in String Theory

$x = \mathbf{replaceAll}(subject, pat, rep)$



Can be a string constant/variable

`pat` can be a regular expression (over string constants)

(semantics: leftmost/longest match)

**Most common usage: `pat/rep` are constants**

`escapeString(x,z) := y = replaceAll(x,"","\'") /\ z = replaceAll(y,'","\')`

**Not so uncommon usage: `rep` is a variable, `pat` is a constant**

`mustache(x,z,bio,userName) := y = replaceAll(x,{{bio}},bio) /\  
z = replaceAll(y,{{userName}},userName)`

# Bad News

**Proposition (Folklore):** String constraints with equality, regex, and replaceAll (pat/rep constants) is **undecidable**

# Bad News

**Proposition (Folklore):** String constraints with equality, regex, and replaceAll (pat/rep constants) is **undecidable**

**Easy reduction from Post Correspondence Problem**

# Bad News

**Proposition (Folklore):** String constraints with equality, regex, and replaceAll (pat/rep constants) is **undecidable**

**Easy reduction from Post Correspondence Problem**

1	2	3
a	ab	bba
baa	aa	bb

# Bad News

**Proposition (Folklore):** String constraints with equality, regex, and replaceAll (pat/rep constants) is **undecidable**

**Easy reduction from Post Correspondence Problem**

1	2	3
a	ab	bba
baa	aa	bb

$x \text{ in } (1+2+3)^* \wedge$

$y = \text{replaceAll}(x, 1, a) \wedge y' = \text{replaceAll}(y, 2, ab) \wedge y'' = \text{replaceAll}(y', 3, bba) \wedge$

$z = \text{replaceAll}(x, 1, baa) \wedge z' = \text{replaceAll}(z, 2, aa) \wedge z'' = \text{replaceAll}(z, 3, bb) \wedge$

$y'' = z''$

# “Straight-Line” Framework

[Lin&Barcelo, POPL’16]

# “Straight-Line” Framework

[Lin&Barcelo, POPL’16]

Consider a symbolic execution in a program



# “Straight-Line” Framework

[Lin&Barcelo, POPL'16]

Consider a symbolic execution in a program

$$S ::= y := f(x_1, \dots, x_n) \mid \mathbf{assert}(g(x_1, \dots, x_n)) \mid S_1; S_2$$

where

$$f : (\Sigma^*)^n \rightarrow \Sigma^*$$
$$g : (\Sigma^*)^n \rightarrow \{0, 1\}$$

# “Straight-Line” Framework

[Lin&Barcelo, POPL'16]

Consider a symbolic execution in a program

$$S ::= y := f(x_1, \dots, x_n) \mid \mathbf{assert}(g(x_1, \dots, x_n)) \mid S_1; S_2$$

where

$$f : (\Sigma^*)^n \rightarrow \Sigma^*$$
$$g : (\Sigma^*)^n \rightarrow \{0, 1\}$$

**Path Feasibility Problem:** decide if there exist input strings that satisfy all the assertions

# “Straight-Line” Framework

[Lin&Barcelo, POPL'16]

Consider a symbolic execution in a program

$$S ::= y := f(x_1, \dots, x_n) \mid \mathbf{assert}(g(x_1, \dots, x_n)) \mid S_1; S_2$$

where

$$f : (\Sigma^*)^n \rightarrow \Sigma^*$$
$$g : (\Sigma^*)^n \rightarrow \{0, 1\}$$

**Path Feasibility Problem:** decide if there exist input strings that satisfy all the assertions

**Theorem:** Path feasibility is decidable whenever:

1. assign.: concatenation/finite transducer
2. assert.: regular constraint

# “Straight-Line” Framework

[Lin&Barcelo, POPL'16]

Consider a symbolic execution in a program

$$S ::= y := f(x_1, \dots, x_n) \mid \mathbf{assert}(g(x_1, \dots, x_n)) \mid S_1; S_2$$

where

$$f : (\Sigma^*)^n \rightarrow \Sigma^*$$
$$g : (\Sigma^*)^n \rightarrow \{0, 1\}$$

**Path Feasibility Problem:** decide if there exist input strings that satisfy all the assertions

includes: **replaceAll**(VAR,const,const)

**Theorem:** Path feasibility is decidable whenever:

1. assign.: concatenation/finite transducer
2. assert.: regular constraint

# “Straight-Line” Framework

[Lin&Barcelo, POPL'16]

Consider a symbolic execution in a program

$$S ::= y := f(x_1, \dots, x_n) \mid \mathbf{assert}(g(x_1, \dots, x_n)) \mid S_1; S_2$$

where

$$f : (\Sigma^*)^n \rightarrow \Sigma^*$$
$$g : (\Sigma^*)^n \rightarrow \{0, 1\}$$

**Path Feasibility Problem:** decide if there exist input strings that satisfy all the assertions

includes: **replaceAll(VAR, const, const)**

**Theorem:** Path feasibility is decidable whenever:

1. assign.: concatenation/**finite transducer**
2. assert.: regular constraint

Key Idea: NO general string equality in conditionals!

# “Straight-Line” Framework

[Lin&Barcelo,POPL'16]

Consider a symbolic execution in a program

$$S ::= y := f(x_1, \dots, x_n) \mid \mathbf{assert}(g(x_1, \dots, x_n)) \mid S_1; S_2$$

where

$$f : (\Sigma^*)^n \rightarrow \Sigma^*$$
$$g : (\Sigma^*)^n \rightarrow \{0, 1\}$$

**Path Feasibility Problem:** decide if there exist input strings that satisfy all the assertions

# “Straight-Line” Framework

[Lin&Barcelo, POPL'16]

Consider a symbolic execution in a program

$$S ::= y := f(x_1, \dots, x_n) \mid \mathbf{assert}(g(x_1, \dots, x_n)) \mid S_1; S_2$$

where

$$f : (\Sigma^*)^n \rightarrow \Sigma^*$$
$$g : (\Sigma^*)^n \rightarrow \{0, 1\}$$

**Path Feasibility Problem:** decide if there exist input strings that satisfy all the assertions

```
x := x + 'aba' + y;  
y := replaceall(x, 'a', 'c');  
assert( y in ('b')* )
```

Symbolic Execution

# “Straight-Line” Framework

[Lin&Barcelo, POPL'16]

Consider a symbolic execution in a program

$$S ::= y := f(x_1, \dots, x_n) \mid \mathbf{assert}(g(x_1, \dots, x_n)) \mid S_1; S_2$$

where

$$f : (\Sigma^*)^n \rightarrow \Sigma^*$$
$$g : (\Sigma^*)^n \rightarrow \{0, 1\}$$

**Path Feasibility Problem:** decide if there exist input strings that satisfy all the assertions

```
x := x + 'aba' + y;  
y := replaceall(x, 'a', 'c');  
assert( y in ('b')* )
```

Symbolic Execution

**Path Feasibility = Satisfiability (in disguise)**



# “Straight-Line” Framework

[Lin&Barcelo, POPL’16]

Consider a symbolic execution in a program

$$S ::= y := f(x_1, \dots, x_n) \mid \mathbf{assert}(g(x_1, \dots, x_n)) \mid S_1; S_2$$

where

$$f : (\Sigma^*)^n \rightarrow \Sigma^*$$
$$g : (\Sigma^*)^n \rightarrow \{0, 1\}$$

**Path Feasibility Problem:** decide if there exist input strings that satisfy all the assertions

```
x := x + 'aba' + y;  
y := replaceall(x, 'a', 'c');  
assert( y in ('b')* )
```

Symbolic Execution

```
x1 := x + 'aba' + y ∧  
y1 := replaceall(x1, 'a', 'c') ∧  
assert( y1 in ('b')* )
```

Formula (use SSA form)

**Path Feasibility = Satisfiability (in disguise)**

# Why Straight-Line

# Why Straight-Line

- Prohibits bad formulas

# Why Straight-Line

- Prohibits bad formulas

$x \text{ in } (1+2+3)^* \wedge$

$y = \text{replaceAll}(x, 1, a) \wedge y' = \text{replaceAll}(y, 2, ab) \wedge y'' = \text{replaceAll}(y', 3, bba) \wedge$

$z = \text{replaceAll}(x, 1, baa) \wedge z' = \text{replaceAll}(z, 2, aa) \wedge z'' = \text{replaceAll}(z, 3, bb) \wedge$

$y'' = z''$

# Why Straight-Line

- Prohibits bad formulas

$x \text{ in } (1+2+3)^* \wedge$

$y = \text{replaceAll}(x, 1, a) \wedge y' = \text{replaceAll}(y, 2, ab) \wedge y'' = \text{replaceAll}(y', 3, bba) \wedge$

$z = \text{replaceAll}(x, 1, baa) \wedge z' = \text{replaceAll}(z, 2, aa) \wedge z'' = \text{replaceAll}(z, 3, bb) \wedge$

$y'' = z''$

# Why Straight-Line

- Prohibits bad formulas

$x \text{ in } (1+2+3)^* \wedge$

$y = \text{replaceAll}(x, 1, a) \wedge y' = \text{replaceAll}(y, 2, ab) \wedge y'' = \text{replaceAll}(y', 3, bba) \wedge$

$z = \text{replaceAll}(x, 1, baa) \wedge z' = \text{replaceAll}(z, 2, aa) \wedge z'' = \text{replaceAll}(z, 3, bb) \wedge$

$y'' = z''$

- Captures constraints from symbolic execution in practice

# Why Straight-Line

- Prohibits bad formulas

$x \text{ in } (1+2+3)^* \wedge$

$y = \text{replaceAll}(x, 1, a) \wedge y' = \text{replaceAll}(y, 2, ab) \wedge y'' = \text{replaceAll}(y', 3, bba) \wedge$

$z = \text{replaceAll}(x, 1, baa) \wedge z' = \text{replaceAll}(z, 2, aa) \wedge z'' = \text{replaceAll}(z, 3, bb) \wedge$

$y'' = z''$

- Captures constraints from symbolic execution in practice

```
var x = htmlEscape(name);
var y = escapeString(x);
nameElem.innerHTML = '<a onclick=' +
    '"viewPerson(\"' + y + '\")">' + x + '</a>';
```

assert(nameElem matches

'<a onclick="viewPerson(""); attackScript();....."> ..... </a>')

# Why Straight-Line

- Prohibits bad formulas

$x \text{ in } (1+2+3)^* \wedge$

$y = \text{replaceAll}(x, 1, a) \wedge y' = \text{replaceAll}(y, 2, ab) \wedge y'' = \text{replaceAll}(y', 3, bba) \wedge$

$z = \text{replaceAll}(x, 1, baa) \wedge z' = \text{replaceAll}(z, 2, aa) \wedge z'' = \text{replaceAll}(z, 3, bb) \wedge$

$y'' = z''$

- Captures constraints from symbolic execution in practice

```
var x = htmlEscape(name);
var y = escapeString(x);
nameElem.innerHTML = '<a onclick=' +
    '"viewPerson(\"' + y + '\")">' + x + '</a>';
```

assert(nameElem matches

'<a onclick="viewPerson(""); attackScript();....."> ..... </a>')

*LOTS of existing benchmarks are in SL*



# Limitation of SL [LB'16]

## HTML template (with Mustache)

```
...  
<h1> User <span  
  onclick="popupText('{{bio}}')">  
  {{userName}}</span> </h1>  
...
```

## HTML

```
...  
<h1> User <span  
  onclick="popupText(''); attackScript('')">  
  Evil</span> </h1>  
...
```

## JSON files

```
...  
bio = "'); attackScript('';  
userName = "Evil";  
...
```

# Limitation of SL [LB'16]

## HTML template (with Mustache)

```
...  
<h1> User <span  
  onclick="popupText('{{bio}}')">  
  {{userName}}</span> </h1>  
...
```

## HTML

```
...  
<h1> User <span  
  onclick="popupText(''); attackScript('')">  
  Evil</span> </h1>  
...
```

## JSON files

```
...  
bio = "'); attackScript('";  
userName = "Evil";  
...
```

Requires more general replaceall!

```
x = replaceAll(text, '{{bio}}', bio)
```

# Our Main Result

A more expressive decidable straight-line fragment with **replaceAll!**

# Our Main Result

A more expressive decidable straight-line fragment with **replaceAll**!

**Theorem:** Path feasibility is decidable whenever:

1. assign.: concatenation/**replaceAll**(VAR,regex,VAR)
2. assertion: regular constraint

# Our Main Result

A more expressive decidable straight-line fragment with **replaceAll**!

**Theorem:** Path feasibility is decidable whenever:

1. assign.: concatenation/**replaceAll**(VAR,regex,VAR)
2. assertion: regular constraint

Can model string operations used in auto-sanitisation in web templates!  
**Closure, Angular, Handlebars**

# Our Main Result

A more expressive decidable straight-line fragment with **replaceAll**!

**Theorem:** Path feasibility is decidable whenever:

1. assign.: concatenation/**replaceAll**(VAR,regex,VAR)
2. assertion: regular constraint

Can model string operations used in auto-sanitisation in web templates!  
**Closure, Angular, Handlebars**

This decidability was surprising since arithmetic can be simulated!

# Our Main Result

A more expressive decidable straight-line fragment with **replaceAll**!

**Theorem:** Path feasibility is decidable whenever:

1. assign.: concatenation/**replaceAll**(VAR,regex,VAR)
2. assertion: regular constraint

Can model string operations used in auto-sanitisation in web templates!  
**Closure, Angular, Handlebars**

This decidability was surprising since arithmetic can be simulated!

$5 \text{ ---} \rightarrow \text{'aaaaa'}$

$z = x^*y \text{ ---} \rightarrow z = \text{replaceAll}(x, \text{'a'}, y)$

$z = x+y \text{ ---} \rightarrow z = x+y \quad (\text{concatenation})$

# Proof Idea

**Lemma:** Concatenation in SL can be expressed as **replaceAll**(VAR,regex,VAR).



# Proof Idea

**Lemma:** Concatenation in SL can be expressed as **replaceAll**(VAR,regex,VAR).

$X = Y + \text{'aba'} + Y + Z$

# Proof Idea

**Lemma:** Concatenation in SL can be expressed as **replaceAll**(VAR,regex,VAR).

$X = Y + \text{'aba'} + Y + Z \longrightarrow$

$X0 = \text{replaceAll}(\text{'yabayz'}, y, Y) \wedge$   
 $X = \text{replaceAll}(X', z, Z)$

# Proof Idea

**Definition:** The pre-image of a language  $L$  under  $\mathbf{replaceAll}_{\text{pat}}$  with pattern  $\text{pat}$  is:

$$\mathbf{replaceAll}_{\text{pat}}^{-1}(L) := \{(v, w) : \mathbf{replaceAll}(v, \text{pat}, w) \in L\}$$

# Proof Idea

**Definition:** The pre-image of a language  $L$  under **replaceAll**<sub>pat</sub> with pattern pat is:

$$\text{replaceAll}_{\text{pat}}^{-1}(L) := \{(v, w) : \text{replaceAll}(v, \text{pat}, w) \in L\}$$

$L = \text{'Hi [A-Z][a-z]^*, [A-Za-z]^* is a nice name'}$

pat = '9'

# Proof Idea

**Definition:** The pre-image of a language  $L$  under **replaceAll**<sub>pat</sub> with pattern pat is:

$$\text{replaceAll}_{\text{pat}}^{-1}(L) := \{(v, w) : \text{replaceAll}(v, \text{pat}, w) \in L\}$$

$L = \text{'Hi [A-Z][a-z]^*, [A-Za-z]^* is a nice name'}$

pat = **'9'**

**replaceAll**<sub>pat</sub><sup>-1</sup>( $L$ ) contains:

# Proof Idea

**Definition:** The pre-image of a language  $L$  under **replaceAll**<sub>pat</sub> with pattern pat is:

$$\text{replaceAll}_{\text{pat}}^{-1}(L) := \{(v, w) : \text{replaceAll}(v, \text{pat}, w) \in L\}$$

$L = \text{'Hi [A-Z][a-z]^*, [A-Za-z]^* is a nice name'}$

pat = '9'

**replaceAll**<sub>pat</sub><sup>-1</sup>( $L$ ) contains:

$L \times \Sigma^*$  when 9 doesn't occur in  $v$

# Proof Idea

**Definition:** The pre-image of a language  $L$  under **replaceAll**<sub>pat</sub> with pattern pat is:

$$\text{replaceAll}_{\text{pat}}^{-1}(L) := \{(v, w) : \text{replaceAll}(v, \text{pat}, w) \in L\}$$

$L = \text{'Hi [A-Z][a-z]^*, [A-Za-z]^* is a nice name'}$

pat = **'9'**

**replaceAll**<sub>pat</sub><sup>-1</sup>( $L$ ) contains:

$L \times \Sigma^*$  when **9** doesn't occur in  $v$

$v = \text{'9 is a nice name'}$                        $w$  matches **'Hi [A-z][a-z]^\*, [A-Za-z]^\*'**

# Proof Idea

**Definition:** The pre-image of a language  $L$  under **replaceAll**<sub>pat</sub> with pattern pat is:

$$\text{replaceAll}_{\text{pat}}^{-1}(L) := \{(v, w) : \text{replaceAll}(v, \text{pat}, w) \in L\}$$

$L = \text{'Hi [A-Z][a-z]^*, [A-Za-z]^* is a nice name'}$

pat = '9'

**replaceAll**<sub>pat</sub><sup>-1</sup>( $L$ ) contains:

$L \times \Sigma^*$  when 9 doesn't occur in  $v$

$v = \text{'9 is a nice name'}$                        $w$  matches  $\text{'Hi [A-z][a-z]^*, [A-Za-z]^*'}$

$v = \text{'Hi 9, 9 is a nice name'}$                $w$  matches  $\text{'[A-z][a-z]^*'}$



# Proof Idea

**Definition:** The pre-image of a language  $L$  under **replaceAll**<sub>pat</sub> with pattern pat is:

$$\text{replaceAll}_{\text{pat}}^{-1}(L) := \{(v, w) : \text{replaceAll}(v, \text{pat}, w) \in L\}$$

$L = \text{'Hi [A-Z][a-z]^*, [A-Za-z]^* is a nice name'}$

pat = '9'

**replaceAll**<sub>pat</sub><sup>-1</sup>( $L$ ) contains:

$L \times \Sigma^*$  when 9 doesn't occur in  $v$

$v = \text{'9 is a nice name'}$        $w$  matches  $\text{'Hi [A-z][a-z]^*, [A-Za-z]^*'}$

$v = \text{'Hi 9, 9 is a nice name'}$        $w$  matches  $\text{'[A-z][a-z]^*'}$

**There are many other combinations!**

# Proof Idea

**Lemma:**  $\text{replaceAll}_{\text{pat}}^{-1}(L)$  is a recognisable set, i.e., a finite union of products of regular languages  $S \times S'$ .

# Proof Idea

**Lemma:**  $\text{replaceAll}_{\text{pat}}^{-1}(L)$  is a recognisable set, i.e., a finite union of products of regular languages  $S \times S'$ .

Why does this imply decidability?

# Proof Idea

**Lemma:**  $\text{replaceAll}_{\text{pat}}^{-1}(L)$  is a recognisable set, i.e., a finite union of products of regular languages  $S \times S'$ .

Why does this imply decidability?

```
assert( x in L0 );  
x0 = replaceAll(x, 'a', y);  
assert( x0 in L1 );  
z  = replaceAll(x0, 'b', y);  
assert( z in L2 );
```

# Proof Idea

**Lemma:**  $\text{replaceAll}_{\text{pat}}^{-1}(L)$  is a recognisable set, i.e., a finite union of products of regular languages  $S \times S'$ .

Why does this imply decidability?

```
assert( x in L0 );  
x0 = replaceAll(x, 'a', y);  
assert( x0 in L1 );  
z = replaceAll(x0, 'b', y);  
assert( z in L2 );
```


$\text{replaceAll}_{\text{pat}}^{-1}(L_2)$

```
assert( x in L0 );  
x0 = replaceAll(x, 'a', y);  
assert( x0 in L1 );  
assert( x0 in S );  
assert( y in S' );
```

# Proof Idea

**Lemma:**  $\text{replaceAll}_{\text{pat}}^{-1}(L)$  is a recognisable set, i.e., a finite union of products of regular languages  $S \times S'$ .


Why does this imply decidability?



# Proof Idea

**Lemma:**  $\text{replaceAll}_{\text{pat}}^{-1}(L)$  is a recognisable set, i.e., a finite union of products of regular languages  $S \times S'$ .

Why does this imply decidability?



# Proof Idea of Lemma

**Lemma:**  $\text{replaceAll}_{\text{pat}}^{-1}(L)$  is a recognisable set, i.e., a finite union of products of regular languages  $S \times S$ .

$L = \text{'Hi [A-Z][a-z]*,[A-Z][a-z]* is a nice name'}$

$\text{pat} = \text{'9'}$



# Proof Idea of Lemma

**Lemma:**  $\text{replaceAll}_{\text{pat}}^{-1}(L)$  is a recognisable set, i.e., a finite union of products of regular languages  $S \times S'$ .

$L = \text{'Hi [A-Z][a-z]*,[A-Z][a-z]* is a nice name'}$

$\text{pat} = \text{'9'}$

**Step 1:** Guess where 9 could appear in subject (w.r.t.  $L$ )

# Proof Idea of Lemma

**Lemma:**  $\text{replaceAll}_{\text{pat}}^{-1}(L)$  is a recognisable set, i.e., a finite union of products of regular languages  $S \times S'$ .

$L = \text{'Hi [A-Z][a-z]*,[A-Z][a-z]* is a nice name'}$

$\text{pat} = \text{'9'}$

**Step 1:** Guess where 9 could appear in subject (w.r.t.  $L$ )

nondeterministically add transitions with label 9 to NFA  $L$

# Proof Idea of Lemma

**Lemma:**  $\text{replaceAll}_{\text{pat}}^{-1}(L)$  is a recognisable set, i.e., a finite union of products of regular languages  $S \times S'$ .

$L = \text{'Hi [A-Z][a-z]*,[A-Z][a-z]* is a nice name'}$

$\text{pat} = \text{'9'}$

**Step 1:** Guess where 9 could appear in subject (w.r.t.  $L$ )

nondeterministically add transitions with label 9 to NFA  $L$

**Observation:** finitely many resulting NFA  $S$

# Proof Idea of Lemma

**Lemma:**  $\text{replaceAll}_{\text{pat}}^{-1}(L)$  is a recognisable set, i.e., a finite union of products of regular languages  $S \times S'$ .

$L = \text{'Hi [A-Z][a-z]*,[A-Z][a-z]* is a nice name'}$

$\text{pat} = \text{'9'}$

**Step 1:** Guess where 9 could appear in subject (w.r.t.  $L$ )

nondeterministically add transitions with label 9 to NFA  $L$

**Observation:** finitely many resulting NFA  $S$

**Step 2:** Extract regular constraint  $S'$  for replacement string

# Proof Idea of Lemma

**Lemma:**  $\text{replaceAll}_{\text{pat}}^{-1}(L)$  is a recognisable set, i.e., a finite union of products of regular languages  $S \times S'$ .

$L = \text{'Hi [A-Z][a-z]*,[A-Z][a-z]* is a nice name'}$

$\text{pat} = \text{'9'}$

**Step 1:** Guess where 9 could appear in subject (w.r.t.  $L$ )

nondeterministically add transitions with label 9 to NFA  $L$

**Observation:** finitely many resulting NFA  $S$

**Step 2:** Extract regular constraint  $S'$  for replacement string

Each 9-labeled transition in  $L$  contributes to  $S'$

# Proof Idea of Lemma

**Lemma:**  $\text{replaceAll}_{\text{pat}}^{-1}(L)$  is a recognisable set, i.e., a finite union of products of regular languages  $S \times S'$ .

$L = \text{'Hi [A-Z][a-z]*,[A-Z][a-z]* is a nice name'}$

$\text{pat} = \text{'9'}$

**Step 1:** Guess where 9 could appear in subject (w.r.t.  $L$ )

nondeterministically add transitions with label 9 to NFA  $L$

**Observation:** finitely many resulting NFA  $S$

**Step 2:** Extract regular constraint  $S'$  for replacement string

Each 9-labeled transition in  $L$  contributes to  $S'$

$\text{subject} = \text{'Hi 9, 9 is a nice name'}$

# Proof Idea of Lemma

**Lemma:**  $\text{replaceAll}_{\text{pat}}^{-1}(L)$  is a recognisable set, i.e., a finite union of products of regular languages  $S \times S'$ .

$L = \text{'Hi [A-Z][a-z]*,[A-Z][a-z]* is a nice name'}$

$\text{pat} = \text{'9'}$

**Step 1:** Guess where 9 could appear in subject (w.r.t.  $L$ )

nondeterministically add transitions with label 9 to NFA  $L$

**Observation:** finitely many resulting NFA  $S$

**Step 2:** Extract regular constraint  $S'$  for replacement string

Each 9-labeled transition in  $L$  contributes to  $S'$

$\text{subject} = \text{'Hi 9, 9 is a nice name'}$

$S' = \text{'[A-z][a-z]*'} \cap \text{'[A-za-z]*'}$

# Proof Idea of Lemma

**Lemma:**  $\text{replaceAll}_{\text{pat}}^{-1}(L)$  is a recognisable set, i.e., a finite union of products of regular languages  $S \times S'$ .

$L = \text{'Hi [A-Z][a-z]*,[A-Z][a-z]* is a nice name'}$

$\text{pat} = \text{'9'}$

**Step 1:** Guess where 9 could appear in subject (w.r.t.  $L$ )

nondeterministically add transitions with label 9 to NFA  $L$

**Observation:** finitely many resulting NFA  $S$

**Step 2:** Extract regular constraint  $S'$  for replacement string

Each 9-labeled transition in  $L$  contributes to  $S'$

$\text{subject} = \text{'Hi 9, 9 is a nice name'}$

$S' = \text{'[A-z][a-z]*'} \cap \text{'[A-za-z]*'}$   
 $= \text{'[A-z][a-z]*'}$



# Complexity Consideration

**Theorem:** Our algorithm has the same complexity as LB'16 SL: EXPSPACE (double exp-time).

# Complexity Consideration

**Theorem:** Our algorithm has the same complexity as LB'16 SL: EXPSPACE (double exp-time).

Best lower bound is PSPACE-hardness

# Complexity Consideration

**Theorem:** Our algorithm has the same complexity as LB'16 SL: EXPSPACE (double exp-time).

Best lower bound is PSPACE-hardness

We identified a PSPACE-complete fragment of our constraint language

# Complexity Consideration

**Theorem:** Our algorithm has the same complexity as LB'16 SL: EXPSPACE (double exp-time).

Best lower bound is PSPACE-hardness

We identified a PSPACE-complete fragment of our constraint language

$z = \text{replaceAll}(x, 'a', x)$

prohibits this crazy use



# Extensions

# Length Constraints

```
assert( len(x) = len(y) )
```

# Length Constraints

**assert( len(x) = len(y) )**

**Theorem:** Path feasibility is **un**decidable if:

1. assign.: applies **replaceAll**(VAR,const,VAR)
2. assert.: regular constraint or length constraints

# Length Constraints

**assert( len(x) = len(y) )**

**Theorem:** Path feasibility is **un**decidable if:

1. assign.: applies **replaceAll**(VAR,const,VAR)
2. assert.: regular constraint or length constraints

Can encode existence of solutions to polynomials (all over Nat. Numbers):

$$f(x_1, \dots, x_n) = g(x_1, \dots, x_n)$$



# Length Constraints

**assert( len(x) = len(y) )**

**Theorem:** Path feasibility is **und**ecidable if:

1. assign.: applies **replaceAll**(VAR,const,VAR)
2. assert.: regular constraint or length constraints

Can encode existence of solutions to polynomials (all over Nat. Numbers):

$$f(x_1, \dots, x_n) = g(x_1, \dots, x_n)$$

**Note:**

1. Some length constraints are regular  
 $\text{len}(x) < 7$                        $\text{len}(x) \bmod 7 = 3$
2. [LB'16] decidable for **replaceAll**(VAR,regex,const)

# Variable in the Pattern

# Variable in the Pattern

**Theorem:** Path feasibility is **un**decidable whenever:

1. assign.: **replaceAll**(VAR,VAR,const)
2. assert.: regular constraint

# Variable in the Pattern

**Theorem:** Path feasibility is **un**decidable whenever:

1. assign.: **replaceAll**(VAR,VAR,const)
2. assert.: regular constraint

Proof is by a reduction from PCP

# Final Words

## Summary:

- Decidability boundary of string solving with **replaceAll**
- Reason to be positive!

## Ongoing work:

- Computational complexity issues
- Unify transducers [LB'16] with **replaceAll**(VAR,regex,VAR)
- String solver based on our constraint language

<https://github.com/TinyYan/z3-replaceAll>