

# INTERNATIONAL A-LEVEL FURTHER MATHEMATICS FM05

(9665/FM05) Unit FM2 Mechanics

---

Mark scheme

January 2024

---

Version: 1.1 Final



2 4 1 X F M 0 5 / M S

Mark schemes are prepared by the Lead Assessment Writer and considered, together with the relevant questions, by a panel of subject teachers. This mark scheme includes any amendments made at the standardisation events which all associates participate in and is the scheme which was used by them in this examination. The standardisation process ensures that the mark scheme covers the students' responses to questions and that every associate understands and applies it in the same correct way. As preparation for standardisation each associate analyses a number of students' scripts. Alternative answers not already covered by the mark scheme are discussed and legislated for. If, after the standardisation process, associates encounter unusual answers which have not been raised they are required to refer these to the Lead Examiner.

It must be stressed that a mark scheme is a working document, in many cases further developed and expanded on the basis of students' reactions to a particular paper. Assumptions about future mark schemes on the basis of one year's document should be avoided; whilst the guiding principles of assessment remain constant, details will change, depending on the content of a particular examination paper.

Further copies of this mark scheme are available from [oxfordaqa.com](https://www.oxfordaqa.com)

#### **Copyright information**

OxfordAQA retains the copyright on all its publications. However, registered schools/colleges for OxfordAQA are permitted to copy material from this booklet for their own internal use, with the following important exception: OxfordAQA cannot give permission to schools/colleges to photocopy any material that is acknowledged to a third party even for internal use within the centre.

Copyright © 2024 OxfordAQA International Examinations and its licensors. All rights reserved.

### Key to mark scheme abbreviations

<b>M</b>	Mark is for method
<b>m</b>	Mark is dependent on one or more M marks and is for method
<b>A</b>	Mark is dependent on M or m marks and is for accuracy
<b>B</b>	Mark is independent of M or m marks and is for method and accuracy
<b>E</b>	Mark is for explanation
<b>✓ or ft</b>	Follow through from previous incorrect result
<b>CAO</b>	Correct answer only
<b>CSO</b>	Correct solution only
<b>AWFW</b>	Anything which falls within
<b>AWRT</b>	Anything which rounds to
<b>ACF</b>	Any correct form
<b>AG</b>	Answer given
<b>SC</b>	Special case
<b>oe</b>	Or equivalent
<b>A2, 1</b>	2 or 1 (or 0) accuracy marks
<b>–x EE</b>	Deduct x marks for each error
<b>NMS</b>	No method shown
<b>PI</b>	Possibly implied
<b>SCA</b>	Substantially correct approach
<b>sf</b>	Significant figure(s)
<b>dp</b>	Decimal place(s)
<b>ISW</b>	Ignore subsequent working

Q	Answer	Marks	Comments
1(a)	$2\begin{bmatrix} 4 \\ 7 \end{bmatrix} + 6\begin{bmatrix} 6 \\ -4 \end{bmatrix} = 2\begin{bmatrix} 7 \\ 1 \end{bmatrix} + 6\mathbf{v}_B$ $6\mathbf{v}_B = \begin{bmatrix} 30 \\ -12 \end{bmatrix}$ $\mathbf{v}_B = \begin{bmatrix} 5 \\ -2 \end{bmatrix} \text{ [m s}^{-1}\text{]}$	<b>M1</b>  <b>A1</b>  <b>m1</b>  <b>A1</b>	Applies conservation of momentum in a vector form.  Correct vector equation  Solves their vector equation for velocity of $B$  Correct velocity
		<b>4</b>	

Q	Answer	Marks	Comments
1(b)	$\mathbf{I} = 2\begin{bmatrix} 7 \\ 1 \end{bmatrix} - 2\begin{bmatrix} 4 \\ 7 \end{bmatrix}$ $= \begin{bmatrix} 6 \\ -12 \end{bmatrix}$ $I = \sqrt{6^2 + 12^2}$ $= 6\sqrt{5} \text{ [N s]}$	<b>M1</b>  <b>A1</b>  <b>M1</b>  <b>A1</b>	Uses impulse equation with vectors  Correct impulse  Finds magnitude of their impulse  Correct magnitude of the impulse
		<b>4</b>	

	<b>Question 1 Total</b>	<b>8</b>	
--	-------------------------	----------	--

Q	Answer	Marks	Comments
2(a)	$4 = \frac{2\pi}{\omega}$ $\omega = \frac{\pi}{2}$	M1	Correct value of $\omega$
	$v_{\max} = \frac{3}{4} \times \frac{\pi}{2} = \frac{3\pi}{8} \text{ [m s}^{-1}\text{]}$	A1	Correct speed <del>oe</del> in terms of $\pi$ (eg $0.375\pi$ )
		2	

Q	Answer	Marks	Comments
2(b)	$v^2 = \omega^2 (a^2 - x^2)$ $v^2 = \left(\frac{\pi}{2}\right)^2 (0.75^2 - 0.45^2)$	M1	Uses SHM speed formula or other SHM method with their amplitude and consistent displacement.
	$v = \frac{3\pi}{10} \text{ [m s}^{-1}\text{]}$	A1ft	Correct speed for their amplitude. <del>oe</del> in terms of $\pi$ (eg $0.3\pi$ )
		2	

Q	Answer	Marks	Comments
2(c)	$x = \frac{3}{4} \cos\left(\frac{\pi t}{2}\right)$	M1	Finds expression for displacement in terms of time
	$0.45 = \frac{3}{4} \cos\left(\frac{\pi t}{2}\right)$	A1ft	Correct equation for time, for their amplitude.
	$t = \frac{2}{\pi} \cos^{-1}\left(\frac{3}{5}\right)$ $t = 0.5903 \text{ [seconds]}$	A1	Correct time
		3	

	Question 2 Total	7	
--	------------------	---	--

Q	Answer	Marks	Comments
3(a)	$8 \cos 60^\circ = v \cos 30^\circ$  $4 = \frac{\sqrt{3}}{2} v$  $v = \frac{8}{\sqrt{3}} = \frac{8\sqrt{3}}{3}$	<b>M1 A1</b>	<b>M1:</b> Equation for motion parallel to wall with at least one side correct <b>A1:</b> Fully correct
		<b>A1</b>	Correct value for $v$ <b>ACF</b>
		<b>3</b>	

Q	Answer	Marks	Comments
3(b)	$e \times 8 \sin 60^\circ = v \sin 30^\circ$  $e \times 4\sqrt{3} = \frac{4\sqrt{3}}{3}$  $e = \frac{1}{3}$	<b>M1 A1ft</b>	<b>M1:</b> Equation for motion perpendicular to wall with at least one side correct <b>A1ft:</b> Fully correct <b>ft</b> their $v$
		<b>A1</b>	Correct value for $e$ <b>ACF</b>
		<b>3</b>	

Q	Answer	Marks	Comments
3(c)	$I = 0.2 \times \frac{4\sqrt{3}}{3} - 0.2 \times (-4\sqrt{3})$  $= \frac{16\sqrt{3}}{15} \text{ [N s]}$	<b>M1 A1</b>	<b>M1:</b> Impulse equation with correct values and any signs <b>A1:</b> Fully correct
		<b>A1</b>	Correct impulse <b>ACF</b>
		<b>3</b>	

	<b>Question 3 Total</b>	<b>9</b>	
--	-------------------------	----------	--

Q	Answer	Marks	Comments
4	<p>At highest point the tension in the string is zero when <math>U</math> is the minimum possible value</p> $m \times 9.8 = \frac{mv^2}{0.8}$ $v^2 = 7.84$ $v = 2.8$ <p>Conservation of energy</p> $\frac{1}{2} \times mU^2 = \frac{1}{2} \times m \times 7.84 + m \times 9.8 \times 1.6$ $U^2 = 39.2$ $U = \frac{14\sqrt{5}}{5} = 6.3 \text{ [to 2sf]}$	<p><b>M1</b></p> <p><b>A1</b></p> <p><b>M1 A1</b></p> <p><b>A1</b></p>	<p>Equation for motion at highest point</p> <p>Correct speed at highest point (<math>v^2 = rg</math>)</p> <p><b>M1</b>: Three term equation for conservation of energy <b>A1</b>: Fully correct (<math>U^2 = 5rg</math>)</p> <p>Correct value for <math>U</math> <b>AWRT</b> 6.3</p>
	Question 4 Total	5	

Q	Answer	Marks	Comments
5	$m \frac{dv}{dt} = mg \sin 30^\circ - \mu \times mg \cos 30^\circ - mkv$ $\frac{dv}{dt} = \frac{g}{2} - \mu g \frac{\sqrt{3}}{2} - kv$ $\frac{dv}{dt} = \frac{1}{2}(g - \mu g \sqrt{3} - 2kv)$ $\int \frac{1}{(2kv - g + \mu g \sqrt{3})} dv = \int -\frac{1}{2} dt$ $\frac{1}{2k} \ln(2kv - g + \mu g \sqrt{3}) = -\frac{1}{2}t + c$ $v = 0, t = 0 \Rightarrow c = \frac{1}{2k} \ln(\mu g \sqrt{3} - g)$ $\ln(2kv - g + \mu g \sqrt{3}) = -kt + \ln(\mu g \sqrt{3} - g)$ $\frac{2kv - g + \mu g \sqrt{3}}{\mu g \sqrt{3} - g} = e^{-kt}$ $v = \frac{g}{2k} (1 - \mu \sqrt{3}) (1 - e^{-kt})$	<p><b>M1</b></p> <p><b>A1</b></p> <p><b>M1</b></p> <p><b>m1</b></p> <p><b>A1</b></p> <p><b>A1</b></p> <p><b>M1</b></p> <p><b>A1</b></p>	<p>Four term differential equation from Newton's second law</p> <p>Correct differential equation</p> <p>Uses separation of variables or integrating factor</p> <p>Integrates</p> <p>Correct integration</p> <p>Finds correct constant of integration</p> <p>Solves a logarithmic equation for <math>v</math></p> <p>Correct expression for <math>v</math> <b>ACF</b> not involving trigonometric functions</p>
	<b>Question 5 Total</b>	<b>8</b>	



Q	Answer	Marks	Comments
6(a)	<p>Let <math>\theta</math> be the angle between the string and the vertical at time <math>t</math></p> $m \times 1.4 \ddot{\theta} = -m \times 9.8 \sin \theta$ $\sin \theta \approx \theta$ $\ddot{\theta} \approx -\frac{9.8}{1.4} \theta = -7\theta$ <p><math>\therefore</math> SHM</p> <p>As acceleration proportional to the displacement and in the opposite sense</p>	<p><b>M1</b></p> <p><b>A1</b></p> <p><b>B1</b></p> <p><b>A1</b></p> <p><b>E1</b></p>	<p>Forms differential equation</p> <p>Correct differential equation</p> <p>Uses small angle approximation</p> <p>Simplifies to SHM form</p> <p>Accept <math>\ddot{\theta} \approx -\frac{g}{l} \theta</math></p> <p>Concludes that motion is SHM from correct working</p>
		<b>5</b>	

Q	Answer	Marks	Comments
6(b)	<p>Period = <math>\frac{2\pi}{\sqrt{7}} = \frac{2\sqrt{7}}{7}\pi</math> [= 2.3748...]</p> <p>Total angle for 1.8 metres  <math>= \frac{1.8}{1.4} = \frac{9}{7}</math> [= 1.286 radians]</p> <p>Angle per complete period  <math>= 4 \times \frac{\pi}{20} = \frac{\pi}{5}</math> [= 0.6283... radians]</p> <p><math>\left(\frac{9}{7}\right) \div \left(\frac{\pi}{5}\right) = \frac{45}{7\pi}</math> [= 2.04627...]</p> <p>[So between 2 and 3 periods required.]  <math>\frac{9}{7} - \frac{2\pi}{5}</math> [= 0.029077... radians]</p> <p><math>\theta = \frac{\pi}{20} - \left(\frac{9}{7} - \frac{2\pi}{5}\right) = \frac{9\pi}{20} - \frac{9}{7}</math> [= 0.12800...]</p> <p><math>\frac{9\pi}{20} - \frac{9}{7} = \frac{\pi}{20} \cos(\sqrt{7}t)</math>  <math>t = 0.23368...</math> seconds</p> <p>Total Time = <math>2 \times \frac{2\pi}{\sqrt{7}} + 0.23368</math>  <math>= 4.98332...</math>  <math>= 5.0</math> seconds</p>	<p><b>B1</b></p> <p><b>M1</b></p> <p><b>A1</b></p> <p><b>A1</b></p> <p><b>M1</b> <b>A1</b></p> <p><b>M1</b></p> <p><b>A1</b></p>	<p>Correct period stated during working</p> <p>Finds total angle for the motion</p> <p>Obtains exact value or <b>AWRT</b> 2.047</p> <p>Correct angle for remaining motion since last complete period or correct distance (0.04071...)</p> <p>Finds <math>\theta</math> Correct <math>\theta</math></p> <p>Finds time for motion since last period</p> <p>Correct total time <b>AWRT</b> 5.0</p>
		8	
	Question 6 Total	13	

Q	Answer	Marks	Comments
7(a)	$e = \sqrt{5^2 + 3^2} - 5$ $= \sqrt{34} - 5$ $\text{EPE} = \frac{800 \times (\sqrt{34} - 5)^2}{2 \times 5}$ $= 55.238\dots$ Total EPE = 110 [J]	<b>M1</b>  <b>A1</b>   <b>M1</b>  <b>A1</b>	Finds extension of strings  Correct extension   Uses EPE formula with their extension  Correct total EPE
		<b>4</b>	

Q	Answer	Marks	Comments
7(b)	Strings slack when height above C is 1 metre  Change in GPE = $7 \times 9.8 \times 1$ $= 68.6$  $110.47\dots - 68.6 = \frac{1}{2} \times 7 \times v^2$  $v^2 = 11.971$  $v = 3.4599\dots$ $= 3.5 \text{ [m s}^{-1} \text{ to 2 sf]}$	<b>B1</b>  <b>B1</b>  <b>M1 A1</b>   <b>A1</b>	Finds height when strings at natural length <b>PI</b>  Correct change in GPE  <b>M1</b> : Three term energy equation <b>A1</b> : Fully correct  <b>AWRT 3.5</b> Allow <b>AWRT 3.4</b> if 110 J used
		<b>5</b>	

Q	Answer	Marks	Comments
7(c)	$110.5 = 7 \times 9.8h$  $h = 1.6 \text{ [m]} \text{ (to 2 sf)}$	<b>M1</b>  <b>A1</b>	Two term energy equation  Correct height
		<b>2</b>	

	<b>Question 7 Total</b>	<b>11</b>	
--	-------------------------	-----------	--

Q	Answer	Marks	Comments
8(a)	$0 = 20 \sin 35^\circ t - \frac{1}{2} g \cos 30^\circ t^2$ $t = \frac{40 \sin 35^\circ}{g \cos 30^\circ} \quad [= 2.703...]$ $\dot{x} = 20 \cos 35^\circ - g \sin 30^\circ \times \frac{40 \sin 35^\circ}{g \cos 30^\circ}$ $= 3.1368...$ $\dot{y} = 20 \sin 35^\circ - g \cos 30^\circ \times \frac{40 \sin 35^\circ}{g \cos 30^\circ}$ $= -20 \sin 35^\circ$ $= -11.4715...$ $v = \sqrt{11.4715...^2 + 3.1368...^2}$ $= 11.89...$ $= 12 \text{ [m s}^{-1}\text{]} \text{ (to 2 sf)}$	<b>M1</b>  <b>A1</b> <b>A1</b>  <b>M1</b> <b>A1</b>   <b>A1</b>   <b>A1</b>	Equation for motion perpendicular to the plane  Correct equation  Correct time   Finds both components of velocity  Correct parallel component   Correct perpendicular component   Correct speed
		<b>7</b>	

Q	Answer	Marks	Comments
8(b)	Require rebound angle to be greater than $60^\circ$  $\tan \theta = \frac{11.4715... \times e}{3.1368...}$ $\frac{11.4715... \times e}{3.1368...} > \sqrt{3}$ $0.47 < e < 1$	<b>B1</b>   <b>M1</b>   <b>A1</b>   <b>A1</b>	Identifies $60^\circ$   Forms expression for tan of the rebound angle   Correct inequality   Correct range Allow lower limit between 0.46 and 0.48 Accept $0.47 \leq e \leq 1$
		<b>4</b>	

	<b>Question 8 Total</b>	<b>11</b>	
--	-------------------------	-----------	--

Q	Answer	Marks	Comments
9(a)	$12 \times 8 \cos 60^\circ = 12v_A + 3v_B$ $16 = 4v_A + v_B$  $v_B - v_A = -e(0 - 8 \cos 60^\circ)$ $v_B - v_A = 4e$  $v_A = \frac{16 - 4e}{5}$  $V^2 = (8 \sin 60^\circ)^2 + \left(\frac{16 - 4e}{5}\right)^2$  $V = \sqrt{48 + \left(\frac{16 - 4e}{5}\right)^2}$	<b>M1</b>   <b>M1</b> <b>A1</b>  <b>A1</b>  <b>M1</b>  <b>A1</b>	Equation for conservation of momentum   Equation for coefficient of restitution  Two correct equations  Correct component of A along line of centres  Finds expression for speed of A after the collision  Correct expression <b>ACF</b>
		<b>6</b>	

Q	Answer	Marks	Comments
9(b)	$V_{\min} = \sqrt{(8 \sin 60^\circ)^2 + \left(\frac{16 - 4}{5}\right)^2} = \frac{8\sqrt{21}}{5}$  Maximum change in speed =  $8 - \frac{8\sqrt{21}}{5} = \frac{40 - 8\sqrt{21}}{5}$	<b>M1</b>   <b>A1</b>	Uses $e = 1$  Correct maximum change in speed <b>ACF</b>
		<b>2</b>	

	<b>Question 9 Total</b>	<b>8</b>	
--	-------------------------	----------	--