

OXFORD

INTERNATIONAL
AQA EXAMINATIONS

INTERNATIONAL A-LEVEL FURTHER MATHEMATICS FM05

(9665/FM05) Unit FM2 Mechanics

Mark scheme

January 2022

Version: 1.0 Final



2 2 1 X F M 0 5 / M S

Mark schemes are prepared by the Lead Assessment Writer and considered, together with the relevant questions, by a panel of subject teachers. This mark scheme includes any amendments made at the standardisation events which all associates participate in and is the scheme which was used by them in this examination. The standardisation process ensures that the mark scheme covers the students' responses to questions and that every associate understands and applies it in the same correct way. As preparation for standardisation each associate analyses a number of students' scripts. Alternative answers not already covered by the mark scheme are discussed and legislated for. If, after the standardisation process, associates encounter unusual answers which have not been raised they are required to refer these to the Lead Examiner.

It must be stressed that a mark scheme is a working document, in many cases further developed and expanded on the basis of students' reactions to a particular paper. Assumptions about future mark schemes on the basis of one year's document should be avoided; whilst the guiding principles of assessment remain constant, details will change, depending on the content of a particular examination paper.

Further copies of this mark scheme are available from oxfordaqaexams.org.uk

Copyright information

OxfordAQA retains the copyright on all its publications. However, registered schools/colleges for OxfordAQA are permitted to copy material from this booklet for their own internal use, with the following important exception: OxfordAQA cannot give permission to schools/colleges to photocopy any material that is acknowledged to a third party even for internal use within the centre.

Copyright © 2022 Oxford International AQA Examinations and its licensors. All rights reserved.

Key to mark scheme abbreviations

M	Mark is for method
m	Mark is dependent on one or more M marks and is for method
A	Mark is dependent on M or m marks and is for accuracy
B	Mark is independent of M or m marks and is for method and accuracy
E	Mark is for explanation
✓ or ft	Follow through from previous incorrect result
CAO	Correct answer only
CSO	Correct solution only
AWFW	Anything which falls within
AWRT	Anything which rounds to
ACF	Any correct form
AG	Answer given
SC	Special case
oe	Or equivalent
A2, 1	2 or 1 (or 0) accuracy marks
–x EE	Deduct x marks for each error
NMS	No method shown
PI	Possibly implied
SCA	Substantially correct approach
sf	Significant figure(s)
dp	Decimal place(s)

Q	Answer	Marks	Comments
1(a)	$5 \cos 50^\circ = v \cos \alpha^\circ$	M1	Equation for motion parallel to the wall
	$0.8 \times 5 \sin 50^\circ = v \sin \alpha^\circ$	M1	Equation for motion perpendicular to the wall
		A1	Both equations correct
	$v^2 = (5 \cos 50^\circ)^2 + (4 \sin 50^\circ)^2$	M1	Eliminates α
	$v = 4.44$	A1	Correct v . Must be a positive value. Condone AWRT 4.4
		5	

Q	Answer	Marks	Comments
1(b)	$\tan \alpha^\circ = \frac{4 \sin 50^\circ}{5 \cos 50^\circ}$	M1	Eliminates v
	$\alpha = 44$	A1	Correct α Condone AWRT 43.6
		2	

Q	Answer	Marks	Comments
1(c)	$I = 0.3(4.4 \sin 43.6^\circ) - 0.3(-5 \sin 50^\circ)$	M1	Applies impulse formula. Must resolve in some way.
	or		
	$I = 0.3(0.8 \times 5 \sin 50^\circ) - 0.3(-5 \sin 50^\circ)$	A1	Correct expression
	$= 2.1 \text{ Ns [to 2 sf]}$	A1	Correct answer with correct units. Must be two significant figures. Do not accept a negative answer.
		3	

	Question 1 Total	10	
--	------------------	----	--

Q	Answer	Marks	Comments
2(a)	$\int_{0.02}^{0.01} -\left(\frac{8}{x^2}\right) dx$ $= \left[\frac{8}{x} \right]_{0.02}^{0.01}$ $= 800 - 400$ $= 400 \text{ J}$	M1 A1 A1 A1	Uses $\int \pm F dx$ Uses limits that are consistent with their sign of F Correct integration Obtains correct work done from consistent working. Must show some numeric simplification after the integration.
		4	

Q	Answer	Marks	Comments
2(b)	$\frac{1}{2} \times 4v^2 = 400$ $v = \sqrt{200} = 14.1 \text{ m s}^{-1}$	M1 A1	Forms an energy equation to find v Do not condone use of constant acceleration equations. Correct speed AWRT 14.1
		2	

	Question 2 Total	6	
--	------------------	---	--

Q	Answer	Marks	Comments
3(a)	$\omega = \frac{2\pi}{5}$	M1	Finding ω
	$v_{\max} = \frac{3}{2} \times \frac{2\pi}{5} = \frac{3\pi}{5} \text{ m s}^{-1}$	A1	Correct speed oe
		2	

Q	Answer	Marks	Comments
3(b)	$v^2 = \left(\frac{2\pi}{5}\right)^2 \left(\left(\frac{3}{2}\right)^2 - \left(\frac{1}{2}\right)^2\right)$	M1	Uses SHM speed formula with their ω Allow one error in the distances.
	$= \frac{8\pi^2}{25}$	A1	Correct substitutions
	$v = \frac{2\sqrt{2}\pi}{5} \text{ m s}^{-1}$	A1	Correct speed, ACF, for example $\sqrt{\frac{8}{25}}\pi$ or $\sqrt{0.32}\pi$
		3	

Q	Answer	Marks	Comments
3(c)(i)	$x = \frac{3}{2} \cos\left(\frac{2\pi t}{5}\right)$	B1	Correct expression with \pm
		1	

Q	Answer	Marks	Comments
3(c)(ii)	$\dot{x} = -\frac{3\pi}{5} \sin\left(\frac{2\pi t}{5}\right)$	M1	Differentiates to find velocity
	$\ddot{x} = -\frac{6\pi^2}{25} \cos\left(\frac{2\pi t}{5}\right)$	M1	Differentiates to find acceleration
	$\ddot{x}_{\max} = \frac{6\pi^2}{25} \text{ m s}^{-2}$	A1	Correct maximum acceleration Accept $0.24\pi^2$ Do not accept a negative answer.
		3	

	Question 3 Total	9	
--	------------------	---	--

Q	Answer	Marks	Comments
4(a)(i)	<p>Let θ be the angle between the string and the vertical at time t</p> $m \times 0.7 \ddot{\theta} = -m \times 9.8 \sin \theta$ $\sin \theta \approx \theta$ $\ddot{\theta} \approx -\frac{9.8}{0.7} \theta = -14\theta$ <p>Therefore SHM as [angular] acceleration proportional to the [angular] displacement.</p>	<p>M1 A1</p> <p>M1</p> <p>A1</p> <p>E1</p>	<p>PI</p> <p>Forms differential equation Correct differential equation</p> <p>Uses small angle approximation, PI</p> <p>Simplifies to SHM form with clear use of small angle approximation Accept proof for any l in general case</p> <p>Concludes that motion is SHM from correct working</p>
		5	

Q	Answer	Marks	Comments
4(a)(ii)	<p>Light</p> <p>Inextensible / inelastic / fixed length</p>	<p>B1</p> <p>B1</p>	<p>Correct assumption</p> <p>Correct assumption</p>
		2	

Q	Answer	Marks	Comments
4(b)	<p>Period = $\frac{2\pi}{\sqrt{14}} = \frac{\pi\sqrt{14}}{7}$ s</p>	B1	Correct period, oe such as 0.53π [s]
		1	

	Question 4 Total	8	
--	-------------------------	----------	--

Q	Answer	Marks	Comments
5	$2.5v \frac{dv}{dx} = -10v^2$ $\frac{1}{v} \times \frac{dv}{dx} = -4$ $\ln v = -4x + c$ $x = 0, v = 20 \Rightarrow c = \ln 20$ $\ln v = -4x + \ln 20$ $v = 10$ $x = \frac{1}{4}(\ln 20 - \ln 10) = \frac{1}{4} \ln 2$	M1 A1ft A1ft M1 A1	Sets up correct differential equation. Condone missing negative sign. Rearranges differential equation correctly ready to integrate Follow through sign error from differential equation. Correct integration Follow through sign error from differential equation. Finds constant of integration or uses correct limits in a definite integral Correct distance, ACF
		5	

ALTERNATIVE METHOD

Q	Answer	Marks	Comments
5	$2.5 \frac{dv}{dt} = -10v^2$ $\int \frac{1}{v^2} dv = \int -4 dt$ $-\frac{1}{v} = -4t + c$ $v = 20, t = 0 \Rightarrow c = -\frac{1}{20}$ $v = \frac{20}{80t + 1}$ $x = \frac{20}{80} \ln(80t + 1) + d$ $x = 0, t = 20 \Rightarrow d = 0$ $x = \frac{1}{4} \ln(80t + 1)$ $v = 10 \Rightarrow t = \frac{1}{80}$ $x = \frac{1}{4} \ln\left(\frac{80}{80} + 1\right) = \frac{1}{4} \ln 2$	<p>M1</p> <p>A1ft</p> <p>A1ft</p> <p>M1</p> <p>A1</p>	<p>Sets up correct differential equation. Condone missing negative sign.</p> <p>Correct expression for v in terms of t Follow through sign error from differential equation to obtain $v = \frac{20}{1 - 80t}$ oe</p> <p>Correct expression for x in terms of t Follow through sign error from differential equation to obtain $x = -\frac{1}{4} \ln(1 - 80t)$ oe</p> <p>Finds time for a velocity of 10</p> <p>Correct distance, ACF</p>
		5	

	Question 5 Total	5	
--	-------------------------	----------	--

Q	Answer	Marks	Comments
6(a)	$ke = 2g$	M1	Equation for equilibrium
	$e = \frac{2g}{k}$	A1	Correct extension Do not accept $\frac{mg}{k}$
		2	

Q	Answer	Marks	Comments
6(b)(i)	$2\ddot{x} = 2g - T$	M1	Forms three term differential equation PI
	$2\ddot{x} = 2g - k\left(x + \frac{2g}{k}\right)$	M1	Uses tension with their extension from part (a) Allow $2\ddot{x} = \pm 2g \pm k\left(x + \frac{2g}{k}\right)$
	$2\ddot{x} = 2g - kx - 2g$	A1	Correct differential equation
	$\ddot{x} = -\frac{k}{2}x$	A1	Differential equation simplified to SHM form Accept $\ddot{x} = -\frac{k}{m}x$
	\therefore SHM as acceleration proportional to the displacement.	E1	Concludes that motion is SHM from correct working
		5	

Q	Answer	Marks	Comments
6(b)(ii)	$x = 2a \cos\left(\sqrt{\frac{k}{2}}t\right)$ $\frac{3a}{2} = 2a \cos\left(\sqrt{\frac{k}{2}} \times \frac{\pi}{8}\right)$ $0.7227... = \sqrt{\frac{k}{2}} \times \frac{\pi}{8}$ $k = 6.8$	<p>M1</p> <p>A1</p> <p>M1</p> <p>A1</p>	<p>Expression for displacement using their ω</p> <p>Correct substitution of time and displacement</p> <p>Solves for k</p> <p>Correct k, AWRT 6.8</p> <p>SC2 for using $x = 2a \sin\left(\sqrt{\frac{k}{2}}t\right)$ leading to $k = 9.3$</p> <p>SC1 for seeing $\frac{3}{2}a = 2a \sin\left(\sqrt{\frac{k}{2}}t\right)$</p>
		4	
	Question 6 Total	11	

Q	Answer	Marks	Comments
7(a)	$v^2 = 0^2 + 2 \times g \times 2a$	M1	Uses constant acceleration equation to find speed with $u = 0$
	$v = 2\sqrt{ag}$	A1	Correct speed oe
		2	

Q	Answer	Marks	Comments
7(b)	Resolving parallel and perpendicular to OB		
	$v = -2\sqrt{ag} \cos 30^\circ$	M1	Equation for velocity perpendicular to the string
	Speed $= 2\sqrt{ag} \times \frac{\sqrt{3}}{2}$		
	Speed $= \sqrt{3ag}$	A1	Correct speed, from correct working
	$I = m \times 0 - m \times -2\sqrt{ag} \sin 30^\circ$	M1	Uses impulse equation with some resolving
	$ I = 2m\sqrt{ag} \times \frac{1}{2} = m\sqrt{ag}$	A1	Correct impulse equation
		A1	Correct magnitude of impulse
		5	

Q	Answer	Marks	Comments
7(c)	Resolving radially with zero tension $mg \cos \theta = \frac{mv^2}{2a}$ $v^2 = 2ag \cos \theta$ Energy Equation $\frac{1}{2}mv^2 + mg \times a(1 + 2 \cos \theta) = \frac{1}{2}m \times 3ag$ $ag \cos \theta + ag + 2ag \cos \theta = \frac{3}{2}ag$ $3ag \cos \theta = \frac{1}{2}ag$ $\cos \theta = \frac{1}{6}$ $\theta = 80^\circ$	M1 A1 M1 A1 m1 A1	Resolving radially Correct equation Forms a three term energy equation Correct energy equation Solves for θ Correct angle
		6	
	Question 7 Total	13	

Q	Answer	Marks	Comments
8	<p>Speed at $B = \sqrt{6g}$</p> $\mathbf{u} = \begin{bmatrix} \sqrt{6g} \sin 20^\circ \\ \frac{3}{5} \sqrt{6g} \cos 20^\circ \end{bmatrix} = \begin{bmatrix} 2.62 \\ 4.32 \end{bmatrix}$ $0 = \frac{3}{5} \sqrt{6g} \cos 20^\circ t - \frac{1}{2} g \cos 20^\circ t^2$ $t = \frac{6\sqrt{6g}}{5g} = 0.939$ $BC = \sqrt{6g} \sin 20^\circ t + \frac{1}{2} g \sin 20^\circ t^2$ $= 3.94$ $= 3.9 \text{ metres [to 2 sf]}$	<p>B1</p> <p>M1</p> <p>A1</p> <p>M1</p> <p>A1</p> <p>M1</p> <p>A1</p> <p>M1</p> <p>A1</p>	<p>Correct speed at B</p> <p>Uses coefficient of restitution to find the velocity after the bounce at B</p> <p>Correct velocity</p> <p>Equation for motion perpendicular to the slope</p> <p>Correct equation</p> <p>Solves for t</p> <p>Correct t AWRT 0.94</p> <p>Substitutes t into equation for motion parallel to the slope</p> <p>Correct distance</p> <p>AFWT [3.9, 3.95]</p>
		9	
	Question 8 Total	9	

Q	Answer	Marks	Comments
9	$2 \times 2 - 3 \times 1 = 2v_A + 3v_B$ $1 = 2v_A + 3v_B$ $v_A - v_B = -e \times (2 - (-1))$ $v_A - v_B = -3e$ $1 = 2v_A + 3(v_A + 3e)$ $1 = 5v_A + 9e$ $v_A = \frac{1-9e}{5}$ Let θ be the angle between the velocity of A and the line of centres. $\tan \theta = \frac{5 \times 2\sqrt{3}}{1-9e} = \frac{10\sqrt{3}}{1-9e}$ $e = 0 \Rightarrow \tan \theta = 10\sqrt{3} \Rightarrow \theta = 87^\circ$ $e = 1 \Rightarrow \tan \theta = \frac{10\sqrt{3}}{-8} \Rightarrow \theta = 115^\circ$ $87^\circ \leq \theta \leq 115^\circ$ $27 \leq \alpha \leq 55$	M1 M1 A1 M1 A1 M1 M1 A1 A1	Equation for conservation of momentum Equation for coefficient of restitution Both equations correct Solves for v_A Correct v_A Finds $\tan \theta$ using the perpendicular component Uses $e = 0$ or $e = 1$ in their expression for $\tan \theta$ At least one correct value for θ Accept $27 \leq \alpha \leq 54$ AWRT 27 and 54 or 55
		9	
	Question 9 Total	9	