
INTERNATIONAL A-LEVEL MATHEMATICS MA05

(9660/MA05) Unit M2 Mechanics

Mark scheme

June 2023

Version: 1.0 Final



Mark schemes are prepared by the Lead Assessment Writer and considered, together with the relevant questions, by a panel of subject teachers. This mark scheme includes any amendments made at the standardisation events which all associates participate in and is the scheme which was used by them in this examination. The standardisation process ensures that the mark scheme covers the students' responses to questions and that every associate understands and applies it in the same correct way. As preparation for standardisation each associate analyses a number of students' scripts. Alternative answers not already covered by the mark scheme are discussed and legislated for. If, after the standardisation process, associates encounter unusual answers which have not been raised they are required to refer these to the Lead Examiner.

It must be stressed that a mark scheme is a working document, in many cases further developed and expanded on the basis of students' reactions to a particular paper. Assumptions about future mark schemes on the basis of one year's document should be avoided; whilst the guiding principles of assessment remain constant, details will change, depending on the content of a particular examination paper.

Further copies of this mark scheme are available from [oxfordaqaexams.org.uk](https://www.oxfordaqaexams.org.uk)

Copyright information

OxfordAQA retains the copyright on all its publications. However, registered schools/colleges for OxfordAQA are permitted to copy material from this booklet for their own internal use, with the following important exception: OxfordAQA cannot give permission to schools/colleges to photocopy any material that is acknowledged to a third party even for internal use within the centre.

Copyright © 2023 Oxford International AQA Examinations and its licensors. All rights reserved.

Key to mark scheme abbreviations

| | |
|----------------|--|
| M | Mark is for method |
| m | Mark is dependent on one or more M marks and is for method |
| A | Mark is dependent on M or m marks and is for accuracy |
| B | Mark is independent of M or m marks and is for method and accuracy |
| E | Mark is for explanation |
| ✓ or ft | Follow through from previous incorrect result |
| CAO | Correct answer only |
| CSO | Correct solution only |
| AWFW | Anything which falls within |
| AWRT | Anything which rounds to |
| ACF | Any correct form |
| AG | Answer given |
| SC | Special case |
| oe | Or equivalent |
| A2, 1 | 2 or 1 (or 0) accuracy marks |
| –x EE | Deduct x marks for each error |
| NMS | No method shown |
| PI | Possibly implied |
| SCA | Substantially correct approach |
| sf | Significant figure(s) |
| dp | Decimal place(s) |

| Q | Answer | Marks | Comments |
|---|--|--|--|
| 1 | $(1 + 2 + 4 + 8 + m) \times 4.4$ $= 1 \times 4 + 2 \times 1 + 4 \times 3 + 8 \times 5 + m \times 6$ $66 + 4.4m = 58 + 6m$ $m = 5$ $(1 + 2 + 4 + 8 + m) \times 3.9$ $= 1 \times 2 + 2 \times 4 + 4 \times 1 + 8 \times 3 + m \times k$ $78 = 38 + 5k$ $k = 8$ | <p>M1 A1</p> <p>A1</p> <p>A1ft</p> <p>A1ft</p> | <p>M1: Forming centre of mass equation using x-coordinates or y-coordinates Allow one error A1: Both sides of x-coordinate equation correct</p> <p>Correct value for m</p> <p>Both sides of y-coordinate equation correct, ft their m if substituted</p> <p>Correct value for k from their m $k = \frac{20.5}{\text{their } m} + 3.9$</p> |
| | | 5 | |
| | Question 1 Total | 5 | |

| Q | Answer | Marks | Comments |
|------|---|---|---|
| 2(a) | $P = Fv$ $P = (14 \times 9.8) \times 0.8$ $P = 110$ Units = W or J s^{-1} | M1 A1 B1 | Use of $P = Fv$ Condone 9.81 m s^{-2} for g , but not 10 m s^{-2} Unrounded answer is 109.76 oe |
| | | 3 | |

| Q | Answer | Marks | Comments |
|------|--|---|--|
| 2(b) | Initial Energy (KE & GPE) $= \frac{1}{2} \times 14 \times 0.8^2 + 14 \times 9.8 \times 1.6$ $= 224 \text{ [J]}$ Final Energy (KE only) $224 = \frac{1}{2} \times 14 \times v^2$ $v = 5.7 \text{ [m s}^{-1}\text{]}$ | M1 M1 A1 | Adds potential energy and kinetic energy An initial energy of 219.52 J has not included the initial KE Setting their 224 J equal to final KE PI by correct answer of 5.7 CAO Allow $5.6568... \text{ [m s}^{-1}\text{]}$ or $4\sqrt{2} \text{ [m s}^{-1}\text{]}$ as the correct final answer. If initial KE not included, answer should be $5.6 \text{ [m s}^{-1}\text{]}$ – award SC2 |
| | | 3 | |

| | | | |
|--|-------------------------|----------|--|
| | Question 2 Total | 6 | |
|--|-------------------------|----------|--|

| Q | Answer | Marks | Comments |
|------|---|-------|----------|
| 3(a) | [Resultant Force =] $5000v^2e^{-0.32v} - 0.26v^2$ | B1 | oe |
| | | 1 | |

| Q | Answer | Marks | Comments |
|------|---|----------------------------------|---|
| 3(b) | $5000 \times 8.3^2 e^{-0.32 \times 8.3} - 0.26 \times 8.3^2$ $= 24172.32125 \text{ [N]}$ $F = ma \Rightarrow a = \frac{F}{m}$ $a = \frac{24172.32125}{1800}$ $a = 13 \text{ [m s}^{-2}\text{]}$ | M1 A1 A1ft | Substituting $v = 8.3$ into their resultant force expression from part (a) Correct magnitude of resultant force, AWRT 24000 [N] PI by correct answer Unrounded answer is 13.429... [m s ⁻²] |
| | | 3 | |

| Q | Answer | Marks | Comments |
|------|---|----------------------|--|
| 3(c) | At maximum speed, resultant force on car is zero. $5000v^2e^{-0.32v} - 0.26v^2 = 0$ $e^{-0.32v} = \frac{13}{250\,000} \text{ [} = 5.2 \times 10^{-5} \text{]}$ $v = \frac{\ln\left(\frac{250\,000}{13}\right)}{0.32} \text{ [} = \frac{\ln(19230.76923)}{0.32} \text{]}$ $v = 31 \text{ [m s}^{-1}\text{]}$ | M1 A1 | This line or better PI by correct final answer Note $\ln\left(\frac{250\,000}{13}\right) = 9.864...$ Unrounded answer is 30.8258... [m s ⁻¹] |
| | | 2 | |

| | | | |
|--|------------------|---|--|
| | Question 3 Total | 6 | |
|--|------------------|---|--|


| Q | Answer | Marks | Comments |
|------|--|---|--|
| 4(a) | $\sqrt{25\cos^2(3t) + 1369\sin^2(3t)} = 19$ $\sqrt{25 + 1344\sin^2(3t)} = 19$ $1344\sin^2(3t) = 336$ or $1344\cos^2(3t) = 1008$ $\sin^2(3t) = \frac{1}{4}$ or $\cos^2(3t) = \frac{3}{4}$ $\sin(3t) = [\pm]\frac{1}{2}$ or $\cos(3t) = [\pm]\frac{\sqrt{3}}{2}$ $t = 0.17$ $t = 0.87$ | M1 M1 m1 A1 A1 | Forming a distance equation Use of $\cos^2(3t) + \sin^2(3t) = 1$ PI by at least one correct value of t or sight of 10 and 50 $t = \frac{\pi}{18}$ One correct value of t $t = \frac{5\pi}{18}$ The second correct value of t and no others, and no errors throughout solution |
| | | 5 | |

| Q | Answer | Marks | Comments |
|------|--|---|---|
| 4(b) | $\mathbf{r} = 5\cos(3t)\mathbf{i} + 37\sin(3t)\mathbf{j}$ $\mathbf{v} = -15\sin(3t)\mathbf{i} + 111\cos(3t)\mathbf{j}$ $\mathbf{a} = -45\cos(3t)\mathbf{i} - 333\sin(3t)\mathbf{j}$ $\mathbf{a} = -45\cos\left(\frac{3\pi}{4}\right)\mathbf{i} - 333\sin\left(\frac{3\pi}{4}\right)\mathbf{j}$ $\mathbf{a} = \frac{45}{\sqrt{2}}\mathbf{i} - \frac{333}{\sqrt{2}}\mathbf{j}$ | M1 A1 m1 M1 A1 | M1: At least one component correct or $\mathbf{v} = \mp 15\sin(3t)\mathbf{i} \pm 111\cos(3t)\mathbf{j}$ A1: Both components correct Both marks PI by correct acceleration vector At least one component correct Substituting $t = \frac{\pi}{4}$ into their a Any correct form involving surds CSO , do not ISW |
| | | 5 | |

| | | | |
|--|-------------------------|-----------|--|
| | Question 4 Total | 10 | |
|--|-------------------------|-----------|--|

| Q | Answer | Marks | Comments |
|------|--|-------|-------------------------|
| 5(a) | The entire weight of the rod appears to act through the midpoint of XY | E1 | Any correct explanation |
| | | 1 | |

| Q | Answer | Marks | Comments |
|------|-------------------|--------------|--|
| 5(b) | See artwork below | M1 A1 | At least two of the forces drawn on a diagram in the correct direction and named. All forces correctly drawn and named. Do not condone 'gravity' in place of 'weight' |



| | | | |
|--|--|---|--|
| | | 2 | |
|--|--|---|--|

| Q | Answer | Marks | Comments |
|------|--|---|---|
| 5(c) | <p>Taking moments about X</p> $4 \times 15 \times 9.8 \cos(35^\circ) = 6R_{\text{peg}}$ $R_{\text{peg}} = 80.2769... \text{ [N]}$ <p>Forces in equilibrium (vertical)</p> $R_{\text{ground}} + R_{\text{peg}} \cos(35^\circ) = 15 \times 9.8$ $R_{\text{ground}} = 15 \times 9.8 - 80.2769... \times \cos(35^\circ)$ $R_{\text{ground}} = 81.2410... \text{ [N]}$ <p>Forces in equilibrium (horizontal)</p> $F = R_{\text{peg}} \sin(35^\circ)$ $F = 46.0449... \text{ [N]}$ $F \leq \mu R_{\text{ground}}$ $46.0449... \leq \mu \times 81.2410...$ $0.5667... \leq \mu$ <p>The minimum value of μ is 0.567 to 3 sf</p> | <p>M1</p> <p>A1</p> <p>M1</p> <p>A1</p> <p>M1</p> <p>A1</p> <p>M1</p> <p>A1</p> | <p>At least one side correct R_{peg} = reaction force on rod due to peg</p> <p>$R_{\text{peg}} = 10g \cos(35^\circ)$</p> <p>Both sides correct R_{ground} = reaction force on rod due to ground</p> <p>$R_{\text{ground}} = 15g - 10g \cos^2(35^\circ)$</p> <p>Both sides correct PI F = friction on rod due to rough ground</p> <p>$F = 10g \cos(35^\circ) \sin(35^\circ)$</p> <p>Condone $F = \mu R_{\text{ground}}$</p> $\frac{10g \cos(35^\circ) \sin(35^\circ)}{15g - 10g \cos^2(35^\circ)} \leq \mu$ |
| | | 8 | |
| | Question 5 Total | 11 | |

| Q | Answer | Marks | Comments |
|------|---|-----------------------------------|--|
| 6(a) | $\begin{bmatrix} t^2 + 4t + 1 \\ 2t^2 - 2t \end{bmatrix} + \begin{bmatrix} 2t^2 - 1 \\ -t^2 - 2t + 1 \end{bmatrix}$ $+ \begin{bmatrix} t^2 - 12t + 3 \\ t^2 - t + 1 \end{bmatrix}$ $= \begin{bmatrix} 4t^2 - 8t + 3 \\ 2t^2 - 5t + 2 \end{bmatrix}$ | <p>M1</p> <p>A1</p> | <p>Summing the three forces</p> <p>Both components correct</p> |
| | | 2 | |

| Q | Answer | Marks | Comments |
|------|---|--|---|
| 6(b) | $\begin{bmatrix} 4 \times 2^2 - 8 \times 2 + 3 \\ 2 \times 2^2 - 5 \times 2 + 2 \end{bmatrix}$ $[0.2\mathbf{a} =] \begin{bmatrix} 3 \\ 0 \end{bmatrix}$ <p>Magnitude of acceleration is 15 [m s⁻²]</p> | <p>M1</p> <p>A1</p> <p>A1</p> | <p>Substituting $t = 2$ into their resultant force vector</p> <p>PI by correct magnitude of acceleration.</p> <p>CAO Must be a positive scalar and not a vector.</p> |
| | | 3 | |

| Q | Answer | Marks | Comments |
|------|--|---|--|
| 6(c) | $\begin{bmatrix} 4t^2 - 8t + 3 \\ 2t^2 - 5t + 2 \end{bmatrix} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$ $(2t - 1)(2t - 3) = 0$ $(2t - 1)(t - 2) = 0$ $t = \frac{1}{2}$ | <p>M1</p> <p>M1 A1</p> <p>A1</p> | <p>Sets their resultant force vector from part (a) equal to the zero vector. PI</p> <p>M1: At least one quadratic correctly factorised PI by correct pair of roots A1: Both quadratics correctly factorised PI by both correct pairs of roots</p> <p>oe and no other values of t stated as the answer</p> |
| | | 4 | |

| | | | |
|--|-------------------------|----------|--|
| | Question 6 Total | 9 | |
|--|-------------------------|----------|--|

| Q | Answer | Marks | Comments |
|------|--|--|--|
| 7(a) | Energy at A (GPE) $5 \times 9.8 \times 10 = 490 \text{ [J]}$ $F = 0.3 \times 5 \times 9.8 \times \cos(40^\circ)$ Energy at C (GPE & WD against friction) $5 \times 9.8 \times h$ $+ 0.3 \times 5 \times 9.8 \times \cos(40^\circ) \times \frac{h-2}{\sin(40^\circ)}$ Conservation of Energy (between A and C) $490 = 49h + \frac{14.7h - 29.4}{\tan(40^\circ)}$ $h = \frac{490 + \frac{29.4}{\tan(40^\circ)}}{49 + \frac{14.7}{\tan(40^\circ)}} \left[= \frac{490 + 35.037...}{49 + 15.518...} \right]$ $h = 7.89 \text{ [m]}$ | B1 B1 B1 M1 m1 A1 | PI by later working May be seen in a calculation Friction, 11.26... PI Correct energy expression, GPE + work done against friction, in terms of h or $x = \frac{h-2}{\sin(40^\circ)}$ Setting their energy at A (or B, 392 J) equal to their energy at C Attempt to rearrange their CoE equation for h or for finding $x = 9.16799...$ or $h - 2 = 5.89...$ CAO to 3 sf |
| | | 6 | |

| Q | Answer | Marks | Comments |
|------|---|---|---|
| 7(b) | Magnitude of force down the slope $[5 \times 9.8 \times \sin(40^\circ) =] 31.4965... \text{ [N]}$ Magnitude of force up the slope $[0.3 \times 5 \times 9.8 \times \cos(40^\circ) =] 11.2608... \text{ [N]}$ [As the magnitude of the force down the slope is greater than the magnitude of the force up the slope] the particle slides back down [the rough track from C towards B] | M1 A1 E1ft | M1 At least one correct magnitude of force A1 Both magnitudes correct M1 A1 PI by resultant force of 20[.235] N Correct conclusion based on their magnitudes of the forces up and down the slope. |
| | | 3 | |

| | | | |
|--|-------------------------|----------|--|
| | Question 7 Total | 9 | |
|--|-------------------------|----------|--|

| Q | Answer | Marks | Comments |
|------|--|---|---|
| 8(a) | <p>When the ball collides with the wall, the vertical component of velocity is zero.</p> $v^2 = u^2 + 2as$ $0 = (15 \sin \theta)^2 + 2 \times (-9.8) \times 1.9$ $\sin^2 \theta = \frac{931}{5625} \left[= \frac{37.24}{225} = 0.1655... \right]$ $\sin \theta = [\pm] \frac{7\sqrt{19}}{75} \left[= 0.4068... \right]$ $\theta = 24.00589...^\circ \Rightarrow \theta = 24^\circ$ | <p>B1</p> <p>M1</p> <p>m1</p> <p>A1</p> | <p>Use of $v = 0$ in the vertical direction when ball collides with the wall May be seen in a calculation</p> <p>Use of $u = 15 \sin \theta$ and $g = [\pm] 9.8$ with $v^2 = u^2 + 2as$</p> <p>This line of working or better</p> <p>AG Must be convincingly shown</p> |
| | | 4 | |

| Q | Answer | Marks | Comments |
|---------|--|--|--|
| 8(b)(i) | <p>KE of ball before collision with wall</p> $0.5 \times 0.4 \times (15 \cos 24^\circ)^2 = 37.55543... \text{ [J]}$ <p>KE of ball after collision with wall</p> $0.5 \times 37.55543... = 18.77771... \text{ [J]}$ $v = \sqrt{\frac{2KE}{m}} = \sqrt{\frac{2 \times 18.77771...}{0.4}}$ $= 9.69 \text{ [m s}^{-1}\text{]}$ | <p>B1</p> <p>M1</p> <p>A1</p> | <p>Correct KE before collision PI by correct answer</p> <p>0.5 multiplied by their KE before collision PI by correct answer</p> <p>CAO [Unrounded answer is 9.68961...]</p> |
| | | 3 | |

| Q | Answer | Marks | Comments |
|----------|---|---|--|
| 8(b)(ii) | <p>Time for ball to fall 1.9 metres back to ground level</p> $s = \frac{1}{2}at^2 \Rightarrow t = \sqrt{\frac{2s}{a}}$ $t = \sqrt{\frac{2 \times (-1.9)}{-9.8}} = 0.62269... [s]$ <p>Horizontal displacement of ball when it is at ground level</p> $0.62269... \times 9.69 = 6.03 [m]$ <p>As 6.03 [m] is less than 6.25 [m] [but greater than 5.75 m] so the ball does land in the hole.</p> | <p>B1</p> <p>M1 A1</p> <p>E1ft</p> | <p>oe, such as $\frac{\sqrt{19}}{7}$</p> <p>PI by correct horizontal displacement</p> <p>M1: Multiplies their time to fall by their answer from (b)(i)</p> <p>A1: Correct horizontal displacement. Allow values in the range 6.00 to 6.043</p> <p>Correct conclusion based on comparing their horizontal displacement with the location of the hole, e.g. [5.75, 6.25]</p> |
| | | 4 | |

| | | | |
|--|-------------------------|-----------|--|
| | Question 8 Total | 11 | |
|--|-------------------------|-----------|--|

| Q | Answer | Marks | Comments |
|------|--|-------|---|
| 9(a) | Forces acting on Y $T = m_Y g = 8 \times 9.8$ $T = 78.4 \text{ [N]}$ | B1 | AG Correct calculation leading to given result |
| | | 1 | |

| Q | Answer | Marks | Comments |
|---------|---|--------------|---|
| 9(b)(i) | Forces in vertical direction acting on X $T \cos \alpha = m_X g$ $\cos \alpha = \frac{6 \times 9.8}{78.4} = 0.75$ | M1 A1 | Consideration of vertical forces on X Correct fraction or division shown leading to printed result |
| | | 2 | |

| Q | Answer | Marks | Comments |
|----------|---|--------------------------------|---|
| 9(b)(ii) | Vertical component of force [from string acting on smooth ring] $T + T \cos \alpha$ or $m_X g + m_Y g$ $= 137.2 \text{ [N]}$ Horizontal component of force [from string acting on smooth ring] $T \sin \alpha = 78.4 \times \sqrt{1 - 0.75^2}$ $= 51.85672... \text{ [N]}$ Magnitude of force from string acting on smooth ring $\sqrt{51.85672...^2 + 137.2^2} = 147 \text{ [N]}$ | M1 M1 A1 | Note $\sin \alpha = \frac{\sqrt{7}}{4} \text{ [= 0.6614...]}$ AWRT 147 |
| | | 3 | |

| Q | Answer | Marks | Comments |
|------|--|--|---|
| 9(c) | <p>Resultant force acting on X</p> $T \sin \alpha = m_x \omega^2 r \quad \text{and} \quad r = l \sin \alpha$ $l = \frac{78.4}{6 \times 7^2} \quad \text{or} \quad r = \frac{\sqrt{7}}{15} \quad [= 0.176...]$ $l = \frac{4}{15} \text{ [m]}$ | <p>M1</p> <p>m1</p> <p>A1</p> | <p>Use of $F = m\omega^2 r$</p> <p>PI by $\frac{49\sqrt{7}}{15} [= 8.642...]$, the acceleration, or correct working leading to a value for l or r</p> <p>AWRT 0.27 [m] CSO</p> |
| | | 3 | |

| Q | Answer | Marks | Comments |
|---------|---|-------|------------------------|
| 9(d)(i) | They both accelerate vertically downwards at 9.8 m s^{-2} | E1 | Any correct similarity |
| | | 1 | |

| Q | Answer | Marks | Comments |
|----------|---|-------|------------------------|
| 9(d)(ii) | X has a horizontal component of velocity whilst Y only has a vertical component of velocity | E1 | Any correct difference |
| | | 1 | |

| Q | Answer | Marks | Comments |
|-----------|--|---------------------|---|
| 9(d)(iii) | <p>They both fall the same vertical displacement and their initial components of velocity in the vertical direction are zero [and they both experience the same acceleration]</p> <p>Hence they both have reach the ground simultaneously [as they have the same time of flight]</p> | <p>E1</p> <p>E1</p> | <p>Reference to same vertical displacement or $u = 0$ in vertical direction</p> <p>Reference to same vertical displacement and $u = 0$ in vertical direction, and concludes they both reach ground simultaneously</p> |
| | | 2 | |

| | | | |
|--|-------------------------|-----------|--|
| | Question 9 Total | 13 | |
|--|-------------------------|-----------|--|