

# Tikz P&ID circuit extension

Jelle Spijker

January 28, 2018


# 1 Introduction

Example 1.1: Simple circuit

```

1 \usetikzlibrary{circuits}
2 \usetikzlibrary{circuits.pid.IS014617}
3 \usetikzlibrary{positioning,calc}
4
5 \centering
6 \begin{tikzpicture}[
7   circuit pid IS014617,
8   every info/.style={font=\tiny}]
9
10  \draw (0,0) to [pump={displacement,name=P1,info=$P_1$}] (2,0)
11  to [branch={name=T1}] (2.5,0)
12  to [flow direction={speed=3}] (3,0)
13  to [valve={name=V1,info'=$V_1$}] (4,0)
14  to [three way valve={name=V2,info=below right:$V_2$}] ++(1,0)
15  to [tank={name=B1,with={heating coil}{Opt}{Opt}}] ++(1,0)
16  to [tank={name=F1, with={filter element}{0}{-0.5}, with={spray
    ↪ nozzle}{0}{0.8}}] ++ (1,0);
17  \draw (V2.south) to [pump={name=P2,info=$P_2$}] ++(0,-2)
18  to [measurement point={name=M1}] ++(-2,0)
19  to (\currentcoordinate -| T1)
20  to [valve={non return,info=$V_3$}] (T1);
21  \node[measurement device=local control room, at=M1, measure=P]{};
22  \node[turning actuator, at=V1]{};
23  \node[automatic operation, at=V2]{};
24  \node[tank={name=B2, with={steam generator}{0}{1}, with={fired
    ↪ type}{0}{-0.25}}, below=of F1] {};
25  \draw (B1-heating coil.south) to (B1-heating coil.north |-
    ↪ B2-steam generator.input)
26  to [valve, circuit symbol unit=3pt] (B2-steam generator.input);
27  \draw (B1-heating coil.north) to ++(0, 0.5)
28  to ++(1,0);
29  \draw (F1-spray nozzle.north) to ++(0,0.15)
30  to [valve, circuit symbol unit=3pt] ++(1, 0);
31 \end{tikzpicture}

```









## 2 Available symbols



### 2.1 ISO 14617-1 General information and indexes

No Symbols in norm

### 2.2 ISO 14617-2 Symbols having general application

Symbol 2.2.1: Direction	
<code>\draw (0,0) to [flow direction] (2,0);</code>	
Symbol 2.2.2: Direction speed	
<code>\draw (0,0) to [flow direction={speed=1}] (2,0);</code>	
Symbol 2.2.3: Direction mass flow	
<code>\draw (0,0) to [flow direction={mass flow=1}] (2,0);</code>	
Symbol 2.2.4: Direction volume flow	
<code>\draw (0,0) to [flow direction={volume flow=1}] (2,0);</code>	
Symbol 2.2.5: Envelope	
<code>\draw (0,0) to [envelope] (2,0);</code>	
Symbol 2.2.6: Tank	
<code>\draw (0,0) to [tank] (2,0);</code>	

### 2.3 ISO 14617-3 Connections and related devices

Symbol 2.3.1: Functional connection - 401	
<code>\draw (0,0) to (2,0);</code>	
Symbol 2.3.2: Pipeline, duct - 405	
<code>\draw (0,0) to (2,0);</code>	


Symbol 2.3.3: Joint of connections, branch - 501

```
\draw (0,0) to [branch] (2,0);
```




Symbol 2.3.4: T-branch - X504

```
\draw (0,0) to [branch={name=B1}] (2,0);  
\draw (B1) to ++(0,1);
```



Symbol 2.3.5: Joint of multiple functional connections - X506

```
\draw (0,0) to [branch={name=B1}] (2,0);  
\draw (B1) to ++(0,1);  
\draw (B1) to ++(0,-1);
```



## 2.4 ISO 14617-4 Actuators and related devices


Symbol 2.4.1: Manual actuator operated by turning - 685

```
\node [turning actuator] {};
```



Symbol 2.4.2: Manual actuated valve operated by turning - X685

```
\draw (0,0) to [valve={name=V1}] (2,0);  
\node [turning actuator, at=V1] {};
```




## 2.5 ISO 14617-5 Measurement and control devices

None available at the moment, feel free to contribute!

## 2.6 ISO 14617-6 Measurement and control functions

Symbol 2.6.1: Point of measurement - 1011

```
\draw (0,0) to [measurement point] (2,0);
```



Symbol 2.6.2: Measurement device - 1041

```
\node [measurement device] {};
```



Symbol 2.6.3: Measurement device primary location in a central control room  
- 1101

```
\node [measurement device={central control room}] {};
```




Symbol 2.6.4: Measurement device primary location in a local control room  
- 1101

```
\node [measurement device={local control room}] {};
```




Symbol 2.6.5: Pressure measurement

```
\draw (0,0) to[measurement point={name=M1}] (2,0);
\node [measurement device, at=M1, measure=P] {};
```



Symbol 2.6.6: Temperature indication in central control room - X1075

```
\draw (0,0) to[measurement point={name=M1}] (2,0);
\node [measurement device={central control room}, at=M1,
↪ measure=TI] {};
```



Symbol: 2.6.7: Letter symbols for data processing functions

	Symbol	Measured or initiating variable	Modifier	Function
1051	A			Alarming
1052	B			Displaying discrete state
1053	C			Controlling
1054	D	Density	Difference	
1055	E	Electric variable		Sensing
1056	F	Flow rate	Ratio, fraction	
1057	G	Gauge, position, length		Viewing
1058	H	Hand		
1059	I			Indicating
1060	J	Power	Scanning	
1061	K	Time	Time rate of change	
1062	L	Level		
1063	M	Moisture, humidity	Momentarily	
1064	N	User's choice		User's choice
1065	O	User's choice		
1066	P	Pressure, vacuum		Connection of test point
1067	Q	Quality	Integral, total	Integrating, summing
1068	R	Radiation		Registering, recording
1069	S	Speed, frequency		Switching
1070	T	Temperature		Transmitting
1071	U	Multi-variable		Multi-function
1072	V	User's choice		Impact on process by valve, pump, etc.
1073	W	Weight, force	Multiplying	
1074	X	Unclassified		Unclassified
1075	Y	User's choice		Converting, computing
1076	Z	Number of events, quantity		Emergency or safety acting

Symbol: 2.6.8: Letter codes for set values

	Symbol	set value
1081	H	High
1082	HH	Very high
1083	H2	Very high
1084	HHH	Extremely high
1085	H3	Extremely high
1086	L	Low
1087	LL	Very low
1088	L2	Very low
1089	LLL	Extremely low
1090	L3	Extremely low
1091	HL	High or low

## 2.7 ISO 14617-7 Basic mechanical components

Symbol 2.7.1: Spray nozzle - 2037

```
\node [spray nozzle] {};
```



## 2.8 ISO 14617-8 Valves and dampers

Symbol 2.8.1: Two-way valve - 2101

```
\draw (0,0) to [valve] (2,0);
```



Symbol 2.8.2: Two-way valve non return - 2101, 2111

```
\draw (0,0) to [valve={non return}] (2,0);
```




Symbol 2.8.3: Two-way valve adjustable - 2101, 201

```
\draw (0,0) to [valve={adjustable}] (2,0);
```




Symbol 2.8.4: Two-way valve manual operation - 2101, 1021

```
\draw (0,0) to [valve={name=V1}] (2,0);
\node [manual operation, at=V1] {};
```




Symbol 2.8.5: Two-way valve turning actuator - 2101, 1021

```
\draw (0,0) to [valve={name=V1}] (2,0);
\node [turning actuator, at=V1]{};
```




Symbol 2.8.6: Two-way valve automatic operation (electric motor type) - 2101, 685

```
\draw (0,0) to [valve={name=V1}] (2,0);
\node [automatic operation, at=V1]{M};
```




Symbol 2.8.7: Three-way valve - 2103

```
\draw (0,0) to [three way valve] (2,0);
```



Symbol 2.8.8: Three-way valve automatic operation (electric motor type) - 2103, 685

```
\draw (0,0) to [three way valve={name=V1}] (2,0);
\node [automatic operation, at=V1]{M};
```



## 2.9 ISO 14617-9 Pumps, compressors and fans


Symbol 2.9.1: Pump

```
\draw (0,0) to [pump] (2,0);
```




Symbol 2.9.2: Displacement Pump

```
\draw (0,0) to [pump=displacement] (2,0);
```



Symbol 2.9.3: Adjustable displacement pump

```
\draw (0,0) to [pump={displacement,adjustable}] (2,0);
```



Symbol 2.9.4: Rotodynamic Pump


```
\draw (0,0) to [pump=rotodynamic] (2,0);
```






#### Symbol 2.9.5: Centrifugal Pump

```
\draw (0,0) to [pump=centrifugal] (2,0);
```




#### Symbol 2.9.6: Compressor

```
\draw (0,0) to [compressor] (2,0);
```



#### Symbol 2.9.7: Fan

```
\draw (0,0) to [fan] (2,0);
```




## 2.10 ISO 14617-10 Fluid power converters

None available at the moment, feel free to contribute!

## 2.11 ISO 14617-11 Devices for heat transfer and heat engines

#### Symbol 2.11.1: Tank - 301

```
\draw (0,0) to [tank] (2,0);
```




#### Symbol 2.11.2: Spray nozzle - 2037

```
\node [spray nozzle] {};
```



#### Symbol 2.11.3: Humidifier - X2503, 301, 2037

```
\draw (0,0) to [tank={with={spray nozzle}{0}{0.5},name=HU1}]
  ↪ (2,0);
\draw (HU1-spray nozzle.north) to ++(0, 0.5);
```




#### Symbol 2.11.4: Heating coil - 2501










```
\node [heating coil] {};
```






#### Symbol 2.11.5: Heat-exchanger - X2501, 301, 2501







```
\draw (0,0) to [tank={with={heating coil}{0}{0},name=HE1}]
  ↪ (2,0);
\draw (HE1-heating coil.north) to ++(0, 0.5);
\draw (HE1-heating coil.south) to ++(0, -0.5);
```



Symbol 2.11.6: Cooling coil - 2501	
<pre>\node [cooling coil] {};</pre>	
Symbol 2.11.7: Condensor - X2501, 301, 2501	
<pre>\draw (0,0) to [tank={with={cooling coil}{0}{0},name=C01}]   ↪ (2,0); \draw (C01-cooling coil.north) to ++(0, 0.5); \draw (C01-cooling coil.south) to ++(0, -0.5);</pre>	
Symbol 2.11.8: Boiler - 301, 2531	
<pre>\node [tank={with={boiler}{0}{1}}] {};</pre>	
Symbol 2.11.9: Fired type - 2541	
<pre>\node [fired type] {};</pre>	
Symbol 2.11.10: Boiler - 301, 2531	
<pre>\node [tank={with={boiler}{0}{1}, with={fired   ↪ type}{0}{-0.5}}] {};</pre>	
Symbol 2.11.11: Boiler example - 301, 2531	
<pre>\node[tank={with={boiler}{0}{1}, with={fired   ↪ type}{0}{-0.25},name=B1}] {};</pre> <pre>\draw (B1-boiler.east) to ++(0.5,0) to ++(0,0.5); \draw (B1-boiler.west) to ++(-0.5,0) to ++(0,0.5); \draw (B1-fired type.south) to ++(0,-0.5) to ++(0.5,0);</pre>	
Symbol 2.11.12: Steam generator - 301, 2531	
<pre>\node [tank={with={steam generator}{0}{1}}] {};</pre>	
Symbol 2.11.13: Steam generator with heating coil - 301, 2531, 2501	
<pre>\node [tank={with={steam generator}{0}{1}, with={heating   ↪ coil}{0}{-0.25}, name=SG1}] {};</pre> <pre>\draw (SG1-steam generator.west) to ++(-0.5,0); \draw (SG1-steam generator.east) to ++(0.5,0); \draw (SG1-heating coil.north) to ++(0.75,0); \draw (SG1-heating coil.south) to ++(0.75,0);</pre>	
Symbol 2.11.14: Heat pump - 2551, 130	
<pre>\draw (0,0) to [heat pump={quantity transition to higher}]   ↪ (2,0);</pre>	

Symbol 2.11.15: Heat pump bi-functional - 2551, 132	
<code>\draw (0,0) to [heat pump={quantity transition to higher and ↪ lower}] (2,0);</code>	
Symbol 2.11.16: Refrigerator - 2551, 131	
<code>\draw (0,0) to [refrigerator={quantity transition to lower}] ↪ (2,0);</code>	
Symbol 2.11.17: Freezer - 2551, 131	
<code>\draw (0,0) to [freezer={quantity transition to lower}] ↪ (2,0);</code>	

## 2.12 ISO 14617-12 Devices for separating, purification and mixing

Symbol 2.12.1: Tank - 301	
<code>\draw (0,0) to [tank] (2,0);</code>	
Symbol 2.12.2: Spray nozzle - 2037	
<code>\node [spray nozzle] {};</code>	
Symbol 2.12.3: Screen element - 2602	
<code>\node [screen element] {};</code>	
Symbol 2.12.4: Filter - X2601 301, 2602	
<code>\node [tank={with={filter element}{0}{-0.25}}] {};</code>	
Symbol 2.12.5: Filter with spray - X2607 301, 2037, 2602	
<code>\node [tank={with={filter element}{0}{-0.5}, with={spray ↪ nozzle}{0}{0.5}}] {};</code>	
Symbol 2.12.6: Filter element - 2602	
<code>\node [filter element] {};</code>	

## 2.13 ISO 14617-13 Devices for material processing

None available at the moment, feel free to contribute!

## **2.14 ISO 14617-14 Devices for transport and handling of material**

None available at the moment, feel free to contribute!

## **2.15 ISO 14617-15 Installation diagrams and network maps**

None available at the moment, feel free to contribute!