

cases	doc_1		doc_2		decision	id
					DUPLICATES	251
	authors	<ul style="list-style-type: none">Yan ZhangRuidan HeZuozhu LiuKwan Hui LimLidong Bing	authors	<ul style="list-style-type: none">Yan ZhangRuidan HeKwan Hui LimZuozhu LiuLidong Bing		
	title	An Unsupervised Sentence Embedding Method by Mutual Information Maximization	title	An Unsupervised Sentence Embedding Method by Mutual Information Maximization		
	publication_date	2020-09-25 00:00:00	publication_date	2020-09-25 00:00:00		
	source	SupportedSources.OPENALEX	source	SupportedSources.PAPERS_WITH_CODE		
	journal	Empirical Methods in Natural Language Processing	journal			
	volume		volume			
	doi	10.18653/v1/2020.emnlp-main.124	doi			
	urls	<ul style="list-style-type: none">https://openalex.org/W3100652389https://doi.org/10.18653/v1/2020.emnlp-main.124https://www.aclweb.org/anthology/2020.emnlp-main.124.pdf	urls	<ul style="list-style-type: none">https://arxiv.org/pdf/2009.12061v2.pdfhttps://github.com/yanzhangnlp/IS-BERThttps://aclanthology.org/2020.emnlp-main.124.pdf		
	id	id2240740915645591809	id	id-7194414645328398941		
	abstract		abstract	BERT is inefficient for sentence-pair tasks such as clustering or semantic search as it needs to evaluate combinatorially many sentence pairs which is very time-consuming. Sentence BERT (SBERT) attempted to solve this challenge by learning semantically meaningful representations of single sentences, such that similarity comparison can be easily accessed. However, SBERT is trained on corpus with high-quality labeled sentence pairs, which limits its application to tasks where labeled data is extremely scarce. In this paper, we propose a lightweight extension on top of BERT and a novel self-supervised learning objective based on mutual information maximization strategies to derive meaningful sentence embeddings in an unsupervised manner. Unlike SBERT, our method is not restricted by the availability of labeled data, such that it can be applied on different domain-specific corpus. Experimental results show that the proposed method significantly outperforms other unsupervised sentence embedding baselines on common semantic textual similarity (STS) tasks and downstream supervised tasks. It also outperforms SBERT in a setting where in-domain labeled data is not available, and achieves performance competitive with supervised methods on various tasks.		
	versions		versions			