

cases	doc_1		doc_2		decision	id
					DUPLICATES	302
	authors	<ul style="list-style-type: none">Bin WangC.-C. Jay Kuo	authors	<ul style="list-style-type: none">Bin WangC. -C. Jay Kuo		
	title	SBERT-WK: A Sentence Embedding Method by Dissecting BERT-Based Word Models	title	SBERT-WK: A Sentence Embedding Method by Dissecting BERT-based Word Models		
	publication_date	2020-02-16 00:00:00	publication_date	2020-02-16 19:02:52+00:00		
	source	SupportedSources.SEMANTIC_SCHOLAR	source	SupportedSources.ARXIV		
	journal	IEEE/ACM Transactions on Audio, Speech, and Language Processing	journal	None		
	volume	28	volume			
	doi	10.1109/taslp.2020.3008390	doi			
	urls	<ul style="list-style-type: none">https://www.semanticscholar.org/paper/d808e7468ef6265d39d3cd9c657c9f52e889cbc2	urls	<ul style="list-style-type: none">http://arxiv.org/pdf/2002.06652v2http://arxiv.org/abs/2002.06652v2http://arxiv.org/pdf/2002.06652v2		
	id	id-5252493220629724802	id	id7874431673068679021		
	abstract	Sentence embedding is an important research topic in natural language processing (NLP) since it can transfer knowledge to downstream tasks. Meanwhile, a contextualized word representation, called BERT, achieves the state-of-the-art performance in quite a few NLP tasks. Yet, it is an open problem to generate a high quality sentence representation from BERT-based word models. It was shown in previous study that different layers of BERT capture different linguistic properties. This allows us to fuse information across layers to find better sentence representations. In this work, we study the layer-wise pattern of the word representation of deep contextualized models. Then, we propose a new sentence embedding method by dissecting BERT-based word models through geometric analysis of the space spanned by the word representation. It is called the SBERT-WK method. No further training is required in SBERT-WK. We evaluate SBERT-WK on semantic textual similarity and downstream supervised tasks. Furthermore, ten sentence-level probing tasks are presented for detailed linguistic analysis. Experiments show that SBERT-WK achieves the state-of-the-art performance. Our codes are publicly available.	abstract	Sentence embedding is an important research topic in natural language processing (NLP) since it can transfer knowledge to downstream tasks. Meanwhile, a contextualized word representation, called BERT, achieves the state-of-the-art performance in quite a few NLP tasks. Yet, it is an open problem to generate a high quality sentence representation from BERT-based word models. It was shown in previous study that different layers of BERT capture different linguistic properties. This allows us to fusion information across layers to find better sentence representation. In this work, we study the layer-wise pattern of the word representation of deep contextualized models. Then, we propose a new sentence embedding method by dissecting BERT-based word models through geometric analysis of the space spanned by the word representation. It is called the SBERT-WK method. No further training is required in SBERT-WK. We evaluate SBERT-WK on semantic textual similarity and downstream supervised tasks. Furthermore, ten sentence-level probing tasks are presented for detailed linguistic analysis. Experiments show that SBERT-WK achieves the state-of-the-art performance. Our codes are publicly available.		
	versions		versions			