

cases	doc_1		doc_2		decision	id
					DUPLICATES	14
	authors	<ul style="list-style-type: none">Xing WuChaochen GaoYipeng SuJizhong HanZhongyuan WangSonglin Hu	authors	<ul style="list-style-type: none">Xing WuChaochen GaoYipeng SuJizhong HanZhongyuan WangSonglin Hu		
	title	Smoothed Contrastive Learning for Unsupervised Sentence Embedding	title	Smoothed Contrastive Learning for Unsupervised Sentence Embedding		
	publication_date	2022-09-12 00:00:00	publication_date	2021-09-09 14:54:24+00:00		
	source	SupportedSources.INTERNET_ARCHIVE	source	SupportedSources.ARXIV		
	journal		journal	None		
	volume		volume			
	doi		doi			
	urls	<ul style="list-style-type: none">https://web.archive.org/web/20220915033902/https://arxiv.org/pdf/2109.04321v2.pdf	urls	<ul style="list-style-type: none">http://arxiv.org/pdf/2109.04321v2http://arxiv.org/abs/2109.04321v2http://arxiv.org/pdf/2109.04321v2		
	id	id-8668783657730631915	id	id2150374846178866255		
	abstract	Contrastive learning has been gradually applied to learn high-quality unsupervised sentence embedding. Among the previous un-supervised methods, the latest state-of-the-art method, as far as we know, is unsupervised SimCSE (unsup-SimCSE). Unsup-SimCSE uses the InfoNCE1loss function in the training stage by pulling semantically similar sentences together and pushing apart dis-similar ones.Theoretically, we expect to use larger batches in unsup-SimCSE to get more adequate comparisons among samples and avoid overfitting. However, increasing the batch size does not always lead to improvements, but instead even lead to performance degradation when the batch size exceeds a threshold. Through statistical observation, we find that this is probably due to the introduction of low-confidence negative pairs after in-creasing the batch size. To alleviate this problem, we introduce a simple smoothing strategy upon the InfoNCE loss function, termedGaussian Smoothing InfoNCE (GS-InfoNCE).Specifically, we add random Gaussian noise vectors as negative samples, which act asa smoothing of the negative sample space.Though being simple, the proposed smooth-ing strategy brings substantial improvements to unsup-SimCSE. We evaluate GS-InfoNCEon the standard semantic text similarity (STS)task. GS-InfoNCE outperforms the state-of-the-art unsup-SimCSE by an average Spear-man correlation of 1.38%, 0.72%, 1.17% and0.28% on the base of BERT-base, BERT-large,RoBERTa-base and RoBERTa-large, respectively.	abstract	Contrastive learning has been gradually applied to learn high-quality unsupervised sentence embedding. Among the previous un-supervised methods, the latest state-of-the-art method, as far as we know, is unsupervised SimCSE (unsup-SimCSE). Unsup-SimCSE uses the InfoNCE1loss function in the training stage by pulling semantically similar sentences together and pushing apart dis-similar ones.Theoretically, we expect to use larger batches in unsup-SimCSE to get more adequate comparisons among samples and avoid overfitting. However, increasing the batch size does not always lead to improvements, but instead even lead to performance degradation when the batch size exceeds a threshold. Through statistical observation, we find that this is probably due to the introduction of low-confidence negative pairs after in-creasing the batch size. To alleviate this problem, we introduce a simple smoothing strategy upon the InfoNCE loss function, termedGaussian Smoothing InfoNCE (GS-InfoNCE).Specifically, we add random Gaussian noise vectors as negative samples, which act asa smoothing of the negative sample space.Though being simple, the proposed smooth-ing strategy brings substantial improvements to unsup-SimCSE. We evaluate GS-InfoNCEon the standard semantic text similarity (STS)task. GS-InfoNCE outperforms the state-of-the-art unsup-SimCSE by an average Spear-man correlation of 1.38%, 0.72%, 1.17% and0.28% on the base of BERT-base, BERT-large,RoBERTa-base and RoBERTa-large, respectively.		
	versions		versions			