

cases	doc_1		doc_2				decision	id
	authors	<ul style="list-style-type: none">Bhattacharjee, K.Ballesteros, M.Anubhai, R.Muresan, S.Ma, J.Ladhak, F.Al-Onaizan, Y.	authors	<ul style="list-style-type: none">Kasturi BhattacharjeeMiguel BallesterosRishita AnubhaiSmaranda MuresanJie MaFaisal LadhakYaser Al-Onaizan			DUPLICATES	289
	title	To BERT or Not to BERT: Comparing Task-specific and Task-agnostic Semi-Supervised Approaches for Sequence Tagging	title	To BERT or Not to BERT: Comparing Task-specific and Task-agnostic Semi-Supervised Approaches for Sequence Tagging				
	publication_date	2020-01-01 00:00:00	publication_date	2020-10-27 04:03:47+00:00				
	source	SupportedSources.CROSSREF	source	SupportedSources.ARXIV				
	journal		journal	None				
	volume		volume					
	doi	10.18653/v1/2020.emnlp-main.636	doi					
	urls	<ul style="list-style-type: none">http://dx.doi.org/10.18653/v1/2020.emnlp-main.636	urls	<ul style="list-style-type: none">http://arxiv.org/pdf/2010.14042v1http://arxiv.org/abs/2010.14042v1http://arxiv.org/pdf/2010.14042v1				
	id	id-6747516891727132736	id	id-6131347636948391843				
	abstract		abstract	Leveraging large amounts of unlabeled data using Transformer-like architectures, like BERT, has gained popularity in recent times owing to their effectiveness in learning general representations that can then be further fine-tuned for downstream tasks to much success. However, training these models can be costly both from an economic and environmental standpoint. In this work, we investigate how to effectively use unlabeled data: by exploring the task-specific semi-supervised approach, Cross-View Training (CVT) and comparing it with task-agnostic BERT in multiple settings that include domain and task relevant English data. CVT uses a much lighter model architecture and we show that it achieves similar performance to BERT on a set of sequence tagging tasks, with lesser financial and environmental impact.				
	versions		versions					