	doc_1			doc_2		id
		Nimesh Bhana		Nimesh Bhana Terence L. van Zyl		
	authors	Terence L van Zyl		Knowledge Graph Fusion for Language Model Fine-tuning 2022-06-21 08:06:22+00:00		
	title	Knowledge Graph Fusion for Language Model Fine-Tuning	source	SupportedSources.ARXIV		
		2022-06-21 00:00:00 Symmetric of Symmetric SCHOLAR	journal	None		
	journal	SupportedSources.SEMANTIC_SCHOLAR	volume			
	volume		doi	• http://arxiv.org/pdf/2206.14574v1		
	doi	10.1109/ISCMI56532.2022.10068451	urls	• http://arxiv.org/abs/2206.14574v1	О	
ases	urls	https://www.semanticscholar.org/paper/eeaf05f6f3a8dbd14cc318736d6ec833f8ef3f60		• http://arxiv.org/pdf/2206.14574v1		ES 135
	id	id1771291892618029916	id	id7778742553324208311		
	abstract versions	Language Models such as BERT (Bidirectional Encoder Representations from Transformers) have grown in popularity due to their ability to be pre-trained and perform robustly on a wide range of Natural Language Processing tasks. Often seen as an evolution over traditional word embedding techniques, they can produce semantic representations of text, useful for tasks such as semantic similarity. However, state-of-the-art models often have high computational requirements and lack global context or domain knowledge which is required for complete language understanding. To address these limitations, we investigate the benefits of knowledge incorporation into the fine-tuning stages of BERT. An existing K-BERT model, which enriches sentences with triplets from a Knowledge Graph, is adapted for the English language and extended to inject contextually relevant information into sentences. As a side-effect, changes made to K-BERT for accommodating the English language also extend to other word-based languages. Experiments conducted indicate that injected knowledge introduces noise. We see statistically significant improvements for knowledge-driven tasks when this noise is minimised. We show evidence that, given the appropriate task, modest injection with relevant, high-quality knowledge is most performant.	abstract	Language Models such as BERT have grown in popularity due to their ability to be pre-trained and perform robustly on a wide range of Natural Language Processing tasks. Often seen as an evolution over traditional word embedding techniques, they can produce semantic representations of text, useful for tasks such as semantic similarity. However, state-of-the-art models often have high computational requirements and lack global context or domain knowledge which is required for complete language understanding. To address these limitations, we investigate the benefits of knowledge incorporation into the fine-tuning stages of BERT. An existing K-BERT model, which enriches sentences with triplets from a Knowledge Graph, is adapted for the English language and extended to inject contextually relevant information into sentences. As a side-effect, changes made to K-BERT for accommodating the English language also extend to other word-based languages. Experiments conducted indicate that injected knowledge introduces noise. We see statistically significant improvements for knowledge-driven tasks when this noise is minimised. We show evidence that, given the appropriate task, modest injection with relevant, high-quality knowledge is		
			versions	most performant.		