cases	doc_1		doc_2		decision	id
			authors	• Mohamed I. Nouh • Yosry A. Azzam • Emad A. -B. Abdel-Salam	DUPLICATES	274
	authors	• M. Nouh • Y. A. Azzam • E. Abdel-salam	**title**	Modeling Fractional Polytropic Gas Spheres Using Artificial Neural Network		
	title	Modeling fractional polytropic gas spheres using artificial neural network	**publication_date**	2020-06-27 20:59:50+00:00		
	publication_date	2020-06-27 00:00:00	**source**	SupportedSources.ARXIV		
	source	SupportedSources.SEMANTIC_SCHOLAR	**journal**	None		
	journal	Neural Computing and Applications	**volume**			
	volume	33	**doi**			
	doi	10.1007/s00521-020-05277-9	**urls**	• http://arxiv.org/pdf/2006.15445v1 • http://arxiv.org/abs/2006.15445v1 • http://arxiv.org/pdf/2006.15445v1		
	urls	• https://www.semanticscholar.org/paper/c53cb5a427ca31bfe775490058ddc22d58d65990	**id**	id4028618703417667936		
	id	id2748855012136615655	**abstract**	Lane-Emden differential equations describe different physical and astrophysical phenomena that include forms of stellar structure, isothermal gas spheres, gas spherical cloud thermal history, and thermionic currents. This paper presents a computational approach to solve the problems related to fractional Lane-Emden differential equations based on neural networks. Such a solution will help solve the fractional polytropic gas spheres problems which have different applications in physics, astrophysics, engineering, and several real-life issues. We used Artificial Neural Network (ANN) framework in its feedforward back propagation learning scheme. The efficiency and accuracy of the presented algorithm are checked by testing it on four fractional Lane-Emden equations and compared with the exact solutions for the polytopic indices n=0,1,5 and those of the series expansions for the polytropic index n=3. The results we obtained prove that using the ANN method is feasible, accurate, and may outperform other methods.		
	abstract	None	**versions**			
	versions					