| cases | doc_1 | | doc_2 | | decision | id |
|-------|--|---|-------------|---|------------|--------|
| | | | authors | Wah Meng Lim Harish Tayyar Madabushi | | |
| | authors | | title | UoB at SemEval-2020 Task 12: Boosting BERT with Corpus Level Information | | |
| | | | | 2020-08-19 16:47:15+00:00 | | |
| | title | UoB at SemEval-2020 Task 12: Boosting BERT with | source | SupportedSources.ARXIV | | |
| | | Corpus Level Information | journal | None | | |
| | publication_date 2020-01-01 00:00:00 | | volume | | | |
| | source | SupportedSources.CROSSREF | doi | | | ES 281 |
| | journal | | urls | • http://arxiv.org/pdf/2008.08547v1 | DUPLICATES | |
| | volume | | | • http://arxiv.org/abs/2008.08547v1 | DOTLICATES | |
| | doi | 10.18653/v1/2020.semeval-1.295 | | • http://arxiv.org/pdf/2008.08547v1 | | |
| | | • http://dx.doi.org/10.18653/v1/2020.semeval- | | | | |
| | urls | 1.295 | id | id5256500666332593482 | | |
| | | | | Pre-trained language model word representation, such as BERT, have been extremely successful in several Natural Language Processing tasks significantly | | |
| | id | id4032852201501391561 | abstract | improving on the state-of-the-art. This can largely be attributed to their ability to better capture semantic information contained within a sentence. Several tasks, | | |
| | abstract | | | however, can benefit from information available at a corpus level, such as Term Frequency-Inverse Document Frequency (TF-IDF). In this work we test the effectiveness of integrating this information with BERT on the task of identifying abuse on social media and show that integrating this information with BERT | | |
| | versions | | | does indeed significantly improve performance. We participate in Sub-Task A (abuse detection) wherein we achieve a score within two points of the top | | |
| | | | | performing team and in Sub-Task B (target detection) wherein we are ranked 4 of the 44 participating teams. | | |
| | | | versions | | | . ' |