

cases	doc_1		doc_2		decision	id
	authors	<ul style="list-style-type: none">• Zongyi Li• Nikola Kovachki• Kamyar Azizzadenesheli• Burigede Liu• Kaushik Bhattacharya• Andrew Stuart• Anima Anandkumar	authors	<ul style="list-style-type: none">• Anandkumar, Anima• Azizzadenesheli, Kamyar• Bhattacharya, Kaushik• Kovachki, Nikola• Li, Zongyi• Liu, Burigede• Stuart, Andrew	DUPLICATES	288
	title	Fourier Neural Operator for Parametric Partial Differential Equations	title	Fourier Neural Operator for Parametric Partial Differential Equations		
	publication_date	2020-10-18 00:34:21+00:00	publication_date	2020-10-18 00:00:00		
	source	SupportedSources.ARXIV	source	SupportedSources.CORE		
	journal	None	journal			
	volume		volume			
	doi		doi	None		
	urls	<ul style="list-style-type: none">• http://arxiv.org/pdf/2010.08895v3• http://arxiv.org/abs/2010.08895v3• http://arxiv.org/pdf/2010.08895v3	urls	<ul style="list-style-type: none">• https://core.ac.uk/download/345075922.pdf		
	id	id3767239020258235696	id	id4351499172113280381		
	abstract	The classical development of neural networks has primarily focused on learning mappings between finite-dimensional Euclidean spaces. Recently, this has been generalized to neural operators that learn mappings between function spaces. For partial differential equations (PDEs), neural operators directly learn the mapping from any functional parametric dependence to the solution. Thus, they learn an entire family of PDEs, in contrast to classical methods which solve one instance of the equation. In this work, we formulate a new neural operator by parameterizing the integral kernel directly in Fourier space, allowing for an expressive and efficient architecture. We perform experiments on Burgers' equation, Darcy flow, and Navier-Stokes equation. The Fourier neural operator is the first ML-based method to successfully model turbulent flows with zero-shot super-resolution. It is up to three orders of magnitude faster compared to traditional PDE solvers. Additionally, it achieves superior accuracy compared to previous learning-based solvers under fixed resolution.	abstract	The classical development of neural networks has primarily focused on learning mappings between finite-dimensional Euclidean spaces. Recently, this has been generalized to neural operators that learn mappings between function spaces. For partial differential equations (PDEs), neural operators directly learn the mapping from any functional parametric dependence to the solution. Thus, they learn an entire family of PDEs, in contrast to classical methods which solve one instance of the equation. In this work, we formulate a new neural operator by parameterizing the integral kernel directly in Fourier space, allowing for an expressive and efficient architecture. We perform experiments on Burgers' equation, Darcy flow, and the Navier-Stokes equation (including the turbulent regime). Our Fourier neural operator shows state-of-the-art performance compared to existing neural network methodologies and it is up to three orders of magnitude faster compared to traditional PDE solvers		
	versions		versions			