

cases	doc_1		doc_2		decision	id
	authors	<ul style="list-style-type: none"><li>• Zongyi Li</li><li>• Nikola Kovachki</li><li>• Kamyar Azizzadenesheli</li><li>• Burigede Liu</li><li>• Kaushik Bhattacharya</li><li>• Andrew Stuart</li><li>• Anima Anandkumar</li></ul>	authors	<ul style="list-style-type: none"><li>• Zong-Yi Li</li><li>• Nikola B. Kovachki</li><li>• K. Azizzadenesheli</li><li>• Burigede Liu</li><li>• K. Bhattacharya</li><li>• Andrew Stuart</li><li>• Anima Anandkumar</li></ul>	DUPLICATES	243
	title	Fourier Neural Operator for Parametric Partial Differential Equations	title	Fourier Neural Operator for Parametric Partial Differential Equations		
	publication_date	2021-05-17 00:00:00	publication_date	2020-10-18 00:00:00		
	source	SupportedSources.INTERNET_ARCHIVE	source	SupportedSources.SEMANTIC_SCHOLAR		
	journal		journal	ArXiv		
	volume		volume	abs/2010.08895		
	doi		doi			
	urls	<ul style="list-style-type: none"><li>• <a href="https://web.archive.org/web/20210519090751/https://arxiv.org/pdf/2010.08895v3.pdf">https://web.archive.org/web/20210519090751/https://arxiv.org/pdf/2010.08895v3.pdf</a></li></ul>	urls	<ul style="list-style-type: none"><li>• <a href="https://www.semanticscholar.org/paper/2f7dc1ee85e9f6a97810c66016e09ffeed684f03">https://www.semanticscholar.org/paper/2f7dc1ee85e9f6a97810c66016e09ffeed684f03</a></li></ul>		
	id	id8585267584866657572	id	id-4621747468948422099		
	abstract	The classical development of neural networks has primarily focused on learning mappings between finite-dimensional Euclidean spaces. Recently, this has been generalized to neural operators that learn mappings between function spaces. For partial differential equations (PDEs), neural operators directly learn the mapping from any functional parametric dependence to the solution. Thus, they learn an entire family of PDEs, in contrast to classical methods which solve one instance of the equation. In this work, we formulate a new neural operator by parameterizing the integral kernel directly in Fourier space, allowing for an expressive and efficient architecture. We perform experiments on Burgers' equation, Darcy flow, and Navier-Stokes equation. The Fourier neural operator is the first ML-based method to successfully model turbulent flows with zero-shot super-resolution. It is up to three orders of magnitude faster compared to traditional PDE solvers. Additionally, it achieves superior accuracy compared to previous learning-based solvers under fixed resolution.	abstract	The classical development of neural networks has primarily focused on learning mappings between finite-dimensional Euclidean spaces. Recently, this has been generalized to neural operators that learn mappings between function spaces. For partial differential equations (PDEs), neural operators directly learn the mapping from any functional parametric dependence to the solution. Thus, they learn an entire family of PDEs, in contrast to classical methods which solve one instance of the equation. In this work, we formulate a new neural operator by parameterizing the integral kernel directly in Fourier space, allowing for an expressive and efficient architecture. We perform experiments on Burgers' equation, Darcy flow, and the Navier-Stokes equation (including the turbulent regime). Our Fourier neural operator shows state-of-the-art performance compared to existing neural network methodologies and it is up to three orders of magnitude faster compared to traditional PDE solvers.		
	versions		versions			