

cases	doc_1		doc_2		decision	id
					DUPLICATES	188
	authors	<ul style="list-style-type: none">Ryant, N.Liberman, M.Yuan, J.	authors	<ul style="list-style-type: none">Neville RyantM. LibermanJiahong Yuan		
	title	Speech activity detection on youtube using deep neural networks	title	Speech activity detection on youtube using deep neural networks		
	publication_date	2013-08-25 00:00:00	publication_date	None		
	source	SupportedSources.CROSSREF	source	SupportedSources.SEMANTIC_SCHOLAR		
	journal		journal			
	volume		volume			
	doi	10.21437/interspeech.2013-203	doi			
	urls	<ul style="list-style-type: none">http://dx.doi.org/10.21437/interspeech.2013-203	urls	<ul style="list-style-type: none">https://www.semanticscholar.org/paper/e651c1ec20460ae0f0fcd95f705370090a3bb335		
	id	id4589494756250490056	id	id-8190058057386089388		
	abstract		abstract	Speech activity detection (SAD) is an important first step in speech processing. Commonly used methods (e.g., frame-level classification using gaussian mixture models (GMMs)) work well under stationary noise conditions, but do not generalize well to domains such as YouTube, where videos may exhibit a diverse range of environmental conditions. One solution is to augment the conventional cepstral features with additional, hand-engineered features (e.g., spectral flux, spectral centroid, multiband spectral entropies) which are robust to changes in environment and recording condition. An alternative approach, explored here, is to learn robust features during the course of training using an appropriate architecture such as deep neural networks (DNNs). In this paper we demonstrate that a DNN with input consisting of multiple frames of mel frequency cepstral coefficients (MFCCs) yields drastically lower frame-wise error rates (19.6%) on YouTube videos compared to a conventional GMM based system (40%).		
	versions		versions			