

cases	doc_1		doc_2				decision	id
							DUPLICATES	276
	authors	<ul style="list-style-type: none">Kanjirangat, V.Mitrovic, S.Antonucci, A.Rinaldi, F.	authors	<ul style="list-style-type: none">K VaniSandra MitrovicAlessandro AntonucciFabio Rinaldi				
	title	SST-BERT at SemEval-2020 Task 1: Semantic Shift Tracing by Clustering in BERT-based Embedding Spaces	title	SST-BERT at SemEval-2020 Task 1: Semantic Shift Tracing by Clustering in BERT-based Embedding Spaces				
	publication_date	2020-01-01 00:00:00	publication_date	2020-10-02 08:38:40+00:00				
	source	SupportedSources.CROSSREF	source	SupportedSources.ARXIV				
	journal		journal	None				
	volume		volume					
	doi	10.18653/v1/2020.semeval-1.26	doi					
	urls	<ul style="list-style-type: none">http://dx.doi.org/10.18653/v1/2020.semeval-1.26	urls	<ul style="list-style-type: none">http://arxiv.org/pdf/2010.00857v1http://arxiv.org/abs/2010.00857v1http://arxiv.org/pdf/2010.00857v1				
	id	id1767535054052467758	id	id7769915732204235998				
	abstract		abstract	Lexical semantic change detection (also known as semantic shift tracing) is a task of identifying words that have changed their meaning over time. Unsupervised semantic shift tracing, focal point of SemEval2020, is particularly challenging. Given the unsupervised setup, in this work, we propose to identify clusters among different occurrences of each target word, considering these as representatives of different word meanings. As such, disagreements in obtained clusters naturally allow to quantify the level of semantic shift per each target word in four target languages. To leverage this idea, clustering is performed on contextualized (BERT-based) embeddings of word occurrences. The obtained results show that our approach performs well both measured separately (per language) and overall, where we surpass all provided SemEval baselines.				
	versions		versions					