

cases	doc_1		doc_2		decision	id
					DUPLICATES	317
	authors	<ul style="list-style-type: none">R. Ozgur DorukKechen Zhang	authors	<ul style="list-style-type: none">R.Ozgur DorukKechen Zhang		
	title	Fitting of dynamic recurrent neural network models to sensory stimulus-response data	title	Fitting of dynamic recurrent neural network models to sensory stimulus-response data		
	publication_date	2018-06-02 00:00:00	publication_date	2017-09-26 00:00:00		
	source	SupportedSources.INTERNET_ARCHIVE	source	SupportedSources.INTERNET_ARCHIVE		
	journal	Springer Nature America, Inc	journal			
	volume		volume			
	doi	10.1007/s10867-018-9501-z	doi			
	urls	<ul style="list-style-type: none">https://web.archive.org/web/20190217210507/http://pdfs.semanticscholar.org/0759/41c7085250d3e24b659c47162b4cbeae82fb.pdf	urls	<ul style="list-style-type: none">https://web.archive.org/web/20191013144635/https://arxiv.org/pdf/1709.09541v1.pdf		
	id	id-4308682748567877139	id	id-241492810662412864		
	abstract	We present a theoretical study aiming at model fitting for sensory neurons. Conventional neural network training approaches are not applicable to this problem due to lack of continuous data. Although the stimulus can be considered as a smooth time dependent variable, the associated response will be a set of neural spike timings (roughly the instants of successive action potential peaks) which have no amplitude information. A recurrent neural network model can be fitted to such a stimulus-response data pair by using maximum likelihood estimation method where the likelihood function is derived from Poisson statistics of neural spiking. The universal approximation feature of the recurrent dynamical neuron network models allow us to describe excitatory-inhibitory characteristics of an actual sensory neural network with any desired number of neurons. The stimulus data is generated by a Phased Cosine Fourier series having fixed amplitude and frequency but a randomly shot phase. Various values of amplitude, stimulus component size and sample size are applied in order to examine the effect of stimulus to the * Corresponding Author	abstract	We present a theoretical study aiming at model fitting for sensory neurons. Conventional neural network training approaches are not applicable to this problem due to lack of continuous data. Although the stimulus can be considered as a smooth time dependent variable, the associated response will be a set of neural spike timings (roughly the instants of successive action potential peaks) which have no amplitude information. A recurrent neural network model can be fitted to such a stimulus-response data pair by using maximum likelihood estimation method where the likelihood function is derived from Poisson statistics of neural spiking. The universal approximation feature of the recurrent dynamical neuron network models allow us to describe excitatory-inhibitory characteristics of an actual sensory neural network with any desired number of neurons. The stimulus data is generated by a Phased Cosine Fourier series having fixed amplitude and frequency but a randomly shot phase. Various values of amplitude, stimulus component size and sample size are applied in order to examine the effect of stimulus to the identification process. Results are presented in tabular form at the end of this text.		
	versions		versions			